

Grips and Fixtures

Self Tightening

Self-Tightening Grip

Ideal for rubber or flat samples, the GF-6 has an eccentrically mounted roller that tightens as load is applied. The top grip is self aligning.

Top and Bottom Grips may be ordered separately.
 Top: p/n **GF6-TOP**
 Bottom: p/n **GF6-BOT**



GF-6
Sample Size
 25mm (1 inch) Width
 5mm (0.2 inch) Thickness

Capacity
 225 lbf, 1000 N

Thread
 Upper Grip - 1/4-20M
 Bottom Grip - 3/8-16F

Self-Tightening Grip

Similar to the GF-6 roller grip, this grip is for wider samples up to 3-inches. Ideal for fabrics.

Top and Bottom Grips may be ordered separately.
 Top: p/n **GF7-TOP**
 Bottom: p/n **GF7-BOT**



GF-7
Sample Size
 75mm (3 inch) Width
 5mm (0.2 inch) Thickness

Capacity
 225 lbf, 1000 N

Thread
 Upper Grip - 1/4-20M
 Bottom Grip - 3/8-16F

Eccentric Roller Grip

Grip features an eccentric roller design ideal for flat specimens and dumbbells. Roller has a crosscut, serrated finish for securing the sample.

Fixture is sold as a set.



TG-10
Sample Size
 25mm (1 inch) Width
 5mm (0.2 inch) Thickness

Capacity
 225 lbf, 1000 N

Thread
 Upper Grip - 5/8" Eye End
 Bottom Grip - 5/8" Eye End

Eccentric Roller Grip

Grip is similar to TG-10 except it supports wider samples up to 2 inches.

Fixture is sold as a set.



TG-22
Sample Size
 50mm (2 inch) Width
 5mm (0.2 inch) Thickness

Capacity
 225 lbf, 1000 N

Thread
 Upper Grip - 5/8" Eye End
 Bottom Grip - 5/8" Eye End

Willrich Precision Ph 866-945-5742 email: sales@willrich.com