


# Mecmesin

testing to perfection

# Digital Force & Torque Gauges

Tension and Compression  
Test Solutions



# Advanced Force Gauge

See pages 5 - 8 for 'Smart' Force & Torque Sensors

The Advanced Force Gauge (AFG) is the most versatile and fully-featured digital force gauge on the market. It can be used hand-held or fixed to a manual or motorised test stand and for added flexibility the AFG is able to recognise data from a range of external 'Smart' force and torque sensors, so you can use it as a universal display for remote applications (see pages 5 to 8).

## KEY FEATURES:

- 10 capacities - from 2.5N to 2500N
- Peak capture - Ultimate max + 1st peak
- Data output - RS232, digimatic and analogue
- Pass/Fail Alarms - audible and visual
- Overload warning with trend bar
- Wide range of grips and fixtures

RS232, Mitutoyo, Analogue data output for easy data transmission. A calibrated analogue output can be supplied as an option.



RS232 to Bluetooth adaptor (optional extra)

Recognises data from a range of external force & torque transducers e.g. S-Beam, Load Button Cell and Static Torque Wrench.

View the 1st peak and ultimate peak readings  
On-board memory stores up to 500 readings

Accurate to  $\pm 0.1\%$  full-scale

Internal loadcell stud for quick and easy change of accessories and fixtures  
Loadcell stud 10-32 UNF male (5/16 UNC male for AFG 1000N & 2500N)

Audible & visual pass/fail alarms set a threshold for immediate alert when limits are exceeded

Measurements made in N, kN, mN, lbf, ozf, kgf and gf with a sampling rate of 5000Hz

Reversible display  
View readings even when the gauge is positioned away from you

Rugged metal housing ideal for factory or outdoor use



# AFG Specification Table

Model	Part No.	mN	N	kN	gf	kgf	ozf	lbf
AFG 2.5	850-412	2,500 x 0.5	2.5 x 0.0005	-	250 x 0.05	-	9 x 0.002	0.55 x 0.0001
AFG 5	850-413	5,000 x 1	5 x 0.001	-	500 x 0.1	0.5 x 0.0001	18 x 0.005	1.1 x 0.0002
AFG 10	850-414	10,000 x 2	10 x 0.002	-	1,000 x 0.2	1 x 0.0002	35 x 0.01	2.2 x 0.0005
AFG 25	850-415	25,000 x 5	25 x 0.005	-	2,500 x 0.5	2.5 x 0.0005	90 x 0.02	5.5 x 0.001
AFG 50	850-416	50,000 x 10	50 x 0.01	-	5,000 x 1	5 x 0.001	180 x 0.05	11 x 0.002
AFG 100	850-417	-	100 x 0.02	-	10,000 x 2	10 x 0.002	350 x 0.1	22 x 0.005
AFG 250	850-418	-	250 x 0.05	-	25,000 x 5	25 x 0.005	900 x 0.2	55 x 0.01
AFG 500	850-419	-	500 x 0.1	-	50,000 x 10	50 x 0.01	1,800 x 0.5	110 x 0.02
AFG 1000	850-420	-	1,000 x 0.2	1 x 0.0002	-	100 x 0.02	3,500 x 1	220 x 0.05
AFG 2500	850-421	-	2,500 x 0.5	2.5 x 0.0005	-	250 x 0.05	9,000 x 2	550 x 0.1

- Accuracy  $\pm 0.1\%$  of full scale
- Full scale deflection of loadcell typically 0.5mm



AFG shown mounted to the MultiTest-d motorised test stand

The dual level design of the keypad ensures that operation of this powerful gauge is kept simple, thereby making it ideal for use from production shop floor to R&D.

Housed in an ergonomically shaped, rugged aluminium case, the AFG is powered by either mains-adaptor or standard rechargeable AAA batteries.


All models carry CE marking and are supplied in a robust carrying case with standard accessories and a calibration certificate traceable to UK national standards.

*See page 12 for details of accessories supplied.*

versatile  
rugged  
accurate



Pull test on anchorage points



Compression test on medical device





AFG and accessories

# The Advanced Force & Torque Indicator

See pages 5 - 8 for 'Smart' Force & Torque Sensors

The Advanced Force & Torque Indicator (AFTI) is a high-specification display unit with similar features and benefits of the AFG, for use with Mecmesin 'Smart' force and torque sensors. These plug into the AFTI enabling it to automatically register either force or torque readings for a variety of test applications. 'Smart' sensors may also be used with Mecmesin's Advanced Force Gauge (AFG).

## FORCE



## TORQUE



RS232, Mitutoyo,  
Analogue data output for  
easy data transmission

 RS232 to Bluetooth  
adaptor (optional extra)

Measurements made  
in N, lbf, kgf, kN, N.m,  
kgf.cm, lbf.in, gf.cm and  
ozf.in with a sampling  
rate of 5000Hz

Overload warning  
with trend bar  
and on board  
memory of 500  
readings

Fully interchangeable  
'smart' sensors  
No need for additional  
calibration of display or  
sensor, just 'plug & play'

Tension, compression &  
torque measurement  
with full unit conversion  
of displayed value

1st & ultimate peak capture

These sensors are ideal for mounting onto your own test rigs and jigs to monitor load application. They can also be used for checking calibration of your machinery to assess whether it is applying the expected load.

## 'Smart' Force & Torque Sensors

All sensors are fitted with 1.5m cable length, are fully interchangeable and are supplied with Calibration Certificates traceable to UK National Standards. As standard they are delivered in cardboard transit cases.

### Key Features:

- Sensors for torque, tension & compression
- Calibration Certificates traceable to UK National Standards
- Resolution - 1:5000
- Overload protection feature
- 1.5m cable length as standard


force & torque  
plug-in sensors  
adaptable

All dimensions quoted for the force & torque sensors are for reference only. Please contact the Mecmesin Sales Department for tolerance information if your application is dimensionally critical.

Overload protection by software warning is typically 120% of full scale for all items (without accessories), with additional mechanical overload protection being up to a minimum of 150% of full scale.

All gauges and sensors are calibrated under controlled laboratory conditions at a temperature of  $20\text{C} \pm 2\text{C}$ . Resolution for all sensors is typically 1:5000 - e.g. a 5000N loadcell resolves to 1N.

### Bluetooth/USB Adaptor




- Cableless Communication
- Range in excess of 30 metres
- Easy-to-use, just 'Plug & Play'
- Maximum flexibility for data transfer
- Connects to AFG & AFTI


# Tension & Compression Sensors

For use with AFTI display or Advanced Force Gauge (AFG)

## Junior S-Beam - 'Smart'



The Junior S-Beam is suitable for measuring tension and compression. Ideal for applications where available space is limited. Dedicated fixtures can be fitted via threaded holes.



For use with AFTI display or Advanced Force Gauge (AFG)

Model	Part No.	L mm	W mm	H mm	Thread
1N/100gf/3.5ozf	870 - 101	17	7	19	M3 x 0.5
2.5N/250gf/9ozf	870 - 102	17	7	19	M3 x 0.5
5N/500gf/18ozf	870 - 103	17	7	19	M3 x 0.5
10N/1kgf/2.2lbf	870 - 104	17	7	19	M3 x 0.5
25N/2.5kgf/5.5lbf	870 - 105	17	7	19	M3 x 0.5
50N/5kgf/11lbf	870 - 106	17	7	19	M3 x 0.5
100N/10kgf/22lbf	870 - 107	17	7	19	M3 x 0.5
250N/25kgf/55lbf	870 - 108	17	7	19	M3 x 0.5
500N/50kgf/110lbf	870 - 109	17	7	19	M3 x 0.5

Accuracy  $\pm 0.25\%$  of full scale



## S-Beam - 'Smart'


The S-Beam provides an economical solution to general force measurement applications where space is not restricted. Dedicated fixtures can be fitted via threaded holes.

For use with AFTI display or Advanced Force Gauge (AFG)

Model	Part No.	L mm	W mm**	H mm	Thread
100N/10kgf/22lbf	870 - 002	51	13	64	M6 x 1
200N/20kgf/44lbf	870 - 004	51	13	64	M6 x 1
500N/50kgf/110lbf	870 - 009	51	19	76	M6 x 1
1000N/100kgf/220lbf	870 - 001	51	19	76	M10 x 1.5
2500N/250kgf/550lbf	870 - 006	51	25	76	M12 x 1.75
5000N/500kgf/1100lbf	870 - 008	51	25	76	M12 x 1.75
10kN/1000kgf/2200lbf	870 - 003	51	25	76	M12 x 1.75
25kN/2500kgf/5500lbf	870 - 007	76	25	108	M16 x 2

Cylindrical	Part No.	$\varnothing$ mm	H mm	Thread
* 50kN/5000kgf/11000lbf	870 - 011	70	120	M36 x 3
* 100kN/10000kgf/22000lbf	870 - 010	70	120	M36 x 3

Accuracy  $\pm 0.25\%$  of full scale \* Uni-directional calibration (please specify tension or compression)



\*\* 6mm added to the overall width of the central portion due to the protective cover

# For use with AFTI display or Advanced Force Gauge (AFG)



## Load Button Cell - 'Smart'

The Load Button Cell is a miniature sensor for compression measurement only, where available space is very limited. For optimum results apply compressive load to the top of the sensor's central dome.

For use with AFTI display or Advanced Force Gauge (AFG)

### Miniature Series



Model	Part No.	Capacity	ØD1mm	ØD2mm	ØD3mm	H1mm	H2mm	T
L16010	878 - 008	100N/10kgf/22lbf	25	5	19	8	1	4/40UNC
	878 - 009	250N/25kgf/55lbf	25	5	19	8	1	4/40UNC
	878 - 010	500N/50kgf/110lbf	25	5	19	8	1	4/40UNC
L16020	878 - 011	1000N/100kgf/220lbf	31	8	25	10	1	6/32UNC
	878 - 012	2500N/250kgf/550lbf	31	8	25	10	1	6/32UNC
	878 - 013	5000N/500kgf/1100lbf	31	8	25	10	1	6/32UNC
L16030	878 - 014	10kN/1000kgf/2200lbf	38	11	32	16	2	6/32UNC
	878 - 015	20kN/2000kgf/5500lbf	38	11	32	16	2	6/32UNC
	878 - 016	50kN/5000kgf/11000lbf	38	11	32	16	2	6/32UNC

Accuracy ±1% of full scale

### Sub-miniature Series

Model	Part No.	Capacity	ØD1mm	ØD2mm	H1mm	H2mm
L1630	878 - 001	50N/5kgf/11lbf	19	4.5	7	0.5
	878 - 002	100N/10kgf/22lbf	19	4.5	7	0.5
	878 - 003	250N/25kgf/55lbf	19	4.5	7	0.5
	878 - 004	500N/50kgf/110lbf	19	4.5	7	0.5
	878 - 005	1000N/100kgf/220lbf	19	4.5	7	0.5
	878 - 006	5000N/500kgf/1100lbf	19	4.5	7	0.5

Accuracy ±1% of full scale




Dimensions are approximate.  
Detailed drawings available upon request

## Specialised Loadcells


In addition to the standard range of sensors, Mecmesin also offers specialised loadcells dedicated to specific applications. A few examples are shown below. Contact our sales department for further details.




Pinch Sensor



Donut Loadcell



Pedal Force Accelerator



Hand Gripper

# Static & Rotary Torque Sensors


For use with AFTI display or Advanced Force Gauge (AFG)

## Static Torque Transducer - 'Smart'



For mounting to a bench or integrating into a complete test rig. Equipped with male square drive for easy fitting of adaptors.

For use with AFTI display or Advanced Force Gauge (AFG)



Model	Part No.	Capacity	Sq Drive Male	H mm	W mm	D mm
ST15	872 - 006	15N.m/150kgf.cm/130lbf.in	3/8"	87	80	90
ST60	872 - 008	60N.m/600kgf.cm/520lbf.in	3/8"	87	80	90
ST100	872 - 003	100N.m/1000kgf.cm/870lbf.in	1/2"	93	80	90
ST150	872 - 005	150N.m/1500kgf.cm/1300lbf.in	1/2"	93	80	90


Accuracy  $\pm 0.5\%$  of full scale

## Static Torque Wrench - 'Smart'



For medium capacity applications where it is more practical to apply torque by a lever arm. Equipped with male square drive for easy fitting of adaptors.

For use with AFTI display or Advanced Force Gauge (AFG)



Model	Part No.	Capacity	Sq Drive Male	L mm	H mm	Weight
TW15	873 - 003	15N.m/150kgf.cm/130lbf.in	3/8"	280	25	800g
TW60	873 - 005	60N.m/600kgf.cm/520lbf.in	3/8"	355	25	950g
TW150	873 - 006	150N.m/1500kgf.cm/1300lbf.in	1/2"	508	25	1200g


Accuracy  $\pm 0.5\%$  of full scale

## Static Socket Extension - 'Smart'




For low capacity applications, where space is limited. Fitted with male/female square drives for easy fitting of drivers.

For use with AFTI display or Advanced Force Gauge (AFG)



Model	Part No.	Capacity	Sq Drive	L mm
SE3	871 - 201	3N.m/30kgf.cm/26lbf.in	1/4"	50.8
SE6	871 - 202	6N.m/60kgf.cm/50lbf.in	1/4"	50.8
SE10	871 - 203	10N.m/100kgf.cm/90lbf.in	1/4"	50.8

Accuracy  $\pm 0.5\%$  of full scale






# For use with AFTI display or Advanced Force Gauge (AFG)

## Static Torque Screwdriver - 'Smart'



For low capacity applications. Used as hand-held devices or mounted in a bench stand. Not suitable for applications, which require multiple rotations of the sensor - use rotary torque transducers below.



For use with AFTI display or Advanced Force Gauge (AFG)

Model	Part No.	Capacity	Drive	L mm	Ø mm	Weight
TS0.3	871 - 004	0.3N.m/3kgf.cm/2.6lbf.in	3/8" sq male/3 jaw chuck	143	43	660g
TS1.5	871 - 002	1.5N.m/15kgf.cm/13lbf.in	3/8" sq male/3 jaw chuck	143	43	660g
TS3	871 - 003	3N.m/30kgf.cm/26lbf.in	3/8" sq male/3 jaw chuck	143	43	660g
TS6	871 - 005	6N.m/60kgf.cm/53lbf.in	3/8" sq male/3 jaw chuck	143	43	660g
TS10	871 - 001	10N.m/100kgf.cm/90lbf.in	3/8" sq male/3 jaw chuck	143	43	660g

Accuracy ±0.5% of full scale





## Rotary Torque Transducers - 'Smart'

A complete range of sensors for measuring rotary torque. Suitable for dynamic torque applications with multiple revolutions (e.g. window-winder torque tools).

For use with AFTI display or Advanced Force Gauge (AFG)

Model	Part No.	Capacity	Drive	L1 mm	L2 mm	L3 mm	Ø mm	Max rpm
FAST 2N.m sq	877 - 020	2N.m/20kgf.cm/18lbf.in	1/4" square	70	16	10	40	1000
FAST 2N.m rd	877 - 021	2N.m/20kgf.cm/18lbf.in	Ø 9mm round*	70	28	28	40	5000
FAST 6N.m sq	877 - 022	6N.m/60kgf.cm/53lbf.in	1/4" square	70	16	10	40	1000
FAST 6N.m rd	877 - 023	6N.m/60kgf.cm/53lbf.in	Ø 9mm round*	70	28	28	40	5000
FAST 15N.m sq	877 - 024	15N.m/150kgf.cm/133lbf.in	1/4" square	70	16	10	40	1000
FAST 15N.m rd	877 - 025	15N.m/150kgf.cm/133lbf.in	Ø 9mm round*	70	28	28	40	5000
FAST 60N.m sq	877 - 026	60N.m/600kgf.cm/530lbf.in	3/8" square*	70	24	13	50	1000
FAST 60N.m rd	877 - 027	60N.m/600kgf.cm/530lbf.in	Ø 14mm round*	70	28	28	50	5000
FAST 150N.m sq	877 - 028	150N.m/15.3kgf.m/111lbf.ft	1/2" square	70	35	19	50	1000
FAST 150N.m rd	877 - 029	150N.m/15.3kgf.m/111lbf.ft	Ø 19mm round*	70	55	55	50	5000

Maximum axial force is 40N    Maximum lateral radial force is 50N    Accuracy ±1% of full scale \* fitted with keyway



# Basic Force Gauge

The Basic Force Gauge (BFG) is designed for easy operation and provides outstanding tension and compression measurement performance and reliability at an affordable price.

Constructed in a rigid yet lightweight aluminium housing, with its ergonomically attractive shape, the BFG can be used as a hand-held instrument, or alternatively it can be mounted to manual or motorised test stands to allow testing under more controlled conditions.



# BFG Specification Table

Model	Part No	mN	N	kN	gf	kgf	ozf	lbf
BFG 10	853 - 410	10,000 x 2	10 x 0.002	-	1,000 x 0.2	1 x 0.0002	35 x 0.01	2.2 x 0.0005
BFG 50	853 - 411	50,000 x 10	50 x 0.01	-	5,000 x 1	5 x 0.001	180 x 0.05	11 x 0.002
BFG 200	853 - 412	-	200 x 0.05	-	20,000 x 5	20 x 0.005	720 x 0.2	44 x 0.01
BFG 500	853 - 413	-	500 x 0.1	-	50,000 x 10	50 x 0.01	1,800 x 0.5	110 x 0.02
BFG 1000	853 - 414	-	1,000 x 0.2	1 x 0.0002	-	100 x 0.02	3,500 x 1	220 x 0.05
BFG 2500	853 - 417	-	2,500 x 0.5	2.5 x 0.0005	-	250 x 0.05	9,000 x 2	550 x 0.1

- Accuracy  $\pm 0.25\%$  of full scale
- Calibration temperature 20C  $\pm 2$ C
- Operating temperature 10C - 35C

easy-to-use  
robust  
ergonomic

## KEY FEATURES:

- 6 capacities - from 10N up to 2500N
- Full unit conversion of displayed value
- Powered by 4 nickel metal hydride rechargeable batteries
- M5 mounting holes (57mm pitch) for test stand fixing
- Wide range of grips and fixtures



BFG shown mounted to the MDD manual test stand

All models carry CE marking and are supplied in a robust carrying case with standard accessories and a calibration certificate traceable to UK national standards.



Top-load test



BFG with accessories

# Compact Force Gauge<sup>+</sup>

The Compact Force Gauge<sup>+</sup> (CFG<sup>+</sup>) is a pocket-sized, lightweight force gauge designed for elementary tension and compression measurement. Powered by disposable AA batteries, the CFG<sup>+</sup> is delivered with a Declaration of Conformity as standard. A Calibration Certificate is available upon request.

Peak readings captured at 500Hz with an accuracy of  $\pm 0.5\%$  of full scale

low cost  
peak hold  
portable

Measurements made in N, lbf, ozf, kgf and gf with a resolution of 1.0000

Housed in a lightweight plastic case

Loadcell stud 10-32 UNF male

RS232 output for easy data transmission



The CFG<sup>+</sup> provides a simple digital alternative to traditional analogue spring balances. It is ideal for users with a limited budget, who only measure on an occasional basis for non-critical applications.

## CFG<sup>+</sup> Specification Table

Model No.	Part No.	N	kgf	lbf
CFG <sup>+</sup> 50	860 - 021	50 x 0.05	5 x 0.005	11 x 0.01
CFG <sup>+</sup> 200	860 - 022	200 x 0.2	20 x 0.02	44 x 0.05
CFG <sup>+</sup> 500	860 - 023	500 x 0.5	50 x 0.05	110 x 0.1

- Accuracy  $\pm 0.5\%$  of full scale

**Note.** The following units are available on the majority of CFG<sup>+</sup> models. Those that differ are marked by an asterisk with details given below.

kN\*, N, mN, kgf, gf\*\*, lbf, ozf

\* Not available on the CFG<sup>+</sup> 50N

\*\*Not available on the CFG<sup>+</sup> 200N or 500N




Drawer Testing

# Accessories

Each Mecmesin gauge comes with a set of standard accessories to help perform basic tension or compression tests.

A wide selection of accessories exclusive to Mecmesin are available. See our Accessory datasheets for an extensive range of grips and fixtures, to enable you to complete thousands of different tests. Alternatively make use of our experienced team of engineers to provide a customised grip to solve your particular problem.



- |   |                                   |   |  |
|---|-----------------------------------|---|--|
| A | 6mm Ø - 5/16 UNC thread (432-122) | F | 30mm long - 5/16 UNC (F-M) (432-008)   |
| B | 6mm Ø - 10-32 UNF (F) (432-120)   | G | 30mm - 10-32 UNF (F) to 10-32 UNF (M) (432-006)  |
| C | 3.2mm Ø - 10-32 UNF (F) (432-118) | H | 30mm - 10-32 UNF (F) to M6 (M) (432-007)   |
| D | 19mm Ø - 10-32 UNF (F) (432-121)  | I | Mains adaptor/charger (304-004) - 220V 2-pin round<br>(304-005) - 220V 3-pin square<br>(304-006) - 110V 2-pin flat |
| E | 19mm Ø - 5/16 UNC (F) (432-125)   |   |  |

\* Part numbers shown in brackets

**Table of standard accessories delivered with each gauge:**

Model	A	B	C	D	E	F	G	H	I
AFG 2.5, 5, 10, 25, 50, 100, 250N			•	•			•	•	•
AFG 500N		•		•			•	•	•
AFG 1000 & 2500N	•				•	•			•
BFG 10, 50, 200N			•	•			•	•	•
BFG 500N		•		•			•	•	•
BFG 1000 & 2500N	•				•	•			•
CFG+ 50N			•	•			•	•	
CFG+ 200N		•		•			•	•	
CFG+ 500N		•		•			•	•	

## Service & Calibration

Mecmesin ensures all customers receive a high level of on-going service and support. This includes offering a prompt and cost-effective calibration service. Though calibrations can be completed in our comprehensive in-house facility, customers also have the option of our on-site calibration service.




# Additional Products

To enhance your testing capability, Mecmesin offers a number of additional products including:

## Software

### Emperor™ Lite

Emperor™ Lite is Mecmesin's powerful data-acquisition software, for use with its extensive range of force & torque measurement equipment. The software quickly and easily enables operators to perform in-depth analysis of measurements using a graphical trace of the test. User-selectable calculations provide instant results for key test parameters, allowing you to gain valuable quantitative information about the test samples.



Graphical representation of a peel test

- View test 'live' on PC screen
- Perform multiple calculations e.g. peak, minimum and average
- Easily identify and label critical measurement values and success/failure points during the test
- Summary test report with graphical traces

## Grips

Mecmesin offers a wide range of grips and fixtures, to suit many types of application. For those with a specialised requirement, we can design and manufacture a customised fixture to match your specifications.




- Compression plates
- Test hooks
- Textile attachment grips
- Claw type grips
- Compression probes
- Wedge grips
- Flat-faced jaw grips
- Cam grips



# Applications

Our range of digital gauges can be used in combination with our test stands to perform many different applications.

- Release-torque testing
- Compressive testing
- Deformation testing
- Medical Device testing



Fabric testing



Keypad testing

- Packaging testing
- Tensile testing
- Textile testing
- Top-load testing



Peel testing

Mecmesin's range of testing equipment has been successfully used in a number of different industry sectors including:



aerospace



automotive



beverage



cosmetics



doors, gates & barriers



electrical



engineering



food & drink



manual handling




medical



military



packaging



paper & board




pharmaceutical




plastics



safety



sports



textiles

## Support Services

- Comprehensive network of international distributors
- 24 month warranty
- Website support
- Calibration, service & repair centre
- On-site installation and training
- Accessories
- Application support

# Mecmesin

testing to perfection

## Over 30 Years Experience in Force & Torque Technology

Formed in 1977, Mecmesin Limited is today widely regarded as a leader in force and torque technology for quality control testing in design and production. The Mecmesin brand stands for excellent levels of performance and reliability, guaranteeing high quality results.

Quality control managers, designers and engineers working on production lines and in research laboratories worldwide rely upon Mecmesin force & torque measurement systems for a range of quality control testing applications, which is almost limitless.

Visit us on the web at  
[www.mecmesin.com](http://www.mecmesin.com)



Algeria	Hong Kong	Portugal
Argentina	Hungary	Romania
Australia	India	Russia
Austria	Indonesia	Saudi Arabia
Bangladesh	Iran	Singapore
Belgium	Ireland	South Africa
Brazil	Israel	Slovenia
Canada	Italy	Slovakia
Chile	Japan	Spain
China	Korea	Sri Lanka
Colombia	Lebanon	Sweden
Costa Rica	Malaysia	Switzerland
Czech Republic	Mexico	Taiwan
Denmark	Morocco	Tunisia
Egypt	Netherlands	Thailand
Finland	New Zealand	Turkey
France	Norway	USA
Germany	Philippines	Venezuela
Greece	Poland	Vietnam

Wherever you are in the world Mecmesin can help you through its global distribution network



Certificate No. FS 58553

DISTRIBUTOR STAMP

### Head Office

**Mecmesin Limited**  
Newton House,  
Spring Copse Business Park,  
Slinfold, West Sussex,  
RH13 0SZ, United Kingdom.  
e. [sales@mecmesin.com](mailto:sales@mecmesin.com)  
t. +44 (0) 1403 799979  
f. +44 (0) 1403 799975

### North America

**Mecmesin Corporation**  
45921 Maries Road,  
Suite 120, Sterling  
Virginia 20166,  
U.S.A.  
e. [info@mecmesincorp.com](mailto:info@mecmesincorp.com)  
t. +1 703 433 9247  
f. +1 703 444 9860

### Asia

**Mecmesin Asia Co. Ltd**  
308 Soi Rohitsuk,  
Ratchadapisek 14 Road,  
Huaykwang, Bangkok, 10310,  
Thailand.  
e. [sales@mecmesinasia.com](mailto:sales@mecmesinasia.com)  
t. +66 2 275 2920 1  
f. +66 2 275 2922

### China

**Mecmesin (Shanghai) Pte Ltd**  
Room 302, No. 172,  
Daxue Lu - University Avenue,  
Yangpu District, Shanghai, 200433,  
People's Republic of China.  
e. [sales@mecmesin.cn](mailto:sales@mecmesin.cn)  
t. +86 21 5566 1037 / 3377 1733  
f. +86 21 5566 1036