



SPECIFICATIONS

TNP- XX Series Digital Torque Tester w/USB interface

TNP Models	TNP-0.5	TNP-2	TNP-5	TNP-10
Measuring units	Ncm, mNm, gcm, lbin	Nm, Ncm, Kgcm, Lbin	Nm, Ncm, Kgcm, Lbin	Nm, Ncm, Kgcm, Lbin
Measuring range	0-50.00 Ncm	0-2.000 Nm	0-5.00 Nm	0-10.00 Nm
	0-500.0 mNm	0-200.0 Ncm	0-500.0 Ncm	0-1000 Ncm
	0-5099 gcm	0-20.39 Kgcm	0-50.99 Kgcm	0-102.0 Kgcm
	0-4.425 lbin	0-17.70 Lbin	0-44.25 Lbin	0-88.5 Lbin
Overload protection / Percentage overload	150% of full scale			
Sample diameter range	Φ 10 - 190 mm (0.39 " - 7.48")			
Overload display	Display "OVR" at sub display of LCD, blinking LED			
Display	Main display	4-digit LCD display Character height 12mm		
	Sub display	3-digit LCD display Character height 7mm		
	Comparator Display	HI - GO - LO (green and red LED indicator)		
Accuracy	± 0.5% Full Scale			
Measuring	Opening mode	Show max value when opening (peak display) Displays max counterclockwise torque.		
	Closing mode	Show max value when closing (peak display) Displays max clockwise torque.		
	Average mode	Real time display (average value display) Displays torque in real time.		
Display Update Time	Select from 0.125 second (8 times/second), 0.25 second (4 times/second), 0.5 second (2 times/second), 1 second(1 time/second). Peak display: 0.125 second			
Sampling Rate	1000 times/second			
Memory	Memory data number	1000 data (max)		
	Statistical process	Average value, max value, min value		
Data output	USB1.1			
PC software	Digitorg software (free, download from web site: www.shimpoint.com)			
Standard Accessories	USB cable, 120/240 VAC AC adapter, 30mm chuck pin (4pcs), Manual			
Optional Accessories	Torque pins available: 30mm (4pcs) TNP-TP30, 50mm (4pcs) TNP-TP50			
Power	Built in nickel hydride battery or Auto-ranging AC adapter (AC100 - 240V)			
Dimensions L x W x H mm/ (in)	320 x 227x 126 (12.60" x 8.94" x 4.96")			
Shipping weight	8 kg (17.62lb)	8 kg (17.62lb)	8 kg (17.62lb)	12.5 kg (27.53lb)
Operation environment	0 - 40 degree C / 32 - 104 degree F			
Certifications	CE approval			
Battery Type/Battery Life	NiMH / 8 hours after full charge			
Battery Recharge Time	Max. 16 hours			

DISTRIBUTED BY

Willrich Precision
Ph: 866-945-5742
email: sales@willrich.com