

*Extremely lightweight
 and easy-to-use.*



Ultra-Lite Mark III Electronic Calipers



Fowler's Ultra-Lite Mark III Electronic Calipers offer many advantages over conventional calipers. Featuring a low weight that improves measuring results. Measuring pressure control for improved repeatability. For increased wear resistance, jaw faces are titanium-coated on hardened steel.

Features:

- Internal and external measurements with two presets.
- Min/Max functions.
- Hold feature freezes display for later viewing.
- Menu customizable with free software
- Incremental floating zero.
- Measuring Speed = 60"/1.5m per second.
- Large, high-contrast LCD display indicates in/mm, hold and zero functions.
- New low drain, high efficiency lithium wafer battery—4500 hrs. of continuous on-time.
- Direct inch/metric conversion.
- Direct RS232C output connects tool to any computer or printer without an interface.
- Special application accessories available.
- Includes case (excluding 80", 100" & 120" models).



Part Number	Range	Accuracy	Repeatability	Weight
54-110-312	0-12"/300mm	.0012"(30µm)	.0008"(20µm)	2.4lb(1.1kg)
54-110-324	0-24"/600mm	.0016"(40µm)	.0008"(20µm)	2.9lb(1.3kg)
54-110-340	0-40"/1000mm	.0024"(60µm)	.0008"(20µm)	3.5lb(1.6kg)
54-110-360	0-60"/1500mm	.0048"(120µm)	.0008"(20µm)	4.4lb(2kg)
54-110-380	0-80"/2000mm	.0060"(150µm)	.0012"(30µm)	5lb(2.3kg)
54-110-100	0-100"/2500mm	.0080"(200µm)	.0012"(30µm)	5.67lb(2.6kg)
54-110-120	0-120"/3000mm	.010"(250µm)	.0012"(30µm)	6.54lb(3kg)

- Cables:
- 54-115-525 Opto USB Cable
 - 54-115-333 Opto Serial Cable