

Willrich Precision Ph: 866-945-5742 / sales@willrich.com

### Indicator Stand 815 GN



#### Features

- Rugged base ensures both maximum stability and sturdiness
- The upper side of the base has a convenient hand grip
- Moves easily over surfaces without vibration
- Front of the base is ground to allow movement of the stand along edges and rules
- Stable due to the three point support
- Support arm can be finely adjusted
- Post and support arm are made from stainless steel
- Indicator can be rotated through  $\pm 90^\circ$

#### Technical Data

Total height with base	Max. projection of support arm	Post dia.		Base surface	Fine adjustment range	Weight	Order no.* Mount dia.	Order no.* Mount dia.
a	b	c	d	e			8H7	3/8"
mm <i>inch</i>	mm	mm	mm	mm	mm	kg		
300 <b>12"</b>	185	18	14	150 x 150	2	4.2	<b>4413000</b>	<b>4413050</b>
500 <b>20"</b>	200	25	18	190 x 180	2	9	<b>4413001</b>	<b>4413051</b>
750 <b>30"</b>	230	35	25	190 x 180	2	10	<b>4413005</b>	<b>4413052</b>

\* excludes indicating instrument

### Indicator Stand 2400



#### Features

- A stable Height Stand for electronic measurement,
- Fine adjustment in the base allows easy operator set-up, even at high magnification. Up to 3.8 mm / .150" adjustment when arms fully extended.
- Collar has Teflon bearings and metal-to-metal clamping.
- Post is thermally isolated from heat transfer from the base.
- Arm lock is independent of the pivot lock.
- Uses vertical lug mounting
- EHE-2056 Lever gage head mounts directly to arm (as shown) EHE-2048 Lever gage head requires an EAM-1071 adaptor
- CP-83 Extra arm and swivel clamp assembly (allows mounting two lever gage heads on one stand)

#### Technical Data

Total height with base	Arm reach	Post dia. force	Base surface	Fine adjustment range	Order no.*
mm / <i>inch</i>	mm / <i>inch</i>	mm / <i>inch</i>	mm / <i>inch</i>	mm / <i>inch</i>	
457 / <b>18"</b>	254 / <b>10"</b>	31.8 / <b>1.25"</b>	161.7 x 94 / <b>6.2 x 3.7"</b>	3.8 / <b>0.150"</b>	<b>2400</b>

\* excludes indicating instrument