



*Integrated Bluetooth Technology offers output without the hassle of cables or antennas hanging from the indicator. Your USB port is all you need.*



*The analog display allows you to quickly view reversal points*



Willrich Precision  
Ph 866-945-5742  
email: sales@willrich.com



### Mark VI Electronic Indicators With Integrated Bluetooth Technology

- Features:**
- Robust construction
  - Water and coolant resistant
  - Protection class IP-67
  - Repeatability: 2µm
  - Battery life: 10,000 hours of operation
  - Menu customizable with free software.
  - Wide range of functions (MIN/MAX/DELTA, TOL, Factor, Preset, Auto Off, etc)
  - Aluminum housing
  - Bezel rotates 270°
  - Large display with LED tolerance indicators.
  - Includes lug back.



Part Number	Range	Maximum Error	Resolution
54-530-335	0-.500"/12.5mm	0.00012"/.003mm	.00005"/.001mm
54-530-355	0-1.000"/25mm	0.00016"/.004mm	.00005"/.001mm

### Mark VI Electronic Indicators With Analog Display

- Features:**
- Robust construction
  - Water and coolant resistant
  - Protection class IP-67
  - Repeatability: 2µm
  - Output: Proximity/Power - USB/RS232/digimatic/Wireless
  - Battery life: 10,000 hours of operation
  - Menu customizable with free software.
  - Wide range of functions (MIN/MAX/DELTA, TOL, Factor, Preset, Auto Off, etc)
  - Aluminum housing
  - Bezel rotates 270°
  - Large display with LED tolerance indicators.
  - Includes lug back.



Part Number	Range	Maximum Error	Resolution
54-530-535	0-.500"/12.5mm	0.00012"/.003mm	.00005"/.001mm
54-530-555	0-1.000"/25mm	0.00016"/.004mm	.00005"/.001mm

Indicators