



786 Series Electronic Blade- Type Micrometers with non-rotating spindle (with output) 0-5" / 0-125mm

This micrometer is the same as our 486 with electronic readout and the following additional features:

Readability Features

- Large LCD digital readout is easy to read and reduces errors
- Conventional inch or millimeter graduations standard
- Attractive no-glare black wrinkle finish on the frame
- Starrett no-glare satin chrome finish on thimble and sleeve

Accuracy and Long-Life Features

- One 3-volt battery furnished for over a year of normal usage
- Automatic OFF after 30 minutes of nonuse

Full-Function Action Features

- Instant inch/millimeter conversion
- "ME" millimeter models will turn on in the millimeter mode after installation of a new battery
- Measurement HOLD button
- Ability to zero tool at any position
- Ability to retain and return to the true zero reading of the micrometer
- PRESET button to install any reading at any position
- Ability to install minimum and maximum limits
- RS232 data output port
- Works well with Starrett Datasure® Wireless Data Collection Systems

Willrich Precision
Ph 866-945-5742
email sales@willrich.com



786 Electronic Blade-Type Micrometers With Standard Inch Graduations on Shell and Thimble

Range	Approx. mm	Resolution		Catalog No.	EDP
Inch		Inch	mm		
0 - 1"	0 - 25.4mm	.00005"	0.001mm	786P-1	65225
1 - 2"	25.4 - 51mm			786P-2	65226
2 - 3"	51 - 76mm			786P-3	65227
3 - 4"	76 - 101mm			786P-4	65228
4 - 5"	101 - 127mm			786P-5	65229

786 Electronic Blade-Type Micrometers With Standard Millimeter Graduations on Shell and Thimble

Range	Approx. Inch	Resolution		Catalog No.	EDP
mm		mm	Inch		
0 - 25mm	0 - .984"	0.001mm	.00005"	786MEP-25	66118
25 - 50mm	.984 - 1.968"			786MEP-50	66126
50 - 75mm	1.968 - 2.950"			786MEP-75	66127
75 - 100mm	2.950 - 3.930"			786MEP-100	66128
100 - 125mm	3.930 - 4.920"			786MEP-125	66129

Cable Information for 786 Electronic Blade-Type Micrometers

Part No.	EDP	Description
PT61963	66636	Computer Interface Cable Complete to PC (RS232C)
PT61768	66454	Adaptor from PT22938 Cable to PC (RS232C)
PT22938	64059	Shielded Cable to 761/772 Series Starrett Modules and PT61768 Adaptor
PT61120	65446	One 3-Volt Battery CR2450

Attractive, protective case available by ordering 733ZZ and one size larger than the micrometer. Example: For 786P-2, order 733ZZ-3.