



Countersink Gages

687 Series 82°


688 Series 90°

689 Series 100°

Starrett Countersink Gages are offered in three different angles so that the gage sets on the angular side of the countersink, as opposed to a chamfer gage which sets on the top edge of the chamfer.

This gage directly reads the large diameter of the countersink in .002" or 0.05 mm increments. A set master ring is furnished with each gage for calibration and setting. Press the button on top of the indicator to firmly depress the gage head into the countersink. When the gage is removed, the indicator reading is held in place until the reset button is activated.

All ground surfaces are of hardened tool steel. Indicators are AGD design.



Inch Reading Countersink Gages						
Range	82° Angle		90° Angle		100° Angle	
	Catalog No.	EDP	Catalog No.	EDP	Catalog No.	EDP
.020-.170"	687-1Z	63698	688-1Z	63702	689-1Z	63706
.160-.360"	687-2Z	63699	688-2Z	63703	689-2Z	63707
.360-.560"	687-3Z	63700	688-3Z	63704	689-3Z	63708
.560-.780"	687-4Z	63701	688-4Z	63705	689-4Z	63709

Millimeter Reading Countersink Gages with Yellow Dials						
Range	82° Angle		90° Angle		100° Angle	
	Catalog No.	EDP	Catalog No.	EDP	Catalog No.	EDP
0.5-4.3mm	687M-1Z	65003	688M-1Z	65007	689M-1Z	65011
4-9mm	687M-2Z	65004	688M-2Z	65008	689M-2Z	65012
9-14.2mm	687M-3Z	65005	688M-3Z	65009	689M-3Z	65013
14.2-19.8mm	687M-4Z	65006	688M-4Z	65010	689M-4Z	65014

Check Gage Stand for Chamfer, Countersink and Hole Gages		
Description	Catalog No.	EDP
8-3/16" H x 6" W x 4" D (212 x 150 x 100mm) Hold Downs - 5" (125mm) on Center - 1/4" (6.3mm) Holes	695	63875

Also available with electronic indicators. Please specify.