

Willrich Precision

Ph 866-945-5742 email: sales@willrich.com

## Bench Depth Gages 75B-1

For inspecting small parts



75B-1

### Features

- Available with Dial Indicator (75B-1 Models) or Max $\mu$ m<sup>®</sup>/// and  $\mu$ Max $\mu$ m<sup>®</sup>/// Digital Electronic Indicators (EMD-75B and XLI-75B Models).
- 89 x 102 mm / 3.50 x 4" hardened, ground work surface provides excellent reference surface.
- Four #10-32 tapped holes provided for mounting part location fixturing.
- Indicator adjustable vertically over 32 mm / 1.25".
- Two contact points provided, 6 mm / .25" and 32 mm / 1.25" to check features up to 50 mm / 2" deep.

### Technical Data

Order no. Metric	Inch	Indicator Range / Graduation or Resolution
75B-1M	75B-1	25 mm / .01 mm ( <b>1" / .001"</b> ) graduation Dial Indicator.
EMD-75B-1		Max $\mu$ m <sup>®</sup> /// Digital Indicator with selectable range and resolution, 2033201.
XLI-75B-1		$\mu$ Max $\mu$ m <sup>®</sup> /// XL Digital Indicator, 25 mm / <b>1"</b> range, .001 mm / <b>.00005"</b> resolution
XLI-75B-2		$\mu$ Max $\mu$ m <sup>®</sup> /// XL Digital Indicator, 12 mm / <b>.50"</b> range, .001 mm / <b>.00005"</b> resolution

To specify Digital Output on EMD-75B Models, add suffix "D". Example = EMD-75B-1D.  
Output is standard with XLI and EDI models.