


## Wedge Action Grips

These miniature wedge action grips are ideal for tensile testing wire, filaments, fibers, cables, etc. Grips have serrated teeth for extra gripping power as tensile force is applied.



### GF-11

**Sample Size**  
12mm (0.5 inch)

**Capacity**  
110 lbf, 500 N

**Thread**  
#10-32F

### ML1700

**Sample Size**  
5.6mm (0.2 inch)

**Capacity**  
450 lbf, 2000 N

**Thread**  
5/16-18F

## Universal Wedge Grip

This self-tightening grip is perfect for general purpose tensile testing. Straight cut faces ensure a secure grasp on the sample. Faces may be replaced. Grips feature a spring force lever for quick loading/release of the sample under test.

Grip length is 35mm (1.35 inch).

Replacement Face  
p/n 19058 each

### GF-9

**Sample Size**  
25mm (1 inch)

**Capacity**  
550 lbf, 2500 N

**Thread**  
Upper Grip - 1/4-20M  
Bottom Grip - 1/4-20M



## Sliding Wedge Grip

This self-tightening grip features replaceable faces making it perfect for general purpose tensile testing. Comes standard with Straight Faces. Grips feature a spring force lever for quick loading/release of the sample under test. Grip length is 50mm (2 inch).

Optional jaw faces are available and may be ordered separately.

### Crosscut Faces

25 x 50mm **TG15/C**

### Straight Faces


25 x 50mm **TG15/S**

### V-Notch Faces

4-12mm **TG15/V12**

*Note: When purchasing grip faces separately, faces are supplied in a set of 4 each.*

Maximum sample width: 25mm  
Maximum sample thickness: 10mm




### TG-15

**Sample Size**  
25mm (1 inch) Width  
10mm (0.4 inch) Thickness  
50mm (2 inch) Grip Length

**Capacity**  
1100 lbf, 5000 N

**Thread**  
Upper Grip - 5/8" Eye End  
Bottom Grip - 5/8" Eye End



Cross Cut Faces



Straight Cut  
Faces



V-Notch Cut  
Faces