

Willrich Precision Ph 866-945-5742 email: sales@willrich.com

Snap Gages for Outside Diameters 1000P



The economical way to check outside diameters on the shop floor.

Features

- Flat lower anvil (reference) adjustable over a broad range.
- Radiused upper anvil (sensitive) spring-loaded to counter balance the weight of the gage.
- 0.01 mm grads. on Metric Models. .0005" grads. on Inch Models.
- 0.50 mm / .020" Range of Sensitive Contact.
- Indicator can be rotated to read from front or rear of the gage.
- Anvils are tungsten carbide for long life.

1000P-3
0.01 mm or .0005" Dial Indicator normally furnished

Technical Data

Capacity		Reference Anvil Diameter	Order no. Metric	Order no. Inch
mm	(inch)	mm / inch		
0 - 25	(0 - 1")	13 / .50"	1000P-1M*	1000P-1*
19 - 50	(.75 - 2")	13 / .50"	1000P-2M*	1000P-2*
44 - 82	(1.75 - 3.25")	13 / .50"	1000P-3M	1000P-3
76 - 114	(3 - 4.5")	16 / .625"	1000P-4M	1000P-4
102 - 152	(4 - 6")	16 / .625"	1000P-5M	1000P-5
152 - 203	(6 - 8")	19 / .75"	1000P-6M	1000P-6
203 - 254	(8 - 10")	19 / .75"	1000P-7M	1000P-7

Series 1000P gages with greater capacity, alternate Indicators, alternate contact configurations, or other modification to suit specific applications are available – contact Mahr Federal.

* Insulated grip not available.