

Willrich Precision Ph 866-945-5742 email : sales@willrich.com

Comparator Stands 35 B



Features

- Model 35B has a precision ground base. Indicator arms with and without fine adjustment are available. Models are also available with lapped anvils for the highest precision work.
- Alternate post lengths, Indicators, Anvils and special fixturing available upon request. Contact Mahr Federal Technical Assistance

Excludes indicating instrument. Only indicating instruments that have a horizontal lug back can be used.

Technical Data

Capacity	Post Diameter	Throat Depth	Reference Surface	Gaging Arm	Anvil	Order no. (w/o indicator)
0 - 8.75" 0 - 222 mm	1.25" 31.75 mm	2.5" 62.5 mm	1 x 3" 25 x 75 mm	adjustable AM-146 plain AM-3 adjustable AM-146 adjustable AM-146	plain none none serrated	OMI-35B-21 OMI-35B-30 OMI-35B-32 OMI-35B-41

Accessories

Replacement Anvils

- Anvils for Comparator Stands 35B-21 and 35B-41 are available: Surface is lapped flat to within .00001"

Type	Dimensions	Order no.
plain surface	25 x 25 x 75 mm (1 x 1 x 3")	AL-96
serrated surface	25 x 25 x 75 mm (1 x 1 x 3")	AL-97

Fine Adjustment Arm

- The Fine Adjust Arm is available separately to convert 35B Comparator Stands with plain arms

Range	Order no.
1.5 mm / 0.060"	AM-146

Readout Specification: Because of the versatility of the Series 35B and NB-60 Stands, almost any type of readout can be used.

- With Dial or Digital Indicators having a horizontal lug back