

WILLRICH PRECISION info@willrich.com 866-945-5742



Mant s Stereo Viewing Systems

for a wide range of inspection and material rework tasks

- Patented optical technology for fatigue-free viewing and superb image quality
- Wide range of magnification options (to x20)
- Long working distances; large depths of field .
- Shadow-free true colour LED illumination

Mantis... Compact, Elite, Macro?

The Mantis family is a unique range of patented optical systems without eyepieces, for intricate tasks requiring superb quality viewing over long periods of time.

Mantis is in use in tens of thousands of sites worldwide and has become the accepted standard for ergonomics and high performance magnification.

The latest generation of Mantis incorporates the most modern advances in optical design, moulded plastics and LED illumination.

Vision Engineering has designed and manufactured world leading optical systems since 1958. The company's patented optical viewers, microscopes and measuring systems are manufactured in Vision Engineering factories in the UK and the USA. The stereo eyepieceless Mantis viewers have a wide range of applications; it is used throughout manufacturing industries (electronics, precision engineering, plastics, medical devices) and life science laboratories around the world.

Advantages of the next generation Mantis are:

- Entry level, low investment versions
- Compact, functional units
- Wide range of magnification options (to x20)
- Shadow-free LED cold illumination, both surface and substage
- Long working distances; large depths of field
- Stable structures for high magnification viewing



Mantis Compact

Mantis Compact excels in the low magnification range for inspection or manipulation tasks where bench magnifiers have traditionally been used. Mantis Compact has a small footprint and low investment cost giving a superb price / performance ratio.



Mantis Elite


Mantis Elite offers a wider, higher performance specification including high magnification, large field of view, long working distance and head tilt capability. Mantis Elite has enhanced optical performance, making it a perfect alternative to traditional stereo microscopes for a wide range of inspection, preparation and manipulation tasks requiring hand-to-eye co-ordination.



Mantis Macro

Mantis Macro offers a straight through in-line view of the subject, similar in operation to a bench magnifier, but with increased optical clarity and magnification. Mantis Macro offers a comparatively high magnification for an in-line viewer making it ideal for tasks which require exceptional hand-eye coordination and increased magnification. **Mantis Compact** is a high value, low investment stereo viewer excelling in the low magnification range for inspection or manipulation tasks where bench magnifiers have traditionally been used.


Patented optical technology allows operators freedom of head movement for superb ergonomics and hand-eye co-ordination, with the ability to wear glasses if required. Operators can increase productivity and improve quality, at an affordable price.



- Superior ergonomics for improved productivity and increased throughput
- Long working distances for easy sample manipulation and rework
- x2, x4 and x6 quick change objectives
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing
- Superb hand-eye co-ordination for inspection and manipulation tasks
- Patented eyepieceless optics maximise head freedom providing superb ergonomics and reduced eye fatigue
- Choice of stands. Flexible swing arm with small footprint or rigid bench stand for added stability or illumination options



High stability bench stand with integral focus, dimmable substage illumination.



Dimensions:

- **A** = 395mm 605mm **B** = 213mm **C** = 565mm - 775mm
- **D** = 90mm 300mm

Mantis Compact, with counter-balanced

universal stand, for flexibility and ease of use.


E = 335mm - 545mm

Unpacked weight: Head 2.1kg Stand 3.3kg

Packed weight: Head 4.1kg Stand 4.6kg

Optical Data		
Objective Lenses	Working Distance	Field of View
x2	167mm	45.0mm
x4	96mm	27.5mm
хб	73mm	19.2mm

Power Supply
9V DC external plug transformer.



Dimensions: A = 526mm - 641mm

- **B** = 305mm
- **C** = 487mm 602mm
- **D** = 487mm
- **E** = 103mm 218mm **F** = 198mm
- **G** = 123mm

Unpacked weight:

Head 2.1kg Stand 4.5kg

Packed weight: Head 4.1kg Stand 7.9kg

rieau 4.1kg Stand 7.9kg

Lighting Data		
Light intensity measured at subject plane with colour correction filters.		
20 LEDs	9,400 LUX	10,000 hours
Substage illumination (bench stand only)		
13 LEDs	1,200 - 4,000 LUX	10,000 hours

Accessories


Lens protection caps Floating stage (for bench stand) Dust cover Replacement LED array UV lighting option Mantis Elite is a high performance stereo microscope, offering superb optical performance with magnification options up to x20, making it a perfect alternative to more traditional stereo microscopes.

Large fields of view and generous working distances allow for a wide range of inspection, preparation and manipulation tasks to be carried out, all with exceptional hand-eye co-ordination.



Mantis Elite, with countered-balanced universal stand and 25° tilting head facility, for flexibility and ease of use

Technical Data



Dimensions:

- **A** = 415mm 624mm **B** = 212mm
- **C** = 593mm 802mm **D** = 83mm - 292mm
- E = 352mm 622mm

Unpacked weight: Head 3.0kg Stand 3.3kg

Packed weight: Head 5.0kg Stand 4.6kg

Optical Data		
Objective Lenses	Working Distance	Field of View
x2	160mm	57.0mm
x4	96mm	34.0mm
хб	68mm	23.0mm
x6 SLWD*	112mm	20.0mm
х8	59mm	17.0mm
x10	54mm	13.5mm
x15	40mm	8.8mm
x20	29mm	6.5mm


Power Supply

9V DC external plug transformer

- High value, high specification patented design with superb optical performance
- x2 x20 magnification options with guick change turret allows users to switch between low magnification inspection and high magnification fine detail tasks
- . Patented eyepieceless optics maximise head freedom providing superb ergonomics and minimal eye fatigue
- Superior ergonomics for improved productivity and increased throughput
- Superb hand-eye co-ordination for inspection and manipulation tasks
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing
- Long working distance and large field of view for easy sample manipulation and rework
- Choice of stands. Flexible swing arm with small footprint or rigid bench stand for added stability or illumination options



High stability bench stand with integral focus, dimmable substage illumination and floating stage option



Dimensions: A = 538mm - 653mm

- **B** = 305mm
- **E** = 102mm 217mm
- **F** = 198mm
- **G** = 172mm

Unpacked weight:

Head 5.0kg Stand 7.9kg

Lighting Data		
Light intensity measured at subject plane with colour correction filters.		
24 LEDs	11,000 LUX	10,000 hours
Substage illumination (bench stand only)		
13 LEDs	1,200 - 4,000 LUX	10,000 hours

Accessories

Lens protection caps Floating stage (for bench stand) Dust cover Replacement LED array UV lighting option

* Single mount objective replaces twin turret assembly

- **C** = 496mm 611mm **D** = 487mm

Head 3.0kg Stand 4.5kg

Packed weight:

Unlike other Mantis, which have an upright optical path, the **Mantis Macro** provides straight through in-line viewing which makes the co-ordination of hand and eye even easier.


Mantis Macro offers a straight through in-line view of the subject, similar in operation to a bench magnifier but with increased magnification and optical clarity making it ideal for tasks which require exceptional hand-eye coordination and increased magnification.

- Patented eyepieceless optical technology expands the exit pupil providing head freedom and eye relief for excellent ergonomics
- Straight through in-line optical path offers superb handeye co-ordination for inspection and manipulation tasks
- x2.5 –x5.0 magnification with quick change turret allows user to switch between magnifications
- Superior ergonomics for improved productivity and increased throughput
- Long working distance and large field of view for easy sample manipulation and rework
- Bright white, true colour, LED illumination providing over 10,000 hours of shadow-free viewing



Mantis Macro, with countered-balanced universal stand and 30° tilting head facility, for flexibility and ease of use.

Technical Data



Dimensions:

- **A** = 350mm 570mm
- **B** = 170mm
- **C** = 500mm 700mm **D** = 75mm - 300mm
- **E** = 260mm 450mm
- $\mathbf{F} = 20^\circ 50^\circ$

Unpacked weight: Head 2.6kg Stand 3.3kg

Packed weight: Head 4.9kg Stand 4.6kg

Optical Data		
Objective Lenses	Working Distance	Field of View
x2.5	116mm	48.6mm
x5.0	66mm	23.8mm

Power Supply

9V DC external plug transformer.



Straight through in-line view for optimal hand-eye co-ordination and maximum working distance.



Lighting Data

Light intensity measured	at subject plane with colou	r correction filters.
40 LEDs	9,500 LUX	10,000 hours

Accessories

- Lens protection caps Dust cover
- Replacement LED array



Vision Engineering manufactures a comprehensive range of ergonomic stand-alone mono and stereo microscopes as well as a complete line of non-contact measuring systems.

For more information...

Vision Engineering has a network of offices and technical distributors around the world. For more information, please contact your Vision Engineering branch, local authorised distributor, or visit our website.

Vision Engineering Ltd. (Manufacturing) Send Road, Send, Woking, Surrey, GU23 7ER, England Tel: +44 (0) 1483 248300 +44 (0) 1483 223297 Fax: Email: generalinfo@visioneng.com

Vision Engineering Ltd. (Commercial) Monument House, Monument Way West, Woking, Surrey, GU21 5EN, England Tel: +44 (0) 1483 248300 +44 (0) 1483 248301 Fax: Email: generalinfo@visioneng.com

Distributor

WILLRICH PRECISION INSTRUMENT 866-945-5742 / info@willrich.com www.willrich.com

CT 06776 USA

CA 92865 USA

Vision Engineering Inc.

(Commercial West Coast USA)

745 West Taft Avenue, Orange,

+1 (714) 974 6966

+1 (714) 974 7266

Email: info@visioneng.com

Tel:

Fax:

Tel:

Fax:

Vision Engineering Inc. Vision Engineering Ltd. (Manufacturing & Commercial) (Central Europe) 570 Danbury Road, New Milford, Anton Pendele Strasse 3, D-82275, Emmering, Germany +1 (860) 355 3776 Tel: +1 (860) 355 0712 Fax: Email: info@visioneng.com Email: info@visioneng.de

> Nippon Vision Engineering (Japan) 272-2 Saedo-cho, Tsuduki-ku, Yokohama-shi, 224-0054, Japan Tel: +81 (0) 45 935 1117 Fax: +81 (0) 45 935 1177 Email: info@visioneng.jp

+49 (0) 8141 40167-0

+49 (0) 8141 40167-55

Vision Engineering Ltd.

(France) 1 Rue de Terre Neuve, ZA Courtaboeuf, 91967 Les Ulis Cedex, France Tel: +33 (0) 164 46 90 82 +33 (0) 164 46 31 54 Fax: Email: info@visioneng.fr

Vision Engineering Ltd Italia (Italy) Via Pelizza da Volpedo 51, 20092 Cinisello Balsamo MI, Italy Tel: +39 02 6129 3518 Fax: +39 02 6129 3526 Email: info@visioneng.it

Visit our multi-lingual website: