CHAMFER GAGE

Digital Electronic Gages

 90° MODEL
 CAPACITY

 0090-SPC
 0-3/8"

 5090-SPC
 0-1/2"

 1090-SPC
 0-1"

 2090-SPC
 1-2"

 3090-SPC
 2-3"

 4090-SPC
 3-4"

Wireless option now available.

| 127° MODEL | CAPACITY | PRICE |
|------------|----------|-------|
| 0127-SPC | 0-3/8" | |
| 5127-SPC | 0-1/2" | |
| 1127-SPC | 0-1" | |
| 2127-SPC | 1-2" | |
| 3127-SPC | 2-3" | |
| 4127-SPC | 3-4" | |

METRIC DIGITAL ELECTRONIC GAGES

| 90° MODEL | CAPACITY | |
|-----------|--------------|--|
| 0090M-SPC | 0-9.50mm | |
| 5090M-SPC | 0-12.75mm | |
| 1090M-SPC | 0-25.50mm | |
| 2090M-SPC | 25.0-50.0mm | |
| 3090M-SPC | 50.0-76.5mm | |
| 4090M-SPC | 75.0-101.6mm | |

| 127° MODEL | CAPACITY | |
|------------|--------------|--|
| 0127M-SPC | 0-9.50mm | |
| 5127M-SPC | 0-12.75mm | |
| 1127M-SPC | 0-25.50mm | |
| 2127M-SPC | 25.0-50.0mm | |
| 3127M-SPC | 50.0-76.5mm | |
| 4127M-SPC | 75.0-101.6mm | |

DIGITAL GAGES ARE CALIBRATED IN INCH AND CAN BE SWITCHED FROM INCH TO MM WITH THE PRESS OF A BUTTON. IF CALIBRATION AND PROGRAMMING IS REQUIRED IN MM ADD SUFFIX "M" AND USE ABOVE PRICES.

DIGITAL GAGES ARE SELF ZEROING AND DO NOT INCLUDE SETTING RINGS.

OPTIONAL: NIST TRACEABLE CERTS