

Helping you create the world of tomorrow



“We have a fundamental belief that metrology isn’t just an eliminator of variation but an enabler of new capabilities.”

Our work unleashes the capacity of our customers to do more for less, to produce higher quality and more innovative products, and to better and more profitably serve their customers or patients.

Over the years, we have built a company that is different to others. Different in how we apply technology to real world problems, in how we invest for the long-term, in how we manufacture rather than outsource, and in how we treat our customers as partners.

Which is why we’ve invested in research and development, in high quality manufacturing, in life-changing fields like healthcare, and in the ability to provide local customer support in all our markets around the globe. All of it rooted in our ethos of continual improvement and our passionate belief in the power of metrology.

We’d be proud to work with you on solving the challenges your business faces and helping you manufacture the products that will define our world in the decades to come.

Sir David McMurtry
Co-founder, Chairman and Chief Executive

Let's talk

Our work breaks down into four simple phases: consult, engineer, implement and support. The first of these –consult – can begin now, or as soon as you're ready.

Whatever your metrology or manufacturing problem, with our cutting-edge technology, our decades of experience helping businesses improve and profit, and our highly skilled staff, we'd like to be the ones to solve it for you.

So please get in touch and let's talk about what you need and how we can help.

Find contact details for your nearest office:

www.renishaw.com/contact

Introduction

Foreword

All prices are quoted in U.S. dollars and are subject to change without notice. Prices include packaging, but exclude freight, tax and insurance (where applicable).

All freight is shipped F.O.B. Hoffman Estates, Illinois. Renishaw automatically ships and insures items via United Parcel Service unless the customer specifies otherwise.

Renishaw's terms of business are thirty (30) days net.

Renishaw's return policy for unused items returned by customers is as follows:

A notice requesting goods to be returned must occur within 30 days of shipment. A Return Goods Authorization number (RGA) will be issued by Renishaw's Customer Service department and is required prior to goods being returned. Goods must then be returned within 30 days of issue date. The RGA number must be noted on all paperwork and labels for return. Shipment to Renishaw without an RGA number may be refused.

Goods returned for reasons other than quality issues will be subject to a restocking fee of \$75 or 20% of the net price, whichever is greater. After 60 days, no product will be accepted for return.

Returned product will be inspected and credit will be issued, except where an item is damaged, incomplete, or not in the original packaging. Specials, or non-standard assembled products, are non-returnable.

If you require further information regarding Renishaw products, please contact us at:

Phone: 847-286-9953

Fax: 847-286-9974

email: susan.wilm@renishaw.com

Internet: www.renishaw.com

The Renishaw mission

Renishaw will design, manufacture and supply metrology systems of the highest quality and reliability to enable customers worldwide to carry out dimensional measurements to traceable standards.

Our product offerings will enhance quality and productivity, and we will strive for total customer satisfaction through superior customer service.

Our aim is to provide leading edge technology by encouraging innovation to address our customers' needs.

We are committed to sustained growth through continued investment in product development and manufacturing methods.

Renishaw wishes to be recognized collectively and individually as leaders and contributors in our field and our community.

We wish to achieve our aims in a way that is caring, open and honest.

Renishaw is an environmentally conscious and responsible company. We will strive to ensure that all aspects of the business have the least harmful effect on the environment.

Coordinate measuring machine probes



Fixed and manual probe heads

PH1

A small swivel head, adjustable in both the A and B axes, with limited overtravel protection. The probe is offset from the mounting shank Z axis.

Number of probe sockets:	1
Probe status indication:	1 LED
Cable connection:	5 pin DIN 180° socket
Overtravel break load:	Adjustable from 20 gf (0.7 ozf) to locked solid
A-axis indexing:	Swivel of 115° locked with hexagonal key (3 mm A/F)
B-axis indexing:	15° steps through 360°
Weight:	125 g (4.5 oz)
Mounting options:	Shank to suit your CMM

Part number: A-1049-1795

Price: \$1,764



PH6

A compact, vertical probe head for a single probe, with a choice of integral cables (see below).

Number of probe sockets:	1
Probe status indication:	1 LED
Cable connection:	Integral cable
Mounting options:	Shank to suit your CMM

Part number: A-1046-5097 (coiled 12-28 in, 5 pin DIN)	Price: \$477
Part number: A-1046-5098 (coiled 18-50 in, 5 pin DIN)	Price: \$477
Part number: A-1046-5099 (coiled 30-95 in, 5 pin DIN)	Price: \$477
Part number: A-1046-5094 (plain 177 in, 5 pin DIN)	Price: \$477
Part number: A-1046-5096 (coiled 23-72 in, 7 pin amph)	Price: \$477




PH6A

The PH6A is designed for use with autojoint probes and allows you to change probes or add extensions without having to requalify the probe. **Special order only.**

Number of probe sockets:	1
Probe status indication:	1 LED
Cable connection:	5 pin DIN 180° socket
Mounting options:	Shank to suit your CMM

Part number: A-1051-0012

Price: \$718



PH6M

A fixed head with autojoint connection for probes and adaptors. For use with TP7M, SP600M, and SP25M.

Number of probe sockets:	1 autojoint
Probe status indication:	1 LED
Cable connection:	Micro 'D' connector
Mounting options:	Shank to suit your CMM

Part number: A-1074-0020

Price: \$1,695



MH8

A manually indexable probe head with repeatable indexing, eliminating the need to requalify the stylus tip position after orientation. The MH8 can be used with the TP6 probe directly or with the TP20 probe with up to 50 mm extension. An easy upgrade, as there is no need for special software, cabling, or electronics.

2 σ positional repeatability:	1.5 μ m
Probe status indication:	1 LED
Cable connection:	5 pin DIN type connector
A-axis indexing:	0° to 90° in 15° steps = 7 positions
B-axis indexing:	\pm 180° in 15° steps = 24 positions
Total number of positions:	168
Maximum support capability:	TP6 mounted directly TP20 with PEL1 50 mm extension
Probe mounting:	M8 bush
Mounting options:	Shank to suit your CMM

Part number: A-1332-0002

Price: \$3,385



MIH

A manually indexable head, repeatable in 720 positions over two axes with LCD display, the MIH is designed for use with the autojoint TP6A touch probe and long extensions for large components. TP2, TP6, TP20 touch probes can be used with the addition of the PAA1 or PAA2 extensions.

2 σ positional repeatability:	1 μ m
Probe status indication:	1 LED
Cable connection:	5 pin DIN 180° socket
A-axis indexing:	105° to 0° in 7.5° steps = 15 positions
B-axis indexing:	\pm 180° in 7.5° steps = 48 positions
Probe mounting:	Autojoint
Mounting options:	Shank to suit your CMM

Part number: A-1070-0003

Price: \$6,776



MH20

The MH20 is an ultra-compact manually adjustable probe head offering maximum flexibility in probe orientation. The full range of TP20 probe modules can be used via its integral probe mounting. The MH20 is incompatible with the MCR20.

Probe mounting:	TP20 kinematic mount
Head mounting:	MS/T range of shanks
Suitable interfaces:	PI4-2, PI200-3 or PI7-3
Number of probe sockets:	1
Probe status indication:	1 LED
Cable connection:	5 pin DIN 180° socket
A-axis indexing:	Non-indexing swivel $\pm 93^\circ$
B-axis indexing:	Non-indexing swivel $\pm 300^\circ$
Maximum extension bar:	EM2 extension module – 75 mm (2.95 in)



MH20 head with low force module

Part number: A-4043-0000 **Price:** \$4,090

MH20 head with standard force module

Part number: A-4043-0100 **Price:** \$4,090

MH20 head with medium force module

Part number: A-4043-0200 **Price:** \$4,090

MH20 head with extended force module

Part number: A-4043-0300 **Price:** \$4,090

MH20i

The MH20i offers the significant advantage of repeatable indexing positions, vastly improving productivity for multi-orientation measurement applications. The MH20i is incompatible with the MCR20.

Probe mounting:	TP20 kinematic mount
Head mounting:	MS range of shanks
Suitable interfaces:	PI4-2, PI200-3 or PI7-3
Number of probe sockets:	1
Probe status indication:	1 LED
Cable connection:	5 pin DIN 180° socket
A-axis indexing:	0° to 90° in 15° repeatable steps
B-axis indexing:	180° in 15° repeatable steps
Repeatability of position:	1.5 µm (0.00006 in) with TP20 and 10 mm stylus 2.5 µm (0.0001 in) with EM2 extension module and 10 mm stylus
Maximum extension bar:	EM2 extension module – 75 mm (2.95 in)



MH20i head with low force module

Part number: A-4099-0000 **Price:** \$4,760

MH20i head with standard force module

Part number: A-4099-0100 **Price:** \$4,760

MH20i head with medium force module

Part number: A-4099-0200 **Price:** \$4,760

MH20i head with extended force module

Part number: A-4099-0300 **Price:** \$4,760

RTP20

Renishaw's new RTP20 compact head for DCC coordinate measuring machines (CMMs) offers low-cost 'motorized' head functionality and integral TP20 touch-trigger probe.

The new RTP probe head allows the integral probe to be moved to 168 repeatable positions in 15° increments using both A and B axes, allowing a one-time qualification for a stylus tip position. This eliminates the need for costly time-consuming requalification routines, ensuring fast throughput for part inspection. Users can therefore easily access features to be measured and optimize system performance by ensuring the probe is applied to the surface at the best angle to achieve accurate measurements.



Probe mounting:	TP20 kinematic mount
Head mounting:	MS range of shanks
Suitable interfaces:	PI4-2, PI200-3 or PI7-3
Number of probe sockets:	1
Probe status indication:	1 LED
Cable connection:	5 pin DIN 180° socket
A-axis indexing:	0° to 90° in 15° repeatable steps
B-axis indexing:	180° in 15° repeatable steps
Repeatability of position:	1.5 µm (0.00006 in) with TP20 and 10 mm stylus 2.5 µm (0.0001 in) with EM2 extension module and 10 mm stylus
Maximum extension bar:	EM2 extension module – 75 mm (2.95 in)

RTP20 rack kit

Includes: RTP20 head
Shank (various types)
Pole
Pole adaptor (various types)
MCR20 rack
2 × TP20 modules (standard, medium, extended or low)
2 × M2 stylus spanners
2 × M4 stylus spanners
Cleaning kit

Part number: A-5400-#### (see overleaf) **Price:** \$7,200

(Additional charge for 6-way module \$78 per module)

RTP20 non-rack kit

Includes: RTP20 head
Shank (various types)
Pole
Pole adaptor (various types)
1 × TP20 module (standard, medium, extended or low)
2 × M2 stylus spanners
2 × M4 stylus spanners
Cleaning kit

Part number: A-5400-8#### (see overleaf) **Price:** \$6,300

(Additional charge for 6-way module \$78 per module)

RTP20 part numbers

Non-rack kit

A-5400-8###

This number represents the TP20 module required:

- 1 = Low force module
- 2 = Standard force module
- 3 = Medium force module
- 4 = Extended force module
- 5 = 6-way module
- 6 = EM1 module
- 7 = EM2 module

These numbers represent the shank required:

- 01 = MS1 shank
- 02 = MS2 shank
- 03 = MS3 shank
- 04 = MS4 shank
- 05 = MS5 shank
- 06 = MS6 shank
- 07 = MS7 shank
- 08 = MS8 shank
- 09 = MS9 shank
- 10 = MS10 shank
- 11 = MS11 shank
- 12 = MS12 shank
- 13 = MS13 shank
- 14 = MS14 shank
- 15 = MS15 shank
- 16 = MS7(S) shank
- 17 = MS17 shank
- 18 = MS1(S) shank
- 19 = no shank

PLUS the pole adaptor required:

- +0 = M8 pole adaptor
- +20 = M6 pole adaptor
- +40 = 5/16 pole adaptor
- +60 = 3/8 pole adaptor
- +80 = M10 pole adaptor

Example

RTP20 with:

- No rack (8)
- Standard force module (2)
- MS3 shank + M6 pole adaptor (03 + 20 = 23)

= **A-5400-8223**

Rack kit

A-5400-####

This number represents the first TP20 module required:

- 1 = Low force module
- 2 = Standard force module
- 3 = Medium force module
- 4 = Extended force module
- 5 = 6-way module
- 6 = EM1 module
- 7 = EM2 module

This number represents the second TP20 module required:

- 1 = Low force module
- 2 = Standard force module
- 3 = Medium force module
- 4 = Extended force module
- 5 = 6-way module
- 6 = EM1 module
- 7 = EM2 module

These numbers represent the shank required:

- 01 = MS1 shank
- 02 = MS2 shank
- 03 = MS3 shank
- 04 = MS4 shank
- 05 = MS5 shank
- 06 = MS6 shank
- 07 = MS7 shank
- 08 = MS8 shank
- 09 = MS9 shank
- 10 = MS10 shank
- 11 = MS11 shank
- 12 = MS12 shank
- 13 = MS13 shank
- 14 = MS14 shank
- 15 = MS15 shank
- 16 = MS7(S) shank
- 17 = MS17 shank
- 18 = MS1(S) shank
- 19 = no shank

PLUS the pole adaptor required:

- +0 = M8 pole adaptor
- +20 = M6 pole adaptor
- +40 = 5/16 pole adaptor
- +60 = 3/8 pole adaptor
- +80 = M10 pole adaptor

Example

RTP20 with:

- Rack
- Low force module (1)
- Standard force module (2)
- MS1(S) shank + M10 pole adaptor (18 + 80 = 98)

= **A-5400-1298**

See pages 1-44 to 1-46 for information on the shank type for your machine.

Please call Customer Service on 847-286-9953 for part number assistance.

Motorized probe heads

PH10T PLUS

The new PH10T PLUS motorized probe head allows complete, rapid, and repeatable inspection of most complex components with minimum human intervention. Full orientation of your TP2, TP6, TP20 or TP200 probe between any of 720 positions, under manual or program control, turns your 3 axis CMM into a 5 axis machine.

2 σ positional repeatability:	0.4 μ m
Cycle time (90° move):	3.5 seconds
Total angular movement:	A axis 105° to 0° in 7.5° steps = 15 positions B axis \pm 180° in 7.5° steps = 48 positions
Total number of positions :	720
Maximum extension bar length:	300 mm using PEL4 extension*
Head mounting:	Shank to suit your CMM
Probe mounting facility:	M8 thread
Probe head control:	PHC10-3 PLUS (purchased separately)
Dimensions:	Length 102 mm excluding AM1, width 62 mm
Weight:	645 g

Part number: A-5863-2000

Price: \$19,293



PH10M PLUS

The PH10M PLUS motorized probe head has been developed for the new generation of contact and non-contact scanning probes. It has three times the torque of PH10 PLUS, allowing probe extension bars up to 300 mm long to be used.

The PH10M PLUS has an autojoint mounting.

2 σ positional repeatability:	0.4 μ m
Cycle time (90° move):	3.5 seconds
Total angular movement:	A axis: 105° to 0° in 7.5° steps = 15 positions B axis: \pm 180° in 7.5° steps = 48 positions
Total number of positions:	720
Maximum extension bar length:	300 mm using PAA3 extension*
Head mounting:	Shank to suit your CMM
Probe mounting facility:	Autojoint
Probe head control:	PHC10-3 PLUS (purchased separately)
Dimensions:	Length 102 mm excluding AM1, width 62 mm
Weight:	645 g

Part number: A-5863-1000

Price: \$21,881



* On all the PH10 PLUS series of probe heads, it is possible to extend beyond 300 mm using our range of CF extensions.

PH10MQ PLUS

The PH10MQ PLUS can be mounted vertically inside the CMM's quill for a greater working envelope by increasing the Z axis travel. The specification of the PH10MQ PLUS is identical to that of the PH10M PLUS, with the following exceptions:

Head mounting: Direct to quill
Dimensions: Length 73 mm, width 80 mm
Weight: 730 g

Part number: A-5863-3000

Price: \$21,881

PH10M-iQ PLUS

PH10M-iQ PLUS functions identically to a traditional PH10M PLUS but with the addition of inferred qualification technology. Inferred qualification increases throughput by removing the need to qualify each head position that is used in a measurement program.

PH10M-iQ PLUS works with all PH10M compatible probes, but only touch-trigger probe configurations can utilize inferred qualification. Scanning probes can be used in traditional PH10M qualification mode but cannot use inferred qualification.

Part Number: A-1025-1800

Price: \$24,723



Motorized probe head accessories

AM1/AM2

The AM1 adjustment module is designed for use with the PH10T and PH10M probe heads. The AM2 is designed for the PH10MQ probe heads. Each module provides quick and accurate angular alignment of the motorized probe head with the CMM's axes and/or the autochange rack. The quick release mechanism allows the head to be removed for storage and replaced without further alignment.



	AM1	AM2
Size:	60 mm x 15.5 mm	80 mm x 10 mm
Adjustment:	±2° in pitch and roll* ±4.5° in yaw	±1° in pitch and roll ±1° in yaw
Overtravel:	±3.5° in pitch and roll	0
Mounting:	Mounts to quill using shank	Mounts direct to quill


* Up to ±5.5° in pitch and roll is possible, but at the expense of overtravel.

Part number: A-1026-0320 (AM1)

Price: \$780

Part number: A-1036-0080 (AM2)

Price: \$780



PHC10-3 PLUS

The PHC10-3 PLUS head control receives instructions and processes signals to rotate the angles of the PH10 PLUS series probe heads. The PHC10-3 PLUS is compatible with all PH10 PLUS heads. It has its own internal power supply.

Data transmission:	RS232 or USB
Input connectors:	15 way 'D' probe
Output connectors:	7 pin DIN or 9 pin D type
Maximum cable length:	50 m (164 ft)
Hand control:	HCU1 (purchased separately)



Part number: A-5863-0100

Price: \$2,966

PHC10-3 PLUS with internal PI200-3

This variant of the PHC10-3 PLUS controller includes a prefitted PI200-3 interface card in a single 1U case.

Part number: A-5863-0200

Price: \$3,750

HCU2

The HCU2 hand control unit enables the probe head to be used in a manual mode or during a teach cycle. An LCD dot matrix display provides information and status of the PHC10-3 system.

Part number: A-5882-0010

Price: \$766



MCUlite-2 joystick

Part number: A-5331-0015 **Price:** \$691

MCU5 joystick kit

Part number: A-5121-0003 **Price:** \$2,073

MCU5-2 joystick kit

Part number: A-5734-0100 **Price:** \$2,073

MCU-W wireless joystick kit (no batteries)

Part number: A-5121-0077 **Price:** \$3,579

MCU-W2 wireless joystick kit (no batteries)

Part number: A-5734-0200 **Price:** \$3,579

MCU-W battery (2 pack)

Part number: A-5121-0079 **Price:** \$368

MCU-W 1 battery

Part number: A-5121-0084 **Price:** \$193

PL163

5 meter cable for MCU.

Part number: A-1016-8098 **Price:** \$178

PL164

10 meter cable for MCU.

Part number: A-1016-8099 **Price:** \$274

PL171

20 meter cable for MCU.

Part number: A-1016-8100 **Price:** \$461

12U retrofit cabinet

Part number: A-5567-1000 **Price:** \$2,501



PH20

PH20 is another innovative measurement product from Renishaw that transforms coordinate measuring machine (CMM) performance. For the first time, 5-axis technology developed for the multi-award winning REVO® measurement system is available for touch-trigger applications on all sizes of CMM.

PH20's unique 'head touches' allow measurement points to be taken by moving only the head rather than the CMM structure. Using only the rapid rotary motion of the head, points can be taken faster, and with improved accuracy and repeatability. Furthermore, 5-axis motion eliminates time spent indexing the head. Together these speed increases typically result in a three-fold improvement in throughput over conventional systems.

PH20's infinite positioning capability guarantees optimal feature access, minimizing stylus changes. Five-axis simultaneous motion allows larger parts to be measured on the CMM by minimizing the space required around the part for head rotation.

Users of the PH20 probe head will immediately have access to the range of proven TP20 probe modules, providing a wide selection of trigger forces, directional sensing options and extensions to meet application requirements*. The detachable modules provide crash protection and can be automatically changed using the MCR20 change rack.

* Excepting the extended force module

PH20 features and benefits

- Incorporates 5-axis measurement technology, minimizing CMM motion and the associated CMM dynamic errors.
- Infinite positioning and 5-axis motion reduces non-productive transitions between features.
- Infinite positioning and 5-axis motion aid access to difficult features.
- Rapid calibration with all positions inferred means more time measuring.
- Maximum reach up to 200 mm with maintained effective working length.
- Standard M2 styli for convenience.



Hardware integration

- The UCC controller is fundamental to the PH20 system.
- The UCC controller features routines particular to 5-axis motion and head-touch measurement.
- *MCUlite-2* is the multi-function hand control unit required for the system.
- PH20 can fit to any machine, either directly to the quill or via a shank using a range of mounting adaptors.
- The PH20 is compatible with the existing range of TP20 modules, excepting the extended force module.
- MCR20NI is the recommended rack for stylus changing, but it is possible to use an MCR20.
- No air supply is needed.

Software integration

- The Renishaw UCCserver™ software application will provide the interface for PH20 control.
- UCCserver is based on I++DME command protocol.
- PH20 is fully integrated with Renishaw's MODUSTM application software.

Specification summary		PH20	
Weight (excluding module and cables)		810 g (28.6 oz)	
Temperature range	Operating	15 °C to 35 °C (59 °F to 95 °F)	
	Storage	-25 °C to 70 °C (-13 °F to 158 °F)	
Maximum movement speed		3 revs/s (1281 mm/s with standard module and 10 mm stylus)	
Maximum head touch speed		50 mm/s	
Rotation angles	A axis	-115° to 115°	
	B axis	∞	
Angular resolution		0.4 μRadians	
Bearings		Mechanical	
Change rack system		TCR20 or MCR20 with TDA block	
Joystick		MCU <i>lite</i> -2, MCU5 or MCU-W	
ISO 10360-5 (2001) typical performance standard force module with 12 x 4 mm stylus on a CMM with ISO 10360-2 (2002) specification of 0.48+ L/1000*			
		CMM TOUCH	HEAD TOUCH
	Size	0.0006 mm (0.00002 in)	0.0002 mm (0.00001 in)
	Form	0.0026 mm (0.00010 in)	0.0024 mm (0.00009 in)
	Location	0.0013 mm (0.00005 in)	0.0009 mm (0.00003 in)

* specified with a TP7

PH20 head


Includes: PH20 head with standard force module
 TP20

Part number: A-5669-0001

Price: \$16,400



PH20 shanks



PH20 shank adaptor

Part number: A-3007-1715

Price: \$192

PH20 small quill adaptor

60 mm x 60 mm.

Part number: A-3007-1716

Price: \$192

PH20 large quill adaptor

80 mm x 80 mm.

Part number: A-3007-1717

Price: \$192

PH20 PH10MQ quill adaptor

Part number: A-3007-1720

Price: \$33

PH20 calibration stylus

Part number: A-5004-2182

Price: \$43

PH20 calibration sphere

Part number: A-1034-0026

Price: \$545

Rack for PH20

TCR20

Part number: A-1371-1001

Price: \$2,136



NOTE: See CMM probe shanks starting on page 1-44.

REVO-2

The 5-Axis REVO-2 system incorporating the REVO-2 head provides fast, ultra-high accuracy positioning.

REVO-2 system overview

The system comprises the following elements:

- REVO-2 head
- RSP2 2D tip sensing probe and associated stylus holders and accessories
- RSP3 3D probe and associated accessories
- **UCC** universal CMM controller
- REVO-2 PCI interface card (for **UCC**)
- **SPA** servo power amplifier
- Air filter unit

REVO-2 – ‘tip sensing’ probe technology

- Enclosed laser directed onto a reflector at the stylus tip.
- The stylus touches the part and bends.
- The reflector is displaced.
- The altered return path of the laser is sensed by a PSD.
- The exact tip position is known because the reflector and the stylus ball are close together.
- Stylus wear is minimized by using a low scanning force.

REVO-2 features and benefits:

- Incorporates **Renscan5™** five axis scanning technology minimizing CMM motion and the associated CMM dynamic errors
- Increased measuring speed, up to 500 mm/s resulting in increased measurement throughput
- Data collection rates up to 6,000 points per second
- Infinite positioning and five axis motion reduces non-productive transitions between features
- Stylus wear minimized by extremely low scanning forces
- Infinite positioning and five axis motion aid access to difficult features
- Rapid calibration with all positions inferred means more time measuring
- Maximum reach up to 500 mm with maintained effective working length
- Standard M2 styli for convenience
- Probe and stylus changing capability allowing flexibility and future probing technology compatibility



Hardware integration

- The **UCC** is fundamental to the REVO-2 system
- The **UCC** controller features **Renscan5™** scanning routines particular to five-axis motion and scanning
- **SPA** is a servo power amplifier used to drive the head and CMM
- **MCU** is the multi-function hand control unit required for the system

Software integration

- The Renishaw **UCCserver™** software application will provide the interface for REVO® control
- **UCCserver™** is based on I++DME command protocol

Specification summary		REVO-2			
Operating temperature		14 °C to 30 °C (57 °F to 86 °F)			
Storage temperature		-10 °C to 70 °C (14 °F to 158 °F)			
Weight (excluding probe and cables)		1.75 kg			
Dimensions	Height (overall)	239 mm (9.41 in)			
	B axis	86 mm (3.40 in) square			
	A axis swept diameter	118 mm (4.65 in)			
Air specification	Incoming supply to filter specification (ref: ISO8537.1)	Particle size	Class 4	15 µm	Line pressure of 6 bar to 6.5 bar
		Dirt concentration	Class 4	8 mg/m ³	
		Dewpoint	Class 4	3 °C	
		Oil	Class 4	5 mg/m ³	
	After filtration air specification (ref: ISO8537.1)	Particle size	Class 2	1 µm	Pressure 5 bar
		Dirt concentration	Class 2	1 mg/m ³	
		Dewpoint	Class 3	-20 °C	
		Oil	Class 2	0.1 mg/m ³	
Movement speed		3 revolutions per second			
Rotation angles	A axis	-5° to 120°			
	B axis	Continuous			
Angular resolution		0.08 arc second			
Bearings		Air			
Change rack system		Allowing both probe changing and stylus holder changing			

REVO-2 head kit

Includes: REVO-2®
RSP2
RSH250
45 mm diameter datum ball

Part number: A-5518-1095 **Price:** \$46,993

REVO-2 head only

Part number: A-5759-0001 **Price:** \$44,492

REVO® RSP2 V2 probe

Part number: A-3060-0028 **Price:** \$4,838

REVO® RSH250 stylus holder kit

Part number: A-3060-0021 **Price:** \$1,162

REVO® RSH350 stylus holder kit

Part number: A-3060-0022 **Price:** \$1,258

REVO® RSH500 stylus holder kit

Part number: A-3060-0023 **Price:** \$1,354

REVO® RSH175 stylus holder kit

Part number: A-3060-0024 **Price:** \$1,165

REVO® RSH450 stylus holder kit

Part number: A-3060-0026 **Price:** \$1,306

RSP3-1 REVO® probe kit

Includes: RSP3-1
PSH3-1

Part number: A-3060-0331 **Price:** \$6,773

RSP3-2 REVO® probe kit

Includes: RSP3-2
RSH3-2

Part number: A-3060-0332 **Price:** \$6,773

RSP3-3 REVO® probe kit

Includes: RSP3-3
RSH3-3

Part number: A-3060-0333 **Price:** \$6,773

RSP3-4 REVO® probe kit

Includes: RSP3-4
RSH3-4

Part number: A-3060-0334 **Price:** \$7,934

RSH3-1

Includes: PA25 - RSH3

Part number: A-3061-2521 **Price:** \$199

RSH3-2

Includes: PA25 - RSH3

Part number: A-3061-2522 **Price:** \$300

RSH3-3

Includes: PA25 - RSH3

Part number: A-3061-2523 **Price:** \$366

RSH3-4

Includes: PA25 - RSH3

Part number: A-3061-2524 **Price:** \$484

RSP3-6 probe kit

Includes: Probe
Portspacer

Part number: A-6084-0001 **Price:** \$10,643

REVO® RSH3-6C-500 (500 mm crank)

Part number: A-6084-0015 **Price:** \$968

REVO® RSH3-6C-600 (600 mm crank)

Part number: A-6084-0016 **Price:** \$1,016

REVO® RSH3-6-600 (600 mm straight)

Part number: A-6084-0006 **Price:** \$1,016

REVO® RSH3-6-700 (700 mm straight)

Part number: A-6084-0007 **Price:** \$1,064


REVO® RSH3-6-800 (800 mm straight)

Part number: A-6084-0008 **Price:** \$1,161

REVO® to REVO-2 upgrade kit

Includes: REVO-2
UCCS5 and PSU
SPA3
Blanking plate

Part number: A-1032-0025 **Price:** \$29,250



RVP vision probe for REVO-2

The REVO vision probe (RVP) provides non-contact vision measurement on an infinitely positioning, 5-axis platform. Now, tactile scanning measurement, surface finish analysis and non-contact inspection can all be performed on one CMM.

The RVP system is a breakthrough in technology in the world of non-contact CMM inspection. The combination of non-contact vision measurement and a 5-axis, infinitely positioning platform makes the RVP system truly unique.

RVP further expands the range of applications for the REVO-2 system with a non-contact edge detecting sensor automatically interchangeable with all other REVO probe options. As a result, the system provides the optimum tool to measure multiple features, and a wider variety of parts can be inspected.

System components

The RVP system comprises a vision probe body, a number of vision modules, rack ports and a calibration artefact. The image capture and processing components of the system are held inside the vision probe body and include an industry standard, robust, CMOS sensor for reliable image capture. The vision modules allow a range of features with different sizes and shapes to be inspected. All vision modules contain integral LED lighting to achieve a sharp contrast between holes and part material. Background feature enhancement is also available using backlighting combined with bespoke part fixturing.

Benefits

Added part inspection capability

Small features and delicate or flexible parts that cannot be measured using tactile probes can now be inspected on a 5-axis non-contact measurement platform.

Added value multi-sensor system

A machine equipped with REVO-2 can be used for a large range of inspection applications including scanning measurement, surface finish analysis and now, non-contact inspection.

High speed data collection

5-axis motion between part features and real time image processing dramatically increase data collection rates.



Innovations

5-axis movement, infinite positioning

RVP benefits from REVO's infinite positioning and 5-axis movement, which ensure accurate and unrestricted placement in front of features at any angle.

Automatically interchangeable sensors

The RVP non-contact probe is automatically interchangeable with all other probe options available for REVO-2, and data from multiple sensors is automatically referenced to a common datum.

3D surface reconstruction

5-axis motion and infinite positioning provide access to the data required for 3D surface reconstruction.

Probe specification	RVP
Weight	551 g
Dimensions	158 mm x 131 mm x 134 mm
Rack port compatibility	VPCP (heated)
Sensor type	1/1.8" CMOS sensor
Head compatibility	REVO-2
Operating temperature	+10°C to +40°C
Software compatibility	UCCsuite 5.0 onwards MODUS™ 1.7 onwards
Integration	I++ DME protocol

Module specification	VM10	VM11
----------------------	------	------



Weight	153 g	145 g
Dimensions	86 mm x 39 mm	75 mm x 67 mm
Rack port compatibility	VMCP (heated)	VMCP (heated)
Measurement range	1 mm diameter or greater	0.5 mm diameter or greater
Field of view	50 mm x 40 mm	12.5 x 10 mm
Stand-off	80 mm	120 mm
Depth of field	5 mm	5 mm
Resolution	40 µm	20 µm
LED illumination	24 LEDs	10 LEDs
Backlight compatibility	Yes	Yes

RVP probe

Part number: A-5378-0080 Price: \$27,090

VM10 vision module

Part number: A-5378-0082 Price: \$5,805

VM11 vision module

Part number: A-5378-0087 Price: \$7,256

VPCP vision probe change port

Part number: A-5378-0081 Price: \$1,838

VMCP vision module change port

Part number: A-5378-0083 Price: \$1,838

VA10 calibration artefact

Part number: A-5378-0085 Price: \$1,258

RVP kits

RVP combo kit

Includes: RVP probe

- VPCP vision probe change port
- VM10 vision module
- VM11 vision module
- VMCP vision module change port
- VA10 calibration artefact

Part number: A-5378-9504 **Price:** \$46,924

RVP VM10 kit

Includes: RVP probe

- VPCP vision probe change port
- VM10 vision module
- VMCP vision module change port
- VA10 calibration artefact


Part number: A-5378-9505 **Price:** \$37,829

RVP VM11 kit

Includes: RVP probe

- VPCP vision probe change port
- VM11 vision module
- VMCP vision module change port
- VA10 calibration artefact

Part number: A-5378-9506 **Price:** \$39,281



SFP2 surface finish probe

Enhanced access and inspection capability for integrated surface finish measurement.

The SFP2 probe increases the surface finish measurement ability of the REVO® system, which offers multi-sensor capability providing touch-trigger, high speed tactile scanning and non-contact vision measurement on a single CMM.

Powered by 5-axis measurement technology, the SFP2's automated surface finish inspection offers significant time savings, reduced part handling and greater return on CMM investment.

The SFP2 system consists of a probe and a range of modules and is automatically interchangeable with all other probe options available for REVO, providing the flexibility to easily select the optimum tool to inspect a wide range of features, all on one CMM platform. Data from multiple sensors is automatically referenced to a common datum.

The surface finish system is managed by the same I++ DME compliant interface as the REVO system, and full user functionality is provided by Renishaw's MODUS™ metrology software.

Key benefits

Unrivalled feature access

SFP2 benefits from REVO's infinite positioning and 5-axis movement, and features an integral motorized C-axis. The SFM variants offer a range of tip arrangements which, combined with the knuckle joint between module and holder, provide access to the features most difficult to reach.

Operator independent data collection

CMM programs can now include automated and operator-independent surface finish measurement. All results, including surface finish data, are recorded and stored in a single location for easy retrieval.

Greater return on investment in CMMs

Integrated surface finish and dimensional inspection can remove the need for dedicated surface measurement equipment, reducing factory footprint, part handling and associated costs.



Specification summary		SFP2 surface finish probe			
SFM-A1 and SFM-A2 modules	Surface finish range	0.05 – 6.3 µm Ra			
	Surface finish accuracy (of nominal Rs)	± (5% +15 nm)			
	Surface forces	Skid: 0.2 N	Stylus tip: 0.005 N		
	Encoder resolution	1 nm			
	Measurement range	1.0 mm			
	Measurement speed	Up to 1 mm/s			
	SFM range of adjustment	± 90° at the knuckle joint			
SFP2 probe	C-axis positioning accuracy	± 0.25°			
	C-axis rotation speed	Up to 90°/sec			
	Rotational capability	A-axis (from REVO-2)	+120° / –110°		
		B-axis (from REVO-2)	Infinite positioning		
		C-axis	± 180°		
	Mounting (probe and holder)	Magnetized coupling			
	Probe head	REVO-2 only			
Change rack	MRS2 recommended for full capability				
System features	Software compatibility	UCCsuite 5.2 onwards MODUS 1.8 onwards			
	Weight	SFP2 probe	SFH1 holder	SFM-A1 module	SFM-A2 module
		330 g	33 g	12 g	12 g
	Operating temperature range	+10 °C to +40 °C			
	Storage temperature range	–25 °C to +70 °C			
	Operating humidity	0% to 80% (non-condensing)			
	Calibration and verification artefacts	SFA1	3.0 µm Ra sinusoid		
		SFA2	0.5 µm Ra sinusoid		
		SFA3	0.4 µm Ra sawtooth		
		TFP	Uses LF TP20 module; PICS interface to SPA3 amplifier		
Outputs	MODUS basic	Ra, Rms(Rq)			
	MODUS standard surface texture	Rt, R3z, Rz, Rz1max, RzDIN, RzJIS, Rseg Rp, Rv Rpm, Rvm, Rc, Rsm			
	MODUS advanced surface texture	Rk, Rpk, Rvk, Rmr, Rmr1, Rmr2, Rpq, Rvq, Rmq, Rvoid, Rvdd, Rvddl, Rcvx, Rcvxl			
Sampling rate	4 kHz				

REVO® SFP2 base kit

Part number: A-5764-0005-KIT Price: \$27,471

REVO® SFP2 probe

Part number: A-5764-0010 Price: \$23,780

REVO® SFM-A1 (Straight, Type A)

Part number: A-5764-0020 Price: \$8,941

REVO® SFM-A2 (Crank, Type A, Skid)

Part number: A-5764-0021 Price: \$8,941

REVO® SFM-B1 (SM Straight, Type B, Skid)

Part number: A-5764-0025 Price: \$10,283

REVO® SFM-C2 (Straight, Type C Skid)

Part number: A-5764-0031 Price: \$12,965

REVO® SFM-D1 (90°, Type D, Skid)

Part number: A-5764-0035 Price: \$10,283

Single artefact kit (SFA1 and 1 AF holder)

Part number: A-5764-0072 Price: \$2,397

REVO® SFH-1 module holder

Part number: A-5764-0080 Price: \$1,332

REVO® SFH-2 module holder

Part number: A-5764-0081 Price: \$1,522

REVO® SFA1 3.0 sin artefact

Part number: A-5764-0060 Price: \$1,807

REVO® SFA2 0.5 sin artefact

Part number: A-5764-0061 Price: \$1,807

REVO® SFA3 0.4 ST artefact

Part number: A-5764-0062 Price: \$1,807

REVO® OFA optical flat artefact

Part number: A-5764-3142 Price: \$3,710

Triple artefact kit (SFA1,2,3 and 3 AF holder)

Part number: A-5764-0073 Price: \$6,106

REVO® single AF holder (SFAH-1, tools)

Part number: A-5764-0070 Price: \$590

REVO® triple AF holder (SFAH-2, tools)

Part number: A-5764-0071 Price: \$685

REVO® SF2 TFP probe kit (LF, PL24, styli)

Part number: A-5764-0063 Price: \$4,280

REVO® SF2 MST - module setting tool

Part number: A-5764-0091 Price: \$190

REVO® SF2 system storage box

Part number: A-5764-0090 Price: \$333

REVO® RCP TC-3 high force rack port

Part number: A-3061-0320 Price: \$1,807

MRS MPS1 port spacing tool

Part number: A-6084-0017 Price: \$60



Touch probes

TP1S/TP1SM

A robust and reliable probe which is especially suited for manual CMMs. It is available in two versions with differing plug socket orientations:

TP1S cable connects vertically

TP1SM cable connects horizontally

Sense directions: $\pm X, \pm Y, +Z$

2σ unidirectional repeatability: $0.5 \mu\text{m}$

Pre-travel variation: $\pm 2.0 \mu\text{m}$

Stylus force range: 10 g to 50 g

Stylus overtravel:
XY plane $\pm 19.5^\circ$
+Z axis 8.5 mm @ 15 g
5.0 mm @ 50 g

Suitable interfaces: PI4-2, PI7-3, or PI200-3

Stylus thread size: M3

Mounting option: Shank to suit your CMM

Test conditions: 31 mm stylus @ 8 mm/s with
trigger force of 15 g



Part number: A-1041-7540 (TP1S)

Price: \$3,316

Part number: A-1041-7541 (TP1SM)

Price: \$3,316

TP20/TP20 NI modular probes

The TP20 is a 5-way or 6-way kinematic touch-trigger probe. Its two piece design comprises a probe body and detachable stylus module(s) which gives the ability to change stylus configurations either manually or automatically without requalification of the stylus tips. It affords significant time savings in inspection routines.


A direct replacement for the industry standard Renishaw TP2 probe, the TP20 probe system brings a range of new benefits to manual and DCC CMM applications, and can easily be retrofitted to existing TP2 installations.

The TP20 can be used on a wide range of Renishaw's manual or motorized probe heads, either by direct mounting using the standard M8 thread or, alternatively, by using a PAA# adaptor to connect to an autojoint.

The system components are:

- TP20/TP20 NI probe body
- TP20 stylus module – seven module variants allow for optimization of performance to suit the application
- MCR20 module changing rack – automatic operation

The TP20 probe system may be used with Renishaw's PI 4-2, PI 7-2 or PI 200 probe interfaces.




TP20 probe body

The TP20 probe body houses one half of the highly repeatable magnetic kinematic coupling that attaches the stylus module and body. The body also contains a magnetic proximity switch to inhibit triggering of the probe during automatic module changing with MCR20.

Note: If the probe is operated close to magnetized parts/clamping etc, the probe trigger may become inhibited. Countermeasures include the use of long styli, stylus extensions or body orientation to increase the distance to the magnetic source. Alternatively, use the TP20 NI probe body.

TP20 NI probe body

The TP20 NI probe differs from the TP20 body in that it is not affected by magnetic fields. However the probe trigger must be inhibited through software during change cycles using the MCR20.



+Z overtravel

SF/EM1/EM2	4.0 mm (0.16 in)
LF	3.1 mm (0.12 in)
MF	3.7 mm (0.15 in)
EF	2.4 mm (0.09 in)
6W	4.5 mm (0.177 in)

-Z overtravel

6W	1.5 mm (0.06 in)
-----------	------------------

Specification summary		TP20	TP20 NI
Principal application		DCC and manual CMMs suitable for most applications	DCC and manual CMMs where operation is within a magnetic field
Sense directions	All modules except 6W 6W	±X, ±Y, +Z ±X, ±Y, ±Z	±X, ±Y, +Z ±X, ±Y, ±Z
Pre-travel variation	LF	±0.6 µm (±0.000023 in)	±0.6 µm (±0.000023 in)
	SF/EM1/EM2	±0.8 µm (±0.000032 in)	±0.8 µm (±0.000032 in)
	MF	±1.0 µm (±0.000039 in)	±1.0 µm (±0.000039 in)
	EF	±2.0 µm (±0.000079 in)	±2.0 µm (±0.000079 in)
	6W	±1.5 µm (±0.000058 in)	±1.5 µm (±0.000058 in)
Repeatability of stylus change (max)	With SCR200	±0.5 µm (±0.000020 in)	±0.5 µm (±0.000020 in)
	Manual	±1.0 µm (±0.000040 in)	±1.0 µm (±0.000040 in)
Stylus range		M2	M2
Probe mounting method		M8 thread	M8 thread
Suitable interface		PI 4-2, PI 7-2, PI 200	PI 4-2, PI 7-2, PI 200
Stylus module changing rack (automatic)		MCR20	MCR20
Stylus module storage rack (manual)		MSR1	MSR1




Module type and test stylus length	Trigger force		Overtravel force			Overtravel displacement			Unidirectional repeatability 2σ at stylus tip	2D (XY) form error
	XY	Z	XY	+Z	-Z	XY	+Z	-Z		
SF (black cap) 10 mm	0.08 N	0.75 N	0.2-0.3 N	3.5 N	-	±14°	4.0 mm (0.16 in)	-	0.35 µm (0.000014 in)	±0.8 µm (±0.000032 in)
LF (green cap) 10 mm	0.055 N	0.65 N	0.09 N	1.15 N	-	±14°	3.1 mm (0.12 in)	-	0.35 µm (0.000014 in)	±0.6 µm (±0.000024 in)
MF (grey cap) 25 mm	0.1 N	1.9 N	0.2-0.4 N	7.0 N	-	±14°	3.7 mm (0.15 in)	-	0.50 µm (0.000020 in)	±1.0 µm (±0.000039 in)
EF (brown cap) 50 mm	0.1 N	3.2 N	0.2-0.5 N	10.0 N	-	±14°	2.4 mm (0.09 in)	-	0.65 µm (0.000026 in)	±2.0 µm (±0.000079 in)
6W (blue cap) 10 mm	0.14 N	1.6 N	0.25 N	2.5 N	9.0 N	±14°	4.5 mm (0.18 in)	1.5 mm (0.059 in)	0.80 µm (0.000032 in)	±1.5 µm (±0.000059 in)
EM1 10 mm	0.08 N	0.75 N	0.2-0.3 N	3.5 N	-	±14°	4.0 mm (0.16 in)	-	0.35 µm (0.000014 in)	±0.8 µm (±0.000032 in)
EM2 10 mm	0.08 N	0.75 N	0.2-0.3 N	3.5 N	-	±14°	4.0 mm (0.16 in)	-	0.35 µm (0.000014 in)	±0.8 µm (±0.000032 in)

The above data applies for test conditions as follows:

Stylus length as stated above.

Stylus velocity 480 mm/min (1.57 ft/min)



TP20 probe kits

TP20 probe kit 1

Includes two standard force modules.

Part number: A-1371-0290 **Price:** \$3,875

TP20 probe kit 2

Includes one standard force and one medium force module.

Part number: A-1371-0291 **Price:** \$3,875

TP20 probe kit 3

Includes one standard force and one extended force module.

Part number: A-1371-0292 **Price:** \$3,875

TP20 probe kit 4

Includes two medium force modules.

Part number: A-1371-0293 **Price:** \$3,875

TP20 probe kit 5

Includes one medium force and one extended force module.

Part number: A-1371-0294 **Price:** \$3,875

TP20 probe kit 6

Includes two extended force modules.

Part number: A-1371-0295 **Price:** \$3,875

TP20 probe kit 7

Includes one standard force and one 6-way module.

Part number: A-1371-0418 **Price:** \$4,198

TP20 non-inhibit (NI) probe kits

TP20 non-inhibit probe kit 1

Includes two standard force modules.

Part number: A-1371-0640 **Price:** \$3,875

TP20 non-inhibit probe kit 2

Includes one standard force and one medium force module.

Part number: A-1371-0641 **Price:** \$3,875

TP20 non-inhibit probe kit 3

Includes one standard force and one extended force module.

Part number: A-1371-0642 **Price:** \$3,875

TP20 non-inhibit probe kit 4

Includes two medium force modules.

Part number: A-1371-0643 **Price:** \$3,875

TP20 non-inhibit probe kit 5

Includes one medium force and one extended force module.

Part number: A-1371-0644 **Price:** \$3,875

TP20 non-inhibit probe kit 6

Includes two extended force modules.

Part number: A-1371-0645 **Price:** \$3,875

TP20 accessories

TP20 probe modules

Standard force probe module

Part number: A-1371-0270 **Price:** \$969

Medium force probe module

Part number: A-1371-0271 **Price:** \$969

Extended force probe module

Part number: A-1371-0272 **Price:** \$969

Low force module

This module has a lower trigger force for use on components where a low probing force is needed.

Part number: A-1371-0392 **Price:** \$969

6-way probe module

Part number: A-1371-0419 **Price:** \$1,292

EM1 module only kit

This module is based on the standard force module with an integral 50 mm carbon fiber extension piece.

Part number: A-1371-0430 **Price:** \$1,173

EM2 module only kit

This module is based on the standard force module with an integral 75 mm carbon fiber extension piece.

Part number: A-1371-0431 **Price:** \$1,211

EM1/EM2 kit

Includes: TP20 EM1 standard module assembly
TP20 EM2 standard module assembly
Test certificate
EM1/EM2 user's information

Part number: A-1371-0432 **Price:** \$2,153

Cleaning kit

Part number: A-1085-0016 **Price:** \$18

MCR20

The MCR20 module changing rack provides rapid automatic changing of probe modules without the need to requalify. Rack function is completely passive and does not require any electrical connections.

Installation and set-up of the system is achieved with minimal operator skill as no special software or communications are required. The rack base and docking port assembly incorporate hinged overtravel mechanisms to assist crash protection. The kits include two probe modules, a mounting kit, a location plate, and a PS2R stylus.

Mounting fixture:	Single stud
Number of ports:	6
Repeatability of module change:	Automatic $\leq 1 \mu\text{m}$ Manual $\leq 2 \mu\text{m}$



MCR20 probe module change rack kits

MCR20 module change rack kit 1

Includes two standard force modules.

Part number: A-1371-0261 **Price:** \$5,263

MCR20 probe module change rack kit 2

Includes one standard force and one medium force module.

Part number: A-1371-0262 **Price:** \$5,263

MCR20 probe module change rack kit 3

Includes one standard force and one extended force module.

Part number: A-1371-0263 **Price:** \$5,263

MCR20 probe module change rack kit 4

Includes two medium force modules.

Part number: A-1371-0264 **Price:** \$5,263

MCR20 probe module change rack kit 5

Includes one medium force and one extended force module.

Part number: A-1371-0265 **Price:** \$5,263

MCR20 probe module change rack kit 6

Includes two extended force modules.

Part number: A-1371-0266 **Price:** \$5,263

MCR20 location plate

Part number: M-1085-0301 **Price:** \$10

TP2 5-way

TP2 5-way is the industry-standard probe for most CMM applications. Its compact dimensions are ideal for probing into restricted component features.

Sense directions:	5-way ($\pm X$, $\pm Y$, $+Z$)
2σ unidirectional repeatability:	0.35 μm
Pre-travel variation:	$\pm 0.80 \mu\text{m}$
Stylus force range:	7 g to 15 g
Stylus overtravel:	XY plane $\pm 14^\circ$ +Z axis 4.5 mm @ 7 g 3.0 mm @ 15 g
Mounting options:	M8 thread
Stylus thread size:	M2
Suitable interface:	PI4-2, PI7-3 or PI200-3
Test conditions:	10 mm stylus @ 8 mm/s with trigger force of 7 g to 8 g

Part number: A-1042-1890

Price: \$3,641



TP6/TP6A

The TP6 combines the robust characteristics of the TP1(S) with the repeatability of the TP2. It can be used on manual or DCC CMMs along with Renishaw's vast range of heads and extensions. The TP6A incorporates an autojoint for use with the Renishaw autochange system, or for manual probe changing. The TP6A allows for fast probe exchange without redatuming.

Sense directions:	$\pm X$, $\pm Y$, $+Z$
2σ unidirectional repeatability:	0.35 μm
Pre-travel variation:	$\pm 1.0 \mu\text{m}$
Stylus force range:	10 g to 30 g
Stylus overtravel:	XY plane $\pm 22^\circ$ +Z axis 6.5 mm @ 12 g 3.0 mm @ 30 g
Mounting options:	TP6 M8 thread TP6A Autojoint
Stylus thread size:	M3
Test stylus length:	21 mm
Suitable interface:	PI4-2, PI7-3, PI200-3
Test conditions:	21 mm stylus @ 8 mm/s with trigger force of 11 g to 13 g

Part number: A-1039-0001 (TP6)

Price: \$3,522

Part number: A-1039-0028 (TP6A)

Price: \$3,641



TP7M

The TP7M is designed to maintain a high level of accurate and reliable performance across a wide range of conditions. The TP7M must be used with either the PH10M probe head or a PH6M fixed head.

Sense directions:	±X, ±Y, ±Z	
2σ unidirectional repeatability:	High sensitivity	0.25 μm
	Mid sensitivity	0.25 μm
Pre-travel variation:	High sensitivity	±0.25 μm
	Mid sensitivity	±0.50 μm
Trigger force:	XY plane	2 g
	Z axis	15 g
Overtravel force:	XY plane	50 g
	Z axis	300 g
Stylus overtravel:	XY plane	16°
	+Z axis	5 mm
	-Z axis	5 mm
Max. extension on PH10M:	200 mm	
Mounting options:	Autojoint	
Stylus thread size:	M4	
Test stylus length:	50 mm	
Suitable interface:	PI7-3 only	
Test conditions:	50 mm stylus @ 8 mm/s	



TP7M probe kit

Part number: A-1073-0121

Price: \$5,370

TP7M EP

The TP7M EP (enhanced performance) is capable of achieving a 3D accuracy of <0.6 μm tested to ISO 10360 Pt 2.

TP7M EP probe kit

Part number: A-1073-0261

Price: \$6,657

TP200/TP200B modular probes

The TP200 and TP200B are electronic probes using strain gauge technology which gives higher accuracy than kinematic touch-trigger probes. They combine outstanding metrology performance with superior functionality to produce a highly versatile DCC CMM probing system with excellent productivity.

The TP200 system components are:

- TP200 probe body – the standard model
- TP200B probe body – a variant model with increased vibration tolerance
- TP200 stylus module – choice of fixed overtravel forces: 'SF' (standard force) or 'LF' (low force)
- PI 200 probe interface
- SCR200 stylus changing rack



TP200 probe body

The TP200 probe incorporates micro strain gauge transducers delivering excellent repeatability and accurate 3D form measurement even with long styli. The sensor technology gives sub-micron triggering performance and eliminates the lobing characteristics encountered with standard probes. The solid state ASIC electronics within the probe ensure reliable operation over millions of trigger points.

TP200B probe body

The TP200B probe uses the same technology as TP200 but has been designed to have a higher tolerance to vibration. This helps to overcome the problem of 'air' trigger generation which can arise from vibrations transmitted through the CMM or when using longer styli with faster positioning speeds. Please note that we do not recommend the use of TP200B with the LF module or cranked/star styli.

Measuring performance			TP200	TP200B	
Principal application			DCC CMM where high accuracy measurement is required	As TP200 but where 'air' * trigger events occur	
Sense directions			6-way: $\pm X, \pm Y, \pm Z$	6 way: $\pm X, \pm Y, \pm Z$	
Unidirectional repeatability (2 σ μ m)	Trigger level 1	0.4 μ m	(0.000016 in)	0.4 μ m	(0.000016 in)
	Trigger level 2	0.5 μ m	(0.000020 in)	0.5 μ m	(0.000020 in)
XY (2D) form measurement deviation	Trigger level 1	± 0.8 μ m	(0.000032 in)	± 1.0 μ m	(0.000040 in)
	Trigger level 2	± 0.9 μ m	(0.000036 in)	± 1.2 μ m	(0.000047 in)
XYZ (3D) form measurement deviation	Trigger level 1	± 1.0 μ m	(0.000040 in)	± 2.5 μ m	(0.000100 in)
	Trigger level 2	± 1.4 μ m	(0.000056 in)	± 4.0 μ m	(0.000160 in)
Repeatability of stylus change	With SCR200	± 0.5 μ m	(0.000020 in) max	± 0.5 μ m	(0.000020 in) max
	Manual	± 1.0 μ m	(0.000040 in) max	± 1.0 μ m	(0.000040 in) max
Trigger force	XY plane	All modules	0.02 N	0.02 N	
	Z axis	All modules	0.07 N	0.07 N	
Overtravel force (@ 0.5 mm displacement)	XY plane	SF/EO module	0.2 N - 0.4 N	0.2 N - 0.4 N	
		LF module	0.1 N - 0.15 N	0.1 N - 0.15 N	
	Z axis	SF/EO module	4.9 N	4.9 N	
		LF module	1.6 N	1.6 N	
Weight (probe sensor + module)			22 g (0.8 oz)	22 g (0.8 oz)	
Max. extension (if on PH10 series head)			300 g (11.8 oz)	300 g (11.8 oz)	
Max. recommended stylus length (M2 stylus range)	SF/EO module	50 mm (1.97 in) steel - 100 mm (3.94 in GF)		50 mm (1.97 in) steel - 100 mm (3.94 in GF)	
	LF module	20 mm (0.79 in) steel - 50 mm (1.97 in GF)		20 mm (0.79 in) steel - 50 mm (1.97 in GF)	
Probe mounting method			M8 thread	M8 thread	
Suitable interface			PI 200	PI 200	
Stylus module changing rack (automatic)			SCR200	SCR200	
Stylus module storage rack (manual)			MSR1	MSR1	

The above data applies for test conditions as follows:

Stylus length 50 mm (1.97 in)
Stylus velocity 480 mm/min (1.57 ft/min)

* Air trigger (or false trigger). The TP200B reduces triggers that may be caused by vibrations.

TP200/TP200B probe kits

TP200 probe with standard force module

Part number: A-1207-0001 Price: \$4,516

TP200 probe with low force module

Part number: A-1207-0002 Price: \$4,516

TP200B probe with standard force module

Part number: A-1207-0055 Price: \$4,516

TP200 accessories

Standard force stylus module

Part number: A-1207-0010 Price: \$678

Low force stylus module

Part number: A-1207-0011 Price: \$678

TP200 probe cleaning kit

Part number: A-1085-0016 Price: \$18

GF stylus kit *

Part number: A-5003-2310 Price: \$710

*See Stylus section for kit contents.

SCR200

The SCR200 stylus changing rack provides rapid, automatic changing of styli without the need to requalify probe tips. Installation and set-up of the system are achieved with minimal operator skill, as no special CMM cabling, software or communications are required. The SCR200 is powered and serviced entirely by the PI200-3 interface and is fully crashed protected.



Mounting:	Horizontal or vertical
Mounting fixture:	Single stud
Number of ports:	6
Module location and retention:	Magnetic
Repeatability of stylus change (2σ) at 50 mm:	Automatic: 1 μ m
	Manual: 2 μ m
Change cycle:	<2 seconds

SCR200 kit

Includes: 3 stylus changing modules
Mounting kit
PS2R stylus
Location plate

Part number: A-1207-0030 (standard force modules) **Price:** \$8,692
Part number: A-1207-0070 (low force modules) **Price:** \$8,692

SCR200 stylus changing rack only

Part number: A-1085-0370 **Price:** \$6,855

SCR200 datum stylus (PS35R)

Part number: A-5000-7812 **Price:** \$147

SCR200 cables

Part number: A-1016-7630 (PL63S – 5 m) **Price:** \$104
Part number: A-1016-7631 (PL64S – 10 m) **Price:** \$119
Part number: A-1016-7632 (PL65S – 20 m) **Price:** \$156

SCR200 mounting kit

Part number: A-1085-0005 **Price:** \$19

SCR200 location plate

Part number: M-1085-0301 **Price:** \$10

Special probing systems

SP25

The SP25M is actually two sensors in one! – enabling the user to SCAN for form measurement or reverse engineering and TOUCH-TRIGGER PROBE (TTP) for geometry.

Highly accurate scanning performance with (M3) stylus lengths from 20 mm to 200 mm together with the ability to carry Renishaw's TP20 range of touch-trigger probe modules mean that the SP25M system provides unmatched flexibility to optimize a measurement solution to suit the application.

The probe is just 25 mm in diameter, compatible with Renishaw's PH10M/MQ, PH6M and PHS1 probe heads, and can also be mounted using a multiwired extension bar. Together these combinations permit excellent reach and access to part features.

Physical measurement range: ± 0.5 mm deflection in all directions in all orientations

Physical overtravel range: X,Y ± 2.0 mm
+Z 1.7 mm
-Z 1.2 mm

Resolution: Capable of < 0.1 μ m

Spring rate: 0.6 N/mm to 0.2 N/mm – dependent on stylus length

Dimensions: $\varnothing 25$ mm x length dependent on module used

Mass: SP25M body	65 g
SM25-1 scan module	35 g (includes SH25-1, but excludes stylus)
SM25-2 scan module	40 g (includes SH25-2, but excludes stylus)
SM25-3 scan module	49 g (includes SH25-3, but excludes stylus)
TM25-20 TTP module	40 g (includes TP20 standard module, but excludes stylus)

Mounting: Multiwired autojoint connection

- compatible with PH10M PLUS, PH10MQ PLUS, and PH6M
- may be mounted to autojoint extension bars

Signal outputs: Non-linear and non-orthogonal analog outputs – rate, gain and resolution are not fixed

Interface: AC3 card



SP25M special SCAN/TTP full combination kit

The full scanning system plus the capability to use TP20 modules – this kit includes all the equipment in these separate kits and is supplied as one complete kit:

1 x A-2237-1001	SP25M scanning probe kit #1 (includes SM25-1 kit)
1 x A-2237-1102	SM25-2 scanning module kit
1 x A-2237-1103	SM25-3 scanning module kit
1 x A-2237-1200	TM25-20 TTP module adaptor ONLY (to directly carry any TP20 module)

Part number: A-2237-1015

Price: \$17,934

SP25M scanning probe kit #1 (entry level kit)

Includes: 1 x SP25M probe body
1 x SM25-1 scanning module kit (see below)

Part number: A-2237-1001 **Price:** \$10,362

SP25M scanning probe kit #2 (entry level kit)

Includes: 1 x SP25M probe body
1 x SM25-2 scanning module kit (see below)

Part number: A-2237-1002 **Price:** \$10,362

SP25M scanning probe kit #3 (entry level kit)

Includes: 1 x SP25M probe body
1 x SM25-3 scanning module kit (see below)

Part number: A-2237-1003 **Price:** \$10,362

SP25M scanning probe kit #4 (entry level kit)

Includes: 1 x SP25M probe body
1 x SM25-4 scanning module kit (see below)

Part number: A-2237-1004 **Price:** \$12,189

SM25-1 scanning module kit

Includes: 1 x SM25-1
2 x SH25-1

Part number: A-2237-1101 **Price:** \$4,765

SM25-2 scanning module kit

Includes: 1 x SM25-2
2 x SH25-2

Part number: A-2237-1102 **Price:** \$4,765

SM25-3 scanning module kit

Includes: 1 x SM25-3
2 x SH25-3

Part number: A-2237-1103 **Price:** \$4,765



SM25-4 full module kit

Includes: 1 x SM25-4
2 x SH25-4
full stylus kit containing:
1 x M3 stylus D5R L21 EWL21 d2.5SS
1 x M3 stylus D5R L50 EWL50 d2.5CE
1 x M3 stylus D10R L200 EWL200 d4C/F
1 x M3 stylus D10R L150 EWL150 d4C/F
1 x M3 stylus D10R L100 EWL100 d4C/F
1 x M3 stylus D10R L75 EWL75 d4C/F
2 x M2-M3 stylus tools

Part number: A-2237-1104 **Price:** \$7,756

SM25-4 entry level module kit

Includes: 1 x SM25-4
1 x SH25-4
basic stylus kit containing:
1 x M3 stylus D5R L21 EWL21 d2.5SS
1 x M3 stylus D10R L100 EWL100 d4C/F
2 x M2-M3 stylus tools

Part number: A-2237-1108 **Price:** \$6,084

SM25-4 basic module kit

Includes: 1 x SM25-4
2 x SH25-4
basic stylus kit containing:
1 x M3 stylus D5R L21 EWL21 d2.5SS
1 x M3 stylus D10R L100 EWL100 d4C/F
2 x M2-M3 stylus tools

Part number: A-2237-1109 **Price:** \$6,582

SM25-5 scanning module kit

Includes: 1 x SM25-5
2 x SH25-5

Part number: A-2237-1105 **Price:** \$6,016

TM25-20 TTP module adaptor only

Part number: A-2237-1200 **Price:** \$3,392

TM25-20 TTP module adaptor kit #1

Includes: 1 x TM25-20
2 x TP20 standard modules

Part number: A-2237-1201 **Price:** \$4,765

SM25-1 scanning module only

Part number: A-2237-1111 **Price:** \$4,432

SM25-2 scanning module only

Part number: A-2237-1112 **Price:** \$4,432

SM25-3 scanning module only

Part number: A-2237-1113 **Price:** \$4,432

SM25-4 scanning module only

Part number: A-2237-1114 **Price:** \$5,185

SM25-5 scanning module only

Part number: A-2237-1115 **Price:** \$5,730

SH25-1 stylus holder only

Part number: A-2237-1301 **Price:** \$199

SH25-2 stylus holder only

Part number: A-2237-1302 **Price:** \$300

SH25-3 stylus holder only

Part number: A-2237-1303 **Price:** \$366

SH25-4 stylus holder only

Part number: A-2237-1304 **Price:** \$484

SH25-5 stylus holder only

Part number: A-2237-1305 **Price:** \$258

AC3 interface card

Part number: A-2237-1601 **Price:** \$3,325

FCR25

The full potential of the SP25M system may be realized when the flexible change rack option is incorporated. Based on the versatile FCR25 triple-port rack unit, which allows any of the SP25M system elements to be rapidly exchanged in any of the ports, this is undoubtedly the most adaptable rack system yet from Renishaw. The FCR25 mounts directly to Renishaw's MRS modular rack system. Alternatively, compact 3-port and 6-port 'standalone' racks are available which incorporate FCR25.



FCR25 flexible change rack unit

Triple-port unit for MRS system.

Includes: 1 × FCR25
3 × PA25-SH
3 × PA25-20

Note: Requires an MRS kit for CMM mounting.

Part number: A-2237-1401

Price: \$2,549



FCR25 TC

Thermally controlled FCR25 for use with SM25 modules only.

Part number: A-2237-1408

Price: \$2,893

FCR25-L3 3-port standalone change rack unit

Includes: 1 × FCR25 with integral leg for table mounting
3 × PA25-SH
3 × PA25-20

Part number: A-2237-1403

Price: \$3,768



FCR25-L6 6-port standalone change rack unit

Includes: 2 × FCR25 with integral leg for table mounting
3 × PA25-SH
3 × PA25-20

Part number: A-2237-1406

Price: \$6,316



FCR25 port adaptor insert kit

Includes: 3 × PA25-SH
3 × PA25-20

Part number: A-2237-1415

Price: \$366

SP80

The SP80 is a quill-mounted scanning probe that uses digital scale and readhead technology, plus Renishaw's innovative isolated optical metrology principles, to provide exceptional scanning performance, even with long styli.


It is able to reach deep into parts by carrying styli up to 500 mm long and 500 g mass, including star configurations which do not require counterbalancing. Renishaw's M5 styli products are designed to complement SP80 and ensure maximum performance.

Detachable stylus holders (SH80) permit rapid and repeatable interchange between stylus configurations, thus eliminating recalibration, maximizing productivity and permitting optimum solutions to match the application.

A simple and robust passive design, with no internal motors to generate heat or reliability issues, avoids unnecessary system complexity.

The SP80 probe body houses the sensor mechanism comprising a 'box' spring motion system and the isolated metrology system featuring high accuracy digital scale and readheads.

Longer stylus lengths may be carried subject to operating conditions (consult Renishaw for application assistance).



SP80 probe kit 1

- Includes: SP80 probe body
SH80 stylus holder
KM80 quill mount plate
PL157 probe cable
60 mm long stylus
Tools

Part number: A-2238-0700 **Price:** \$16,844

SP80 probe kit 2

- Includes: SP80 probe kit 1
SCP80 stylus change port (3 off)
MRS kit 2 (600 mm rail length – see page 1-57)

Part number: A-2238-0732 **Price:** \$20,752

SP80 probe kit 3

- Includes: SP80 probe kit 1
SCP80 stylus change port (4 off)
MRS kit 2 (600 mm rail length – see page 1-57)

Part number: A-2238-0733 **Price:** \$21,101

SP80 probe kit 4

- Includes: SP80 probe kit 1
SCP80 stylus change port (5 off)
MRS kit 3 (1000 mm rail length – see page 1-57)

Part number: A-2238-0734 **Price:** \$21,515

SP80 probe kit 5

- Includes: SP80 probe kit 2
SH80 stylus holder (3 off)

Part number: A-2238-0735 **Price:** \$22,051

SP80 probe kit 6

- Includes: SP80 probe kit 3
SH80 stylus holder (4 off)

Part number: A-2238-0736 **Price:** \$22,926

SP80 probe kit 7

- Includes: SP80 probe kit 4
SH80 stylus holder (5 off)

Part number: A-2238-0737 **Price:** \$23,820

SP80H

The SP80H is a horizontal quill-mounted version of the SP80 probe that uses the same digital scale and readhead technology as the SP80 probe.

The SP80H is intended for use on horizontal arm machines and uses the standard SH80 stylus holder and KM80 quill mount. It uses the SCP80V for automated stylus changing.

It is able to carry Renishaw's range of M5 threaded styli up to 500 mm long. Stylus configurations up to 300 g unbalanced are possible.



SP80H probe kit 1

Includes:

- SP80H probe body
- SH80 stylus holder
- SH80K stylus holder
- KM80 quill mount plate
- SH80 removal tool
- PL157 probe cable
- 60 mm long stylus
- Tools

Part number: A-2238-0419

Price: \$16,844

Other probe kits similarly configured to the SP80 probe kits are available upon request. Please contact Renishaw for details.

SCP80 stylus change port

Individual ports for rapid interchange between SH80s. The SCP80 mounts to Renishaw's modular rack system (MRS) – see page 1-55.

Part number: A-2238-0706 **Price:** \$1,076

SCP80V rack port

The SCP80V is a rack port designed for use with SP80H to allow automatic changing of the SCP80 stylus holders on horizontal arm machines. It may also be used for changing stylus holders that have long styli protruding from the rear of a horizontally mounted port.

Part number: A-2238-0726 **Price:** \$1,157

SH80 stylus holder

Rapidly interchangeable onto the probe body via a magnetic kinematic joint, the SH80 features a 5-way stylus cube which can be rotated to align styli as desired.

Part number: A-2238-0705 **Price:** \$541

SH80K stylus holder

The SH80K is a stylus holder that allows you to power off the SP80 and SP80H probes and turn them back on without needing to re-home the probe.

Part number: A-2238-0430 **Price:** \$581

SH80 removal tool

The SH80 removal tool is used to manually remove the SH80 or SH80K stylus holder from the SP80 or SP80H.

Part number: M-2238-0443 **Price:** \$58

KM80 quill mount plate


The standard mounting plate between the CMM quill (80 mm square) and the SP80 probe body. Provides easy and repeatable removal/replacement of the probe. Alternative CMM quill mountings are available (see KM6080 and SM80 below).

Part number: A-2238-0703 **Price:** \$180

KM6080 quill mount plate

As KM80 but used to mount SP80 onto a 60 mm square CMM quill.

Part number: A-2238-0020 **Price:** \$180



SM80 shank mount plate

As KM80 but with a shank mount to the CMM (non-preferred method).

Part number: A-2238-0704 **Price:** \$901

IU80 interpolator unit

Required for all OEM controller installations (as opposed to Renishaw's UCC controller installations which require use of the UCC/SP80 daughter card).

Part number: A-2238-0720 **Price:** \$866

CC6 counter card

Required where this function is not performed by the CMM controller/PC.

Part number: A-4068-0400 **Price:** \$1,560

Cables

PL156

IU80 to OEM controller (supplied unterminated).

Part number: A-1016-7129 **Price:** \$99

PL157

SP80 probe cable (included with all SP80 kits).

Part number: A-1016-7132 **Price:** \$119

PL158

IU80 to CC6.

Part number: A-1016-7133 **Price:** \$252

SP600M

The SP600M is an autojointed, multiwired analog scanning probe which enables a CMM to gather large amounts of data very rapidly for inspection or digitizing purposes. Low spring forces allow scanning of finely detailed parts. The probe can be used with a PH10M or PH6M probe head and is compatible with the Renishaw autochange system.

Measurement range:	±1 mm (0.04 in) X, Y, and Z
Return to zero:	<5 µm (0.0002 in) from 0.5 mm deflection
Resolution:	0.1 µm (0.000004 in) with optional AC2 interface 0.5 µm (0.00002 in) with optional AC1 interface
Spring rate:	120 gf/mm nominal
Outputs (X,Y,Z):	Analog proportional voltage output scaling: 4 V to 8.5 V/mm
Interface:	AC1 or AC2 analog converter PC card (optional)
Mounting:	Multi-wired autojoint
Dimension:	Length 107.5 mm, diameter 50 mm
Weight:	216 g

Part number: A-2098-0105 **Price:** \$11,020

AC1 analog converter PC card

Part number: A-2098-1000 **Price:** \$2,315

AC2 analog converter PC card

Part number: A-2172-0001 **Price:** \$2,692

Stylus module - SH600 standard

Part number: A-2098-0284 **Price:** \$458

Stylus module - SH600 extended

Part number: A-2098-1036 **Price:** \$623

SP600Q

The SP600Q is a quill-mounted version of the SP600M probe. It can therefore be connected directly to the quill of a CMM and an external cable carries the probe signal to the interface card. The specification for the SP600Q is identical to the SP600M, with the following exceptions:

Mounting:	Direct in quill
Dimensions:	Length 99 mm, diameter 60 mm
Weight:	299 g

SP600Q kit

Part number: A-2098-0890 **Price:** \$11,020

SCR600 stylus changing rack

The SCR600 is a passive stylus change rack for use with the SP600M and requires no electrical connections. It houses up to four stylus modules per rack. The rack kit includes two stylus changing modules and additional modules can be purchased separately.

Part number: A-2098-0255 **Price:** \$5,113



Gram gage

The gram gage allows you to adjust, reset and check probe trigger force settings on all standard Renishaw CMM touch-trigger probes. Setting the optimum trigger force using the gram gage maximizes probe performance. It can be used to set trigger force settings over a range of 3 to 30 grams.

Overall length: 95 mm
 Needle length: 41 mm
 Depth: 27 mm
 Width: 43 mm
 Range: 4 to 35 gram range with 1 gram graduations

Probe	Stylus length (mm)	Optimum trigger force (grams) *
TP1	31	15
TP2-5W	10	7 to 8
TP2-6W	10	7 to 8
TP6	21	11 to 13
TP6A	21	11 to 13

* This is the optimum trigger force recommended by Renishaw. Higher trigger forces may be required for longer styli.

Part number: P-GA01-0001

Price: \$374



CMM probe shanks

Shanks are used to mount the probe head to the quill of the CMM. The shanks listed below are suitable for all Renishaw manual and motorized heads, as well as the TP1 and MIP probes.


Note: The PH6 requires a different shank and has a separate listing (see overleaf).

The correct shank must be chosen to suit the mounting facility of your coordinate measuring machine.

Shanks are included in the price of Renishaw heads and TP1 and MIP probes, but must be specified when placing an order. See the drawings on the following pages for the exact dimensions of each shank.

Shank	Used on the following machines	Part number	Price
MS1	Brown & Sharpe, Bridgeport, Elm Systems, Fanamation, Giddings & Lewis, I.T.P., Poli, Portage Machine, Tesa, Zett-Mess	M-1041-2146	\$151
MS1(S)	New Carl Zeiss	A-1041-7114	\$151
MS2	Boice, Carl Zeiss, Federal Products, Helmel, Kemco, Metrologic, MFO, Mora, Numerex, Real Meca, Starrett, Tokyo-Boeki, Tri-mesures, TSK, and Wenzel	M-1041-1650	\$151
MS3	LK Tool (meter 4), Ferranti, Tarus, W & A, Eley & Warren	M-1041-1656	\$151
MS5	Ferranti	M-1041-1652	\$151
MS6	C.E. Johannson (old specification)	M-1041-1653	\$151
MS7	Renault (Seiv), Tri-Measures	M-1041-1654	\$151
MS7(S)	Starrett (new specification)	M-1041-7132	\$193
MS8	Olivetti	M-1041-1657	\$151
MS9	MTI Corporation (UK)	M-1041-4843	\$151
MS10	MTI Corporation	M-1041-7507	\$151
MS11	Crown Windley	M-1041-1088	\$151
MS12	MTI Corporation (new specification)	M-1041-7068	\$151
MS13	DEA Corp	M-1041-5348	\$151
MS14	CTA, Real Meca	M-1041-5981	\$151
MS15	C.E. Johannson (new specification)	M-1041-2153	\$151
MS17	Stiefelmayer	A-1041-7113	\$215

Standard base diameter 41.35 - 41.45 mm (1.630 - 1.632 in)




PH6 shanks

Shank Used on the following machines

Shank	Used on the following machines	Part number	Price
MS1/T	Brown & Sharpe, Bridgeport, Elm Systems, Fanamation, Giddings & Lewis, Poli, & Portage Machine	M-1046-1121	\$215
MS2/T	Federal Products, Helmel, Kemco, Mora, Numerex, Starrett, Tokyo-Boeki, & Wenzel	M-1046-1120	\$151
MS3/T	Eley, Ferranti, LK Tool (meter 4), Tarus, W & A, & Warren	M-1046-1126	\$151
MS4/T	LK Tool (micro)	M-1046-1128	\$151
MS5/T	Ferranti	M-1046-1122	\$151
MS6/T	C.E. Johannson	M-1046-1123	\$151
MS7/T	Renault	M-1046-1124	\$151
MS8/T	Olivetti	M-1046-1802	\$151
MS9/T	MTI Corporation (UK)	M-1046-4545	\$151
MS11/T	Crown & Windley	M-1046-2661	\$151
MS18/T	Mora	M-1046-7107	\$151

Standard base diameter 18.9 - 19.1 mm (0.74 - 0.75 in) unless stated



CMM cables

Manual probe head cables

Cable	Type	Overall length	Machine connector	Part number	Price
PL1(T)	Coiled	315 mm – 730 mm (12.4 in – 28.7 in)	5 pin mold – 5 pin DIN	A-1016-0004	\$97
PL2(T)	Coiled	465 mm – 1290 mm (18.3 in – 50.8 in)	5 pin mold – 5 pin DIN	A-1016-0006	\$97
PL3(T)	Coiled	765 mm – 2415 mm (30.1 in – 95.1 in)	5 pin mold – 5 pin DIN	A-1016-0012	\$97
PL4(T)	Plain	4510 mm (177.6 in)	5 pin mold – 5 pin DIN	A-1016-0001	\$97
PL14	Coiled	595 mm – 1830 mm (23.4 in – 72 in)	5 pin mold – 7 pin AMPHENOL	A-1016-0003	\$108
PL17(T)	Coiled	200 mm – 400 mm (7.9 in – 15.8 in)	5 pin mold – 14 pin LEMO	A-1023-7024	\$243
PL18(T)	Coiled	500 mm – 1300 mm (19.7 in – 51.2 in)	5 pin mold – 14 pin LEMO	A-1023-7025	\$243
PL27(T)	Coiled	203 mm (8 in)	5 pin mold – 5 pin mold	A-1016-6370	\$57
PL27(T)	Plain	152 mm (6 in)	5 pin mold – 5 pin mold	A-1016-6440	\$57

Motorized probe head cables

Cable	Type	Overall length	Machine connector	Part number	Price
PL5(U)	Coiled	0.4 m – 0.8 m (16 in – 31 in)	PH9/10 to machine cable	A-1016-7672	\$271
PL6(U)	Coiled	0.8 m – 1.6 m (31 in – 63 in)	PH9/10 to machine cable	A-1016-7673	\$271
PL12(U)	Plain	0.1 m (4 in)	PH9/10 to machine cable	A-1016-7674	\$238
PL13(U)	Coiled	0.1 m – 0.2 m (4 in – 8 in)	PH9/10 to machine cable	A-1016-7675	\$238
PL33(U)	Plain	3 m (118 in)	PH9/10 to machine cable	A-1023-7056	\$311
PL93(U)	Plain	0.1 m (4 in)	PH10MQ to PLM6/7/8/9S	A-1016-7676	\$271

Machine cables

Cable	Type	Overall length	Machine connector	Part number	Price
PLM6(T)	Plain	6 m (19 ft)	PH10 cable to PHC10-3 controller (chassis)	A-1016-7564	\$156
PLM7(T)	Plain	4 m (13 ft)	PH10 cable to PHC10-3 controller (chassis)	A-1016-7563	\$156
PLM8(U)	Plain	6 m (19 ft)	PH10 cable to PHC10-3 controller (socket)	A-1016-7677	\$156
PLM9(U)	Plain	4 m (13 ft)	PH10 cable to PHC10-3 controller (socket)	A-1016-7678	\$156

Output cables

Cable	Type	Overall length	Machine connector	Part number	Price
PL7	Plain	3 m (118 in)	5 pin DIN to 5 pin DIN	A-1029-0166	\$57
PL15	Plain	4.5 m (177 in)	5 pin DIN, interface to CMM	A-1004-0110	\$68
PL26(T)	Plain	0.6 m (23 in)	PI200-3 to PHC9 (7 pin)	A-1057-0132	\$97
PL37	Plain	0.5 m (19 in)	7 pin DIN to 7 pin DIN	A-1054-0003	\$57

Multiwired cables

Cable	Type	Overall length	Description	Part number	Price
PL38V	Plain	25 m (82 ft)	Multiwired cable	A-1016-7625	\$859
PL42V	Plain	15 m (49 ft)	Multiwired cable	A-1016-7624	\$690
PL44V	Plain	8 m (26 ft)	Multiwired cable	A-1016-7627	\$554
PL45V	Plain	1.8 m (5.9 ft)	Multiwired cable	A-1016-7629	\$373
PL46V	Plain	3.7 m (12 ft)	Multiwired cable	A-1016-7628	\$441
PL56V	Plain	12 m (39.3 ft)	Multiwired cable	A-1016-7626	\$622
PL75V	Plain	1 m (3.2 ft)	IS1-2 extension cable	A-1016-7644	\$171

Adaptor/extension cables

Cable	Type	Overall length	Description	Part number	Price
PL9	Plain	0.6 m (23 in)	Machine cable to probe interface cable	A-1029-0182	\$57
PL10	Plain	0.1 m (4 in)	Machine cable to probe/head cable (5 pin)	A-1029-0111	\$85
PL22	Plain	0.3 m (12 in)	Probe head cable adaptor (PL1S, 2S, 3S, 4S to PI4-2, PI200-3 input)	A-1057-0131	\$57
PL23(T)		0.5 m (19 in)	PI4-2, PI200-3 adaptor cable (machine cable to PHC9 extension cable PL82V to video interface)	A-1057-0133	\$85
PL97(S)	Plain	0.1 m (4 in)	SCR200 Y adaptor cable	A-1016-7660	\$226

PICS interconnection cables

Cable	Overall length	Description	Part number	Price
PL24	5 m (16 in)	PI200-3 or PI7-3 to CMM	A-1016-0121	\$151
PL25(T)	0.3 m (11 in)	PI200-3 or PI7-3 to PHC10-3/ACC2-2	A-1016-0120	\$151
PL70(V)	0.5 m (19 in)	PI200-3 and PI7-3 interfaces	A-1016-7634	\$362
PL72	2 m (6.5 in)	PI200-3 or PI7-3 to PHC10-3/ACC2-2	A-1016-7637	\$151
PL76(S)	0.7 m (2.25 in)	T cable	A-1016-7643	\$171

Extensions

The extensions and knuckle joint are the primary means of adding flexibility to fixed heads. Extensions provide penetration into deep features, while the knuckle joint allows inspection of angular features. The knuckle joint allows 360° in the B axis and ±100° in the A axis.

Extension bars

Number	Description	Material	Length	Diameter	Part number	Price
PEL1	M8 thread to M8 thread	Aluminum	50 mm (1.97 in)	13 mm	A-1047-3484	\$284
PEL2	M8 thread to M8 thread	Aluminum	100 mm (3.94 in)	18 mm – 13 mm	A-1047-3485	\$346
PEL3	M8 thread to M8 thread	Aluminum	200 mm (7.87 in)	18 mm – 13 mm	A-1047-3486	\$363
PEL4	M8 thread to M8 thread	Aluminum	300 mm (11.81 in)	13 mm	A-1047-3487	\$458
PECF1*	M8 thread to M8 thread	Carbon fiber	50 mm (1.97 in)	13 mm	A-1047-7065	\$571
PECF2*	M8 thread to M8 thread	Carbon fiber	100 mm (3.94 in)	13 mm	A-1047-7064	\$616
PECF3*	M8 thread to M8 thread	Carbon fiber	200 mm (7.87 in)	13 mm	A-1047-7066	\$683

* These products are special order only. Please call Customer Service for details.

Knuckle joint

Number	Description	Part number	Price
PK1	Knuckle joint	A-1014-1720	\$604

Autojoint extension bars

Number	Description	Material	Length	Diameter	Part number	Price
PAA1	Autojoint to M8 thread	Steel	30 mm (1.18 in)	25 mm – 18 mm	A-1051-0417	\$353
PAA2	Autojoint to M8 thread	Aluminum	140 mm (5.51 in)	25 mm – 13 mm	A-1051-0418	\$451
PAA3	Autojoint to M8 thread	Aluminum	300 mm (11.81 in)	25 mm – 13 mm	A-1051-0419	\$548
PAACF2*	Autojoint to M8 thread	Carbon fiber	140 mm (5.51 in)	25 mm – 13 mm	A-1051-0488	\$981
PAACF3*	Autojoint to M8 thread	Carbon fiber	300 mm (11.81 in)	25 mm – 13 mm	A-1051-0493	\$1,029
PAACF*	Autojoint to M8 thread	Carbon fiber	400 mm (15.74 in)	25 mm – 14 mm	A-1051-0513	\$1,644
PAACF*	Autojoint to M8 thread	Carbon fiber	450 mm (17.72 in)	25 mm – 14 mm	A-1051-0394	\$1,713
PEM1	Autojoint to autojoint	Steel/aluminum	50 mm (1.97 in)	25 mm	A-1076-0070	\$972
PEM2	Autojoint to autojoint	Steel/aluminum	100 mm (3.94 in)	25 mm	A-1076-0071	\$1,198
PEM3	Autojoint to autojoint	Steel/aluminum	200 mm (7.87 in)	25 mm	A-1076-0072	\$1,424
PEM4	Autojoint to autojoint	Steel/aluminum	150 mm (5.91 in)	25 mm (90°)	A-1076-0073	\$1,481
PEMCF1*	Autojoint to autojoint	Carbon fiber	50 mm (1.97 in)	25 mm	A-1051-0490	\$765
PEMCF2*	Autojoint to autojoint	Carbon fiber	100 mm (3.94 in)	25 mm	A-1051-0443	\$1,210
PEMCF3*	Autojoint to autojoint	Carbon fiber	200 mm (7.87 in)	25 mm	A-1051-0491	\$1,438
PEMCF*	Autojoint to autojoint	Carbon fiber	150 mm (5.91 in)	25 mm	A-1051-1132	\$1,375

* These products are special order only. Please call Customer Service for details.

Interfaces

PI7-3

The PI7-3 interface is a dual-purpose probe interface designed to process signals from the TP7M high-accuracy probe and standard touch-trigger probes (TP2, TP20, TP6, and TP6A). Special auto-selecting electronics within the interface allow the automatic use and exchange of all of these probes without any setting changes to the interface.

The PI7-3 performs all the functions of the PI4 and PI9 interfaces, but has additional features such as probe damping, probe inhibit, and emergency stop. This interface can be either free-standing or rack-mounted.

Application:	TP7, TP2, TP6, TP6A, TP20, MH20, and MH20i
Power supply:	85 V – 135 V, 50/60 Hz 170 V – 270 V, 50/60 Hz
Dimensions:	Height 88 mm (3.46 in) Width 146 mm (5.75 in) Depth 208.5 mm (8.21 in)
Input:	9 way 'D' type socket
TP7M input:	15 way double density 'D' type socket or 9 pin 'D' type socket
Compatibility:	Output TTL(PICS)/SSR 5 pin DIN socket (PICS-9 pin 'D' type plug)
Cables	Contact Renishaw

Part number: A-5726-0100

Price: \$1,117



PI200-3

The PI200-3 interface can be interconnected within the majority of Renishaw's manual and motorized probing installations with no additional CMM communications or control signalling required. Optimum performance will be obtained on installations utilizing probe damping or halt signal facilities. Probe signalling between TP200 and PI200-3 must be direct and uninterrupted. Probe signal interfacing may be present within some CMM cabling arrangements. Call Renishaw for further details.

Application: TP1, MIP, TP2, TP20, TP6, TP6A, TP200, MH20, and MH20i
 Power supply: 85 V – 264 V, 47 Hz – 66 Hz
 Dimensions: Height 88 mm (3.46 in)
 Width 146 mm (5.75 in)
 Depth 183 mm (7.19 in)
 Input: 9 way 'D' type socket
 Compatibility: Output PICS/SSR

Part number: A-5707-0100

Price: \$780

IS1-2

The IS1-2 interface selector is a fully-automatic system for use on CMM installations requiring multiple sensor types (i.e. video, laser, analog, etc.). The unit functions by identifying which probe has been fitted to the probe head and switches the probe signal/power lines to the appropriate interface. The unit is configurable by inserting different programming modules.

Applications: TP7M, SP600M, TP2, TP20, TP6, TP200, SP25M, TP800
 Power supply: 85 V – 264 V, 47 Hz – 66 Hz
 Dimensions: Height 88 mm (3.46 in)
 Width 164 mm (5.75 in)
 Depth 208 mm (8.21 in)
 Input: 15 way double density 'D' type socket
 Output: 15 way double density 'D' type plug and
 9 way 'D' type plug (PICS)
 Cables: Contact Renishaw

Part number: A-1327-0100


Price: \$2,826



Mounting brackets


Renishaw controllers and interfaces are supplied in various different types of enclosures. Consult the drawings below to determine your bracket requirements based upon the combination of products you are installing.

PHC9 / PHC50 / PHC10-2 / ACC2-2



- | | | |
|---------------------------|---------------------------------|--------------------|
| 1. Rack mount bracket kit | Part number: A-1018-0124 | Price: \$23 |
| 2. 1/3 blanking panel kit | Part number: A-1018-0123 | Price: \$30 |

PHC10-3 PLUS cabinet mounting



Mounting kit containing 2 brackets and 4 M5 x 6 mm screws

Part number: A-1018-0189 **Price:** \$33


PI7-3 alone / PI200-3



1/3 mounting panel kit containing 1U x 1/3 blanking plate and 2 M6 x 5 mm screws (2 kits required)

Part number: A-1018-0179 **Price:** \$22

PI7-3 next to PHC10-2



Mounting kit containing PI7-3 to PHC10-2 conversion bracket

Part number: A-1018-0173 **Price:** \$46

Autochange system

Renishaw's autochange equipment is the world's first integrated CMM probe exchange system. Mounted within the CMM's working envelope, autochange facilitates fast, automatic probe exchange without the need for redatuming. In addition, it provides covered storage for probes and extension bars.

ACR1 autochange rack with adjustable base

The ACR1 is designed to accept the SP600 and SP25M as well as all other Renishaw autojoint probes and extension bars (must be used in conjunction with the horizontal mounting kit – see below). The rack is supplied with eight long ports for maximum support. Where a probe greater than Ø25 mm is required, the rack can be configured by the user by swapping a long port for a short port (see below).

Number of stations: 8
Dimensions: 460 mm × 109 mm × 81 mm

This system can be mounted either horizontally or vertically.

Part number: A-1051-1300 **Price:** \$19,027

Note: Adjustable base, legs and cable sold separately (see page 1-54).



Horizontal mounting kit

Includes: 1 × adjustable rack base
2 × 200 mm legs
2 × screws

Part number: A-1051-0441 **Price:** \$368

Vertical mounting kit

Includes: 1 × support plate
8 × support pins (short)
8 × support pins (long)

Part number: A-1051-1308 **Price:** \$87

ACC2-2 autochange controller

Data transmission: Serial (RS232)
User-definable parameters: Baud rate 300–19200
Voltage range: 85 V–135 V, 170 V–275 V, 50/60 Hz automatic selection
Dimensions: Height 88 mm (3.46 in)
Width 290 mm (11.42 in)
Depth 220 mm (8.66 in)

Part number: A-1520-0101 **Price:** \$2,959



ACR1 autochange system accessories

Adjustable rack base

Part number: A-1051-0440 Price: \$315

Leg (100 mm)

Part number: M-1051-0147 Price: \$13

Leg (200 mm)

Part number: M-1051-0148 Price: \$24

Port replacement kits

All kits contain four ports.

Short port replacement kit

Part number: A-5036-0049 Price: \$273

Long port replacement kit

Part number: A-1051-7077 Price: \$263

Mixed port replacement kit

Contains two short and two long ports.

Part number: A-1051-7076 Price: \$374

ACR1 autochange system cables

PL19 5 m cable

Part number: A-1051-0199 Price: \$212

PL20 10 m cable

Part number: A-1051-0045 Price: \$352

PL21 15 m cable

Part number: A-1051-0102 Price: \$461

PL40 30 m cable

Part number: A-1054-0002 Price: \$899

ACR3 autochange rack

The ACR3 forms part of the modular rack system (MRS) and is an autochange rack for probes and extension bars that incorporate the Renishaw autojoint. The ACR3 is a four-port mechanical design that traverses the MRS rail. Driven by the motion of the CMM, it locks and unlocks the autojoint between the probe and the probe head.

ACR3 4-port rack

Part number: A-5036-0005

Price: \$9,589

Note: For 8-port applications, two 4-port racks can be connected together. The 8-port configuration requires the use of either the MRS kit 2 or MRS kit 3 (see below).

MRS kits

Include: MRS rail (see below)
MRS feet (2)
125 mm legs (4)
Step back adaptors (2)

The MRS rail is available in 400 mm, 600 mm and 1000 mm lengths.

MRS kit 1

400 mm long rail.

Part number: A-4192-0001

Price: \$1,205

MRS kit 2

600 mm long rail.

Part number: A-4192-0002

Price: \$1,292

MRS kit 3

1000 mm long rail.

Part number: A-4192-0003

Price: \$1,400

Note: The MRS kits are compatible with FCR25, SCP600 and ACR3.

MRS rails

Part number: A-4192-0050 (400 mm)

Price: \$205

Part number: A-4192-0051 (600 mm)

Price: \$269

Part number: A-4192-0052 (1000 mm)

Price: \$376

ACR3 components

SCP600

Stylus change port for SP600.

Part number: A-2098-0933

Price: \$1,400



MRS legs

One per kit.

Part number: A-4192-0061 (62.5 mm) **Price:** \$86
Part number: A-4192-0053 (125 mm) **Price:** \$102

MRS heavy duty leg kit

Ø60 mm x 350 mm long. One per kit.

Part number: A-4192-0020 **Price:** \$364

MRS adjustable foot plate

Two per kit.

Part number: A-4192-0702 **Price:** \$376

MRS leg and foot adaptor

One per kit.

Part number: A-4192-0055 **Price:** \$151

MRS fixed foot

One per kit.

Part number: A-4192-0056 **Price:** \$151

MRS step back adaptor

One per kit.

Part number: A-4192-0058 **Price:** \$151

M8 T nut *

Part number: P-NU18-0005 **Price:** \$13

* no discounts

MRS spacer kit

Two per kit.

Part number: A-4192-0014 **Price:** \$77

MRS2 kits

The MRS2 is a highly versatile storage solution for Renishaw probe and stylus configurations. It has been designed for users who are increasingly using their CMMs for multi sensor measurement, and therefore need to store greater varieties of probes and styli on racks within a limited machine working volume.

MRS2 is built entirely from extruded aluminum and is available in a variety of interchangeable rail and leg kits that can be configured according to the need of the individual. Leg and rail kits are sold separately to allow maximum flexibility. Rails can be tiered, using the front and back spacer kits, to offer up to three meters of rail space.

MRS2 leg kits

Includes: 2 × leg extrusions
4 × 40 mm brackets
6 × square end caps
2 × extrusion clamp plate kits

Not included: Rail, front spacer, and back spacer.

Part number: A-6007-1020 (H = 200 mm)	Price: \$700
Part number: A-6007-1040 (H = 400 mm)	Price: \$790
Part number: A-6007-1060 (H = 600 mm)	Price: \$1,058
Part number: A-6007-1080 (H = 800 mm)	Price: \$1,148

MRS2 rail kits

Includes: 1 × rail
2 × triangular end caps
2 × 40 mm brackets

Not included: Leg, front spacer, and back spacer.

Part number: A-6007-2040 (L = 400 mm)	Price: \$215
Part number: A-6007-2060 (L = 600 mm)	Price: \$269
Part number: A-6007-2100 (L = 1000 mm)	Price: \$359

MRS2 spacer kits

Part number: A-6007-3010 (Front spacer kit)	Price: \$154
Part number: A-6007-4008 (Back spacer kit)	Price: \$269

MRS2 accessories

MRS2 spirit level


Part number: A-6007-0630	Price: \$27
---------------------------------	--------------------

MRS2 extrusion clamp plate kit

Part number: A-6007-0620 (1 per kit)	Price: \$180
---	---------------------

MRS2 end caps and brackets

Part number: A-6007-0710 (4 × triangular end caps)	Price: \$44
Part number: A-6007-0720 (6 × square end caps)	Price: \$64
Part number: A-6007-0740 (4 × 40 mm bracket end caps)	Price: \$44
Part number: A-6007-0780 (4 × 80 mm bracket end caps)	Price: \$72
Part number: A-6007-0810 (10 × D-nuts and bolts)	Price: \$72



M8 D-Nut

Manual autojoint probe stand

Renishaw's manual autojoint probe stand (MAPS) is a low-cost storage rack capable of holding up to six combinations of probes, extension bars, and accessories. The stand can be mounted directly on the table of a CMM using the appropriate socket head bolt (maximum size M10, 3/8 in) which is passed through the center of the base.

Standard autochange rack legs (100 mm and 200 mm long) are compatible with this stand and can be stacked to accommodate longer probe extensions with longer stylus extensions. As an alternative to the support pillar, a wall mounting bracket is available to enable the stand to be mounted to a cabinet, wall or any other vertical surface.

Height: 285 mm
 Depth: 80 mm
 Width: 235 mm

Part number: A-1071-0001

Price: \$222



MSR1 rack


The MSR1 rack is intended for use on either manual or DCC CMMs to hold pre-qualified stylus assemblies fitted to TP20 or TP200 probe modules. The rack provides convenient storage and protects the kinematic coupling mechanism from contamination.

Overall height: 285 mm
 Depth (inc wall bracket): 86 mm
 Width: 236 mm

MSR1 with leg and base (wall mount kit included)

Part number: A-1371-0347

Price: \$404



Datum sphere

The Renishaw universal datum sphere enhances the performance of manual and fully automated CMMs. It allows for quick and easy adjustment to set ball stem over a wide range of probe datuming angles. This enables datuming above, centrally and below the ball. Each datum sphere is supplied with its own certificate, giving ball diameter and roundness. All sphere measurements are performed on equipment traceable to UK (NPL) standards.

Specifications:	Hard-wearing tungsten carbide sphere (ball) available in five sizes
Metric:	Ø12 mm, Ø19 mm and Ø25 mm
Inch:	Ø3/4 in and Ø1 in
Sphericity:	to within 0.1 µm (0.000004 in)
Diametric tolerance:	±1 µm (0.00004 in)

Datum sphere kit

Includes: 1 datum ball (selected by size)
Pivot pillar
Base
C spanner
Ball certificate
Storage box

Description	Part number	Price
Ø12 mm ball	A-1034-0028	\$545
Ø19 mm ball	A-1034-0027	\$545
Ø25 mm ball	A-1034-0026	\$545
Ø¾ in ball	A-1034-0031	\$545
Ø1 in ball	A-1034-0035	\$545

Datum sphere fixing studs

A fixing stud is required with each kit to attach the pillar to the table surface. Select one from the list below.

Description	Manufacturer	Part number	Price
M6 × 1		A-1034-0352	\$27
M8 × 1.25	MTI	A-1034-0351	\$27
M10 × 1.5	B&S, LK Tool & Sheffield	A-1034-0350	\$27
5/16–18 UNC		A-1034-0354	\$27
3/8–16 UNC	Carl Zeiss, Fanamation, LK Tool, & L.S. Starrett	A-1034-0353	\$27

Datum sphere accessories (M6 thread – stem is attached to the ball)

Description	Part number	Price
Ø12 mm datum ball	A-1034-0005	\$335
Ø19 mm datum ball	A-1034-0023	\$335
Ø25 mm datum ball	A-1034-0002	\$335
Ø¾ in datum ball	A-1034-0032	\$335
Ø1 in datum ball	A-1034-0036	\$335
2 way adaptor	A-1034-0356	\$82
3 way adaptor *	A-1034-0357	\$186
Pillar extension 75 mm (2.96 in) long	A-1034-0355	\$82

* Special order



Mahogany boxes

Probe head boxes

Description	Part number	Price
PH1 probe head, cable, TK6 box	A-1015-7725	\$100
PH6 probe head, TP2 probe, stylus, TK6 box	A-1015-7731	\$100
PH5 or PH5-1 probe head, cable, TK6 box	A-1015-7727	\$100
PH10M probe head kit box	A-1015-7698	\$108
PH6A probe head kit box	A-1015-7674	\$198
TP1 probe and stylus box (PC10)	A-1015-7686	\$136
MIH and accessories box	A-1015-7765	\$113
TP200 probe and stylus box	A-1015-7869	\$135

Extension bar boxes

Description	Part number	Price
PEL extension bars (PC19)	A-1015-7694	\$113
PEM extension bars	A-1015-7761	\$131

Probe extension kits

Kit EKL **Part number:** A-1047-7005 **Price:** \$994

Description	Quantity	Part number
Lightweight extension bar (50 mm) PEL1	1	A-1047-3484
Lightweight extension bar (100 mm) PEL2	1	A-1047-3485
Lightweight extension bar (200 mm) PEL3	1	A-1047-3486
Double-ended spanner	1	A-1047-3932
Box	1	A-1015-7694

PEM Kit **Part number:** A-1076-0100 **Price:** \$3,305

Description	Quantity	Part number
Multiwire extension bar (50 mm) PEM1	1	A-1076-0070
Multiwire extension bar (100 mm) PEM2	1	A-1076-0071
Multiwire extension bar (200 mm) PEM3	1	A-1076-0072
Joint key	1	A-1051-0040
Box	1	A-1015-7761

Stylus tools

S1 C spanner (for use with TP20 probe body)

Part number: A-1042-1486 Price: \$20

S3 hex key 1.5 mm A/F

Part number: P-TL01-0150 Price: \$4

S4 hex key 3.0 mm straight arm

Part number: P-TL01-0300 Price: \$4

S5 wrench 2 mm A/F

Part number: P-TL01-0200 Price: \$4

S6 hex key 2.5 mm A/F

Part number: P-TL01-0250 Price: \$4

S7 stylus tool (for use with M2 and M3 styli)

Part number: M-5000-3540 Price: \$9

S9 double-ended spanner

Part number: A-1047-3932 Price: \$14

S10 joint key (for use with autojoint)

Part number: A-1051-0040 Price: \$17

S12 hex key 0.9 mm A/F

Part number: P-TL01-0089 Price: \$4

S20 torque tool (for use with M2 carbon fiber stylus)



Part number: A-5003-2300 Price: \$48

M4 stylus tool (for use with M4 and M5 styli)

Part number: M-5000-3707 Price: \$12

Stylus tool (for use with adaptor M-5000-9301)

Part number: M-5000-9304 Price: \$15



Tool kits

TK1 tool kit

The TK1 tool kit is included with the MP1, MP3, MP4, MP7, MP8, MP9, MP10, MP11, MP12, MP14 and LP2 probes.

Includes: Stylus tool Ø1.98 mm
Hex key 1.5 mm A/F
Hex key 2.0 mm A/F
Hex key 2.5 mm A/F
Hex key 3.0 mm A/F
Hex key 4.0 mm A/F

Part number: A-2053-7531

Price: \$36

TK3 tool kit

The TK3 tool kit is included with the M6-3 probe.

Includes: Stylus tool Ø1.98 mm
Hex key 1.5 mm A/F
Hex key 2.0 mm A/F
Hex key 2.5 mm A/F
Hex key 3.0 mm A/F
Hex key 4.0 mm A/F
Hex key 5.0 mm A/F

Part number: A-2027-7046

Price: \$36

TK4 tool kit

Includes: S7 stylus tool (2)
Hex key 1.5 mm A/F
Hex key 2.5 mm A/F

Part number: A-1041-7041

Price: \$24

TK5 tool kit

Includes: S7 stylus tool (2)
S8 spanner
C spanner
Double-ended spanner
Hex key 1.5mm A/F

Part number: A-1042-7030

Price: \$62

TK6 tool kit

Includes: Hex key 2.0 mm A/F
Hex key 2.5 mm A/F
Hex key 3.0 mm A/F

Part number: A-1042-7031

Price: \$7

TK7 tool kit

Includes: Joint key
S7 stylus tools (2)
Hex key 1.5 mm A/F

Part number: A-1039-0041


Price: \$28

CMM metrology software

MODUS™

Renishaw's new MODUS™ software provides a powerful platform for 3-axis and 5-axis measurement. A configurable user interface allows native DMIS programs to be developed online or offline, drawing geometry, embedded dimensions and tolerance data from CAD, with full simulation and collision detection. The software includes certified algorithms for feature measurement, feature construction and part alignment.

- Full support for I++ DME compliant metrology controllers, including Renishaw's UCC range of universal CMM controllers
- Full compatibility with REVO® and PH20
- CAD-driven online / offline programming
- Full motion simulation and collision detection, including 5-axis moves
- Native DMIS support
- Certified mathematical algorithms
- Powerful text and graphical reporting
- Flexible output of results data including certified Q-DAS



Coordinate measuring machine probes
1-63

MODUS™

MODUS™ – 3-axis and 5-axis touch-trigger

Part number: A-5639-0001 Price: \$8,800

MODUS™ – 3-axis scanning

Part number: A-5639-0003 Price: \$12,800

MODUS™ – 5-axis scanning

Part number: A-5639-0005 Price: \$20,800

MODUS™ Offline*

MODUS™ – Offline 3-axis and 5-axis touch-trigger

Part number: A-5639-0101 Price: \$4,400

MODUS™ – Offline 3-axis scanning

Part number: A-5639-0103 Price: \$6,400

MODUS™ – Offline 5-axis scanning

Part number: A-5639-0105 Price: \$10,400

Offline – Graphical reporting

Part number: A-5639-0007 Price: \$1,600

Options

Renishaw offers multiple application-specific analysis packages including Modus Gear, Modus Spline and Modus Airfoil. These are chargeable modules added to a base package of Modus 3-axis or 5-axis. Please contact Renishaw for details.

* The online version of MODUS™ can also be run offline without the need to purchase MODUS™ Offline. Only purchase MODUS™ Offline if you require a dedicated offline seat of MODUS™.

CAD integration options

In addition to the native IGES and STEP support, MODUSTM offers a wide range of CAD options including VDA-FS, STEP, CATIA® (v5 and v4), Unigraphics®, Parasolid®, Pro/E® and SolidWorks®. For a complete list and pricing of CAD import / export options please contact Renishaw sales.

Software maintenance agreements

Every new purchase of MODUSTM comes with one year's free software updates, maintenance and support. After the first year, one-year maintenance agreements can be purchased for MODUSTM and its software options. Please contact Renishaw sales for details.

MODUSTM training at Renishaw Inc

Charge per student.

4 days

Part number: A-5639-1701 **Price:** \$3,000

3 days

Part number: A-5639-1700 **Price:** \$2,250

2 days

Part number: A-5639-1702 **Price:** \$1,500

1 day

Part number: A-5639-1703 **Price:** \$750

Onsite MODUSTM training

Up to four people, all inclusive of expenses.

4 days

Part number: RI-5639-1701 **Price:** \$9,625

3 days

Part number: RI-5639-1700 **Price:** \$7,700

2 days

Part number: RI-5639-1702 **Price:** \$5,775

1 day

Part number: RI-5639-1703 **Price:** \$3,850

MODUSTM training block

Part number: A-5639-2500 **Price:** \$680

Renishaw services

Renishaw has set up a series of part numbers which should be referenced when ordering Renishaw services. These part numbers will appear on your invoice.

Part number	Description	Price
RI-6002-0001	CMM hourly labor	\$150/hour
RI-6002-0002	CMM hourly travel	\$75/hour
RI-6002-0003	CMM expenses	as incurred
RI-6002-0004	CMM in-house training	\$750/day



Machine tool probes



Inspection probes for machining centers

MP11

The MP11 is a hard-wired probe ideal for small machine tools with manual tool changing. The probe is mounted in the machine spindle with the signal transmission cable connected to the machine control. With the MP11, the illuminated LED switches off every time the probe stylus contacts the workpiece.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 17.5^\circ$
	Z: 8 mm (0.31 in)
Stylus trigger force	X and Y: 50 gf – 150 gf
	Z: 180 gf – 700 gf
Unidirectional repeatability	1.0 μm (0.00004 in)



MP11 retrofit kit

Includes: MP11 probe with cable and connectors
Remote socket kit
50 mm and 100 mm ceramic styli
Renishaw Inspection Plus software
Installation and applications support

A shank is not included in this kit. See the section entitled Shanks and Toolholders for price and part number information.

Part number: MP11-NS-S (Available at fixed price)
Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

MP11 hardware only kit

Includes: MP11 probe with cable and connectors
Remote socket kit
50 mm and 100 mm ceramic styli

A shank is not included in this kit. See the section entitled Shanks and Toolholders for price and part number information.

Part number: MP11-NS-KIT **Price:** \$3,558

MP11 probe

Includes: MP11 probe with cable and connectors

Part number: A-2045-0001 **Price:** \$3,079

MP11 replacement parts

Spare MP11 cable

Part number: A-2045-0051 **Price:** \$132

4 pin connector for MP11 cable

Part number: MP11 PLUG KIT **Price:** \$64

4 pin socket for MP11

Part number: P-CN21-0304 **Price:** \$65


Outer diaphragm kit

Part number: A-2051-7105 **Price:** \$103

MP15

The MP15 probe is used on small CNC machines with limited Z travel and manual tool changing.

The probe is mounted in the machine spindle with the signal transmission cable connected to the machine control. With the MP15, the illuminated LED switches off every time the probe stylus contacts the workpiece.



MP15 hard-wired probe kit

Part number: A-2116-1802

Price: \$2,114

MP15/MP11 adaptor

Part number: M-2116-1356

Price: \$225

HSI interface

Part number: A-5500-1000

Price: \$198

OMP600

OMP600 is the latest generation optical transmission probe using strain gage technology and suitable for medium to large machining and mill-turn centers. Utilizing a revised state-of-the-art modulated optical transmission method, the system offers the highest resistance to light interference.

The OMP600 probe is also backwards compatible with existing OMM/MI12 and OMI receivers. OMP600 also supports all methods of probe activation – shank switch, spin and M code – enabling current MP700 users to benefit from some of its innovations.

Sense directions	±X, ±Y, +Z	
Stylus overtravel	X and Y:	±15°
	Z:	11 mm (0.43 in)
Stylus trigger force	X and Y:	15 gf
	Z:	178 gf
Unidirectional repeatability	0.25 µm (0.00001 in)	



OMP600 retrofit kit

- Includes: OMP600 probe
 OMM-2/OSI
 Receiver mounting bracket
 50mm and 100 mm carbon fiber styli
 Sealrite kit
 Renishaw Inspection Plus software
 Installation and application support

A shank (tool holder) is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: OMP600-NS-S (Available at fixed price)
 Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

OMP600 hardware only kit

- Includes: OMP600 probe
 OMM-2/OSI
 Receiver mounting bracket
 50 mm and 100 mm carbon fiber styli
 Sealrite kit

Part number: OMP600-NS-KIT **Price:** \$6,954

OMP600 probe kit

- Includes: OMP600 probe
 AA battery (2)
 Tool kit

Legacy

Part number: A-5180-0001 **Price:** \$4,564

Modulated

Part number: A-5180-2001 **Price:** \$4,564

OMP600 upgrade kit

Current users of MP700 optical transmission probes may upgrade to OMP600. A complete working system (probe module plus transmission system) must be exchanged.

- Includes: OMP600 probe

Part number: RI-5180-0001 **Price:** \$2,282

OMP600 continued

OMM-2 optical receiver

Part number: A-5492-0051 **Price:** \$986

OMI-2 optical receiver/interface

With 8 m cable.

Part number: A-5191-0049 **Price:** \$1,582

OMI-2 optical receiver/interface

With 15 m cable.

Part number: A-5191-0050 **Price:** \$1,664

OMI-2T optical receiver/interface

With 8 m cable.

Part number: A-5439-0049 **Price:** \$1,582

OMI-2T optical receiver/interface

With 15 m cable.

Part number: A-5439-0050 **Price:** \$1,664

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

OSI interface

Part number: A-5492-2000 **Price:** \$931

Sealtite conduit for OMM-2, OMI-2 or OMI-2T

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

OMP40-2

The OMP40-2 is an ultra-compact optical transmission part probing system. Measuring just 40 mm diameter and 50 mm in length, the OMP40-2 is suitable for all machining and mill-turn centers. Utilizing a revised state-of-the-art modulated optical transmission method, the system offers the highest level of resistance to light interference when used with the OMI-2/OMI-2T. The OMP40-2 probe is also backwards compatible with existing OMM/MI12 and OMI receivers, enabling current MP7, MP8, MP9 and MP10 system users to benefit from its innovative features.

Sense directions	±X, ±Y, +Z
Stylus overtravel	X and Y: ±12.5°
	Z: 6 mm (0.23 in)
Stylus trigger force	X and Y: 50 gf – 90 gf
	Z: 585 gf
Unidirectional repeatability	1.0 µm (0.00004 in)

OMP40-2 retrofit kit

Includes: OMP40-2 probe
OMM-2
Receiver mounting bracket
OSI interface
50 mm and 100 mm ceramic styli
Sealtite kit
Renishaw Inspection Plus software
Installation and applications support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: OMP40-NS-S (Available at fixed price)
Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

OMP40-2 hardware only kit

Includes: OMP40-2 probe
OMM-2
Receiver mounting bracket
OSI interface
50 mm and 100 mm ceramic styli
Sealtite kit

Part number: OMP40-NS-KIT **Price:** \$6,126



OMP40-2 probe kit

Includes: OMP40-2
½ AA battery (2)
Tool kit

Legacy

Part number: A-4071-0001 **Price:** \$3,803

Modulated

Part number: A-4071-2001 **Price:** \$3,803

OMP40-2 upgrade kit

Current users of MP7, MP8, MP9 or MP10 optical transmission probes may upgrade to OMP40-2. A complete working system (probe module plus transmission system) must be exchanged.

Includes: OMP40-2 probe system

Part number: RI-4071-0001 **Price:** \$1,902

OMP40-2 accessories and replacement parts

½AA battery (2 pack)

Part number: P-BT03-0007 **Price:** \$43

OMP60/RMP60 style shank adaptor

Part number: A-4071-0031 **Price:** \$171

OMP40-2 continued

OMM-2 optical receiver

Part number: A-5492-0051 **Price:** \$986

OMI-2 optical receiver/interface

With 8 m cable.

Part number: A-5191-0049 **Price:** \$1,582

OMI-2 optical receiver/interface

With 15 m cable.

Part number: A-5191-0050 **Price:** \$1,664

OMI-2T optical receiver/interface

With 8 m cable.

Part number: A-5439-0049 **Price:** \$1,582

OMI-2T optical receiver/interface

With 15 m cable.

Part number: A-5439-0050 **Price:** \$1,664

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

OSI interface

Part number: A-5492-2000 **Price:** \$931

Sealtite conduit for OMM-2, OMI-2 or OMI-2T

5/16 in conduit, 1 meter long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

OMP400

OMP400 is an ultra-compact optical transmission probe using strain gage technology. Measuring just 40 mm diameter x 50 mm in length, OMP400 is suitable for all machining and mill-turn centers requiring uncompromised 3D metrology performance. Utilizing a revised state-of-the-art modulated optical transmission method, the system offers the highest level of resistance to light interference when used with OMI-2. The OMP400 probe is also backwards compatible with existing OMM/MI12 and OMI receivers, enabling current MP7, MP8, MP9 and MP10 system users to benefit from its innovative features.

Sense directions	±X, ±Y, +Z	
Stylus overtravel	X and Y:	±18°
	Z:	11 mm (0.43 in)
Stylus trigger force	X and Y:	6 gf
	Z:	260 gf
Unidirectional repeatability	0.25 µm (0.00001 in)	



OMP400 retrofit kit

- Includes: OMP400 probe
 OMM-2
 Receiver mounting bracket
 OSI interface
 50 mm and 100 mm carbon fiber styli
 Sealtite kit
 Renishaw Inspection Plus software
 Installation and applications support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: OMP400-NS-S (Available at fixed price)
 Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

OMP400 hardware only kit

- Includes: OMP400 probe
 OMM-2
 Receiver mounting bracket
 OSI interface
 50 mm and 100 mm carbon fiber styli
 Sealtite kit

Part number: OMP400-NS-KIT **Price:** \$6,954

OMM-2 optical receiver

Part number: A-5492-0051 **Price:** \$986

OMP400 probe kit

- Includes: OMP400 probe
 ½ AA battery (2)
 Tool kit

Legacy

Part number: A-5069-0001 **Price:** \$4,564

Modulated

Part number: A-5069-2001 **Price:** \$4,564

OMP400 upgrade kit

Current users of MP700 optical transmission probes may upgrade to OMP400. A complete working system (probe module plus transmission system) must be exchanged.

- Includes: OMP400 probe

Part number: RI-5069-0001 **Price:** \$2,282

Note: A new shank is required. See section entitled Shanks and Toolholders for price and part number information.

OMP400 continued

OMI-2 optical receiver/interface

With 8 m cable.

Part number: A-5191-0049 **Price:** \$1,582

OMI-2 optical receiver/interface

With 15 m cable.

Part number: A-5191-0050 **Price:** \$1,664

OMI-2T optical receiver/interface

With 8 m cable.

Part number: A-5439-0049 **Price:** \$1,582

OMI-2T optical receiver/interface

With 15 m cable.

Part number: A-5439-0050 **Price:** \$1,664

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

OSI interface

Part number: A-5492-2000 **Price:** \$931

Sealtite conduit for OMM-2, OMI-2 or OMI-2T

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

To obtain optimal metrology performance, the following carbon fiber styli are recommended. Refer to the Styli section for more details.

Stylus	Part number	Price
6 × 50 mm CF	A-5003-7306	\$128
6 × 100 mm CF	A-5003-6510	\$145
6 × 150 mm CF	A-5003-6511	\$274
6 × 200 mm CF	A-5003-6512	\$289

OMP60

OMP60 is an optical transmission probing system suitable for medium to large machining and mill-turn centers. Utilizing a revised state-of-the-art modulated optical transmission method, the system offers the highest level of resistance to light interference. The OMP60 probe is also backwards compatible with existing OMM/MI12 and OMI receivers. OMP60 also supports all methods of probe activation – shank switch, spin and M code – enabling current MP7, MP8, MP9 and MP10 users to benefit from some of its innovative features.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 18^\circ$
	Z: 11 mm (0.43 in)
Stylus trigger force	X and Y: 75 gf – 140 gf
	Z: 530 gf
Unidirectional repeatability	1.0 μm (0.00004 in)

OMP60 retrofit kit

Includes: OMP60 probe
 OMM-2
 Receiver mounting bracket
 OSI interface
 50 mm and 100 mm ceramic styli
 Sealtite kit
 Renishaw Inspection Plus software
 Installation and applications support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: OMP60-NS-S (Available at a fixed price)
 Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

OMP60 hardware only kit

Includes: OMP60 probe
 OMM-2
 Receiver mounting bracket
 OSI interface
 50 mm and 100 mm ceramic styli
 Sealtite kit

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: OMP60-NS-KIT **Price:** \$6,126



OMP60 probe kit

Includes: OMP60 probe
 AA battery (2)
 Tool kit

Legacy

Part number: A-4038-0001 **Price:** \$3,803

Modulated

Part number: A-4038-2001 **Price:** \$3,803

OMP60 upgrade kit

Current users of MP7, MP8, MP9 or MP10 optical transmission probes may upgrade to OMP60. A complete working system (probe module plus transmission system) must be exchanged.

Includes: OMP60 probe system

Part number: RI-4038-0001 **Price:** \$1,902

OMP60 continued

OMM-2 optical receiver

Part number: A-5492-0051 **Price:** \$986

OMI-2 optical receiver/interface

With 8 m cable.

Part number: A-5191-0049 **Price:** \$1,582

OMI-2 optical receiver/interface

With 15 m cable.

Part number: A-5191-0050 **Price:** \$1,664

OMI-2T optical receiver/interface

With 8 m cable.

Part number: A-5439-0049 **Price:** \$1,582

OMI-2T optical receiver/interface

With 15 m cable.

Part number: A-5439-0050 **Price:** \$1,664

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

OSI interface

Part number: A-5492-2000 **Price:** \$931


Sealtite conduit for OMM-2, OMI-2 or OMI-2T

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

OMP60M

OMP60M is a modular version of the OMP60. The OMP60M, probe module, adaptors and extensions need to be purchased separately.



1 – OMP60M transmission module

Part number: A-4038-1003 Price: \$1,170

2 – OMP60M probe module

Part number: A-4038-1002 Price: \$3,056

3 – OMP60M 100 mm extension

Part number: A-4038-1010 Price: \$618

4 – OMP60M 150 mm extension

Part number: A-4038-1027 Price: \$801

5 – OMP60M 200 mm extension

Part number: A-4038-1028 Price: \$832

6 – OMP60M LP2 adaptor

Part number: A-4038-0212 Price: \$618

7 – LPE3 150 mm extension

Part number: A-2063-7003 Price: \$285

8 – LPE2 100 mm extension

Part number: A-2063-7002 Price: \$285

9 – LPE1 50 mm extension

Part number: A-2063-7001 Price: \$285

10 – MA4 90° adaptor

Part number: A-2063-7600 Price: \$464

11 – LP2 probe assembly

Part number: A-2063-6098 Price: \$2,961

12 – OMP60M 3-way adaptor

Part number: A-4113-0784 Price: \$1,248

13 – OMP60M probe module adaptor

Part number: A-4113-0771 Price: \$707

14 – MP3 probe

Part number: A-2053-5358 Price: \$3,098

15 – Shorting cover

Part number: A-2053-6468 Price: \$137

OMP60M upgrade kit

Current users of MP7, MP8, MP9 or MP10 optical transmission probes may upgrade to OMP60M. A complete working probe must be exchanged.

Includes: OMP60M module
OMP60M probe module

Part number: RI-4038-1003 Price: \$2,422

RMP40

RMP40 is an ultra-compact radio transmission part probe, ideal for use on small to medium machining centers. RMP40 features an integrated probe module delivering exceptional robustness and generous overtravel. RMP40 complies with FCC regulations and operates in the 2.4 GHz range. RMP40 delivers interference-free transmission through the use of FHSS (frequency hopping spread spectrum).

RMP40 supports two methods of probe activation:

Radio-on The probe is turned on via an RF signal produced by the RMI-Q and initiated by an M code. The probe is turned off via an RF signal or the internal timer.

Spin-on The probe is turned on via an internal centrifugal switch. The probe is turned off via the centrifugal switch or the internal timer.

Sense directions	±X, ±Y, +Z	
Stylus overtravel	X and Y:	±12.5°
	Z:	6 mm (0.24 in)
Stylus trigger force	X and Y:	50 gf – 90 gf
	Z:	585 gf
Unidirectional repeatability	1.0 µm (0.00004 in)	

RMP40 retrofit kit

Includes: RMP40 probe and transmission system
RMI-Q radio machine interface
Receiver mounting bracket
50 mm and 100 mm ceramic styli
Sealtite kit
Renishaw Inspection Plus software
Installation and applications support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: RMP40-NS-S (Available at a fixed price)
Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

RMP40 hardware only kit

Includes: RMP40 probe and transmission system
RMI-Q radio machine interface
Receiver mounting bracket
50 mm and 100 mm ceramic styli
Sealtite kit

Part number: RMP40-NS-KIT **Price:** \$8,085



RMP40 probe kit

Includes: RMP40 probe
½AA battery (2)
Tool kit

Part number: A-5480-0001 **Price:** \$5,120

RMI-Q radio machine interface

Part number: A-4113-0050 **Price:** \$2,559

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

Sealtite conduit

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

RMP60

RMP60 is a radio transmission part probing system ideal for use on all machine tools. RMP60 features an integrated probe module delivering exceptional robustness and generous overtravel. RMP60 complies with FCC regulations and operates in the 2.4 GHz range. RMP60 delivers interference-free transmission through the use of FHSS (frequency hopping spread spectrum).

RMP60 supports three methods of probe activation:

- Radio-on** The probe is turned on via an RF signal produced by the RMI-Q and initiated by an M code. The probe is turned off via an RF signal or the internal timer.
- Spin-on** The probe is turned on via an internal centrifugal switch. The probe is turned off via the centrifugal switch or the internal timer.
- Switch-on** The probe is turned on and off via a switch incorporated into the shank, activated when the probe is loaded into the spindle.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 18^\circ$
	Z: 11 mm (0.43 in)
Stylus trigger force	X and Y: 75 gf – 140 gf
	Z: 530 gf
Unidirectional repeatability	1.0 μm (0.00004 in)

RMP60 retrofit kit

- Includes: RMP60 probe and transmission system
RMI-Q radio machine interface
Receiver mounting bracket
50 mm and 100 mm ceramic styli
Sealtite kit
Renishaw Inspection Plus software
Installation and applications support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: RMP60-NS-S (Available at a fixed price)
Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

RMP60 hardware only kit

- Includes: RMP60 probe and transmission system
RMI-Q radio machine interface
Receiver mounting bracket
50 mm and 100 mm ceramic styli
Sealtite kit

Part number: RMP60-NS-KIT **Price:** \$8,085



RMP60 probe kit

- Includes: RMP60 probe
AA battery (2)
Tool kit

Part number: A-4113-0001 **Price:** \$5,120

RMI-Q radio machine interface

Part number: A-4113-0050 **Price:** \$2,559

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

Sealtite conduit

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

RMP60 upgrade kit


Current users of MP14, MP16 or MP18 radio probes may upgrade to RMP60. A complete working system (MP3 probe, transmission system, MI14 or MI16 interface and RMM antennas) must be exchanged.

- Includes: RMP60 probe
RMI-Q radio machine interface
Receiver mounting bracket
Sealtite kit

Part number: RI-4113-0001 **Price:** \$5,200

RMP60M

RMP60M is a modular version of the RMP60. The RMP60M, probe module, adaptors and extensions need to be purchased separately. RMP60M complies with FCC regulations and operates in the 2.4 GHz range.



1 – RMP60M transmission module

Part number: A-4113-1003 Price: \$2,499

2 – RMP60M probe module

Part number: A-4038-1002 Price: \$3,056

3 – RMP60M 100 mm extension

Part number: A-4038-1010 Price: \$618

4 – RMP60M 150 mm extension

Part number: A-4038-1027 Price: \$801

5 – RMP60M 200 mm extension

Part number: A-4038-1028 Price: \$832

6 – RMP60M LP2 adaptor

Part number: A-4038-0212 Price: \$618

7 – LPE3 150 mm extension

Part number: A-2063-7003 Price: \$285

8 – LPE2 100 mm extension

Part number: A-2063-7002 Price: \$285

9 – LPE1 50 mm extension

Part number: A-2063-7001 Price: \$285

10 – MA4 90° adaptor

Part number: A-2063-7600 Price: \$464

11 – LP2 probe assembly

Part number: A-2063-6098 Price: \$2,961

12 – RMP60M 3-way adaptor

Part number: A-4113-0784 Price: \$1,248

13 – RMP60M probe module adaptor

Part number: A-4113-0771 Price: \$707

14 – MP3 probe

Part number: A-2053-5358 Price: \$3,098

15 – Shorting cover

Part number: A-2053-6468 Price: \$137

RMP60M upgrade kit

Current users of MP14, MP16 or MP18 radio probes may upgrade to RMP60M. A complete working system (probe, MI14 or MI16 interface and RMM antennas) must be exchanged.

Includes: RMP60M module
RMP60M probe module
RMI radio machine interface
Receiver mounting bracket
Sealtite kit

Part number: RI-4113-1003 Price: \$5,720

RMP600

RMP600 is a radio transmission probe using strain gage technology. Measuring only 63 mm in diameter and 76 mm in length, with an omni-directional transmission distance of 15 m, it is ideal for use on all machine tools. RMP600 features an integrated probe module delivering exceptional robustness and generous overtravel. It delivers interference-free transmission through the use of FHSS (frequency hopping spread spectrum). RMP600 complies with FCC regulations and operates in the 2.4 GHz range.

RMP600 supports three methods of probe activation:

- Radio-on** The probe is turned on via an RF signal produced by the RMI-Q and initiated by an M code. The probe is turned off via an RF signal or the internal timer.
- Spin-on** The probe is turned on via an internal centrifugal switch. The probe is turned off via the centrifugal switch or the internal timer.
- Switch-on** The probe is turned on and off via a switch incorporated into the shank, activated when the probe is loaded into the spindle.

Sense directions	±X, ±Y, +Z
Stylus overtravel	X and Y: ±15°
	Z: 11 mm (0.43 in)
Stylus trigger force	X and Y: 20 gf
	Z: 193 gf
Unidirectional repeatability	0.25 µm (0.00001 in)

RMP600 retrofit kit

- Includes: RMP600 probe
RMI-Q radio machine interface
Receiver mounting bracket
50 mm and 100 mm carbon fiber styli
Sealtite kit
Renishaw Inspection Plus software
Installation and application support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: RMP600-NS-S (Available at a fixed price)
Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

RMP600 hardware only kit

- Includes: RMP600 probe
RMI-Q radio machine interface
Receiver mounting bracket
50 mm and 100 mm carbon fiber styli
Sealtite kit

Part number: RMP600-NS-KIT **Price:** \$10,032



RMP600 probe kit

- Includes: RMP600 probe
AA battery (2)
Tool kit

Part number: A-5312-0001 **Price:** \$7,000

RMI-Q radio machine interface

Part number: A-4113-0050 **Price:** \$2,559

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

Sealtite conduit

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

RMP600 upgrade kit

Current users of MP14, MP16 or MP18 radio probes may upgrade to RMP600. A complete working system (MP3 probe, transmission system, MI14 or MI16 interface and RMM antennas) must be exchanged.

- Includes: RMP600 probe
RMI-Q radio machine interface
Receiver mounting bracket
Sealtite kit

Part number: RI-5312-0001 **Price:** \$6,440

Shanks and Toolholders

Shanks for OMP60, MP11, OMP600, RMP60 and RMP600 (spin-on, optical-on, radio-on) systems

Part number	Description	Price
M-2045-0068	CAT30	\$368
M-2045-0069	CAT40	\$368
M-2045-0138	CAT45	\$818
M-2045-0071	CAT50	\$368
M-2045-0292	CAT60	\$1,700
M-2045-0077	BT30	\$368
M-2045-0027	BT40	\$368
M-2045-0038	BT45	\$818
M-2045-0073	BT50	\$368
M-2045-0186	HSK A40	\$693
M-2045-0187	HSK A50	\$826
M-2045-0188	HSK A63	\$887
M-2045-0189	HSK A80	\$1,074
M-2045-0190	HSK A100	\$1,077
A-2045-0243	½ in straight shank	\$218
A-2030-0252	1 in straight shank	\$218
A-2030-0211	25 mm straight shank	\$218
M-2045-0313	CAPTO C4	\$750
M-2045-0346	CAPTO C5	\$995
M-2045-0310	CAPTO C6	\$676
M-2045-0311	CAPTO C8	\$1,672
M-2045-0335	KM63	\$1,388
M-2045-1831591	KM63Y (Mazak)	\$1,573

Calibration masters

Calibration tools

Part number	Description	Price
M-2253-0954	CAT40	\$431
M-2253-0955	CAT50	\$539
M-2253-1562	BT30	\$697
M-2253-1263	BT40	\$431
M-2253-1262	BT50	\$539

Shanks for OMP40-2, OMP400 and RMP40

Part number	Description	Price
M-4071-0050	CAT30	\$413
M-4071-0058	CAT40	\$368
M-4071-0072	CAT50	\$368
M-4071-0049	BT30	\$425
M-4071-0057	BT40	\$368
M-4071-0071	BT50	\$368
M-4071-0048	ISO30 DIN69871	\$413
M-4071-0069	ISO40 DIN69871	\$395
M-4071-0044	HSK E25	\$482
M-4071-0055	HSK E32	\$482
M-4071-0054	HSK E40	\$482
M-4071-0045	HSK A32	\$482
M-4071-0046	HSK A40	\$482
M-4071-0047	HSK A50	\$649
M-4071-0129	HSK A63	\$568
M-4071-0141	CAPTO C4	\$791
M-4071-0066	CAPTO C5	\$822
M-4071-0067	CAPTO C6	\$822
M-4071-0065	KM63	\$822

OMP40, OMP400 and RMP40 shank kits

CAT40 shank kit

Includes: CAT40 shank
OMP60/RMP60 shank adaptor

Part number: M-4071-0058-RI **Price:** \$539

BT40 shank kit

Includes: BT40 shank
OMP60/RMP60 shank adaptor

Part number: M-4071-0057-RI **Price:** \$539

Shanks for OLP40 and RLP40

Part number	Description	Price
A-5625-1003	25 mm straight shank	\$218
A-5625-1004	½ in straight shank	\$218
A-5625-1007	1 in straight shank	\$218

Tool setting probes for machining centers

NC4 tool setter

NC4 is a non-contact tool setter and our most compact design. NC4 is available in fixed or separate configurations. NC4F (fixed) is available in four different sizes. NC4S (separate) systems are user-configurable operating between 500 mm and 5 m.

Repeatability	±1.0 µm (0.00004 in)	
Minimum tool diameter	Measurement	0.03 mm (0.0012 in)
	Breakage	0.03 mm (0.0012 in)

NC4 fixed system retrofit kits

Include: NC4 fixed unit with 12.5 m cable
NCi-5 interface
Air regulator kit
Ø22 mm OD steel braided conduit
Mounting plate
Tool setting software
Installation and application support

Part numbers: NC4-F300-Modular-S *
NC4-F300-S *
NC4-F230-S *
NC4-F145-S *
NC4-F115-S *
NC4-F95-S *

NC4 separate system retrofit kits

Include: NC4 separate unit with 12.5 m cable
NCi-5 interface
Air regulator kit
Ø17 mm OD steel braided conduit
Tool setting software
Installation and application support

Part numbers: NC4-S800-S *
NC4-S1500-S *
NC4-S2000-S *
NC4-S3000-S *
NC4-S5000-S *

Note: When ordering a separate system retrofit kit, the customer must select an NC4 based on its operating range. In addition, the customer must select tool setting software based on the control type. Brackets and an adjusting method (see following page) are also needed for NC4 separate systems. These are not included with NC4 separate systems and must be ordered additionally. Mounting brackets for various machines are continually developed. Contact Renishaw for the latest list of compatibility. Bracket installation is **not** included with the standard separate system retrofit price, this service can be quoted upon request.

* Available at a fixed price. Call for details.

NC4 fixed kits

NC4 F300/225 with NCi-5 kit

Separation 225 mm

Part number: NC4-F300-Modular-kit **Price:** \$4,781



NC4 F300/240 with NCi-5 kit

Separation 240 mm

Part number: NC4-F300-kit **Price:** \$4,781



NC4 F230/170 with NCi-5 kit

Separation 170 mm

Part number: NC4-F230-kit **Price:** \$4,781

NC4 F145/85 with NCi-5 kit

Separation 85 mm

Part number: NC4-F145-kit **Price:** \$4,781

NC4 F115/55 with NCi-5 kit

Separation 55 mm

Part number: NC4-F115-kit **Price:** \$4,781

NC4 F95/23 with NCi-5 kit

Separation 23 mm

Part number: NC4-F95-kit **Price:** \$4,781

NC4 separate kits

NC4 S800 with NCi-5 kit

Separation 500 mm – 800 mm

Part number: A-4114-5060 **Price:** \$4,747



NC4 S1500 with NCi-5 kit

Separation 800 mm – 1500 mm

Part number: A-4114-5065 **Price:** \$4,747

NC4 S2000 with NCi-5 kit

Separation 1500 mm – 2000 mm

Part number: A-4114-5070 **Price:** \$4,747

NC4 S3000 with NCi-5 kit

Separation 2000 mm – 3000 mm

Part number: A-4114-5075 **Price:** \$4,747

NC4 S5000 with NCi-5 kit

Separation 3000 mm – 5000 mm

Part number: A-4114-5080 **Price:** \$4,747

NC4 tool kit

Part number: A-4114-4110 Price: \$43

NC4 air regulator kit

Part number: A-2253-5120 Price: \$443

NC4 air filter service kit

Part number: P-FI01-S002 Price: \$147

NCi-5 interface

Part number: A-5259-2000 Price: \$226

NC4 access panel 0.2

Part number: A-4114-0082 Price: \$22

NC4 access panel 0.4

Part number: A-4114-0084 Price: \$22

NC4 access panel 0.6

Part number: A-4114-0086 Price: \$22

NC4 set-up tool

Part number: A-4114-8000 Price: \$342

Steel sheath conduit 22 mm OD x 1 m

For NC4 fixed cable protection.

Part number: P-HO01-0011 Price: \$23

Steel sheath conduit 17 mm OD x 1 m

For NC4 separate cable protection.

Part number: P-HO01-0008 Price: \$23

NC4F 90-degree cable exit kit

Part number: P-CA61-0068 Price: \$22

Part number: P-CA61-0069 Price: \$22

NC4F air blast nozzle and bracket

Part number: A-5450-0480 Price: \$305

Solenoid kit

Part number: A-5450-0490 Price: \$850


NC4S mounting hardware options

1. NC4 spacer plate – separate

Part number: A-4114-4400 Price: \$102

2. NC4 adjuster pack – separate

Part number: A-4114-3100 Price: \$228



OTS

The OTS is a new optical transmission tool setter for vertical and horizontal machining centers. Modeled on the TS27R, OTS can set tool length and diameter of rotating tools and perform broken tool detection. OTS is available in two configurations – OTS ½AA and OTS AA. OTS can be used with the OMI-2, OMI-2T or OMM-2/OSI interface. OMI-2T or OMM-2/OSI must be used if OTS is to be paired with another optical transmission probe.

Sense directions	±X, ±Y, +Z
Stylus overtravel	X and Y: ±10°
	Z: 5.5 mm (0.21 in)
Stylus trigger force	130 gf – 240 gf
Unidirectional repeatability	1.0 µm (0.00004 in)

OTS retrofit kit

Includes: OTS ½AA or OTS AA probe
OMM-2
Receiver mounting bracket
OSI interface
Sealtite kit
Renishaw tool setting software
Installation and application support

Part number: OTS-S (½AA configuration)

Part number: OTSAA-S (AA configuration)

Available at fixed price – call for details.

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

OTS hardware only kit

Includes: OTS ½AA probe or OTS AA probe
OMM-2
Receiver mounting bracket
OSI interface
Sealtite kit

Part number: OTS-KIT **Price:** \$4,388

Part number: OTSAA-KIT **Price:** \$4,388

OTS ½AA probe kit

Includes: OTS probe
½ AA battery (2)
Tool kit

Part number: A-5401-2001 **Price:** \$2,271

OTS AA probe kit

Includes: OTS probe
AA battery (2)
Tool kit

Part number: A-5514-2001 **Price:** \$2,271

OTS ½AA



OTS AA

OMM-2 optical receiver

Part number: A-5492-0051

Price: \$986

OMI-2 optical receiver/interface

With 8 m cable.

Part number: A-5191-0049

Price: \$1,582

OMI-2 optical receiver/interface

With 15 m cable.

Part number: A-5191-0050

Price: \$1,664

OMI-2T optical receiver/interface

With 8 m cable.

Part number: A-5439-0049

Price: \$1,582

OMI-2T optical receiver/interface

With 15 m cable.

Part number: A-5439-0050

Price: \$1,664

Receiver mounting bracket

Part number: A-2033-0830

Price: \$119

OSI interface

Part number: A-5492-2000

Price: \$931

Sealtite conduit for OMM-2, OMI-2 or OMI-2T

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306

Price: \$27

RTS

The RTS is a radio transmission tool setter for vertical and horizontal machining centers. Modeled after the OTS, RTS can set tool length and diameter of rotating tools and perform broken tool detection. RTS uses AA batteries (identical to RMP60). RTS can be used with either the RMI or the RMI-Q. The RMI-Q must be used if RTS is to be paired with another radio transmission probe.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 10^\circ$
	Z: 5.5 mm (0.21 in)
Stylus trigger force	130 gf – 240 gf
Unidirectional repeatability	1.0 μm (0.00004 in)



RTS retrofit kit

Includes: RTS AA probe
RMI-Q
Receiver mounting bracket
Sealtite kit
Renishaw tool setting software
Installation and application support

Part number: RTSAA-S

Available at fixed price – call for details.

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

RTS hardware only kit

Includes: RTS AA probe
RMI-Q
Receiver mounting bracket
Sealtite kit

Part number: RTSAA-KIT **Price:** \$5,711

RTS AA probe kit

Includes: RTS probe
AA battery (2)
Tool kit

Part number: A-5646-0001 **Price:** \$2,952

RMI radio machine interface

Part number: A-4113-0050 **Price:** \$2,559

RMI-Q radio machine interface

Part number: A-5687-0050 **Price:** \$2,559

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

Sealtite conduit

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

TS27R

The TS27R is a tool setter for vertical machining centers that enables the user to set both tool length and diameter of rotating tools, and to carry out broken tool detection.

Sense directions	±X, ±Y, +Z
Stylus overtravel	X and Y: ±10°
	Z: 5.5 mm (0.21 in)
Stylus trigger force	130 gf – 240 gf
Unidirectional repeatability	1.0 μm (0.00004 in)



TS27R retrofit kit

Includes: TS27R probe
HSI interface
Sealtite kit
Renishaw toolsetting software
Installation and application support

Part number: TS27R-S (Available at fixed price)
Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

TS27R hardware only kit

Includes: TS27R probe
HSI interface
Sealtite kit

Part number: TS27R-KIT **Price:** \$1,403

TS27R probe, stylus, and holder kit

Part number: A-2008-0368 **Price:** \$1,136

HSI interface

Part number: A-5500-1000 **Price:** \$198

OTS, RTS or TS27R replacement parts and accessories

Tungsten carbide stylus (0.5 in disk)

Part number: A-2008-0382 **Price:** \$111

Ceramic stylus (19 mm square)

Part number: A-2008-0384 **Price:** \$260

Retrofit stylus kit

Includes: Break protection
Tether
Screws

Part number: A-5003-5171 **Price:** \$35

Break protect link

Part number: A-5003-0661 **Price:** \$25

Stylus holder with 4 set screws

Part number: A-2008-0389 **Price:** \$25

Stylus holder set screws

Part number: P-SC13-0403 **Price:** \$2

Crank for horizontal machining centers

Part number: A-2008-0448 **Price:** \$120

100 mm riser

Part number: M-2008-0866-RI-KIT **Price:** \$129

TS27 stylus (0.5 in disk)

For TS27 probes shipped prior to July 1995.

Part number: M-5003-1033 (steel) **Price:** \$111

Part number: M-2008-0197 (ceramic) **Price:** \$244

TS34

TS34 is a hard-wired tool setter for vertical and horizontal machining centers that enables users to set both length and diameter of rotating tools and perform broken tool detection.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 9^\circ$
	Z: 4 mm (0.157 in)
Stylus trigger force	X and Y: 65 gf – 142 gf
	Z: 550 gf
Unidirectional repeatability	1.0 μm (0.00004 in)

TS34 probe, stylus and holder kit

Rear exit

Part number: A-2197-2100 **Price:** \$3,364

Side exit

Part number: A-2197-3000 **Price:** \$3,364

HSI interface

Part number: A-5500-1000 **Price:** \$198



Primo™ LTS

The Primo LTS (length tool setter) is a hard wired single-axis tool setter which provides users with the ability to set tool length, check for tool wear and tool breakage, and to compensate for machine thermal growth. The LTS is used in conjunction with LTS application software which is available to download free of charge.

Sense directions	+Z
Stylus overtravel	Z: 7.5 mm (0.29 in)
Stylus trigger force	3N / 306 gf
Repeatability	0.75 µm (0.00003 in)



Primo LTS kit

Includes: Primo LTS
Ø26 mm contact pad

Part number: A-5475-0001 **Price:** \$938

Primo LTS with adaptor block

Includes: Primo LTS
Ø26 mm contact pad
Adaptor

Part number: A-5475-0002 **Price:** \$1,015

Primo LTS replacement parts and accessories

LTS tool kit

Includes: Ferrules (× 3)
1.5 mm hex key (× 1)

Part number: A-5475-0060 **Price:** \$23

LTS installation kit

Includes: M5 cap head screws (× 4)
Air pipe fitting (× 1)
Air flow regulator (× 1)
5 m × Ø6 mm air pipe

Part number: A-5475-0401 **Price:** \$90

LTS Ø26 mm contact pad kit

Includes: Ø26 mm (Ø1.02 in) contact pad (tungsten carbide)
Tool kit

Part number: A-5475-0402 **Price:** \$196

LTS air pipe

Part number: A-5475-0403 **Price:** \$60

LTS adaptor block (for T-slot mounting)

Part number: A-5475-0404 **Price:** \$78

LTS riser block 50 mm

Part number: A-5475-0405 **Price:** \$175

LTS riser block 100 mm

Part number: A-5475-0406 **Price:** \$277

LTS conduit bulkhead kit

Part number: A-5475-0407 **Price:** \$152

LTS conduit extension kit 2 m

Part number: A-5475-0408 **Price:** \$152

LTS conduit extension kit 5 m

Part number: A-5475-0409 **Price:** \$244

Solenoid kit

Part number: A-5299-2933 **Price:** \$448

TRS2

TRS2 is a cost-effective laser-based solution for high-speed broken tool detection. Working with the reflective properties of a rotating tool, TRS2 can detect broken tools at a distance of between 300 mm and 2 m, but optimized for use between 300 mm and 1 m. Toolwise™ Electronics makes TRS2 especially effective with tiny, easily broken tools down to 0.019 in (0.5 mm) diameter. TRS2 is suitable for solid profile tools including drills, taps, reamers and end mills.



TRS2 hardware kit

Includes: TRS2 laser system with integral interface
Tool kit
Air regulator kit
Sealtite kit
Basic mounting bracket (shown)
Renishaw TRS2 LTD software

Part number: TRS2-KIT **Price:** \$2,600

TRS2 probe only

Includes: TRS2 laser system with integral interface

Part number: A-5450-0400 **Price:** \$2,008

TRS2 retrofit kit

Includes: TRS2 laser system with integral interface
Tool kit
Air regulator kit
Sealtite kit
Basic mounting bracket (shown)
Renishaw TRS2 LTD software
Installation and application support

Part number: TRS2-S (Available at fixed price)
Call for details

Special pricing available for multiple systems.

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

TRS2 air regulator kit

Part number: A-2253-5120 **Price:** \$443

TRS2 air filter service kit

Part number: P-FI01-S002 **Price:** \$147

Sealtite conduit for TRS2

¼ in conduit, 5 ft long. Includes one fitting.

Part number: SEALTITE, 7455 **Price:** \$23

TRS2 replacement air cap

Part number: A-4178-0440 **Price:** \$30

Inspection probes for turning centers

OLP40

OLP40 is a compact optical transmission part probe, ideal for use on turning centers. OLP40's compact design features an integrated probe module delivering exceptional robustness and generous overtravel. Utilizing a revised state-of-the-art modulated optical transmission method, the system offers the highest level of resistance to light interference. The OLP40 probe is also backwards compatible with existing OMM/MI12 and OMI receivers. OLP40 supports two methods of probe activation – M code and spin-on.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 12.5^\circ$
	Z: 6 mm (0.24 in)
Stylus trigger force	X and Y: 50 gf – 90 gf
	Z: 585 gf
Unidirectional repeatability	1.0 μm (0.00004 in)



OLP40 retrofit kit

Includes: OLP40 probe and transmission system
 OMM-2
 Receiver mounting bracket
 OSI interface
 30 mm stainless steel stylus (x2)
 Sealtite kit
 Renishaw lathe inspection software
 Installation and applications support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: OLP40-NS-S (Available at fixed price)
 Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to us before a retrofit order can be processed.

OLP40 hardware only kit

Includes: OLP40 probe and transmission system
 OMM-2
 Receiver mounting bracket
 OSI interface
 30 mm stainless steel stylus (x2)
 Sealtite kit

Part number: OLP40-NS-KIT **Price:** \$6,060

OLP40 probe kit

Includes: OLP40 probe
 ½ AA battery (2)
 Tool kit

Legacy

Part number: A-5625-0001 **Price:** \$3,803

Modulated

Part number: A-5625-2001 **Price:** \$3,803

OLP40 continued

OMM-2 optical receiver

Part number: A-5492-0051 **Price:** \$986

OMI-2 optical receiver/interface

With 8 m cable.

Part number: A-5191-0049 **Price:** \$1,582

OMI-2 optical receiver/interface

With 15 m cable.

Part number: A-5191-0050 **Price:** \$1,664

OMI-2T optical receiver/interface

With 8 m cable.

Part number: A-5439-0049 **Price:** \$1,582

OMI-2T optical receiver/interface

With 15 m cable.

Part number: A-5439-0050 **Price:** \$1,664

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119

OSI interface

Part number: A-5492-2000 **Price:** \$931


Sealtite conduit for OMM-2, OMI-2 or OMI-2T

5/16 in conduit, 1 meter long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

OMP40M

OMP40M is a modular version of the OLP40. The LP2 probe module, adaptors and extensions need to be purchased separately.



1 – OMP40M transmission module

Legacy

Part number: A-5626-0001 Price: \$1,320

Modulated

Part number: A-5626-2001 Price: \$1,320

2 – LPE3 extension 150 mm

Part number: A-2063-7003 Price: \$285

3 – LPE2 extension 100 mm

Part number: A-2063-7002 Price: \$285

4 – LPE1 extension 50 mm

Part number: A-2063-7001 Price: \$285

5 – MA4 90° adaptor

Part number: A-2063-7600 Price: \$464

6 – LP2 probe assembly

Part number: A-2063-6098 Price: \$2,961

OMP40M retrofit kit

Includes: OMP40M transmission system
LP2 probe
OMM-2
Receiver mounting bracket
OSI interface
30 mm stainless steel stylus (x2)
Sealtite kit
Renishaw lathe inspection software
Installation and applications support

Part number: OMP40M-NS-S (Available at fixed price)
Call for details

OMP40M hardware only kit

Includes: OMP40 transmission system
LP2 probe
OMM-2
Receiver mounting bracket
OSI interface
30 mm stainless steel stylus (x2)
Sealtite kit

Part number: OMP40M-NS-KIT Price: \$6,538

A shank is not included in the above kits. See section entitled Shanks and Toolholders for price and part number information.

OMM-2 optical receiver

Part number: A-5492-0051 Price: \$986

OMI-2 optical receiver/interface

Part number: A-5191-0049 Price: \$1,582

OMI-2T optical receiver/interface

Part number: A-5439-0049 Price: \$1,582

Receiver mounting bracket

Part number: A-2033-0830 Price: \$119

OSI interface

Part number: A-5492-2000 Price: \$931

Sealtite conduit for OMM-2, OMI-2 or OMI-2T

5/16 in conduit, 1 meter long. Includes one fitting.

Part number: A-4113-0306 Price: \$27

RLP40

RLP40 is a compact radio transmission part probe, ideal for use on turning centers. RLP40's compact design features an integrated probe module delivering exceptional robustness and generous overtravel. RLP40 complies with FCC regulations and operates in the 2.4 Ghz range. RLP40 delivers interference-free transmission through the use of FHSS (frequency hopping spread spectrum).

RLP40 supports two methods of probe activation:

- Radio-on** The probe is turned on via an RF signal produced by the RMI-Q and initiated by an M code. The probe is turned off via an RF signal or the internal timer.
- Spin-on** The probe is turned on via an internal centrifugal switch. The probe is turned off via the centrifugal switch or the internal timer.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 12.5^\circ$
	Z: 6 mm (0.24 in)
Stylus trigger force	X and Y: 50 gf – 90 gf
	Z: 585 gf
Unidirectional repeatability	1.0 μm (0.00004 in)

RLP40 retrofit kit

- Includes: RLP40 probe and transmission system
RMI-Q radio machine interface
Receiver mounting bracket
30 mm stainless steel stylus (x2)
Sealtite kit
Renishaw lathe inspection software
Installation and applications support

A shank is not included in this kit. See section entitled Shanks and Toolholders for price and part number information.

Part number: RLP40-NS-S (Available at fixed price)
Call for details

Note: The retrofit questionnaire at the end of this section must be filled out and returned to Renishaw before a retrofit order can be processed.

RLP40 hardware only kit

- Includes: RLP40 probe and transmission system
RMI-Q radio machine interface
Receiver mounting bracket
30 mm stainless steel stylus (x2)
Sealtite kit

Part number: RLP40-NS-KIT **Price:** \$7,499



RLP40 probe kit

- Includes: RLP40 probe
 $\frac{1}{2}$ AA battery (2)
Tool kit

Part number: A-5627-0001 **Price:** \$4,600

RMI-Q radio machine interface

Part number: A-5687-0050 **Price:** \$2,559

Receiver mounting bracket

Part number: A-2033-0830 **Price:** \$119


Sealtite conduit

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 **Price:** \$27

RMP40M

RMP40M is a modular version of the RLP40. The LP2 probe module, adaptors and extensions need to be purchased separately.



1 – RMP40M transmission module

Part number: A-5628-0001 Price: \$2,000

2 – LPE3 extension 150 mm

Part number: A-2063-7003 Price: \$285

3 – LPE2 extension 100 mm

Part number: A-2063-7002 Price: \$285

4 – LPE1 extension 50 mm

Part number: A-2063-7001 Price: \$285

5 – MA4 90° adaptor

Part number: A-2063-7600 Price: \$464

6 – LP2 probe assembly

Part number: A-2063-6098 Price: \$2,961

RMP40M retrofit kit

Includes: RMP40M transmission system
LP2 probe
RMI-Q radio machine interface
Receiver mounting bracket
30 mm stainless steel stylus (x2)
Sealtite kit
Renishaw lathe inspection software
Installation and applications support

Part number: RMP40M-NS-S (Available at fixed price)
Call for details

RMP40M hardware only kit

Includes: RMP40M transmission system
LP2 probe
RMI-Q radio machine interface
Receiver mounting bracket
30 mm stainless steel stylus (x2)
Sealtite kit

Part number: RMP40M-NS-KIT Price: \$7,860

A shank is not included in the above kits. See section entitled Shanks and Toolholders for price and part number information.

RMI-Q radio machine interface

Part number: A-5687-0050 Price: \$2,559

Receiver mounting bracket

Part number: A-2033-0830 Price: \$119

Sealtite conduit

5/16 in conduit, 1 m long. Includes one fitting.

Part number: A-4113-0306 Price: \$27

LP2

The LP2 probe is used on CNC lathes for workpiece inspection and tool setting. It is also used in special applications where its small body makes it suitable for gaging workpiece features with restricted access.

The LP2 is universal and can be fitted to optical, inductive, hard-wired and radio transmission systems. An array of sockets and adaptors is available to support these applications. Please contact Renishaw for further details.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 12.5^\circ$
	Z: 6.5 mm (0.25 in)
Stylus trigger force	X and Y: 50 gf – 90 gf
	Z: 585 gf
Unidirectional repeatability	1.0 μm (0.00004 in)

Includes: LP2 probe
2 C spanners
TK1 tool kit

Part number: A-2063-6098

Price: \$2,961



LP2H

The LP2H probe is used on CNC lathes for workpiece inspection and tool setting. It is designed for heavier duty applications where machine vibration or heavy stylus arrangements may cause unexpected triggers.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 12.5^\circ$
	Z: 5 mm (0.20 in)
Stylus trigger force	X and Y: 200 gf – 400 gf
	Z: 3000 gf
Unidirectional repeatability	2.0 μm (0.00008 in)

Includes: LP2H probe
2 C spanners
TK1 tool kit

Part number: A-2064-0002

Price: \$2,961



LP2DD

The LP2DD probe is based on the LP2 design, but incorporates a revised diaphragm assembly. This probe is recommended for grinding machines and other installations where dust-filled coolant is abundant.

Sense directions	$\pm X, \pm Y, +Z$
Stylus overtravel	X and Y: $\pm 15^\circ$
	Z: 6.5 mm (0.25 in)
Stylus trigger force	X and Y: 50 gf – 90 gf
	Z: 585 gf
Unidirectional repeatability	1.0 μm (0.00004 in)

Includes: LP2DD probe
2 C spanners
TK1 tool kit

Part number: A-2063-8020

Price: \$2,961



LP2/LP2DD replacement parts

Conversion kit

This kit allows the conversion of your existing LP2 probe to LP2DD.

Includes: 2 C spanners
Front ring
Outer diaphragm
O ring

Part number: A-2063-8023 **Price:** \$175

LP2DD diaphragm replacement kit

An outer diaphragm replacement kit for the LP2DD.

Includes: Diaphragm
O ring

Part number: A-2063-8030 **Price:** \$40

Chip deflector

This deflector is recommended if the LP2DD is subjected to continual exposure to hot chips.

Part number: M-2063-8003 **Price:** \$136

C spanner

A C spanner is required for fitting an LP2 to your machine.

Part number: A-2063-7587 **Price:** \$17

LP2 service kit (DK2)

Includes: Front cap
Metal eyelid
Spring
O ring

Part number: A-2063-7542 **Price:** \$80

TK1 tool kit

Includes: Stylus tool
1.5 mm A/F hex key
2.0 mm A/F hex key
2.5 mm A/F hex key
3.0 mm A/F hex key
4.0 mm A/F hex key

Part number: A-2053-7531 **Price:** \$36

LP2 accessories

FS1 adjustable female socket

Provides $\pm 4^\circ$ of angular rotation about the centerline of the LP2. Supplied with 500 mm long cable, protective cover and adjusting screws.

Part number: A-2063-6697 **Price:** \$136

FS2 fixed female socket

Designed for rigid mounting of an LP2. Supplied with 500 mm long cable and protective cover.

Part number: A-2063-5431 **Price:** \$136

FS3 single axis adjustable holder

The socket pivots on two balls, this provides $\pm 4^\circ$ of pitch adjustment about the centerline of the LP2. Supplied with 500 mm long cable, protective cover and adjusting screws.

Part number: A-2063-5308 **Price:** \$238

MA4 90° adaptor

Part number: A-2063-7600 **Price:** \$464

HSI interface

Part number: A-5500-1000 **Price:** \$198

LPE1 extension

A 50 mm long extension which can be fitted between the LP2 and holder.

Part number: A-2063-7001 **Price:** \$285

LPE2 extension

100 mm long.

Part number: A-2063-7002 **Price:** \$285

LPE3 extension

150 mm long

Part number: A-2063-7003 **Price:** \$285

LP2 straight shanks

LP2 straight shanks are fitted with FS2 socket assemblies to accommodate the LP2 probe. An HSI interface is also required.

LP2 0.75 in straight shank with FS2 and cable assembly

Part number: A-2063-8326 **Price:** \$1,223

LP2 1 in straight shank with FS2 and cable assembly

Part number: A-2063-8328 **Price:** \$1,223

LP2 22 mm straight shank with FS2 and cable assembly

Part number: A-2063-8366 **Price:** \$1,223

MP250

MP250 is the next generation compact probe. Measuring just 25 mm in diameter and 40 mm in length, MP250 is identical in size to the popular LP2. MP250 uses Rengage™ strain gage sensing technology and delivers superior metrology performance. MP250 is aimed at the tool cutter grinder and special CNC lathe markets. MP250 is supported via hard-wired only and must be used with the HSI interface and FS sockets designed specifically for the MP250. MP250 is not suitable for use with inductive, optical or radio transmission.

Sense directions	±X, ±Y, +Z
Stylus overtravel	X and Y: ±15°
	Z: 6.5 mm (0.25 in)
Stylus trigger force	X and Y: 11 gf
	Z: 220 gf
Unidirectional repeatability	0.25 µm (0.00001 in)



MP250 probe kit

Includes: MP250 probe
 Tool kit

Part number: A-5500-1600

Price: \$4,420

MP250 accessories

FS10 adjustable female socket for MP250

Part number: A-5500-1710

Price: \$226

FS20 fixed female socket for MP250

Part number: A-5500-1810

Price: \$226

HSI interface for MP250

Part number: A-5500-1000

Price: \$198

Tool setting for turning centers

High precision removable arm (HPRA)

The HPRA is a 'plug-in', cost effective, precision tool setting system for use on CNC lathes. When needed, the arm is manually introduced to the machine envelope and held in place through the use of the machine resident HPRA base. The arm is locked in position through the duration of the tool setting cycle. After use, the arm is removed and stored on the HPRA storage stand.

Unidirectional repeatability

Max 2 sigma value: 5.0 μm (0.0002 in) for arms supporting 6 in to 15 in chucks
 8.0 μm (0.0003 in) for arms supporting 18 in to 24 in chucks



Max arm dimensions: A=580 mm B=450 mm

Min arm dimensions: A=250 mm B=211 mm

HPRA is available to fit most common chuck sizes from 6 in to 24 in.

Each HPRA standard kit (see below) is supplied complete with:

- RP3 probe (A-2197-0049)
- 90° probe holder
- TSi2 interface (A-2176-0010)
- HPRA storage stand (A-2176-0019)



Standard kits

Part number: See below

Price: \$3,538*


* A stylus assembly and base (R/E or S/E) rear exit or side exit are not included and must be ordered separately.

Part description	Part number	A-dimension	B-dimension
HPRA 6 in chuck with RP3 kit	A-2176-0883	250	211
HPRA 8 in chuck with RP3 kit	A-2176-0884	280	241
HPRA 10 in chuck with RP3 kit	A-2176-0885	325	290
HPRA 12 in chuck with RP3 kit	A-2176-0886	355	290
HPRA 15 in chuck with RP3 kit	A-2176-0887	455	335
HPRA 18 in chuck with RP3 kit	A-2176-0888	510	375
HPRA 24 in chuck with RP3 kit	A-2176-0889	580	450

Custom kits

The HPRA can also be designed for specific applications. The customer must specify arm length, probe holder, stylus configuration etc. The items below depict some of the options. Please contact Renishaw for pricing.

- | | | |
|---|-------------|--------------------|
| 1 | A-2176-0268 | PCB/LED housing |
| 2 | A-2176-0018 | 90° holder fixed |
| 3 | A-2176-0257 | I/L holder fixed |
| 4 | A-2048-0523 | LP2 adaptor |
| 5 | A-2176-1291 | I/L adj RP3 holder |
| 6 | A-2176-1290 | 30° adj RP3 holder |
| 7 | A-2176-0269 | 45° adj RP3 holder |
| 8 | A-2176-1289 | 60° adj RP3 holder |
| 9 | A-2176-1288 | 90° adj RP3 holder |



HPRA bases

The HPRA base is designed to provide a repeatable location for fixing the HPRA arm during tool setting cycles. The base is designed to stay resident within the machine and is supplied with a cover to protect the unit from coolant and debris when the arm is not in use. HPRA bases are available in rear and side exit configurations and are supplied with 3 meters of cable.

HPRA rear exit base

Part number: A-2176-0025

Price: \$748

HPRA side exit base



Part number: A-2176-0187

Price: \$748

HPRA storage stand

Part number: A-2176-0019

Price: \$297



HPRA/HPPA/HPMA stylus kits

There are six primary configurations of styli to support HPRA. Each is designed to be compatible with standard sizes of block tooling ranging from 5/8 in to 2 in. Each stylus kit is supplied complete with:

- 15x15x4 stylus assembly
- Break stem
- Stylus extension/adaptor

Part number: A-2197-0157 (16 mm tooling)

Price: \$116

Part number: A-2197-0158 (20 mm tooling)

Price: \$116

Part number: A-2197-0159 (25 mm tooling)

Price: \$116

Part number: A-2197-0160 (32 mm tooling)


Price: \$116

Part number: A-2197-0161 (40 mm tooling)

Price: \$116

Part number: A-2197-0162 (50 mm tooling)

Price: \$116



HPRA/HPPA/HPMA break stems and tool kits

Part number: M-2197-0156 (16 mm and 20 mm tooling)

Price: \$25

Part number: M-2197-0150 (25 mm to 50 mm tooling)

Price: \$25

Part number: A-2176-0639 (16 mm to 20 mm tooling)

Price: \$26

Part number: A-2176-0636 (25 mm to 50 mm tooling)

Price: \$26



High precision pull-down arm (HPPA)

High precision motorized arm (HPMA)

The HPPA is a manual 'pull-down' 'push-up' tool setting system for use on CNC lathes. The HPMA is an 'automatic' servo driven system. Both products are designed to permanently reside in the machine envelope.

When needed, the HPPA is manually 'pulled-down' into position. After use, the arm is 'pushed-up' away from the cutting volume. HPMA requires the use of CNC M codes to drive the arm to its active and stowed positions.

All HPPA and HPMA systems are supplied with an enclosure to protect the probe and stylus assembly when not in use. HPPA and HPMA hubs are available in both R/E (rear exit) and S/E (side exit) configurations. S/E hubs are supplied with a fixed 5 m cable.

R/E hubs are supplied with a bulkhead connector and require the purchase of a separate cable.



Specifications

Unidirectional repeatability

max 2σ value in machine XZ axis: 5.0 μm (0.0002 in) for arms supporting 6 in to 15 in chucks
8.0 μm (0.0003 in) for arms supporting 18 in to 24 in chucks

HPPA max arm dimensions: A=555 mm B=458 mm


HPPA min arm dimensions: A=250 mm B=219 mm

HPMA max arm dimensions: A=555 mm B=458 mm

HPMA min arm dimensions: A=250 mm B=219 mm

HPPA and HPMA are available to fit most common chuck sizes from 6 in to 24 in. Each 'standard' kit (see below) is supplied complete with:

- Arm
- HPPA or HPMA hub
- RP3 probe (A-2197-0049)
- 90° probe holder
- TSi2 interface for HPPA (A-2176-0010)
- TSi3 interface for HPMA (A-2181-0465)
- Probe enclosure (A-2275-0098)
- Cable (supplied with S/E systems only, **purchase separately for R/E systems**)




HPPA standard kits

Part number: See below

Price: \$4,181*

* A stylus assembly is not included and must be ordered separately. In addition HPPA and HPMA R/E systems require the separate purchase of a cable.

Part description	Part number	A-dimension	B-dimension
HPPA 6 in R/E with RP3 kit	A-2275-0181	250	219
HPPA 8 in R/E with RP3 kit	A-2275-0182	286	249
HPPA 10 in R/E with RP3 kit	A-2275-0183	335	298
HPPA 12 in R/E with RP3 kit	A-2275-0184	368	298
HPPA 15 in R/E with RP3 kit	A-2275-0185	400	343
HPPA 18 in R/E with RP3 kit	A-2275-0186	469	383
HPPA 24 in R/E with RP3 kit	A-2275-0187	555	458
HPPA 6 in S/E with RP3 kit	A-2275-0188	250	219
HPPA 8 in S/E with RP3 kit	A-2275-0189	286	249
HPPA 10 in S/E with RP3 kit	A-2275-0190	335	298
HPPA 12 in S/E with RP3 kit	A-2275-0191	368	298
HPPA 15 in S/E with RP3 kit	A-2275-0192	400	343
HPPA 18 in S/E with RP3 kit	A-2275-0193	469	383
HPPA 24 in S/E with RP3 kit	A-2275-0194	555	458




HPMA standard kits

Part number: See below

Price: \$4,718


Part description	Part number	A-dimension	B-dimension
HPMA 6 in R/E with RP3 kit	A-2181-0645	250	219
HPMA 8 in R/E with RP3 kit	A-2181-0646	286	249
HPMA 10 in R/E with RP3 kit	A-2181-0647	335	298
HPMA 12 in R/E with RP3 kit	A-2181-0648	368	298
HPMA 15 in R/E with RP3 kit	A-2181-0649	400	343
HPMA 18 in R/E with RP3 kit	A-2181-0650	469	383
HPMA 24 in R/E with RP3 kit	A-2181-0651	555	458
HPMA 6 in S/E with RP3 kit	A-2181-0652	250	219
HPMA 8 in S/E with RP3 kit	A-2181-0653	286	249
HPMA 10 in S/E with RP3 kit	A-2181-0654	355	298
HPMA 12 in S/E with RP3 kit	A-2181-0655	368	298
HPMA 15 in S/E with RP3 kit	A-2181-0656	400	343
HPMA 18 in S/E with RP3 kit	A-2181-0657	469	383
HPMA 24 in S/E with RP3 kit	A-2181-0658	555	458



Custom kits

The HPPA and HPMA can also be designed for specific applications. The customer must specify arm length, probe holder, stylus configuration, hub type etc. The items below depict some of the options. Please contact Renishaw for pricing.

- 1 A-2176-0268 PCB/LED housing
- 2 A-2176-0018 90° holder fixed
- 3 A-2176-0257 I/L holder fixed
- 4 A-2048-0523 LP2 adaptor
- 5 A-2176-1291 I/L adj RP3 holder
- 6 A-2176-1290 30° adj RP3 holder
- 7 A-2176-0269 45° adj RP3 holder
- 8 A-2176-1289 60° adj RP3 holder
- 9 A-2176-1288 90° adj RP3 holder



HPPA/HPMA cables

The HPPA and HPMA R/E systems require the use of one of the cables below:


Part number: P-CA82-1010 (2 meters)	Price: \$32
Part number: P-CA82-1009 (5 meters)	Price: \$52
Part number: P-CA82-1011 (10 meters)	Price: \$73

HPRA/HPPA/HPMA stylus kits

There are six primary configurations of styli to support HPPA and HPMA. Each is designed to be compatible with standard sizes of block tooling ranging from 5/8 in to 2 in. Each stylus kit is supplied complete with:

- 15x15x4 stylus assembly
- Break stem
- Stylus extension/adaptor

Part number: A-2197-0157 (16 mm tooling)	Price: \$116
Part number: A-2197-0158 (20 mm tooling)	Price: \$116
Part number: A-2197-0159 (25 mm tooling)	Price: \$116
Part number: A-2197-0160 (32 mm tooling)	Price: \$116
Part number: A-2197-0161 (40 mm tooling)	Price: \$116
Part number: A-2197-0162 (50 mm tooling)	Price: \$116



HPRA/HPPA/HPMA M4 break stems and tool kits

Part number: M-2197-0156 (16 mm and 20 mm tooling)	Price: \$25
Part number: M-2197-0150 (25 mm to 50 mm tooling)	Price: \$25
Part number: M-2048-2093 (Mori Seiki)	Price: \$25
Part number: A-2176-0639 (16 mm to 20 mm tooling)	Price: \$26
Part number: A-2176-0636 (25 mm to 50 mm tooling)	Price: \$26



Legacy HPA stylus kits

TS20 replacement stylus kit

Includes stylus 10x10x4, break protect link, adaptor and screw.

Part number: A-2008-0601 (25 mm tooling)	Price: \$116
Part number: A-2008-0602 (32 mm tooling)	Price: \$116
Part number: A-2008-0603 (40 mm tooling)	Price: \$116

TS20 break protect link

Part number: M-2008-0333 (25 mm tooling)	Price: \$25
Part number: M-2008-0604 (32 mm tooling)	Price: \$25
Part number: M-2008-0605 (40 mm tooling)	Price: \$25


RP1, RP2 and RP3 tool setting probes

The RP1, RP2 and RP3 probes are suitable for OEM installation into purpose-built holders, or for use with Renishaw's automatic or manual tool setting arms.

RP1 – Tool setting/inspection probe and tool kit

For use on OEM installation into purpose-built holders.

Part number: A-2154-0007 **Price:** \$1,470



RP1 DD – RP1 double diaphragm version and tool kit

For use on OEM installation into purpose-built holders.

Part number: A-2154-0008 **Price:** \$1,470

RP2 – Probe for tool setting arm (TSA) only

Part number: A-2116-0149 **Price:** \$1,470




RP2DD – RP2 double diaphragm version for TSA only

Part number: A-2116-0150 **Price:** \$1,470

RP3 – Probe for HPRA, HPPA and HPMA arms

Part number: A-2197-0049 **Price:** \$1,470



Interfaces

OSI interface

The OSI interface is required for use with Renishaw optical probes using Modulated transmission. The OSI works exclusively with the OMM-2 receiver.

Part number: A-5492-2000

Price: \$931



HSI interface

The HSI interface is required for use with Renishaw's MP250 and TS34 probes. The HSI converts signals received from the probe into an acceptable form for the CNC machine control. The HSI has solid state relay output.

Part number: A-5500-1000

Price: \$198



NCi-5 interface

An NCI-5 interface is required for use with Renishaw non-contact tool setting systems. The interface converts probe signals into an acceptable form for the CNC machine control. This interface has solid state relay outputs.

Part number: A-5259-2000

Price: \$226



Receivers and interfaces

OMI-2 and OMI-2T are optical receivers that transmit signals between the probe and CNC control. All systems offer visual indicators of probe status, start signal status, battery condition and error condition.

OMI-2

OMI-2 offers increased resistance to light interference and is exclusively compatible with Renishaw optical transmission systems operating in Modulated transmission mode (OMP60, OMP40, OMP400 or OLP40).

Part number: A-5191-0049 (8 m cable) **Price:** \$1,582

Part number: A-5191-0050 (15 m cable) **Price:** \$1,664



OMI-2T

OMI-2T is identical to the OMI-2 and is the exclusive interface supporting the twin probe system. OMI-2T is capable of communicating with multiple optical probes. CNC must have supporting M codes. This interface should be used when combining an OTS with an OMP60, OMP40 or OMP400.

Part number: A-5439-0049 (8 m cable) **Price:** \$1,582

Part number: A-5439-0050 (15 m cable) **Price:** \$1,664



OMM-2 optical machine module

The OMM-2 receiver is required for use with Renishaw optical probes using Modulated transmission. The OMM-2 works exclusively with the OSI. OMM-2 is capable of communicating with multiple optical probes.

Part number: A-5492-0051 (25 m cable) **Price:** \$986



RMI-Q radio machine interface

RMI-Q is identical to RMI and is the exclusive interface supporting multiple (up to four) probe systems. RMI-Q is capable of communicating with multiple radio probes. CNC must have supporting M codes. This interface should be used when combining an RTS with an RMP40, RMP60 or RMP600.

Part number: A-5687-0049 (8 m cable) **Price:** \$2,559

Part number: A-5687-0050 (15 m cable) **Price:** \$2,559



RMI-Q accessories

RMI-Q 30 m replacement cable

Part number: A-5687-0303 **Price:** \$378

RMI-Q 50 m replacement cable

Part number: A-5687-0304 **Price:** \$515

RMI-Q antenna cover

Part number: A-5687-0305 **Price:** \$125

Lathe tool setting arm interfaces

There are two primary configurations of interfaces supporting lathe arms. The TSi2 and TSi3 deliver OCT (active high) output for probe status and arm positions, while the TSi2-C and TSi3-C interfaces deliver SSR solid state relay outputs for probe status and arm positions. The TSi2 and TSi2-C support the HPRA and HPPA lathe arms. The TSi3 and TSi-3C support the HPMA lathe arm.

TSi2

Part number: A-2176-0010

Price: \$185

TSi2-C

Part number: A-2176-1152

Price: \$185

TSi3

Part number: A-2181-0465

Price: \$226

TSi3-C

Part number: A-2181-2239

Price: \$226



Machine tool software

Macro based programming

Renishaw probing and tool setting software is a set of macros that control probing motion and data manipulation for a number of routines with input of a few parameters. Some capabilities may vary by specific software package and individual controller. All software is supplied on CD-ROM with electronic user's guide.

Inspection Plus software for machining centers

Available measurement cycles include:

- X or Y or Z single surface measure
- Any angle web/pocket
- 3 or 4 point bore/boss
- Internal/external corner
- 4th or 5th axis measure
- Feature to feature measure
- Print data via RS232

Description	Memory	Part number	Price
Brother 32A (June 2002 and above)	35K/87M	A-4012-0908	\$1,076
Brother 32B	35K/87M	A-4012-1028	\$1,076
Fagor 8065/8070	54K/119M	A-4016-0071	\$1,076
Fanuc 0-31	47K/117M	A-4012-0516	\$1,076
Haas	47K/117M	A-4012-0880	\$1,076
Mazak Fusion	47K/117M	A-4013-0023	\$1,076
Mazak Matrix	65K/163M	A-4013-0112	\$1,076
Meldas	47K/117M	A-4012-0516	\$1,076
Mori Seiki (Fanuc control)	47K/117M	A-4012-0936	\$1,076
Okuma OSP	53K/133M	A-4016-1035	\$1,076
Siemens 810D/840D (Ver 5 and above)	77K/190M	A-4014-0356	\$1,076
Toshiba Tosnuc 888	47K/117M	A-4012-0610	\$1,076
Yasnac I80, MX3, J50, J300	47K/117M	A-4014-0070	\$1,076

Inspection Plus software for machining centers using strain gage probes

Available measurement cycles include:

- X or Y or Z single surface measure
- XYZ vector measure
- Any angle web/pocket
- 3 or 4 point bore/boss
- Internation/external corner
- 4th or 5th axis measure
- Feature to feature measure
- Print data via RS232

Description	Memory	Part number	Price
Fanuc 0-31	47K/117M	A-4012-0516	\$1,076
Haas	47K/117M	A-4012-0890	\$1,076
Mazak Fusion	47K/117M	A-4013-0040	\$1,076
Meldas	47K/117M	A-4012-0516	\$1,076
Mori Seiki (Fanuc control)	47K/117M	A-4012-0942	\$1,076
Okuma OSP	53K/133M	A-4016-1035	\$1,076
Siemens 810D/840D (Ver 5 and above)	77K/190M	A-4014-0356	\$1,076
Yasnac I80, MX3, J50, J300	47K/117M	A-4014-0104	\$1,076

Tool setting software for machining centers

Renishaw tool setting software allows you to set tool length and diameter offsets for single point and multiple point tools, perform in-cycle broken tool detection and manual or automatic (programmed) positioning.

Contact tool setting

Description	Memory	Part number	Price
Brother 32A (June 2002 and above)	13K/32M	A-4012-1007	\$431
Brother 32B	13K/32M	A-4012-1103	\$431
Fadal	13K/32M	A-4016-0043	\$431
Fagor 8065/8070	32K/71M	A-4016-0078	\$431
Fanuc 0-31	9K/23M	A-4012-0584	\$431
Haas	9K/23M	A-4012-0886	\$431
Mazak 640M, M32, M+	9K/23M	A-4013-0036	\$431
Meldas	9K/23M	A-4012-0584	\$431
Okuma OSP	9K/23M	A-4016-1039	\$431
Siemens 810/840D (Ver 5 and above)	9K/23M	A-4014-0396	\$431
Yasnac J50, J300, I80/MX3	9K/23M	A-4014-0018	\$431

Non-contact tool setting

Description	Memory	Part number	Price
Brother 32A (June 2002 and above)	27K/67M	A-4012-0904	\$646
Brother 32B	27K/67M	A-4012-1035	\$646
Fadal	27K/67M	A-4016-0061	\$646
Fanuc 0-31	24K/67M	A-4012-0820	\$646
Haas	24K/67M	A-4012-0895	\$646
Makino	27K/67M	A-4012-0900	\$646
Mazak Fusion	24K/67M	A-4013-0062	\$646
Mazak Matrix	57K/143M	A-4013-0119	\$646
Meldas	24K/67M	A-4013-0050	\$646
Okuma OSP	27K/67M	A-4016-1021	\$646
Siemens 810/840D (Ver 5 and above)	27K/67M	A-4014-0401	\$646
Yasnac MX3, I80, J50, J300	27K/67M	A-4014-0020	\$646

Special non-contact tool setting

Description	Memory	Part number	Price
Fanuc angle beam 0-31	27K/67M	A-4012-0821	\$646
Makino angle beam	27K/67M	A-4013-0900	\$646
Mazak angle beam Fusion	27K/67M	A-4013-0088	\$646
Mazak Matrix angle beam	57K/143M	A-4013-0119	\$646
Mazak E-Series Matrix	52K/130M	A-4013-0123	\$646
Mazak E-Series Fusion	27K/67M	A-4013-0092	\$646
Mazak Mark III Fusion	27K/67M	A-4013-0567	\$646
Yasnac angle beam	27K/67M	A-4014-0025	\$646

Inspection software for turning centers

Renishaw's Inspection software for turning centers offers macros for:

- single-point (radial) measurement
- two-point (diameter) measurement
- rib/groove measurement
- single Z-surface measurement

It can update tool offsets and work offsets. It has an upper tolerance band which can be set for no offset correction. On completion of each measurement cycle it is possible to print out the results.

Description	Memory	Part number	Price
Fanuc 0-31	11K/27M	A-4012-0541	\$861
Haas	11K/27M	A-4012-0874	\$861
Mazak Fusion	11K/28M	A-4013-0071	\$861
Siemens 810D/840D	19K/47M	A-4014-0137	\$861
Yasnac LX3	10K/26M	A-4014-0011	\$861

Inspection software for multi-axis turning centers

- horizontal and vertical head orientations
- X, Y and Z single surface measure
- bore/boss
- web/pocket
- C axis find

Description	Memory	Part number	Price
Mazak Mark III Fusion	45K/113M	A-4013-0030	\$1,076
Mazak E-series Fusion	75K/188M	A-4013-0083	\$1,076
Mori Seiki MTNT	43K/106M	A-4012-0834	\$1,076
Hitachi Hi-Cell	75K/188M	A-4012-0843	\$1,076
Nakamura NTX	46K/113M	A-4012-1074	\$1,076
Mazak Mark IV and E-series Matrix	110K/275M	A-4013-0106	\$1,076
Doosan MT	43K/106M	A-4012-1016	\$1,076

Tool setting software for turning centers

The Renishaw tool setting software for turning centers sets tool length and/or diameter for static and powered tools. It has manual or automatic (programmed) positioning capability.

Description	Memory	Part number	Price
Fanuc 0-31	4K/8M	A-4012-0528	\$431
Haas	4K/8M	A-4012-0877	\$431

AxiSet™ Check-Up

Compatible with common formats of 5-axis machines, AxiSet™ Check-Up provides machine users a fast and accurate method for determining rotary axis pivot points. The system is comprised of macro software, dedicated calibration artifact and PC-based data analysis software. Performance analysis is reported graphically via Microsoft® Excel®, compared against user-defined tolerances and stored for historical comparison.

The solutions defined below are compatible with 5-axis table-table machines. New solutions are being developed. Contact Renishaw for the latest list of compatibility. Each solution includes:

- CNC specific macro
- Artifact with magnetic base
- PC-based data analysis software



AxiSet™ Check-Up Mazak Variaxis

Part number: A-5642-1000 Price: \$2,500

AxiSet™ Check-Up Fanuc (Table-Table)

Part number: A-5642-1100 Price: \$2,500

AxiSet™ Check-Up Mori Seiki NMV NMH

Part number: A-5642-1400 Price: \$2,500

AxiSet™ Check-Up Siemens (Table-Table)

Part number: A-5642-1500 Price: \$2,500

AxiSet™ Check-Up Mazak Mark IV

Part number: A-5642-1005 Price: \$2,500

AxiSet™ Check-Up Mazak eV/eH

Part number: A-5642-1009 Price: \$2,500

AxiSet™ Check-Up Hurco Winmax (Table-Table)

Part number: A-5642-1105 Price: \$2,500

AxiSet™ Check-Up Haas

Part number: A-5642-1600 Price: \$2,500

AxiSet™ Check-Up Mori Seiki NT

Part number: A-5642-1405 Price: \$2,500

AxiSet™ Check-Up Siemens (Head-Head)

Part number: A-5642-1515 Price: \$2,500

Off-line programming

Productivity+™ is a new software module designed to simplify the process of integrating probing cycles into the CNC machining program. Productivity+™ Active Editor Pro runs standalone, while the Productivity+™ GibbsCAM® plug-in runs in the GibbsCAM® environment and requires GibbsCAM® version 7 or above.

Productivity+™:

- Imports the native CAD model
- Creates and edits probing programs
- Allows simulation of inspection routines in a virtual environment
- Requires no detailed knowledge of macro codes
- Is compatible with many popular controls

Productivity+™ comes with three CAD importers as standard: IGES, STEP and Parasolid®. Other CAD importers are available (select from the list below).

Productivity+™ is supplied with one post processor (select from the list below).

The Productivity+™ GibbsCAM® plug-in requires the GibbsCAM® machine post processor to be upgraded to allow compatibility. The first post processor upgrade is included.

Productivity+™ GibbsCAM® plug-in

Part number: A-4007-1000 **Price:** \$4,995

Productivity+™ Active Editor Pro

Part number: A-4007-1400 **Price:** \$4,995

Productivity+™ multi-axis option for Active Editor Pro

Part number: A-5226-2000 **Price:** FOC

Productivity+™ post processors

Control	Part number	Price
Brother	A-4007-5900	\$1,500
Fanuc Macro B	A-4007-5100	\$1,500
Haas	A-4007-5200	\$1,500
Heidenhain	A-4007-6000	\$1,500
Hitachi Seicos	A-4007-5300	\$1,500
Hurco	A-4007-6800	\$1,500
Makino	A-4007-5400	\$1,500
Mazatrol ISO	A-4007-5500	\$1,500
Mitsubishi Meldas	A-4007-5600	\$1,500
Mori Seiki	A-4007-6600	\$1,500
Okuma	A-4007-6300	\$1,500
Siemens	A-4007-6700	\$1,500
Yasnac	A-4007-5700	\$1,500



Productivity+™ CAD importers

CAD system	Part number	Price
Pro-E	A-5226-0007	\$1,500
CATIA	A-5226-0008	\$1,500
UG/NX	A-5226-0009	\$1,500
ACIS	A-5226-0010	\$1,000
SolidWorks®	A-5226-0011	\$1,500
Inventor™	A-5226-0012	\$1,500
All of the above	A-5226-0020	\$2,000

GibbsCAM® post processor upgrade service

Part number: A-4007-1000-RI **Price:** \$300

Productivity+™ maintenance

The first year's maintenance is included in the purchase price.

One-year maintenance contract for GibbsCAM® plug-in

Part number: YI-4007-1000 **Price:** \$840

One-year maintenance contract for Active Editor Pro

Part number: YI-4007-1400 **Price:** \$840

One-year maintenance contract for multi-axis option for Active Editor Pro

Part number: YI-A-5226-2000 **Price:** \$480

Productivity+™ Active Editor Pro 90-day trial

Part number: A-4007-8999 **Price:** FOC

CNC Reporter

Part number: A-4007-1500 **Price:** \$2,500

Renishaw CappsNC

Renishaw CappsNC is a comprehensive part verification software package for machine tools, designed to give confidence to the user that the part produced conforms to the CAD model.

- Generate measurement programs from the CAD model, offline, in a virtual PC environment.
- Using the comprehensive probe builder, various shanks, Renishaw probes and styli can be modeled.
- Generate probe paths for 3-axis machines measuring 2D and 3D prismatic features and 3D free-form surfaces.
- Collision avoidance automatically detects obstructions and generates avoidance paths.
- Supports a variety of CNCs and machine communication protocols (RS232, Ethernet, FOCAS, Mnet, TNCDirect, Siemens OPC, MTConnect).
- Uses industry-standard DMIS code to generate machine motion, construction, dimensioning and tolerance instructions.
- Generate comprehensive measurement reports with full GD&T.
- Using the optional 4th/5th axis module, CappsNC supports a variety of multi-axis machine configurations.
- Using the optional tool and work offset module, tool compensation commands and work offset shifts can be incorporated into the post processed output.
- First year maintenance and support included.

CappsNC Advanced

CappsNC Advanced is a single software license designed for the user who intends to program inspection cycles and capture measurement results on a single PC.

Includes: Complete CappsNC license
Machine interface option*
CAD importers (IGES and STEP)
One-year CappsNC maintenance and support

Part number: A-5722-1000 **Price:** \$15,345

CappsNC options

Capps NC Advanced to Programming System upgrade for 3 axis machines


Part number: A-5722-1002 **Price:** \$3,245

RevEng - Reverse engineering option

Part number: A-5722-6007 **Price:** \$4,950

Additional machine interface option

Part number: A-5722-3000 **Price:** \$1,650



Additional execution module

Includes one machine interface option.

Part number: A-5722-1100 **Price:** \$6,545

4th-axis option

Part number: A-5722-6000 (ADV) **Price:** \$3,190

Part number: A-5722-6100 (PROGSTA) **Price:** \$2,145

Part number: A-5722-6200 (EXECMOD) **Price:** \$1,045

5th-axis option

Part number: A-5722-6001 (ADV) **Price:** \$3,190

Part number: A-5722-6101 (PROGSTA) **Price:** \$2,145

Part number: A-5722-6201 (EXECMOD) **Price:** \$1,045

Work offset and tool compensation

Part number: A-5722-6002 (ADV) **Price:** \$6,490

Part number: A-5722-6106 (PROGSTA) **Price:** \$2,145

Part number: A-5722-6202 (EXECMOD) **Price:** \$4,345

Work offset only

Part number: A-5722-6005 (ADV) **Price:** \$3,245

Part number: A-5722-6102 (PROGSTA) **Price:** \$1,045

Part number: A-5722-6205 (EXECMOD) **Price:** \$2,145

Tool compensation only

Part number: A-5722-6006 (ADV) **Price:** \$3,465

Part number: A-5722-6105 (PROGSTA) **Price:** \$1,375

Part number: A-5722-6206 (EXECMOD) **Price:** \$2,475

AAT SPC

Part number: A-5722-6003 **Price:** \$2,695

AAT NC-fit for NC part program correction

Part number: A-5722-6004 **Price:** \$12,500

CappsNC CAD importers

Catia4 Direct Import

Part number: A-5722-5000 Price: \$4,345

Catia5 Direct Import

Part number: A-5722-5001 Price: \$4,345

Pro-E Direct Import

Part number: A-5722-5002 Price: \$4,345

Unigraphics Import

Part number: A-5722-5003 Price: \$4,345

Parasolid Import

Part number: A-5722-5004 Price: \$1,650

Solid Works Import

Part number: A-5722-5005 Price: \$1,650

VDA Import

Part number: A-5722-5006 Price: \$1,045

CappsNC maintenance

The first year's maintenance is included. Subsequent years' maintenance is offered at 15% of the list price for all components.

Part number: A-5722-4000 Price: Varies

CappsNC networking options

CappsNC License MGR – Programming Server

Includes two connections.

Part number: A-5722-3100 Price: \$4,950

Execution Modules configured for License Manager

Includes two connections.

Part number: A-5722-3101 Price: 1/3 DISCOUNT
 CONFIG PRICE

Renishaw services

Renishaw has set up a series of part numbers which should be referenced when ordering Renishaw services. These part numbers will appear on your invoice.

Commissioning 3-axis machine

Part number: RI-6000-1001 Price: \$7,500

Commissioning multi-axis machine

Part number: RI-6000-1003 Price: \$9,500

Training for 3-axis machine

Part number: RI-6000-1002 Price: \$2,950

Training for multi-axis machine

Part number: RI-6000-1004 Price: \$4,950

Custom Application Programming per day

Part number: RI-6000-1007 Price: \$1,100

Probe retrofit questionnaire

Customer information (location of installation)



Important! This document consists of four pages. Please be sure to read all information before returning.

Address of installation:

Company name _____ Contact name _____

Street _____

City _____ State _____ Zip _____

Telephone _____ Fax _____ E-mail _____

Product being purchased _____

Machine information

Machine make _____ Control make _____

Machine model _____ Control model _____

Machine type (i.e. VMC, HMC, lathe, gantry etc.) _____

Tool holder type/size (i.e. CAT50, BT40, HSK A80, VDI, other) _____

Axis/Axis travels: X _____ Y _____ Z _____ B _____ Other _____

Is the machine still in warranty? Yes No Serial # _____

Is the machine installed? Yes No If no, when will installation be complete? _____

Spindle orientation: Yes No

Pallet shuttle: Yes No If Yes, indexer or full 4th axis

Is there currently a probe system on the machine (i.e. tool post, part probe, tool eye)? Yes No

If yes, please explain _____

Is a safety briefing required to work at location of installation? Yes No

Note: If a non-disclosure form is required to enter the facility, please provide at least two weeks prior to the scheduled visit.

Application information _____

Note: The machine must be operational at the time of installation. A pull stud is required for spindle-mounted probes, but is not provided by Renishaw. A calibration device is not supplied.

The following options must be installed and activated (turned on) by your OEM, machine distributor or control manufacturer prior to Renishaw's arrival.

Required control features/options

Indicate which options are installed on your control.

Fanuc/Yasnac/Mitsubishi/Mazak

Haas

G31 skip	Yes	<input type="checkbox"/>	No	<input type="checkbox"/>
G31 high speed skip	Yes	<input type="checkbox"/>	No	<input type="checkbox"/>
G31 multi-skip	Yes	<input type="checkbox"/>	No	<input type="checkbox"/>
Custom macro	Yes	<input type="checkbox"/>	No	<input type="checkbox"/>

Promac Yes No

Connector type/pin location of skip signal _____

- 24 V dc required to power probe interface
- M codes may be required – see the following information pages for details

Note: Controls not listed may have similar features/options. Contact Renishaw regarding support for other controls.

IMPORTANT

This questionnaire is intended for information purposes for installation only and shall in no event constitute a binding contract with Renishaw.

Please note – The issuer of the purchase order is responsible for all information provided to Renishaw. Please make sure that the information is as accurate and current as possible, as this will expedite the installation. If additional time or hardware is required, due to incorrect information, additional costs may be billed to you.

The installation timeframe is 2 to 3 weeks. Please keep in mind that your installation is not considered for scheduling until this form is completed and returned to us. At that time, the form will be reviewed and you will be contacted as to the acceptability of the retrofit and dates available for installation.

I have read and understood the preceding information.



Important – this document consists of four pages. Please be sure to read all information before returning.

Signed _____ Date _____

Purchase order issued to Renishaw by:

Company name _____ Contact name _____

Street _____

City _____ State _____ Zip _____

Telephone _____ Fax _____

Additional retrofit customer information

Machine tool software requirements

Machining center:	Inspection Plus	46.5 Kb	117 m
	Tool setting	9 Kb	23 m
	NC4 tool setting	15 Kb	38 m
Lathe software:	Inspection	11 Kb	28 m
	Tool setting	6 Kb	15 m

Program number requirements

Renishaw program numbers range from 9002 through 9100, and 9700 through 9900.

Macro variables required #100–#149 (only used while macro is running)
#500–#565 (some variables in this range required and must be dedicated)

Training

Training will be provided after installation on the use and application of Renishaw probing cycles. Training will **not** include the incorporation of probe cycles into the customer's current manufacturing programs. Any special applications or additional software training which requires additional time or visits to the original scheduled installation/training will be charged at Renishaw Inc standard service rates.

Note: Please indicate any additional training requirements on your purchase order.

Part probe system details

OMP40/OMP60/RMP60	Turn on (via optical or RF) / Turn off (via optical or RF) or time out	Installation time: Up to 8 hours Training time: Up to 6 hours
	Turn on methods	Auto start (OMP40/OMP60) sends a start signal every second until a probe command is received. This method can only be used if the probe is stored outside the machine enclosure when not in use. Machine start (OMP40/OMP60/RMP60) requires that an M code be available for use to issue the start command. Spin start (OMP60/RMP60) uses an internal switch. The probe will turn on after being spun at 650 RPM for 1 second.
	Turn off methods	Time out (OMP40/OMP60/RMP60). A timer automatically switches the power off 12, 33 or 134 seconds (selectable) after turn on. Each time the probe is triggered, the timer is reset to the selected value. Optical off (OMP40/OMP60) / RF off (RMP60) requires that an M code be available to initiate the turn off sequence.
	OMP400	Optical (flash) on/optical off or time out (optical transmission) Installation time Up to 8 hours Training time Up to 6 hours
	Turn on method	Machine start (optical on) requires that an M code be available for use to issue the start command. Auto start cannot be used with the strain gage probes.
	Turn off methods	Time out. A timer automatically switches the power off 33 or 134 seconds (selectable) after turn on. Each time the probe is triggered, the timer is reset to 33 or 134 seconds. Optical off. Requires the use of an M code as stated for machine start above.
RMP40M OLP40M	Turn on (via optical or RF) / Turn off (via optical or RF) or time out	Installation time Up to 8 hours Training time Up to 6 hours
	Turn on method	Machine start requires that an M code be available for use to issue the start command. Auto start cannot be used with these probes (for lathe applications).
	Turn off method	Optical off. Requires the use of an M code as stated for machine start above.

Tool setting probe details

TS27R	Hard-wired		Installation time	Up to 6 hours
			Training time	Up to 6 hours
OTS	Machine start requires that an M code be available for use to issue the start command. Auto start cannot be used with these probes.			
	These probes are fixed either to a T slot in the machine bed, or can be mounted on a riser if required to allow tools to reach the stylus. A riser is not provided by Renishaw unless specified on the quotation. The TS27R is wired to the probe interface via a tough cable conduit. The TS27R cannot be mounted on pallets or rotary tables.			
NC4 or TRS2	Hard-wired		Fixed installation time	Up to 8 hours
			Training time	Up to 6 hours
	Fixed system	The probe is fixed either to a T slot in the machine bed, or can be mounted on a riser if required to allow tools to reach the laser beam. A riser is not provided by Renishaw unless specified on the quotation. The NC4 is wired to the probe interface via a tough cable conduit. The NC4 cannot be mounted on pallets or rotary tables.		
			Separate installation time	Up to 12 hours *
			Training time	Up to 6 hours
	Separate system	The probe transmitter and receiver are mounted to brackets which attach to the machine. Brackets and their installation are not provided by Renishaw unless specifically stated in the quotation. Brackets not provided by Renishaw must be mounted prior to the arrival of a Renishaw engineer. The brackets should allow for complete machine motion (pallet shuttles, rotary tables, axis travels etc), laser beam alignment and expected system performance.		
		* Depending on bracket mounting requirements, additional time may be required.		
	Fixed or separate	The NC4 must be mounted in such a way that the tool can access the laser beam and move in all three axes (X, Y, Z) with respect to the beam. For basic functionality (length, diameter, basic broken tool), no M code is required. For additional features (missing/ broken insert, profile checking, rapid broken tool check) a level M code pair is required.		
HPRA	Hard-wired	The HPRA must be mounted to a bracket which attaches to the machine. The brackets and their installation are not provided by Renishaw unless specifically stated in the quotation. Brackets not provided by Renishaw must be mounted prior to the arrival of a Renishaw engineer. The brackets should allow for complete machine and expected system performance.		

Dual probe installations (part and tool probe on same machine)

Requires either two independent probe inputs (multi-channel skip) or an M code driven relay. The M code driven relay must be installed and available prior to the probe installation.


Example M51 – part probe (selected) M61 – tool setter (selected)

M51 energize relay (coil latches and stays energized) program continues
 M61 de-energize relay (coil resets) program continues

M code for flash (optical) on and off

M71 pulse (momentarily energize relay) program continues

Example: Pulse M code M71 (flash on and flash off)



Gaging systems



EQUATOR™

the versatile gauge™

The Renishaw EQUATOR™ is a versatile alternative to custom gaging, offering inspection of an unprecedented variety of manufactured parts.

Fast, repeatable and versatile

The EQUATOR™ system consists of a highly repeatable, “parallel kinematic” structure, machine coupled with a high-power, multi-axis universal controller and digital servo power amplifier. The resultant system is capable of high-speed, comparative gaging for inspection of high-volume manufactured parts, directly on the shop floor. Additionally, the optimized ratio of working envelope (300 mm x 300 mm x 300 mm*) to machine footprint (~ 570 mm x 500 mm), means EQUATOR™ can be set to work in even the most crowded of factory spaces. The lightweight machine, weighing just 55 lbs, requires just single phase power and needs no costly air supply.

Re-configuration of the gaging system to cater for part design changes, or to measure new parts, is possible in a fraction of the time it would take with conventional custom gaging. An operator can switch between parts in seconds, perfect for flexible manufacturing processes or for accepting parts from multiple machines.

Easy to use

The included, intuitive MODUS™ Organizer operator front-end software requires little or no training, while on the programmable system the comprehensive MODUS™ EQUATOR™ programming software allows engineers to rapidly create gaging routines for any part – simple or complex, prismatic or free-form – using industry-standard DMIS programming.

Thermally “stable” – for shop floor use

Re-mastering is as swift as measuring a production part and immediately compensates both the machine and the part being measured, for temperature variations typical of a shop floor environment.



Integrated stylus changing

Further versatility is offered by the included, EQUATOR™-specific stylus changing rack, allowing automated in-cycle changing of SM25 stylus modules. The SM25 modules couple to the industry-standard SP25 CMM probe, allowing EQUATOR™ users to swap the stylus configurations without re-qualifying each time. Up to six stylus combinations can be loaded into the rack at any time. These can be used on a single complex part or with multiple parts of varying geometries.

Traceability to calibrated CMMs

Master parts do not need to be expensive custom parts like a traditional gage; take a production part and measure it on a CMM to establish feature variation from CAD or drawing nominals. The results from any CMM can be configured to be used directly within the EQUATOR™ software.

Effectively, the calibrated absolute accuracy of the CMM can be “extended” onto the shop floor to provide calibrated traceability to EQUATOR™ measurements. With the calibration file loaded into the EQUATOR™ software, measurements made in the EQUATOR™ system can be referred back to the CAD or drawing nominals. This allows true process control with SPC packages.

* 300 mm Z measurement range available with module change to SM25-3, measuring external features only on an extended height Equator only. Z axis stroke is 150 mm.

Machine kit

Includes: EQUATOR™ 300 machine
EQUATOR™ 6-port rack
SP25M scanning probe kit
Calibration accessory kit
Joystick (or 'E-stop' button)
Cables



Controller kit

Includes: EQUATOR™ controller
Intuitive "front-end" software package

EQUATOR™ tiles

Renishaw fixture plates (various options available).

Regular height EQUATOR™ combination kits

Operator's version

Description	Part number	Price
EQUATOR™ machine with 6-port rack and joystick, controller with Organizer software and M6 threaded fixture plate	A-EQ33-1J10	\$29,165
EQUATOR™ machine with 6-port rack and joystick, controller with Organizer software and ¼ in R&R threaded fixture plate	A-EQ33-1J40	\$29,415
EQUATOR™ machine with 6-port rack and stop button, controller with Organizer software and M6 threaded fixture plate	A-EQ33-1S10	\$28,761
EQUATOR™ machine with 6-port rack and stop button, controller with Organizer software and ¼ in R&R threaded fixture plate	A-EQ33-1S40	\$29,010

Programmer's version

Description	Part number	Price
EQUATOR™ machine with 6-port rack and joystick, controller with Organizer and MODUST™ programming software and M6 threaded fixture plate	A-EQ33-2J10	\$32,465
EQUATOR™ machine with 6-port rack and joystick, controller with Organizer and MODUST™ software and ¼ in R&R threaded fixture plate	A-EQ33-2J40	\$32,715

Extended height EQUATOR™ combination kits

Operator's version

Description	Part number	Price
Extended height EQUATOR™ machine with 6-port rack and joystick with Organizer software and ¼ in R&R threaded fixture plate	A-EH33-1J40	\$30,735

Programmer's version

Description	Part number	Price
Extended height EQUATOR™ machine with 6-port rack and joystick with Organizer and MODUST™ software and ¼ in R&R threaded fixture plate	A-EH33-2J40	\$34,035

Replacement equipment

Stop button

Part number: A-5504-0255 Price: \$375



Joystick kit

Part number: A-5504-0258 Price: \$691



Joystick cable only

Part number: A-5358-5016 Price: \$200

Button interface

Part number: A-6088-0010 Price: \$825



Autochange rack (6 ports)

Part number: A-5504-0250 Price: \$2,250

Rack port inserts for 6 off SH25

Part number: A-2237-1414 Price: \$156

Rack set-up tool

Part number: A-2237-0682 Price: \$48

Rack port clip for autochange rack alignment

6 required.

Part number: M-5358-2589 Price: \$2

MODUS™ EQUATOR™ dongle

Part number: A-5639-3000 Price: \$4,000



Power cables

Part number: P-EQ33-MAINS Price: \$15

Fixturing plate (M6)

Part number: PCR-13300300-12-6 Price: \$550



Fixturing plate (1/4-20 in)

Part number: PCR-501212-50-20 Price: \$550

Fixturing plate (M4)

Part number: PCR-13300300-10-4 Price: \$620

Fixturing plate (M8)

Part number: PCR-13300300-15-8 Price: \$550

Fixturing plate (single ¼-20 hole)

Part number: R-PEC-13300300-6 Price: \$245

Fixturing plate spacer (50 mm)

Part number: A-5504-0203 Price: \$660

Fixturing plate spacer (150 mm)

Part number: A-5504-0207 Price: \$660



Optional equipment

Digital I/O box (normally open)

With Automation software

Part number: A-5923-0050 Price: \$4,950

Additional I/O box only (normally open)

Part number: A-5923-0259 Price: \$1,100

Full 5-sphere calibration artefact only

Part number: A-5504-0252 Price: \$415

Extended calibration artefact stem

Part number: A-5504-0274 Price: \$45

Gauge checker

Part number: A-5925-0200 Price: \$825

Cleaning kit

Part number: A-5504-0955 Price: \$83

Equator enclosure

Equator enclosure kit

Includes top, base and monitor bracket

Part number: A-5504-0210 Price: \$4,130

Equator enclosure top unit

Part number: A-5504-0211 Price: \$2,178

Equator enclosure base unit

Part number: A-5504-0212 Price: \$1,815

Equator enclosure monitor bracket

Part number: A-5504-0213 Price: \$154

MCU docking port for wired joystick

Part number: A-1333-0026 Price: \$83




Fixturing components

R&R component kit FSC-MCR-20 (1/4-20 in)

Part number: FSC-MCR-20

Price: \$2,615



R&R component kit FSC-MCA-20 (1/4-20 in)

Part number: FSC-MCA-20

Price: \$972

R&R component kit FSC-CA-20 (1/4-20 in)

Part number: FSC-CA-20

Price: \$744

Equator probe kits

Equator SP25-2 scanning kit with single calibration sphere

Part number: A-5504-0205

Price: \$4,125

Equator stylus kits

Equator basic stylus kit

Part number: A-5504-0281

Price: \$730

Equator intermediate stylus kit

Part number: A-5504-0282

Price: \$1,385


Equator advanced stylus kit

Part number: A-5504-0283

Price: \$2,715



EQUATOR™ MODUST™ software training



On site training (maximum 4 students)

Description	Part number	Price
EQUATOR™ MODUST™ scanning training (US travel) – 4 days	A-5639-1701-EQT	\$9,625
EQUATOR™ MODUST™ advanced training (US travel) – 2 days	A-5639-1702-EQT	\$5,775

Training at Renishaw Inc*

Description	Part number	Price
EQUATOR™ MODUST™ scanning training (US) – 4 days	A-5639-1701-EQ	\$3,000
EQUATOR™ MODUST™ advanced training (US) – 2 days	A-5639-1702-EQ	\$1,500

* per student

Equator training block

Part number: A-5504-0209 **Price:** \$640

Equator 2nd year extended warranty

Now available.

Part number: Please ask your Renishaw representative **Price:** POA



Fixtures



CMM fixtures

CMM base plate options

Part number	Thread	Height	Width	Depth	Spacing	Price
M4 plates						
R-PC-13150150-10-4	M4	13 mm	150 mm	150 mm	10 mm OC	\$369
R-PC-13300300-10-4	M4	13 mm	300 mm	300 mm	10 mm OC	\$761
M6 plates						
R-PC-13300300-12-6	M6	13 mm	300 mm	300 mm	12.5 mm OC	\$651
R-PC-13450450-12-6	M6	13 mm	450 mm	450 mm	12.5 mm OC	\$1,096
R-PC-19600600-12-6	M6	19 mm	600 mm	600 mm	12.5 mm OC	\$1,996
R-PC-19750750-12-6*	M6	19 mm	750 mm	750 mm	12.5 mm OC	\$2,595
R-PC-197501000-12-6*	M6	19 mm	750 mm	1000 mm	12.5 mm OC	\$3,100
R-PC-199001200-12-6*	M6	19 mm	900 mm	1200 mm	12.5 mm OC	\$4,800
M8 plates						
R-PC-13300300-15-8	M8	13 mm	300 mm	300 mm	15 mm OC	\$626
R-PC-13450450-15-8	M8	13 mm	450 mm	450 mm	15 mm OC	\$1,021
R-PC-19600600-15-8	M8	19 mm	600 mm	600 mm	15 mm OC	\$1,781
R-PC-19750750-15-8*	M8	19 mm	750 mm	750 mm	15 mm OC	\$2,450
R-PC-197501020-15-8*	M8	19 mm	750 mm	1020 mm	15 mm OC	\$2,995
R-PC-199001200-15-8*	M8	19 mm	900 mm	1200 mm	15 mm OC	\$4,495

*Mounting holes may also be added and longer lead times may apply to larger plates



M4 kits: clamping

The M4 CMM clamping kits can be used to hold brass, titanium, aluminum, plastic and other nonferrous parts.

A kit includes a base plate with M4 threaded holes 10 mm on center (choose from plate sizes listed below) and a set of components (A) along with plate clamps for mounting to the CMM.



Kit part number	Base plate size	Set	Price
R-KC-C1A-4	13 mm x 150 mm x 150 mm	A	\$1,298
R-KC-C2A-4	13 mm x 300 mm x 300 mm	A	\$1,690

Component set A

Part number: R-FSC-CA-4 Price: \$929

Includes:

Qty	Part number	Description
3	R-S-610-4	6 mm dia. x 10 mm standoff
3	R-S-625-4	6 mm dia. x 25 mm standoff
3	R-S-95-4	9 mm dia. x 5 mm standoff
3	R-S-910-4	9 mm dia. x 10 mm standoff
3	R-S-925-4	9 mm dia. x 25 mm standoff
2	R-S-950-4	9 mm dia. x 50 mm standoff
3	R-S-1210-4	12 mm dia. x 10 mm standoff
3	R-S-1225-4	12 mm dia. x 25 mm standoff
2	R-S-1250-4	12 mm dia. x 50 mm standoff
2	R-SP-610-4	6 mm dia. x 10 mm pin standoff
2	R-SP-910-4	9 mm dia. x 10 mm pin standoff
2	R-CT-40-25-4	40 mm tension clamp with 25 mm post
3	R-CW-25-25-4	25 mm wire clamp with 25 mm post
2	R-CW-50-50-4	50 mm wire clamp with 50 mm post
4	R-RPA-4	Aluminum resting pin
1	R-AJ-9-4	9 mm dia. adjustable jackstand
1	R-AS-30-4	30 mm long adjustable slide
1	R-AS-45-4	40 mm long adjustable slide
1	R-TB-1619-4	Tower block with base 16 mm x 19 mm
1	R-TC-300190-4	300 mm x 190 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm box (not shown)

Total: 46 pc

M6 kits: clamping

The M6 CMM clamping kits can be used to hold brass, titanium, aluminum, plastic and other nonferrous parts.

A kit includes a base plate with M6 threaded holes 12.5 mm on center (choose from plate sizes listed below) and a set of components (A, B or C) along with plate clamps for mounting to the CMM.



Kit part number	Base plate size	Set	Price
R-KC-C1A-6	13 mm x 300 mm x 300 mm	A	\$1,456
R-KC-C2A-6	13 mm x 450 mm x 450 mm	A	\$1,901
R-KC-C3A-6	19 mm x 600 mm x 600 mm	A	\$2,801
R-KC-C4A-6	19 mm x 750 mm x 750 mm	A	\$3,400
R-KC-C5A-6	19 mm x 750 mm x 1000 mm	A	\$3,905
R-KC-C6A-6	19 mm x 900 mm x 1200 mm	A	\$5,605

Component set A

Part number: R-FSC-CA-6 **Price:** \$805

Includes:

Qty	Part number	Description
3	R-S-1320-6	13 mm dia. x 20 mm standoff
3	R-S-1325-6	13 mm dia. x 25 mm standoff
3	R-S-1350-6	13 mm dia. x 50 mm standoff
3	R-S-1920-6	19 mm dia. x 20 mm standoff
3	R-S-1925-6	19 mm dia. x 25 mm standoff
3	R-S-1950-6	19 mm dia. x 50 mm standoff
3	R-S-2520-6	25 mm dia. x 20 mm standoff
3	R-S-2525-6	25 mm dia. x 25 mm standoff
3	R-S-2550-6	25 mm dia x 50 mm standoff
2	R-SP-1325-6	13 mm dia. x 25 mm pin standoff
2	R-CT-40-30-6	40 mm tension clamp with 30 mm post
4	R-CT-64-70-6	64 mm tension clamp with 70 mm post
4	R-RCD-6	Delrin® resting cone
1	R-AJ-13-6	13 mm dia. adjustable jackstand
1	R-AS-45-6	45 mm long adjustable slide
1	R-AS-70-6	70 mm long adjustable slide
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 44 pc

Kit part number	Base plate size	Set	Price
R-KC-C1B-6	13 mm x 300 mm x 300 mm	B	\$2,705
R-KC-C2B-6	13 mm x 450 mm x 450 mm	B	\$3,150
R-KC-C3B-6	19 mm x 600 mm x 600 mm	B	\$4,050
R-KC-C4B-6	19 mm x 750 mm x 750 mm	B	\$4,649
R-KC-C5B-6	19 mm x 750 mm x 1000 mm	B	\$5,154
R-KC-C6B-6	19 mm x 900 mm x 1200 mm	B	\$6,854

Component set B

Part number: R-FSC-CB-6 **Price:** \$2,054

Includes:

Qty	Part number	Description
3	R-S-910-6	9 mm dia. x 10 mm standoff
6	R-S-1320-6	13 mm dia. x 20 mm standoff
6	R-S-1325-6	13 mm dia. x 25 mm standoff
6	R-S-1350-6	13 mm dia. x 50 mm standoff
3	R-S-1910-6	19 mm dia. x 10 mm standoff
6	R-S-1920-6	19 mm dia. x 20 mm standoff
6	R-S-1925-6	19 mm dia. x 25 mm standoff
6	R-S-1950-6	19 mm dia. x 50 mm standoff
4	R-S-19100-6	19 mm dia. x 100 mm standoff
6	R-S-2520-6	25 mm dia. x 20 mm standoff
6	R-S-2525-6	25 mm dia. x 25 mm standoff
6	R-S-2550-6	25 mm dia. x 50 mm standoff
4	R-S-25100-6	25 mm dia. x 100 mm standoff
4	R-SP-1325-6	13 mm dia. x 25 mm pin standoff
6	R-CT-40-30-6	40 mm tension clamp with 30 mm post
12	R-CT-64-70-6	64 mm tension clamp with 70 mm post
4	R-RCD-6	Delrin® resting cone
4	R-RPS-6	Steel resting pin
2	R-AJ-13-6	13 mm dia. adjustable jackstand
2	R-AJ-25-6	25 mm dia. adjustable jackstand
2	R-AS-45-6	45 mm dia. long adjustable slide
2	R-AS-70-6	70 mm long adjustable slide
2	R-TB-2025-6	Tower block with base 20 mm x 30 mm
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 110 pc

Kit part number	Base plate size	Set	Price
R-KC-C1C-6	13 mm x 300 mm x 300 mm	C	\$4,196
R-KC-C2C-6	13 mm x 450 mm x 450 mm	C	\$4,641
R-KC-C3C-6	19 mm x 600 mm x 600 mm	C	\$5,541
R-KC-C4C-6	19 mm x 750 mm x 750 mm	C	\$6,140
R-KC-C5C-6	19 mm x 750 mm x 1000 mm	C	\$6,645
R-KC-C6C-6	19 mm x 900 mm x 1200 mm	C	\$8,345

Component set C

Part number: R-FSC-CC-6 **Price:** \$3,545

Includes:

Qty	Part number	Description
6	R-S-910-6	9 mm dia. x 10 mm standoff
4	R-S-1310-6	13 mm dia. x 10 mm standoff
8	R-S-1320-6	13 mm dia x 20 mm standoff
8	R-S-1325-6	13 mm dia. x 25 mm standoff
8	R-S-1350-6	13 mm dia. x 50 mm standoff
4	R-S-1910-6	19 mm dia. x 10 mm standoff
8	R-S-1920-6	19 mm dia. x 20 mm standoff
8	R-S-1925-6	19 mm dia. x 25 mm standoff
8	R-S-1950-6	19 mm dia. x 50 mm standoff
6	R-S-19100-6	19 mm dia. x 100 mm standoff
8	R-S-2520-6	25 mm dia. x 20 mm standoff
8	R-S-2525-6	25 mm dia. x 25 mm standoff
8	R-S-2550-6	25 mm dia. x 50 mm standoff
6	R-S-25100-6	25 mm dia. x 100 mm standoff
4	R-SP-1325-6	13 mm dia. x 25 mm pin standoff
2	R-SP-1925-6	19 mm dia. x 25 mm pin standoff
6	R-CT-40-30-6	40 mm tension clamp with 30 mm post
12	R-CT-64-70-6	64 mm tension clamp with 70 mm post
3	R-CT-95-83-6	95 mm tension clamp with 83 mm post
3	R-CT-100P-83-6	100 mm tension clamp plunger with 83 mm post
1	R-CTB-25-6	25 mm tension clamp bracket
6	R-RCD-6	Delrin® resting cone
6	R-RPS-6	Steel resting pin
1	R-APJ-6	Adjustable pivot joint
4	R-AJ-13-6	13 mm dia. adjustable jackstand
3	R-AJ-25-6	25 mm dia adjustable jackstand
3	R-AS-45-6	45 mm long adjustable slide
4	R-AS-70-6	70 mm long adjustable slide
2	R-TB-2025-6	Tower block with base 20 mm x 30 mm
1	R-T-25300-6	25 mm x 300 mm tower
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 163 pc

M6 kits: magnetic and clamping

The M6 CMM magnetic and clamping kits can be used to hold steel, aluminum, plastic and other nonferrous parts.

A kit includes a base plate with M6 threaded holes 12.5 mm on center (choose from plate sizes listed below) and a set of components (A, B or C) along with plate clamps for mounting to the CMM.



Kit part number	Base plate size	Set	Price
R-KC-MC1A-6	13 mm x 300 mm x 300 mm	A	\$1,684
R-KC-MC2A-6	13 mm x 450 mm x 450 mm	A	\$2,129
R-KC-MC3A-6	19 mm x 600 mm x 600 mm	A	\$3,029
R-KC-MC4A-6	19 mm x 750 mm x 750 mm	A	\$3,628
R-KC-MC5A-6	19 mm x 750 mm x 1000 mm	A	\$4,133
R-KC-MC6A-6	19 mm x 900 mm x 1200 mm	A	\$5,833

Component set A

Part number: R-FSC-MCA-6 Price: \$1,033

Includes:

Qty	Part number	Description
3	R-M-13-6	13 mm dia. x 25 mm magnet
3	R-M-19-6	19 mm dia. x 25 mm magnet
3	R-M-25-6	25 mm dia. x 25 mm magnet
3	R-S-1320-6	13 mm dia. x 20 mm standoff
3	R-S-1235-6	13 mm dia. x 25 mm standoff
3	R-S-1350-6	13 mm dia. x 50 mm standoff
3	R-S-1920-6	19 mm dia. x 20 mm standoff
3	R-S-1925-6	19 mm dia. x 25 mm standoff
3	R-S-1950-6	19 mm dia. x 50 mm standoff
3	R-S-2520-6	25 mm dia. x 20 mm standoff
3	R-S-2525-6	25 mm dia. x 25 mm standoff
3	R-S-2550-6	25 mm dia. x 50 mm standoff
4	R-CT-64-70-6	64 mm tension clamp with 70 mm post
4	R-RCD-6	Delrin® resting cone
1	R-AJ-13-6	13 mm dia. adjustable jackstand
1	R-AS-45-6	45 mm long adjustable slide
1	R-AS-70-6	70 mm long adjustable slide
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 49 pc

Kit part number	Base plate size	Set	Price
R-KC-MC1B-6	13 mm x 300 mm x 300 mm	B	\$2,984
R-KC-MC2B-6	13 mm x 450 mm x 450 mm	B	\$3,429
R-KC-MC3B-6	19 mm x 600 mm x 600 mm	B	\$4,329
R-KC-MC4B-6	19 mm x 750 mm x 750 mm	B	\$4,928
R-KC-MC5B-6	19 mm x 750 mm x 1000 mm	B	\$5,433
R-KC-MC6B-6	19 mm x 900 mm x 1200 mm	B	\$7,133

Component set B

Part number: R-FSC-MCB-6 **Price:** \$2,333

Includes:

Qty	Part number	Description
4	R-M-13-6	13 mm dia. x 25 mm magnet
4	R-M-19-6	19 mm dia. x 25 mm magnet
4	R-M-25-6	25 mm dia. x 25 mm magnet
2	R-MP-13-6	13 mm dia. 25 mm pin magnet
3	R-S-1910-6	9 mm dia. x 10 mm standoff
6	R-S-1320-6	13 mm dia. x 20 mm standoff
6	R-S-1325-6	13 mm dia. x 25 mm standoff
6	R-S-1350-6	13 mm dia. x 50 mm standoff
3	R-S-1910-6	19 mm dia. x 10 mm standoff
6	R-S-1920-6	19 mm dia. x 50 mm standoff
6	R-S-1925-6	19 mm dia. x 25 mm standoff
6	R-S-1950-6	19 mm dia. x 50 mm standoff
3	R-S-19100-6	19 mm dia. x 100 mm standoff
6	R-S-2520-6	25 mm dia. x 20 mm standoff
6	R-S-2525-6	25 mm dia. x 25 mm standoff
6	R-S-2550-6	25 mm dia. x 50 mm standoff
3	R-S-25100-6	25 mm dia. x 100 mm standoff
4	R-CT-40-30-6	40 mm tension clamp with 30 mm post
8	R-CT-64-70-6	64 mm tension clamp with 70 mm post
4	R-RCD-6	Delrin® resting cone
4	R-RPS-6	Steel resting pin
2	R-AJ-13-6	13 mm dia. adjustable jackstand
2	R-AJ-25-6	25 mm dia. adjustable jackstand
2	R-AS-45-6	45 mm long adjustable slide
2	R-AS-70-6	70 mm long adjustable slide
2	R-TB-2025-6	Tower block with base 20 mm x 30 mm
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 112 pc

Kit part number	Base plate size	Set	Price
R-KC-MC1C-6	13 mm x 300 mm x 300 mm	C	\$4,478
R-KC-MC2C-6	13 mm x 450 mm x 450 mm	C	\$4,923
R-KC-MC3C-6	19 mm x 600 mm x 600 mm	C	\$5,823
R-KC-MC4C-6	19 mm x 750 mm x 750 mm	C	\$6,422
R-KC-MC5C-6	19 mm x 750 mm x 1000 mm	C	\$6,927
R-KC-MC6C-6	19 mm x 900 mm x 1200 mm	C	\$8,627

Component set C

Part number: R-FSC-MCC-6 **Price:** \$3,827

Includes:

Qty	Part number	Description
6	R-M-13-6	13 mm dia. x 25 mm magnet
6	R-M-19-6	19 mm dia. x 25 mm magnet
6	R-M-25-6	25 mm dia. x 25 mm magnet
2	R-MP-13-6	13 mm dia. x 25 mm pin magnet
2	R-MP-19-6	19 mm dia. x 25 mm pin magnet
4	R-S-910-6	9 mm dia. x 10 mm standoff
4	R-S-1310-6	13 mm dia. x 10 mm standoff
8	R-S-1320-6	13 mm dia. x 20 mm standoff
8	R-S-1325-6	13 mm dia. x 25 mm standoff
8	R-S-1350-6	13 mm dia. x 50 mm standoff
4	R-S-1910-6	19 mm dia. x 10 mm standoff
8	R-S-1920-6	19 mm dia. x 20 mm standoff
8	R-S-1925-6	19 mm dia. x 25 mm standoff
8	R-S-1950-6	19 mm dia. x 50 mm standoff
6	R-S-19100-6	19 mm dia. x 100 mm standoff
8	R-S-2520-6	25 mm dia. x 20 mm standoff
8	R-S-2525-6	25 mm dia. x 25 mm standoff
8	R-S-2550-6	25 mm dia. x 50 mm standoff
6	R-S-25100-6	25 mm dia. x 100 mm standoff
4	R-CT-40-30-6	40 mm tension clamp with 30 mm post
8	R-CT-64-70-6	64 mm tension clamp with 70 mm post
2	R-CT-95-83-6	95 mm tension clamp with 83 mm post
1	R-CTB-25-6	25 mm tension clamp bracket
6	R-RCD-6	Delrin® resting cone
6	R-RPS-6	Steel resting pin
1	R-APJ-6	Adjustable pivot joint
3	R-AJ-13-6	13 mm dia. adjustable jackstand
3	R-AJ-25-6	25 mm dia. adjustable jackstand
3	R-AS-45-6	45 mm long adjustable slide
3	R-AS-70-6	70 mm long adjustable slide
2	R-TB-2025-6	Tower block with base 20 mm x 30 mm
1	R-T 25300-6	25 mm x 300 mm tower
2	R-TC-500200	500 mm x 200 mm x 25 mm component tray
2	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 165 pc

M8 kits: clamping

The M8 CMM clamping kits can be used to hold aluminum, plastic and other nonferrous parts.

A kit includes a base plate with M8 threaded holes 15 mm on center (choose from plate sizes listed below) and a set of components (A, B or C) along with plate clamps for mounting to the CMM.



Kit part number	Base plate size	Set	Price
R-KC-C1A-8	13 mm x 300 mm x 300 mm	A	\$1,415
R-KC-C2A-8	13 mm x 450 mm x 450 mm	A	\$1,810
R-KC-C3A-8	19 mm x 600 mm x 600 mm	A	\$2,570
R-KC-C4A-8	19 mm x 750 mm x 750 mm	A	\$3,239
R-KC-C5A-8	19 mm x 750 mm x 1020 mm	A	\$3,784
R-KC-C6A-8	19 mm x 900 mm x 1200 mm	A	\$5,284

Component set A

Part number: R-FSC-CA-8 **Price:** \$789

Includes:

Qty	Part number	Description
3	R-S-1320-8	13 mm dia. x 20 mm standoff
3	R-S-1325-8	13 mm dia. x 25 mm standoff
3	R-S-1350-8	13 mm dia. x 50 mm standoff
3	R-S-1920-8	19 mm dia. x 20 mm standoff
3	R-S-1925-8	19 mm dia. x 25 mm standoff
3	R-S-1950-8	19 mm dia. x 50 mm standoff
3	R-S-2520-8	25 mm dia. x 20 mm standoff
3	R-S-2525-8	25 mm dia. x 25 mm standoff
3	R-S-2550-8	25 mm dia. x 50 mm standoff
2	R-SP-1325-8	13 mm dia. x 25 mm pin standoff
2	R-CT-40-30-8	40 mm tension clamp with 30 mm post
4	R-CT-64-70-8	64 mm tension clamp with 70 mm post
4	R-RCD-8	Delrin® resting cone
1	R-AJ-19-8	19 mm dia. adjustable jackstand
1	R-AS-70-8	70 mm long adjustable slide
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 43 pc

Kit part number	Base plate size	Set	Price
R-KC-C1B-8	13 mm x 300 mm x 300 mm	B	\$2,779
R-KC-C2B-8	13 mm x 450 mm x 450 mm	B	\$3,174
R-KC-C3B-8	19 mm x 600 mm x 600 mm	B	\$3,934
R-KC-C4B-8	19 mm x 750 mm x 750 mm	B	\$4,603
R-KC-C5B-8	19 mm x 750 mm x 1020 mm	B	\$5,148
R-KC-C6B-8	19 mm x 900 mm x 1200 mm	B	\$6,648

Component set B

Part number: R-FSC-CB-8 **Price:** \$2,153

Includes:

Qty	Part number	Description
3	R-S-1315-8	13 mm dia. x 15 mm standoff
6	R-S-1320-8	13 mm dia. x 20 mm standoff
6	R-S-1325-8	13 mm dia. x 25 mm standoff
6	R-S-1350-8	13 mm dia. x 50 mm standoff
3	R-S-1915-8	19 mm dia. x 15 mm standoff
6	R-S-1920-8	19 mm dia. x 20 mm standoff
6	R-S-1925-8	19 mm dia. x 25 mm standoff
6	R-S-1950-8	19 mm dia. x 50 mm standoff
4	R-S-19100-8	19 mm dia. x 100 mm standoff
6	R-S-2520-8	25 mm dia. x 20 mm standoff
6	R-S-2525-8	25 mm dia. x 25 mm standoff
6	R-S-2550-8	25 mm dia. x 50 mm standoff
4	R-S-25100-8	25 mm dia. x 100 mm standoff
4	R-SP-1325-8	13 mm dia. x 25 mm pin standoff
6	R-CT-40-30-8	40 mm tension clamp with 30 mm post
12	R-CT-64-70-8	64 mm tension clamp with 70 mm post
4	R-RCD-8	Delrin® resting cone
4	R-RSC-8	Steel resting cone
2	R-AJ-19-8	19 mm dia. adjustable jackstand
2	R-AJ-25-8	25 mm dia. adjustable jackstand
1	R-AS-45-8	45 mm long adjustable slide
3	R-AS-70-8	70 mm long adjustable slide
2	R-TB-2530-8	Tower block with base
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 110 pc

Kit part number	Base plate size	Set	Price
R-KC-C1C-8	13 mm x 300 mm x 300 mm	C	\$4,160
R-KC-C2C-8	13 mm x 450 mm x 450 mm	C	\$4,555
R-KC-C3C-8	19 mm x 600 mm x 600 mm	C	\$5,315
R-KC-C4C-8	19 mm x 750 mm x 750 mm	C	\$5,984
R-KC-C5C-8	19 mm x 750 mm x 1020 mm	C	\$6,529
R-KC-C6C-8	19 mm x 900 mm x 1200 mm	C	\$8,029

Component set C

Part number: R-FSC-CC-8 **Price:** \$3,534

Includes:

Qty	Part number	Description
4	R-S-1315-8	13 mm dia. x 15 mm standoff
8	R-S-1320-8	13 mm dia. x 20 mm standoff
8	R-S-1325-8	13 mm dia. x 25 mm standoff
8	R-S-1350-8	13 mm dia. x 50 mm standoff
4	R-S-1915-8	19 mm dia. x 15 mm standoff
8	R-S-1920-8	19 mm dia. x 20 mm standoff
8	R-S-1925-8	19 mm dia. x 25 mm standoff
8	R-S-1950-8	19 mm dia. x 50 mm standoff
6	R-S-19100-8	19 mm dia. x 100 mm standoff
8	R-S-2520-8	25 mm dia. x 20 mm standoff
8	R-S-2525-8	25 mm dia. x 25 mm standoff
8	R-S-2550-8	25 mm dia. x 50 mm standoff
6	R-S-25100-8	25 mm dia. x 100 mm standoff
6	R-SP-1325-8	13 mm dia. x 25 mm pin standoff
6	R-CT-40-30-8	40 mm tension clamp with 30 mm post
12	R-CT-64-70-8	64 mm tension clamp with 70 mm post
3	R-CT-95-83-8	95 mm tension clamp with 83 mm post
3	R-CT-100P-83-8	100 mm tension clamp plunger with 83 mm post
1	R-CTB-25-8	25 mm tension clamp bracket
4	R-RCD-8	Delrin® resting cone
4	R-RCS-8	Steel resting cone
1	R-APJ-8	Adjustable pivot joint
4	R-AJ-19-8	19 mm dia. adjustable jackstand
3	R-AJ-25-8	25 mm dia. adjustable jackstand
3	R-AS-45-8	45 mm long adjustable slide
4	R-AS-70-8	70 mm long adjustable slide
2	R-TB-2530-8	Tower block with base
1	R-TB-25300-8	25 mm x 300 mm tower
2	R-TC-500200	500 mm x 200 mm x 25 mm component tray
2	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 153 pc

M8 kits: magnetic and clamping

The M8 CMM magnetic and clamping kits can be used to hold steel, aluminum, plastic and other nonferrous parts.

A kit includes a base plate with M8 threaded holes 15 mm on center (choose from plate sizes listed below) and a set of components (A, B or C) along with plate clamps for mounting to the CMM.



Kit part number	Base plate size	Set	Price
R-KC-MC1A-8	13 mm x 300 mm x 300 mm	A	\$1,618
R-KC-MC2A-8	13 mm x 450 mm x 450 mm	A	\$2,013
R-KC-MC3A-8	19 mm x 600 mm x 600 mm	A	\$2,773
R-KC-MC4A-8	19 mm x 750 mm x 750 mm	A	\$3,442
R-KC-MC5A-8	19 mm x 750 mm x 1020 mm	A	\$3,987
R-KC-MC6A-8	19 mm x 900 mm x 1200 mm	A	\$5,487

Component set A

Part number: R-FSC-MCA-8 Price: \$992

Includes:

Qty	Part number	Description
3	R-M-13-8	13 mm dia. x 25 mm magnet
3	R-M-19-8	19 mm dia. x 25 mm magnet
3	R-M-25-8	25 mm dia. x 25 mm magnet
3	R-S-1320-8	13 mm dia. x 20 mm standoff
3	R-S-1325-8	13 mm dia. x 25 mm standoff
3	R-S-1350-8	13 mm dia. x 50 mm standoff
3	R-S-1920-8	19 mm dia. x 20 mm standoff
3	R-S-1925-8	19 mm dia. x 25 mm standoff
3	R-S-1950-8	19 mm dia. x 50 mm standoff
3	R-S-2520-8	25 mm dia. x 20 mm standoff
3	R-S-2525-8	25 mm dia. x 25 mm standoff
3	R-S-2550-8	25 mm dia. x 50 mm standoff
3	R-CT-64-70-8	64 mm tension clamp with 70 mm post
4	R-RCD-8	Delrin® resting cone
1	R-AJ-19-8	19 mm dia. adjustable jackstand
1	R-AS-70-8	70 mm long adjustable slide
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 47 pc

Kit part number	Base plate size	Set	Price
R-KC-MC1B-8	13 mm x 300 mm x 300 mm	B	\$3,096
R-KC-MC2B-8	13 mm x 450 mm x 450 mm	B	\$3,491
R-KC-MC3B-8	19 mm x 600 mm x 600 mm	B	\$4,251
R-KC-MC4B-8	19 mm x 750 mm x 750 mm	B	\$4,920
R-KC-MC5B-8	19 mm x 750 mm x 1020 mm	B	\$5,465
R-KC-MC6B-8	19 mm x 900 mm x 1200 mm	B	\$6,965

Component set B

Part number: R-FSC-MCB-8 **Price:** \$2,470

Includes:

Qty	Part number	Description
4	R-M-13-8	13 mm dia. x 25 mm magnet
4	R-M-19-8	19 mm dia. x 25 mm magnet
4	R-M-25-8	25 mm dia. x 25 mm magnet
2	R-MP-13-8	13 mm dia. x 25 mm pin magnet
3	R-S-1315-8	13 mm dia. x 15 mm standoff
6	R-S-1320-8	13 mm dia. x 20 mm standoff
6	R-S-1325-8	13 mm dia. x 25 mm standoff
6	R-S-1350-8	13 mm dia. x 50 mm standoff
3	R-S-1915-8	19 mm dia. x 15 mm standoff
6	R-S-1920-8	19 mm dia. x 20 mm standoff
6	R-S-1925-8	19 mm dia. x 25 mm standoff
6	R-S-1950-8	19 mm dia. x 50 mm standoff
4	R-S-19100-8	19 mm dia. x 100 mm standoff
6	R-S-2520-8	25 mm dia. x 20 mm standoff
6	R-S-2525-8	25 mm dia. x 25 mm standoff
6	R-S-2550-8	25 mm dia. x 50 mm standoff
4	R-S-25100-8	25 mm dia. x 100 mm standoff
4	R-CT-40-30-8	40 mm tension clamp with 30 mm post
8	R-CT-64-70-8	64 mm tension clamp with 70 mm post
4	R-RCD-8	Delrin® resting cone
4	R-RCS-8	Steel resting cone
2	R-AJ-19-8	19 mm dia. adjustable jackstand
2	R-AJ-25-8	25 mm dia. adjustable jackstand
1	R-AS-45-8	45 mm long adjustable slide
3	R-AS-70-8	70 mm long adjustable slide
2	R-TB-2530-8	Tower block with base
1	R-TC-500200	500 mm x 200 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 114 pc

Kit part number	Base plate size	Set	Price
R-KC-MC1C-8	13 mm x 300 mm x 300 mm	C	\$4,476
R-KC-MC2C-8	13 mm x 450 mm x 450 mm	C	\$4,871
R-KC-MC3C-8	19 mm x 600 mm x 600 mm	C	\$5,631
R-KC-MC4C-8	19 mm x 750 mm x 750 mm	C	\$6,300
R-KC-MC5C-8	19 mm x 750 mm x 1020 mm	C	\$6,845
R-KC-MC6C-8	19 mm x 900 mm x 1200 mm	C	\$8,345

Component set C

Part number: R-FSC-MCC-8 **Price:** \$3,850

Includes:

Qty	Part number	Description
6	R-M-13-8	13 mm dia. x 25 mm magnet
6	R-M-19-8	19 mm dia. x 25 mm magnet
6	R-M-25-8	25 mm dia. x 25 mm magnet
2	R-MP-13-8	13 mm dia. x 25 mm pin magnet
2	R-MP-19-8	19 mm dia. x 25 mm pin magnet
3	R-S-1315-8	13 mm dia. x 15 mm standoff
8	R-S-1320-8	13 mm dia. x 20 mm standoff
8	R-S-1325-8	13 mm dia. x 25 mm standoff
8	R-S-1350-8	13 mm dia. x 50 mm standoff
3	R-S-1915-8	19 mm dia. x 15 mm standoff
8	R-S-1920-8	19 mm dia. x 20 mm standoff
8	R-S-1925-8	19 mm dia. x 25 mm standoff
8	R-S-1950-8	19 mm dia. x 50 mm standoff
6	R-S-19100-8	19 mm dia. x 100 mm standoff
8	R-S-2520-8	25 mm dia. x 20 mm standoff
8	R-S-2525-8	25 mm dia. x 25 mm standoff
8	R-S-2550-8	25 mm dia. x 50 mm standoff
6	R-S-25100-8	25 mm dia. x 100 mm standoff
4	R-CT-40-30-8	40 mm tension clamp with 30 mm post
8	R-CT-64-70-8	64 mm tension clamp with 70 mm post
2	R-CT-95-83-8	95 mm tension clamp with 83 mm post
1	R-CTB-25-8	25 mm tension clamp bracket
4	R-RCD-8	Delrin® resting cone
4	R-RCS-8	Steel resting cone
1	R-APJ-8	Adjustable pivot joint
3	R-AJ-19-8	19 mm dia. adjustable jackstand
3	R-AJ-25-8	25 mm dia. adjustable jackstand
3	R-AS-45-8	45 mm long adjustable slide
3	R-AS-70-8	70 mm long adjustable slide
2	R-TB-2530-8	Tower block with base
1	R-TB-25300-8	25 mm x 300 mm tower
2	R-TC-500200	500 mm x 200 mm x 25 mm component tray
2	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 155 pc

Adjustables

Adjustable jackstand

To allow variable heights of up to 22 mm and then lock them into position.


Part number	Thread	Diameter	Height	Adjustment	Price
R-AJ-9-4	M4	9 mm	19 mm	7 mm	\$45
R-AJ-13-6	M6	17 mm	42 mm	13 mm	\$40
R-AJ-25-6	M6	25 mm	42 mm	13 mm	\$55
R-AJ-19-8	M8	19 mm	37 mm	13 mm	\$45
R-AJ-25-8	M8	25 mm	42 mm	13 mm	\$56
R-AJS-35-8	M8	38 mm	65 mm	15 mm	\$88



Adjustable pivot joint

For positioning a component at any angle. Lock the rotating base into position and then set the angle of the pivot.


Part number	Thread	Diameter	Height	Adjustment	Price
R-APJ-6	M6	19 mm	50 mm	93°	\$74
R-APJ-8	M8	19 mm	50 mm	93°	\$77



Adjustable slide

To place components inbetween holes on the plate.


Part number	Thread	Height	A	B	C	Price
R-AS-30-4	M4	5 mm	30 mm	13 mm	9 mm	\$28
R-AS-45-4	M4	5 mm	45 mm	13 mm	24 mm	\$31
R-AS-45-6	M6	10 mm	44 mm	20 mm	13 mm	\$28
R-AS-70-6	M6	10 mm	72 mm	25 mm	34 mm	\$40
R-AS-45-8	M8	10 mm	44 mm	20 mm	13 mm	\$30
R-AS-70-8	M8	10 mm	72 mm	25 mm	34 mm	\$42



Adjustable V-post

For holding cylindrical or tubular parts without marring the part surface. Can be rotated and locked into position.


Part number	Thread	Diameter	Height	Adjustment	Price
R-AVP-2525-6	M6	25 mm	25 mm	360°	\$39
R-AVP-2525-8	M8	25 mm	25 mm	360°	\$39



Adjustable height stand

To allow variable heights without marring the part surface.

Part number	Thread	Diameter	Height	Adjustment	Price
R-AH-2545-6	M6	25 mm	45 mm	9 mm	\$55
R-AH-2545-8	M8	25 mm	45 mm	9 mm	\$55




Adjustable angle plate

Ideal for holding components on an angle. The angle plate is adjustable to 180°.

Part number	Thread	Height	A	B	Adjustment	Price
R-PCA-135075-10-4	M4	13 mm	75 mm	50 mm	180°	\$178
R-PCA-135075-12-6	M6	13 mm	75 mm	50 mm	180°	\$178



R-PCA-135075-12-6




Clamps

Tension clamp

For quick and easy clamping.

Part number	Thread	Height	A	B	C	Price
R-CT-40-25-4	M4	25 mm	40 mm	7.6 mm	4 mm	\$21
R-CT-40-30-6	M6	30 mm	40 mm	7.6 mm	4 mm	\$23
R-CT-40-70-6	M6	68 mm	40 mm	7.6 mm	4 mm	\$25
R-CT-64-70-6	M6	68 mm	63.5 mm	13 mm	5 mm	\$26
R-CT-95-86-6	M6	83 mm	96 mm	19 mm	9 mm	\$45
R-CT-100P-83-6*	M6	83 mm	105 mm	19 mm	9 mm	\$57
R-CT-40-30-8	M8	30 mm	40 mm	7.6 mm	4 mm	\$25
R-CT-40-70-8	M8	68 mm	40 mm	7.6 mm	4 mm	\$27
R-CT-64-70-8	M8	68 mm	63.5 mm	13 mm	5 mm	\$28
R-CT-95-83-8	M8	83 mm	96 mm	19 mm	9 mm	\$45
R-CT-100P-83-8*	M8	83 mm	105 mm	19 mm	9 mm	\$57




*Includes a plunger for reaching over the edge of a part to a more rigid surface or to reach over another support component.

Soft tip tension clamp

Rubber coated tips hold parts without scratching or marring the part surface.


Part number	Thread	Height	A	B	C	Price
R-CTT-40-25-4	M4	25 mm	40 mm	7.6 mm	4 mm	\$24
R-CTT-40-30-6	M6	30 mm	40 mm	7.6 mm	4 mm	\$28
R-CTT-40-70-6	M6	68 mm	40 mm	7.6 mm	4 mm	\$30
R-CTT-64-70-6	M6	68 mm	63.5 mm	13 mm	5 mm	\$31
R-CTT-95-83-6	M6	83 mm	96 mm	19 mm	9 mm	\$50
R-CTT-40-30-8	M6	30 mm	40 mm	7.6 mm	4 mm	\$28
R-CTT-40-70-8	M8	68 mm	40 mm	7.6 mm	4 mm	\$30
R-CTT-64-70-8	M8	68 mm	63.5 mm	13 mm	5 mm	\$31
R-CTT-95-83-8	M8	83 mm	96 mm	19 mm	9 mm	\$50



Spring wire clamp

For light clamping of small parts, minimising the contact area on a part and causing the least possible obstruction.


Part number	Thread	Height	A	B	C	Price
R-CW-25-25-4	M4	25 mm	36 mm	8 mm	1.5 mm	\$28
R-CW-50-50-4	M4	45 mm	55 mm	8 mm	1.5 mm	\$32
R-CW-25-25-6	M6	25 mm	36 mm	8 mm	1.5 mm	\$28
R-CW-50-50-6	M6	50 mm	55 mm	8 mm	1.5 mm	\$32



Soft tip spring wire clamp

With rubber coated tips for light clamping of small parts, minimising the contact area on a part and for the least possible obstruction.

Part number	Thread	Height	A	B	C	Price
R-CWT-25-25-4	M4	25 mm	36 mm	8 mm	1.5 mm	\$30
R-CWT-50-50-4	M4	45 mm	55 mm	8 mm	1.5 mm	\$34
R-CWT-25-25-6	M6	25 mm	36 mm	8 mm	1.5 mm	\$28
R-CWT-50-50-6	M6	50 mm	55 mm	8 mm	1.5 mm	\$33




Pusher clamp

To push a part against standoffs or into corner (two interchangeable tips included).

Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CP-4	M4	32 mm	38 mm	19 mm	8 mm	13 mm	10 mm	\$79
R-CP-6	M6	32 mm	38 mm	19 mm	8 mm	13 mm	10 mm	\$79


Included: socket head cap screw, thumb screw and washer.



Screw pusher clamp

For pushing and holding a part against stops.


Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CSP-6	M6	76 mm	76 mm	25 mm	44 mm	44 mm	38 mm	\$81
R-CSP-8	M8	76 mm	76 mm	25 mm	44 mm	44 mm	38 mm	\$81



Centers

For holding cylindrical parts at each end on their inside diameters.


Part number	Thread	Diameter	Height	A	B	C	Adjustment	Price
R-CC-6	M4/M6	6 mm	38 mm	22 mm	51 mm	20 mm	16 mm	\$186
R-CC-13	M4/M6/M8	13 mm	50 mm	38 mm	64 mm	25 mm	38 mm	\$223
R-CC-25	M4/M6/M8	25 mm	69 mm	51 mm	76 mm	35 mm	50 mm	\$274



Mini vice

For clamping a small area of a part. Vice can be rotated 360° and then locked into a position.


Part number	Thread	Height	A	B	Adjustment	Price
R-CMV-4	M4	58 mm	32 mm	32 mm	11 mm	\$253
R-CMV-6	M4	58 mm	32 mm	32 mm	11 mm	\$253
R-CMV-8	M8	58 mm	32 mm	32 mm	11 mm	\$253



Tension clamp bracket

To hold tension clamp on an angle.

Part number	Thread	Diameter	Height	A	B	C	Price
R-CTB-25-6	M6	25.5 mm	6 mm	86 mm	38 mm	32 mm	\$62
R-CTB-25-8	M8	25.5 mm	6 mm	86 mm	38 mm	32 mm	\$63




Micro vice clamp

Ideal for holding parts horizontally or vertically. Jaws have a V notch for holding cylindrical and tubular parts.

Part number	Thread	Height	A	B	C	Adjustment	Price
R-CVM-4	M4	28 mm	38 mm	10 mm	–	13 mm	\$117
R-CVM-B-4	M4	35 mm	51 mm	16 mm	15 mm	13 mm	\$147
R-CVM-6	M6	28 mm	38 mm	10 mm	–	13 mm	\$117
R-CVM-B-6	M6	38 mm	78 mm	20 mm	35 mm	13 mm	\$147

(with base)



Spring pusher stand off clamp

Designed for fixturing small parts in tight or compact space. Ideal for positioning parts and for profile clamping.

Part number	Thread	Diameter	Height	Price
R-CSPS-1210-4	M4	12 mm	10 mm	\$45
R-CSPS-1210-5	M5	12 mm	10 mm	\$46




3-jaw clamp

For holding round parts at one end or in the middle, allowing the probe to move around the part without interference.

Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CJ-3	M6/M8	127 mm	178 mm	50 mm	70 mm	19 mm	1.5 – 64.5 mm	\$374

Included: socket head cap screws.




Rotating 3-jaw clamp

For clamping on inner and outer diameter of a part. The part is locked into position then rotated to a marked increment.

Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CJR-3	M4/M6	60 mm	102 mm	70 mm	38 mm	6.4 mm	1 – 63 mm	\$291


Included: socket head cap screws and chuck keys.



CMM plate clamp

Non-marking clamp for securing 13 mm and 19 mm thick plates to a CMM. Includes screws for M8, M10 and M12 inserts.


Part number	Thread	Height	A	B	C	D	E	Price
R-CPC-190	M8/M10/M12	34 mm	193 mm	32 mm	90 mm	6.4 mm	11.9 mm	\$54



Positional tension clamp

Allows locking the tension clamp rotational position to avoid probing interferences between measurements.

Part number	Thread	Height	A	B	C	Price
R-CPT-64-58-6	M6	58 mm	63.5 mm	13 mm	5 mm	\$63




Hold down clamp

For additional clamping force.

Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CH-89-6	M6	42 mm	125 mm	38 mm	35 mm	29 mm	13 mm	\$77
R-CH-133-6	M6	50 mm	139 mm	38 mm	49 mm	29 mm	8 mm	\$73
R-CH-89-8	M8	42 mm	124 mm	38 mm	35 mm	30 mm	13 mm	\$77
R-CH-133-8	M8	50 mm	138 mm	38 mm	49 mm	30 mm	8 mm	\$73

Included: socket head cap screws and washers.




Magnets

Magnet

For holding steel or iron parts.


Part number	Thread	Diameter	Height	Price
R-M-6-4	M4	6 mm	25 mm	\$27
R-M-13-4	M4	13 mm	25 mm	\$44
R-M-13-6	M6	13 mm	25 mm	\$30
R-M-19-6	M6	19 mm	25 mm	\$33
R-M-25-6	M6	25 mm	25 mm	\$43
R-M-32-6	M6	32 mm	25 mm	\$53
R-M-13-8	M8	13 mm	25 mm	\$31
R-M-19-8	M8	19 mm	25 mm	\$34
R-M-25-8	M8	25 mm	25 mm	\$44
R-M-32-8	M8	32 mm	25 mm	\$56



Pin magnet

For holding and locating steel or iron parts.


Part number	Thread	Diameter	Height	A	B	Price
R-MP-6-4	M4	6 mm	25 mm	3.8 mm	1.6 mm	\$59
R-MP-13-4	M4	13 mm	25 mm	3.8 mm	1.6 mm	\$67
R-MP-13-6	M6	13 mm	25 mm	3.8 mm	3 mm	\$59
R-MP-19-6	M6	19 mm	25 mm	3.8 mm	3 mm	\$70
R-MP-25-6	M6	25 mm	25 mm	3.8 mm	3 mm	\$74
R-MP-13-8	M8	13 mm	25 mm	3.8 mm	3 mm	\$65
R-MP-19-8	M8	19 mm	25 mm	3.8 mm	3 mm	\$76
R-MP-25-8	M8	25 mm	25 mm	3.8 mm	3 mm	\$80



V magnet

For holding cylindrical parts and bent tubing.


Part number	Thread	Diameter	Height	Price
R-MV-13-6	M6	13 mm	25 mm	\$65
R-MV-19-6	M6	19 mm	25 mm	\$78
R-MV-25-6	M6	25 mm	25 mm	\$84
R-MV-32-6	M6	32 mm	25 mm	\$103
R-MV-13-8	M8	13 mm	25 mm	\$77
R-MV-19-8	M8	19 mm	25 mm	\$87
R-MV-25-8	M8	25 mm	25 mm	\$91
R-MV-32-8	M8	32 mm	25 mm	\$115



V magnet with base

For holding steel or iron parts.

Part number	Thread	Diameter	Height	A	B	C	Price
R-MVB-13-6	M6	13 mm	32 mm	76 mm	19 mm	36 mm	\$116
R-MVB-19-6	M6	19 mm	32 mm	76 mm	19 mm	36 mm	\$118
R-MVB-25-6	M6	25 mm	32 mm	76 mm	19 mm	36 mm	\$12
R-MVB-32-6	M6	32 mm	32 mm	76 mm	19 mm	36 mm	\$14
R-MVB-19-8	M8	19 mm	32 mm	76 mm	19 mm	38 mm	\$13
R-MVB-25-8	M8	25 mm	32 mm	76 mm	19 mm	38 mm	\$13
R-MVB-32-8	M8	32 mm	32 mm	76 mm	19 mm	38 mm	\$16




Miscellaneous

Cone

To rest a part on a rounded point for single-point contact.

Part number	Thread	Diameter	Height	Material	Price
R-RCD-6	M6	16 mm	13 mm	Delrin®	\$9
R-RCS-6	M6	16 mm	13 mm	Steel	\$15
R-RCA-6	M6	25 mm	19 mm	Aluminum	\$26
R-RCD-8	M8	16 mm	13 mm	Delrin®	\$9
R-RCS-8	M8	16 mm	13 mm	Steel	\$11
R-RCA-8	M8	25 mm	19 mm	Aluminum	\$26
R-RCS-25-8	M8	25 mm	19 mm	Steel	\$28



Resting pin

To rest a part on a rounded point.


Part number	Thread	Diameter	Height	Material	A	Price
R-RPD-4	M4	6 mm	5 mm	Delrin®	1.9 mm	\$16
R-RPA-4	M4	6 mm	5 mm	Aluminum	1.9 mm	\$10
R-RPD-6	M65	9 mm	10 mm	Delrin®	1.9 mm	\$16
R-RPS-6	M65	9 mm	10 mm	Steel	1.9 mm	\$10



Screws and adaptors

Component replacement parts.

Part number	Thread	Diameter	Height	Price
Thumb screw				
R-AATK-6	M6	12 mm	20 mm	\$2
Screw				
R-AATS-14	M3	6 mm	15 mm	\$6
R-AATS-20	M3	6 mm	20 mm	\$8
R-ATS-4	M4	13 mm	15 mm	\$8




Adaptor

R-AAS-4	M4	8 mm	15 mm	\$8
R-AAS-6	M6	8 mm	15 mm	\$8
R-AAS-8	M8	11 mm	17 mm	\$11

Vertical base plate

For holding components vertically.



Part number	Thread	Height	A	B	Price
R-PCV-507540-10-4	M4	63.5 mm	75 mm	40 mm	\$138



Adjustable T-arm

To support a part on its side.

Part number	Thread	Diameter	Height	A	B	Adjustment	Price
R-AT-6	M6	7.8 mm	52 mm	100 mm	12.7 mm	89 mm	\$65



Standoffs

To elevate and locate a part.

M4 standoffs

Part number	Thread	Diameter	Height	Price
R-S-65-4*	M4	6 mm	5 mm	\$12
R-S-610-4*	M4	6 mm	10 mm	\$12
R-S-615-4	M4	6 mm	15 mm	\$16
R-S-620-4*	M4	6 mm	20 mm	\$15
R-S-625-4*	M4	6 mm	25 mm	\$14
R-S-95-4*	M4	9 mm	5 mm	\$12
R-S-910-4	M4	9 mm	10 mm	\$12
R-S-915-4	M4	9 mm	15 mm	\$17
R-S-920-4	M4	9 mm	20 mm	\$13
R-S-925-4	M4	9 mm	25 mm	\$13
R-S-950-4	M4	9 mm	50 mm	\$16
R-S-125-4*	M4	12 mm	5 mm	\$12
R-S-1210-4	M4	12 mm	10 mm	\$13
R-S-1215-4	M4	12 mm	15 mm	\$16
R-S-1220-4*	M4	12 mm	20 mm	\$15
R-S-1225-4	M4	12 mm	25 mm	\$14
R-S-1250-4	M4	12 mm	50 mm	\$17



R-S-2550-6



R-S-920-4




R-S-620-4

M6 standoffs

Part number	Thread	Diameter	Height	Price
R-S-610-6*	M6	6 mm	10 mm	\$12
R-S-625-6*	M6	6 mm	25 mm	\$13
R-S-95-6*	M6	9 mm	5 mm	\$12
R-S-910-6	M6	9 mm	10 mm	\$10
R-S-915-6	M6	9 mm	15 mm	\$16
R-S-920-6	M6	9 mm	20 mm	\$13
R-S-925-6	M6	9 mm	25 mm	\$13
R-S-1310-6	M6	13 mm	10 mm	\$11
R-S-1315-6	M6	13 mm	15 mm	\$12
R-S-1320-6	M6	13 mm	20 mm	\$11
R-S-1325-6	M6	13 mm	25 mm	\$11
R-S-1350-6	M6	13 mm	50 mm	\$13
R-S-13100-6	M6	13 mm	100 mm	\$20
R-S-13150-6	M6	13 mm	150 mm	\$21
R-S-1910-6	M6	19 mm	10 mm	\$12
R-S-1915-6	M6	19 mm	15 mm	\$13
R-S-1920-6	M6	19 mm	20 mm	\$12
R-S-1925-6	M6	19 mm	25 mm	\$12
R-S-1950-6	M6	19 mm	50 mm	\$15
R-S-19100-6	M6	19 mm	100 mm	\$16
R-S-19150-6	M6	19 mm	150 mm	\$22

M6 standoffs continued

Part number	Thread	Diameter	Height	Price
R-S-2515-6	M6	25 mm	15 mm	\$18
R-S-2520-6	M6	25 mm	20 mm	\$14
R-S-2525-6	M6	25 mm	25 mm	\$15
R-S-2550-6	M6	25 mm	50 mm	\$16
R-S-25100-6	M6	25 mm	100 mm	\$18
R-S-25150-6	M6	25 mm	150 mm	\$25
R-S-3825-6	M6	38 mm	25 mm	\$28
R-S-3850-6	M6	38 mm	50 mm	\$30
R-S-38150-6	M6	38 mm	150 mm	\$43



M8 standoffs

Part number	Thread	Diameter	Height	Price
R-S-1315-8	M8	13 mm	15 mm	\$11
R-S-1320-8	M8	13 mm	20 mm	\$11
R-S-1325-8	M8	13 mm	25 mm	\$11
R-S-1350-8	M8	13 mm	50 mm	\$11
R-S-13100-8	M8	13 mm	100 mm	\$17
R-S-1915-8	M8	19 mm	15 mm	\$12
R-S-1920-8	M8	19 mm	20 mm	\$12
R-S-1925-8	M8	19 mm	25 mm	\$14
R-S-1950-8	M8	19 mm	50 mm	\$14
R-S-19100-8	M8	19 mm	100 mm	\$16
R-S-19150-8	M8	19 mm	150 mm	\$23
R-S-2520-8	M8	25 mm	20 mm	\$14
R-S-2525-8	M8	25 mm	25 mm	\$14
R-S-2550-8	M8	25 mm	50 mm	\$15
R-S-25100-8	M8	25 mm	100 mm	\$18
R-S-25150-8	M8	25 mm	150 mm	\$25
R-S-3825-8	M8	38 mm	25 mm	\$33
R-S-3850-8	M8	38 mm	50 mm	\$36
R-S-38150-8	M8	38 mm	150 mm	\$54

* Does not have a threaded top.

M4 standoffs are made of aluminum. M6 standoffs are made of steel.

Delrin® standoffs

To elevate and locate a part using a non-marring material.


Part number	Thread	Diameter	Height	Price
R-SD-610-4	M4	6 mm	10 mm	\$13
R-SD-910-4	M4	9 mm	10 mm	\$15
R-SD-1210-4	M4	12 mm	10 mm	\$16
R-SD-925-6	M6	9 mm	25 mm	\$15
R-SD-1325-6	M6	13 mm	25 mm	\$14
R-SD-1925-6	M6	19 mm	25 mm	\$15



Pin standoffs

To elevate and locate a part against a pin.

Part number	Thread	Diameter	Height	A	B	Price
R-SP-610-4	M4	6 mm	10 mm	3.8 mm	2 mm	\$14
R-SP-910-4	M4	9 mm	10 mm	3.8 mm	2 mm	\$14
R-SP-1210-4	M4	12 mm	10 mm	3.8 mm	2 mm	\$14
R-SP-610-6	M6	6 mm	10 mm	3.8 mm	2 mm	\$15
R-SP-910-6	M6	9 mm	10 mm	3.8 mm	2 mm	\$15
R-SP-1325-6	M6	13 mm	25 mm	3.8 mm	3 mm	\$15
R-SP-1925-6	M6	19 mm	25 mm	3.8 mm	3 mm	\$26
R-SP-1325-8	M8	13 mm	25 mm	3.8 mm	3 mm	\$16
R-SP-2525-8	M8	25 mm	25 mm	3.8 mm	3 mm	\$30



Delrin® pin standoffs

To elevate and locate a part against a pin using a non-marring material.

Part number	Thread	Diameter	Height	A	B	Price
R-SPD-910-4	M4	9 mm	10 mm	3.8 mm	2 mm	\$15
R-SPD-1325-6	M6	13 mm	25 mm	3.8 mm	3 mm	\$15



2-way spring-loaded pin

For locating within a hole or slot of a part.

Part number	Thread	Diameter	Height	A	B	Adjustment	Price
R-S-1350-2W-6	M6	13 mm	50 mm	2 mm	9 mm	12.5 mm	\$121
R-S-2550-2W-6	M6	25 mm	50 mm	7 mm	19 mm	12.5 mm	\$113
R-S-2550-2W-8	M8	25 mm	50 mm	7.1 mm	19 mm	12.5 mm	\$113




R-S-2550-2W-6 R-S-2550-4W-6

4-way spring-loaded pin

For locating within a hole or slot of a part.


Part number	Thread	Diameter	Height	A	B	Adjustment	Price
R-S-1350-4W-6	M6	13 mm	50 mm	2 mm	9 mm	12.5 mm	\$109
R-S-2550-4W-6	M6	25 mm	50 mm	7 mm	19 mm	12.5 mm	\$103
R-S-2550-4W-8	M8	25 mm	50 mm	7.1 mm	19 mm	12.5 mm	\$103



Standoff adaptor

For step clamps and calibration sphere.


Part number	Thread	Diameter	Height	A	Price
R-SA-6-4	M4	16 mm	15 mm	M6	\$15
R-SA-4-6	M6	9 mm	15 mm	M4	\$15
R-SA-8-6	M6	25 mm	25 mm	M8	\$17
R-SA-6-8	M8	25 mm	25 mm	M6	\$18



Rotator standoff

To secure parts against stops/supports.

Part number	Thread	Diameter	Height	Adjustment	Price
R-SR-2525-6	M6	25 mm	25 mm	19 mm	\$67



Tooling ball

For referencing CMM to co-ordinates to a program part.

Part number	Thread	Diameter	Height	A	Price
R-STB-13-6	M6	16 mm	41 mm	13 mm	\$72
R-STB-13-8	M8	19 mm	41 mm	13 mm	\$72



Suction cups

Suction cup

For holding contoured surfaces.

Part number	Thread	Diameter	Height	A	Price
R-CS-5-6	M6	19 mm	35 mm	5 mm	\$63
R-CS-10-6	M6	19 mm	45 mm	10 mm	\$62
R-CS-20-6	M6	31 mm	45 mm	20 mm	\$75
R-CS-30-6	M6	44 mm	65 mm	30 mm	\$88
R-CS-50-6	M6	70 mm	65 mm	50 mm	\$123

Requires R-CSH-MSC, available seperately.



Exposed suction cup

For holding contoured surfaces.

Part number	Thread	Diameter	Height	A	Price
R-CES-10-6	M6	19 mm	42 mm	10 mm	\$49
R-CES-20-6	M6	31 mm	49 mm	20 mm	\$58
R-CES-30-6	M6	31 mm	57 mm	30 mm	\$68
R-CES-50-6	M6	31 mm	67 mm	50 mm	\$86

Requires R-CSH-MSC, available seperately.




Suction V cup

For holding cylindrical tubes and shafts.

Part number	Thread	Diameter	Height	A	B	Price
R-CVS-5-6	M6	19 mm	35 mm	5 mm	90°	\$81
R-CVS-10-6	M6	19 mm	41 mm	10 mm	120°	\$79
R-CVS-20-6	M6	31 mm	51 mm	20 mm	120°	\$96
R-CVS-30-6	M6	44 mm	76 mm	30 mm	120°	\$124
R-CVS-50-6	M6	70 mm	89 mm	50 mm	120°	\$171

Requires R-CSH-MSC, available seperately.



Vacuum pump

For suction cups with on/off valve, hose connector and quick disconnect.

Part number	Description	Price
R-CSVP	Vacuum pump assembly	\$218




Manifold

6-port or 10-port manifold can be used vertically or horizontally on a base plate.

Part number	Description	Height	A	B	C	Price
R-CSM-6P	6-port manifold	52 mm	121 mm	25 mm	67 mm	\$197
R-CSM-10P	10-port manifold	52 mm	197 mm	25 mm	67 mm	\$267

Requires R-CSH-MP and R-CSH-MSC, available separately.



Vacuum hose

Hose for connecting manifold to vacuum pump and to suction cups.

Part number	Description	Price
R-CSH-MP	9.5 mm diameter hose to connect manifold to vacuum pump (sold per meter)	\$7
R-CSH-MSC	6.4mm diameter hose to connect manifold to suction cups (sold per meter)	\$13



Suction cup tray

For holding and organizing suction cups.

Part number	Thread	Height	Width	Depth	Price
R-TCS-300200	M6	25 mm	300 mm	200 mm	\$133



Towers


Tower

To hold a part vertically.

Part number	Thread	Height	A	B	C	Threaded rows	Price
R-T-25150-6	M6	150 mm	127 mm	25 mm	25 mm	1	\$166
R-T-25300-6	M6	300 mm	127 mm	25 mm	25 mm	1	\$211
R-T-35300-6	M6	300 mm	152 mm	51 mm	35 mm	2	\$315
R-T-35450-6	M6	450 mm	152 mm	51 mm	50 mm	2	\$381
R-T-50600-6	M6	600 mm	152 mm	51 mm	50 mm	2	\$613
R-T-50750-6	M6	760 mm	152 mm	51 mm	50 mm	2	\$732
R-T-25150-8	M8	150 mm	127 mm	25 mm	25 mm	1	\$166
R-T-25300-8	M8	300 mm	127 mm	25 mm	25 mm	1	\$217
R-T-35300-8	M8	300 mm	152 mm	51 mm	35 mm	2/1*	\$368
R-T-35450-8	M8	450 mm	152 mm	51 mm	35 mm	2/1*	\$433
R-T-50600-8	M8	600 mm	152 mm	51 mm	50 mm	2	\$650
R-T-50750-8	M8	760 mm	152 mm	51 mm	50 mm	2	\$759

Included: socket head cap screws.

* Two sides have two rows of holes; two sides have one row of holes in the center.




Tower block with base

For positioning a component vertically to the part set-up. Can be used without the base to allow full rotation.

Part number	Thread	Height	A	B	C	D	Price
R-TB-1619-4	M4	26 mm	41 mm	16 mm	16 mm	15 mm	\$66
R-TB-2025-6	M6	35 mm	70 mm	20 mm	20 mm	35 mm	\$70
R-TB-2530-8	M8	40 mm	89 mm	25 mm	25 mm	45 mm	\$91

Included: socket head cap screws.




Trays

Large component tray

For holding and organizing components.

Part number	Thread	Height	Depth	Width	Price
R-TC-560500	M6/M8	25 mm	560 mm	500 mm	\$338



R-TC-560500

Medium component tray

For holding and organizing components.

Part number	Thread	Height	Depth	Width	Price
R-TC-500200	M6/M8	25 mm	500 mm	200 mm	\$152




R-TC-500200


Small component tray

For holding and organizing components.

Part number	Thread	Height	Depth	Width	Price
R-TC-300190-4	M4	25 mm	300 mm	190 mm	\$138
R-TC-300190-6	M6	25 mm	300 mm	190 mm	\$148
R-TC-300190-6	M6/M8	25 mm	300 mm	200 mm	\$148



R-TC-300190-4



R-TC-300200

Component storage box

10-compartment box to hold and organize components.

Part number	Height	Depth	Width	Price
R-BC10	45 mm	203 mm	152 mm	\$15



R-BC10

Vision fixtures

QLC M4 vision kits

The QLC M4 vision kit is ideal for parts that fit within a 75 mm x 75 mm working volume.

A kit includes an acrylic base plate with M4 threaded holes 10 mm on center, a quick load corner and one set of components (A or B).

Note: Each QLC frame is specific to your machine. Please contact Renishaw to determine which frame you need and for pricing.




Plate sizes multi-hole set A

Part number	Base plate size	Price
R-QLC-PV1-A-4	13 mm x 150 mm x 150 mm	Call for price
R-QLC-PV2-A-4	13 mm x 200 mm x 200 mm	Call for price
R-QLC-PV3-A-4	13 mm x 250 mm x 150 mm	Call for price
R-QLC-PV4-A-4	13 mm x 250 mm x 250 mm	Call for price

Plate sizes multi-hole set B

Part number	Base plate size	Price
R-QLC-PV1-B-4	13 mm x 150 mm x 150 mm	Call for price
R-QLC-PV2-B-4	13 mm x 200 mm x 200 mm	Call for price
R-QLC-PV3-B-4	13 mm x 250 mm x 150 mm	Call for price
R-QLC-PV4-B-4	13 mm x 250 mm x 250 mm	Call for price

Component set A

Price: Call for price

Includes:

Qty	Part number	Description
3	R-S-610-4	6 mm dia. x 10 mm standoff
3	R-S-625-4	6 mm dia. x 25 mm standoff
3	R-S-95-4	9 mm dia. x 5 mm standoff
3	R-S-910-4	9 mm dia. x 10 mm standoff
3	R-S-920-4	9 mm dia. x 20 mm standoff
3	R-S-925-4	9 mm dia. x 25 mm standoff
3	R-S-1210-4	12 mm dia. x 10 mm standoff
3	R-S-1225-4	12 mm dia. x 25 mm standoff
2	R-SP-610-4	6 mm dia. x 10 mm pin standoff
2	R-SP-910-4	9 mm dia. x 10 mm pin standoff
2	R-CTT-40-25-4	40 mm tension clamp with coated soft tip w/25 mm post
2	R-CWT-25-25-4	25 mm wire clamp with coated soft tip w/25 mm post
2	R-CWT-50-50-4	50 mm wire clamp with coated soft tip w/50 mm post
1	R-CP-4	Pusher clamp
1	R-CVM-B-4	Micro-clamp vice with base
1	R-CSPS-1210-4	Spring pusher standoff clamp

Plate sizes multi-hole set A

Part number	Base plate size	Price
R-QLC-PV1-A-4	13 mm x 150 mm x 150 mm	Call for price
R-QLC-PV2-A-4	13 mm x 200 mm x 200 mm	Call for price
R-QLC-PV3-A-4	13 mm x 250 mm x 150 mm	Call for price
R-QLC-PV4-A-4	13 mm x 250 mm x 250 mm	Call for price

Plate sizes multi-hole set B

Part number	Base plate size	Price
R-QLC-PV1-B-4	13 mm x 150 mm x 150 mm	Call for price
R-QLC-PV2-B-4	13 mm x 200 mm x 200 mm	Call for price
R-QLC-PV3-B-4	13 mm x 250 mm x 150 mm	Call for price
R-QLC-PV4-B-4	13 mm x 250 mm x 250 mm	Call for price

Component set A

Price: Call for price

Includes:

Qty	Part number	Description
3	R-S-610-4	6 mm dia. x 10 mm standoff
3	R-S-625-4	6 mm dia. x 25 mm standoff
3	R-S-95-4	9 mm dia. x 5 mm standoff
3	R-S-910-4	9 mm dia. x 10 mm standoff
3	R-S-920-4	9 mm dia. x 20 mm standoff
3	R-S-925-4	9 mm dia. x 25 mm standoff
3	R-S-1210-4	12 mm dia. x 10 mm standoff
3	R-S-1225-4	12 mm dia. x 25 mm standoff
2	R-SP-610-4	6 mm dia. x 10 mm pin standoff
2	R-SP-910-4	9 mm dia. x 10 mm pin standoff
2	R-CTT-40-25-4	40 mm tension clamp with coated soft tip w/25 mm post
2	R-CWT-25-25-4	25 mm wire clamp with coated soft tip w/25 mm post
2	R-CWT-50-50-4	50 mm wire clamp with coated soft tip w/50 mm post
1	R-CP-4	Pusher clamp
1	R-CVM-B-4	Micro-clamp vice with base
1	R-CSPS-1210-4	Spring pusher standoff clamp
4	R-RPA-4	Aluminum resting pin
1	R-VC-5050-4	50 mm x 50 mm corner viewer
1	R-AJ-9-4	9 mm dia. adjustable jackstand
1	R-AS-30-4	30 mm long adjustable slide
1	R-ASA-45-4	45 mm long adjustable acrylic slide base
1	R-TB-1619-4	Tower block with base 16 mm x 19 mm
1	R-TC-300-190-4	300 mm x 190 mm x 25 mm component tray
1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 48 pc

Plate sizes multi-window set A

Part number	Base plate size	Price
R-QLC-PVW1-A-4	13 mm × 200 mm × 200 mm	Call for price
R-QLC-PVW2-A-4	13 mm × 250 mm × 150 mm	Call for price
R-QLC-PVW3-A-4	13 mm × 250 mm × 250 mm	Call for price
R-QLC-PVW4-A-4	13 mm × 400 mm × 400 mm	Call for price

Plate sizes multi-window set B

Part number	Base plate size	Price
R-QLC-PVW1-B-4	13 mm × 200 mm × 200 mm	Call for price
R-QLC-PVW2-B-4	13 mm × 250 mm × 150 mm	Call for price
R-QLC-PVW3-B-4	13 mm × 250 mm × 250 mm	Call for price
R-QLC-PVW4-B-4	13 mm × 400 mm × 400 mm	Call for price

Component set B

Price: Call for price

Includes:

Qty	Part number	Description
3	R-S-65-4*	6 mm dia. × 5 mm standoff
6	R-S-610-4	6 mm dia. × 10 mm standoff
6	R-S-625-4	6 mm dia. × 25 mm standoff
3	R-S-95-4	9 mm dia. × 5 mm standoff
6	R-S-910-4	9 mm dia. × 10 mm standoff
6	R-S-920-4	9 mm dia. × 20 mm standoff
6	R-S-925-4	9 mm dia. × 25 mm standoff
6	R-S-1210-4	12 mm dia. × 10 mm standoff
6	R-S-1225-4	12 mm dia. × 25 mm standoff
4	R-SP-610-4	6 mm dia. × 10 mm pin standoff
4	R-SP-910-4	9 mm dia. × 10 mm pin standoff
4	R-CTT 40-25-4	40 mm tension clamp with coated soft tip w/25 mm post
4	R-CWT-25-25-4	25 mm wire clamp with coated soft tip w/25 mm post
4	R-CWT-50-50-4	50 mm wire clamp with coated soft tip w/50 mm post
1	R-CP-4	Pusher clamp
1	R-CVM-B-4	Micro-clamp vice with base
1	R-CSPS-1210-4	Spring pusher standoff clamp
4	R-RPA-4	Aluminum resting pin
1	R-VC-5050-4	50 mm × 50 mm corner viewer
2	R-AJ-9-4	9 mm dia. adjustable jackstand
2	R-AS-30-4	30 mm long adjustable slide
2	R-ASA-45-4	45 mm long adjustable acrylic slide base
1	R-TB-1619-4	Tower block with base 16 mm × 19 mm
1	R-TC-300190-4	300 mm × 190 mm × 25 mm component tray
1	R-BC10	50 mm × 200 mm × 150 mm compartment box

Total: 85 pc

* Does not have a threaded top

QLC M6 vision kits

The QLC M6 vision kit is a comprehensive kit for holding plastic, aluminum, rubber and other non-ferrous parts.

A kit includes an acrylic base plate with M6 threaded holes 12.5 mm on center, a quick load corner and one set of components (A).



Note: Each QLC frame is specific to your machine. Please contact Renishaw to determine which frame you need and for pricing.

Plate sizes multi-hole set A

Part number	Base plate size	Price
R-QLC-PV1-A-6	13 mm x 150 mm x 150 mm	Call for price
R-QLC-PV2-A-6	13 mm x 250 mm x 250 mm	Call for price

Component set A

Price: Call for price

Includes:	Qty	Part number	Description
	3	R-S-610-6*	6 mm dia x 10 mm standoff
	3	R-S-625-6*	6 mm dia. x 25 mm standoff
	3	R-S-95-6*	9 mm dia. x 5 mm standoff
	3	R-S-910-6	9 mm dia. x 10 mm standoff
	3	R-S-920-6	9 mm dia. x 20 mm standoff
	3	R-S-925-6	9 mm dia. x 25 mm standoff
	3	R-S-1310-6	13 mm dia. x 10 mm standoff
	3	R-S-1320-6	13 mm dia. x 20 mm standoff
	2	R-SP-610-6	6 mm dia. x 10 mm pin standoff
	2	R-SP-910-6	9 mm dia. x 10 mm pin standoff
	4	R-CTT-40-30-6	40 mm tension clamp with coated soft tip w/30 mm post
	4	R-CWT-25-25-6	25 mm wire clamp with coated soft tip w/ 25 mm post
	4	R-CWT-50-50-6	50 mm wire clamp with coated soft tip w/ 50 mm post
	1	R-CP-6	Pusher clamp
	1	R-CVM-B-6	Micro-clamp vice with base
	1	R-CSPS-1925-6	19 mm dia. x 25 mm spring pusher standoff clamp
	4	R-RPS-6	Steel resting pin
	1	R-VC-7575-6	75 mm x 75 mm corner viewer
	1	R-AJ-13-6	13 mm dia. adjustable jackstand
	1	R-AS-45-6	45 mm long adjustable slide
	1	R-ASA-45-6	45 mm long adjustable acrylic slide base
	1	R-TB-2025-6	Tower block with base 20 mm x 30 mm
	1	R-TC-300190-6	300 mm x 190 mm x 25 mm component tray
	1	R-BC10	50 mm x 200 mm x 150 mm compartment box

Total: 54 pc

* Does not have a threaded top

Plate sizes multi-window set A

Part number	Base plate size	Price
R-QLC1-PVW1-A-6	13 mm x 250 mm x 250 mm	Call for price
R-QLC1-PVW2-A-6	13 mm x 400 mm x 400 mm	Call for price

Plates


Vision plates

Acrylic base plates with dowel pins.



Part number	Thread	Height	Width	Depth	Windows	Hole spacing (OC*)	Price
M4 multi-hole plates							
R-PV-13150150-10-4	M4	13 mm	150 mm	150 mm	1	10 mm	\$333
R-PV-13200200-10-4	M4	13 mm	200 mm	200 mm	1	10 mm	\$438
R-PV-13250150-10-4	M4	13 mm	250 mm	150 mm	1	10 mm	\$428
R-PV-13250250-10-4	M4	13 mm	250 mm	250 mm	1	10 mm	\$518
M4 multi-window plates							
R-PV-W-13200200-10-4	M4	13 mm	200 mm	200 mm	5	10 mm	\$353
R-PV-W-13250150-10-4	M4	13 mm	250 mm	150 mm	3	10 mm	\$343
R-PV-W-13250250-10-4	M4	13 mm	250 mm	250 mm	5	10 mm	\$373
R-PV-W-13400400-10-4	M4	13 mm	400 mm	400 mm	7	10 mm	\$1,007
M6 multi-hole plates							
R-PV-13150150-12-6	M6	13 mm	150 mm	150 mm	1	12.5 mm	\$333
R-PV-13250250-12-6	M6	13 mm	250 mm	250 mm	1	12.5 mm	\$458
M6 multi-window plates							
R-PV-W-13250250-12-6	M6	13 mm	250 mm	250 mm	5	12.5 mm	\$343
R-PV-W-13400400-12-6	M6	13 mm	400 mm	400 mm	7	12.5 mm	\$1,002

*On center



Multi-hole plate R-PV-132000200-10-4



Multi-window plate R-PV-W-132000200-10-4

Adjustables

Adjustable jackstand

To allow variable heights of up to 22 mm and then lock them into position.


Part number	Thread	Diameter	Height	Adjustment	Price
R-AJ-9-4	M4	9 mm	19 mm	7 mm	\$45
R-AJ-13-6	M6	17 mm	42 mm	13 mm	\$40
R-AJ-25-6	M6	25 mm	42 mm	13 mm	\$55



Adjustable pivot joint

For positioning a component at any angle. Lock the rotating base into position and then set the angle of the pivot.


Part number	Thread	Diameter	Height	Adjustment	Price
R-APJ-6	M6	19 mm	50 mm	93°	\$74



Adjustable slide

To place components inbetween holes on the plate.


Part number	Thread	Height	A	B	C	Price
R-AS-30-4	M4	5 mm	30 mm	13 mm	9 mm	\$28
R-AS-45-4	M4	5 mm	45 mm	13 mm	24 mm	\$30
R-ASA-45-4 (Acrylic)	M4	5 mm	45 mm	13 mm	24 mm	\$30
R-ASA-45-6 (Acrylic)	M6	10 mm	44 mm	20 mm	13 mm	\$33
R-AS-45-6	M6	10 mm	44 mm	20 mm	13 mm	\$28
R-AS-70-6	M6	10 mm	72 mm	25 mm	34 mm	\$40



Adjustable V-post

For holding cylindrical or tubular parts without marring the part surface. Can be rotated and locked into position.


Part number	Thread	Diameter	Height	Adjustment	Price
A-AVP-2525-6	M6	25 mm	25 mm	360°	\$39



Adjustable height stand

To allow variable heights without marring the part surface.

Part number	Thread	Diameter	Height	Adjustment	Price
R-AH-2545-6	M6	25 mm	45 mm	9 mm	\$55



Adjustable angle plate

Ideal for holding components on an angle. The angle plate is adjustable to 180°.


Part number	Thread	Height	A	B	Adjustment	Price
R-PCA-135075-10-4	M4	13 mm	75 mm	50 mm	180°	\$178
R-PCA-135075-12-6	M6	13 mm	75 mm	50 mm	180°	\$178



Adjustable slide mirror

To aid viewing and inspecting a part.


Part number	Thread	Height	A	B	C	Price
R-ASM-4	M4	29 mm	75 mm	20 mm	34 mm	\$97



Adjustable slide acrylic extension

Screw any component to the acrylic slide to extend the reach of the component.


Part number	Thread	Height	A	B	C	Adjustment	Price
R-ASAE-4	M4	10 mm	82 mm	13 mm	25 mm	190°	\$87



Micro adjustable V

For cylindrical parts smaller than 6.5 mm in diameter.

Part number	Thread	Height	A	B	C	Price
R-AVM-4	M4	8 mm	25 mm	24 mm	10 mm	\$132




Clamps

Tension clamp

For quick and easy clamping.

Part number	Thread	Height	A	B	C	Price
R-CT-40-25-4	M4	25 mm	40 mm	7.6 mm	4 mm	\$21
R-CT-40-30-6	M6	30 mm	40 mm	7.6 mm	4 mm	\$23
R-CT-40-70-6	M6	68 mm	40 mm	7.6 mm	4 mm	\$25
R-CT-64-70-6	M6	68 mm	63.5 mm	13 mm	5 mm	\$26
R-CT-95-83-6	M6	83 mm	96 mm	19 mm	9 mm	\$45
R-CT-100P-83-6*	M6	83 mm	105 mm	19 mm	9 mm	\$57


*Includes a plunger for reaching over the edge of a part to a more rigid surface or to reach over another support component.



Soft tip tension clamp

Rubber coated tips hold parts without scratching or marring the part surface.


Part number	Thread	Height	A	B	C	Price
R-CTT-40-25-4	M4	25 mm	40 mm	7.6 mm	4 mm	\$24
R-CTT-40-30-6	M6	30 mm	40 mm	7.6 mm	4 mm	\$28
R-CTT-40-70-6	M6	68 mm	40 mm	7.6 mm	4 mm	\$30
R-CTT-64-70-6	M6	68 mm	63.5 mm	13 mm	5 mm	\$31
R-CTT-95-83-6	M6	83 mm	96 mm	19 mm	9 mm	\$50



Spring wire clamp

For light clamping of small parts, minimising the contact area on a part and causing the least possible obstruction.


Part number	Thread	Height	A	B	C	Price
R-CW-25-25-4	M4	25 mm	36 mm	8 mm	1.5 mm	\$28
R-CW-50-50-4	M4	42 mm	55 mm	8 mm	1.5 mm	\$32
R-CW-25-25-6	M6	25 mm	36 mm	8 mm	1.5 mm	\$28
R-CW-50-50-6	M6	50 mm	55 mm	8 mm	1.5 mm	\$32



Soft tip spring wire clamp

With rubber coated tips for light clamping of small parts, minimising the contact area on a part and for the least possible obstruction.

Part number	Thread	Height	A	B	C	Price
R-CWT-25-25-4	M4	25 mm	36 mm	8 mm	1.5 mm	\$30
R-CWT-50-50-4	M4	45 mm	55 mm	8 mm	1.5 mm	\$34
R-CWT-25-25-6	M6	25 mm	36 mm	8 mm	1.5 mm	\$28
R-CWT-50-50-6	M6	50 mm	55 mm	8 mm	1.5 mm	\$33




Pusher clamp

To push a part against standoffs or into corner (two interchangeable tips included).

Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CP-4	M4	32 mm	38 mm	19 mm	8 mm	13 mm	10 mm	\$79
R-CP-6	M6	32 mm	38 mm	19 mm	8 mm	13 mm	10 mm	\$79


Included: socket head cap screw, thumb screw and washer.



Screw pusher clamp

For pushing and holding a part against stops.

Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CSP-6	M6	76 mm	76 mm	25 mm	44 mm	44 mm	38 mm	\$81




Centers

For holding cylindrical parts at each end on their inside diameters.

Part number	Thread	Diameter	Height	A	B	C	Adjustment	Price
R-CC-6	M4/M6	6 mm	38 mm	22 mm	51 mm	20 mm	16 mm	\$186
R-CC-13	M4/M6/M8	13 mm	50 mm	38 mm	64 mm	25 mm	38 mm	\$223
R-CC-25	M4/M6/M8	25 mm	69 mm	51 mm	76 mm	35 mm	50 mm	\$274


Included: both male and female centering options, and socket head cap screws.



Micro center

Has adjustability to hold cylindrical parts up to 26 mm in length and 25.5 mm in diameter.

Part number	Thread	Diameter	Height	A	B	C	D	Price
R-CMC-4	M4	4.8 mm	30 mm	51 mm	32 mm	12.5 mm	25.5 mm	\$147




Mini vice

For clamping a small area of a part. Vice can be rotated 360° and then locked into a position.

Part number	Thread	Height	A	B	Adjustment	Price
R-CMV-4	M4	58 mm	32 mm	32 mm	11 mm	\$253
R-CMV-6	M4	58 mm	32 mm	32 mm	11 mm	\$253



R-CMV-4




Micro vice clamp

Ideal for holding parts horizontally or vertically. Jaws have a V notch for holding cylindrical and tubular parts.


Part number	Thread	Height	A	B	C	Adjustment	Price
R-CVM-4	M4	28 mm	38 mm	10 mm	–	13 mm	\$117
R-CVM-B-4 (with base)	M4	35 mm	51 mm	16 mm	15 mm	13 mm	\$147
R-CVM-6	M6	28 mm	38 mm	10 mm	–	13 mm	\$117
R-CVM-B-6 (with base)	M6	38 mm	78 mm	20 mm	35 mm	13 mm	\$147



R-CVM-4



R-CVM-B-4



Spring pusher stand off clamp

Designed for fixturing small parts in tight or compact space. Ideal for positioning parts and for profile clamping.


Part number	Thread	Diameter	Height	A	Price
R-CSPS-1210-4	M4	12 mm	10 mm	4 mm	\$45
R-CSPS-1925-6	M6	19 mm	25 mm	10 mm	\$50



R-CSPS-1210-4



R-CSPS-1925-6



Rotating 3-jaw clamp



For clamping on inner and outer diameter of a part. The part is locked into position then rotated to a marked increment.

Part number	Thread	Height	A	B	C	D	Adjustment	Price
R-CJR-3	M4/M6	60 mm	102 mm	70 mm	38 mm	6.4 mm	1 – 63 mm	\$291

Included: socket head cap screws and chuck keys.



R-CJR-3




Magnets

Magnet

For holding steel or iron parts.

Part number	Thread	Diameter	Height	Price
R-M-6-4	M4	6 mm	25 mm	\$27
R-M-13-4	M4	13 mm	25 mm	\$44
R-M-13-6	M6	13 mm	25 mm	\$30
R-M-19-6	M6	19 mm	25 mm	\$33
R-M-25-6	M6	25 mm	25 mm	\$43
R-M-32-6	M6	32 mm	25 mm	\$53



R-M-19-6

Pin magnet

For holding and locating steel or iron parts.

Part number	Thread	Diameter	Height	A	B	Price
R-MP-6-4	M4	6 mm	25 mm	3.8 mm	1.6 mm	\$59
R-MP-13-4	M4	13 mm	25 mm	3.8 mm	1.6 mm	\$67
R-MP-13-6	M6	13 mm	25 mm	3.8 mm	3 mm	\$59
R-MP-19-6	M6	19 mm	25 mm	3.8 mm	3 mm	\$70
R-MP-25-6	M6	25 mm	25 mm	3.8 mm	3 mm	\$74




R-MP-13-6

V magnet with base

For holding cylindrical parts and bent tubing.

Part number	Thread	Diameter	Height	Price
R-MV-13-6	M6	13 mm	25 mm	\$65
R-MV-19-6	M6	19 mm	25 mm	\$78
R-MV-25-6	M6	25 mm	25 mm	\$84
R-MV-32-6	M6	32 mm	25 mm	\$103



R-MV-25-6

V magnet with base


For holding steel or iron parts.

Part number	Thread	Diameter	Height	A	B	C	Price
R-MVB-13-6	M6	13 mm	32 mm	76 mm	19 mm	36 mm	\$116
R-MVB-19-6	M6	19 mm	32 mm	76 mm	19 mm	36 mm	\$118
R-MVB-25-6	M6	25 mm	32 mm	76 mm	19 mm	36 mm	\$121
R-MVB-32-6	M6	32 mm	32 mm	76 mm	19 mm	36 mm	\$142



R-MVB-25-6

Included: socket head cap, thumb screws and washers.



Miscellaneous

Cone

To rest a part on a rounded point for single-point contact.


Part number	Thread	Diameter	Height	Material	Price
R-RCD-6	M6	16 mm	13 mm	Delrin®	\$9
R-RCS-6	M6	16 mm	13 mm	Steel	\$15
R-RCA-6	M6	25 mm	19 mm	Aluminum	\$26



Resting pin

To rest a part on a rounded point.


Part number	Thread	Diameter	Height	Material	A	Price
R-RPD-4	M4	6 mm	5 mm	Delrin®	1.9 mm	\$16
R-RPA-4	M4	6 mm	5 mm	Aluminum	1.9 mm	\$10
R-RPD-6	M6	9 mm	10 mm	Aluminum	1.9 mm	\$16
R-RPS-6	M6	9 mm	10 mm	Steel	1.9 mm	\$10



Screws and adaptors

Component replacement parts.


Part number	Thread	Diameter	Height	Price
Thumb screw				
R-AATK-6	M6	12 mm	20 mm	\$2
Screw				
R-AATS-14	M3	6 mm	15 mm	\$6
R-AATS-20	M3	6 mm	20 mm	\$8
R-ATS-4	M4	13 mm	15 mm	\$8
Adaptor				
R-AAS-4	M4	8 mm	15 mm	\$8
R-AAS-6	M6	8 mm	15 mm	\$8



Vertical base plate

For holding components vertically.


Part number	Thread	Height	A	B	Price
R-PCV-507540-10-4	M4	63.5 mm	75 mm	40 mm	\$138



Corner viewer

Allows the part to be located in a corner. The serrations allow backlighting along the sides of a part.

Part number	Thread	Height	A	B	C	Price
R-VC-5050-4	M4	5 mm	50 mm	50 mm	10 mm	\$48
R-VC-7575-6	M6	6 mm	83 mm	83 mm	19 mm	\$58



Standoffs

To elevate and locate a part.

M4 standoffs

Part number	Thread	Diameter	Height	Price
R-S-65-4*	M4	6 mm	5 mm	\$12
R-S-610-4*	M4	6 mm	10 mm	\$12
R-S-615-4	M4	6 mm	15 mm	\$16
R-S-620-4*	M4	6 mm	20 mm	\$15
R-S-625-4*	M4	6 mm	25 mm	\$14
R-S-95-4*	M4	9 mm	5 mm	\$12
R-S-910-4	M4	9 mm	10 mm	\$12
R-S-915-4	M4	9 mm	15 mm	\$17
R-S-920-4	M4	9 mm	20 mm	\$13
R-S-925-4	M4	9 mm	25 mm	\$13
R-S-950-4	M4	9 mm	50 mm	\$16
R-S-125-4*	M4	12 mm	5 mm	\$12
R-S-1210-4	M4	12 mm	10 mm	\$13
R-S-1215-4	M4	12 mm	15 mm	\$16
R-S-1220-4*	M4	12 mm	20 mm	\$15
R-S-1225-4	M4	12 mm	25 mm	\$14
R-S-1250-4	M4	12 mm	50 mm	\$17



R-S-2550-6



R-S-920-4




R-S-620-4*

M6 standoffs

Part number	Thread	Diameter	Height	Price
R-S-610-6*	M6	6 mm	10 mm	\$12
R-S-625-6*	M6	6 mm	25 mm	\$13
R-S-95-6*	M6	9 mm	5 mm	\$12
R-S-910-6	M6	9 mm	10 mm	\$10
R-S-915-6	M6	9 mm	15 mm	\$16
R-S-920-6	M6	9 mm	20 mm	\$13
R-S-925-6	M6	9 mm	25 mm	\$13
R-S-1310-6	M6	13 mm	10 mm	\$11
R-S-1315-6	M6	13 mm	15 mm	\$12
R-S-1320-6	M6	13 mm	20 mm	\$11
R-S-1325-6	M6	13 mm	25 mm	\$11
R-S-1350-6	M6	13 mm	50 mm	\$13
R-S-13100-6	M6	13 mm	100 mm	\$20
R-S-13150-6	M6	13 mm	150 mm	\$21
R-S-1910-6	M6	19 mm	10 mm	\$12
R-S-1915-6	M6	19 mm	15 mm	\$13
R-S-1920-6	M6	19 mm	20 mm	\$12
R-S-1925-6	M6	19 mm	25 mm	\$12
R-S-1950-6	M6	19 mm	50 mm	\$15
R-S-19100-6	M6	19 mm	100 mm	\$16
R-S-19150-6	M6	19 mm	150 mm	\$22

M6 standoffs continued

Part number	Thread	Diameter	Height	Price
R-S-2515-6	M6	25 mm	15 mm	\$18
R-S-2520-6	M6	25 mm	20 mm	\$14
R-S-2525-6	M6	25 mm	25 mm	\$15
R-S-2550-6	M6	25 mm	50 mm	\$16
R-S-25100-6	M6	25 mm	100 mm	\$18
R-S-25150-6	M6	25 mm	150 mm	\$25
R-S-3825-6	M6	38 mm	25 mm	\$28
R-S-3850-6	M6	38 mm	50 mm	\$30
R-S-38150-6	M6	38 mm	150 mm	\$43



* Does not have a threaded top.

M4 standoffs are made of aluminum. M6 standoffs are made of steel.

Delrin® standoffs

To elevate and locate a part using a non-marring material.


Part number	Thread	Diameter	Height	Price
R-SD-610-4	M4	6 mm	10 mm	\$13
R-SD-910-4	M4	9 mm	10 mm	\$15
R-SD-1210-4	M4	12 mm	10 mm	\$16
R-SD-925-6	M6	9 mm	25 mm	\$15
R-SD-1325-6	M6	13 mm	25 mm	\$14
R-SD-1925-6	M6	19 mm	25 mm	\$15



Pin standoffs

To elevate and locate a part against a pin.


Part number	Thread	Diameter	Height	A	B	Price
R-SP-610-4	M4	6 mm	10 mm	3.8 mm	2 mm	\$14
R-SP-910-4	M4	9 mm	10 mm	3.8 mm	2 mm	\$14
R-SP-1210-4	M4	12 mm	10 mm	3.8 mm	2 mm	\$14
R-SP-610-6	M6	6 mm	10 mm	3.8 mm	2 mm	\$15
R-SP-910-6	M6	9 mm	10 mm	3.8 mm	2 mm	\$15
R-SP-1325-6	M6	13 mm	25 mm	3.8 mm	3 mm	\$15
R-SP-1925-6	M6	19 mm	25 mm	3.8 mm <td 3 mm	\$26	



Delrin® pin standoffs

To elevate and locate a part against a pin using a non-marring material.

Part number	Thread	Diameter	Height	A	B	Price
R-SPD-910-4	M4	9 mm	10 mm	3.8 mm	2 mm	\$15
R-SPD-1325-6	M6	13 mm	25 mm	3.8 mm	3 mm	\$15



2-way spring-loaded pin

For locating within a hole or slot of a part.


Part number	Thread	Diameter	Height	A	B	Adjustment	Price
R-S-1350-2W-6	M6	13 mm	50 mm	2 mm	9 mm	12.5 mm	\$121
R-S-2550-2W-6	M6	25 mm	50 mm	7 mm	19 mm	12.5 mm	\$113



4-way spring-loaded pin

For locating within a hole or slot of a part.

Part number	Thread	Diameter	Height	A	B	Adjustment	Price
R-S-1350-4W-6	M6	13 mm	50 mm	2 mm	9 mm	12.5 mm	\$109
R-S-2550-4W-6	M6	25 mm	50 mm	7 mm	19 mm	12.5 mm	\$103




Standoff adaptor

For step clamps and calibration sphere.

Part number	Thread	Diameter	Height	A	Price
R-SA-6-4	M4	16 mm	15 mm	M6	\$15
R-SA-4-6	M6	9 mm	15 mm	M4	\$15
R-SA-8-6	M6	25 mm	25 mm	M8	\$17



R-SA-6-8




Rotator standoff

To secure parts against stops/supports.

Part number	Thread	Diameter	Height	Adjustment	Price
R-SR-2525-6	M6	25 mm	25 mm	19 mm	\$67



R-SR-2525-6




Towers

Tower

To hold a part vertically.

Part number	Thread	Height	A	B	C	Threaded rows	Price
R-T-25150-6	M6	150 mm	127 mm	25 mm	25 mm	1	\$166

Included: socket head cap screws.



R-T-25150-6

Tower block with base


For positioning a component vertically to the part set-up. Can be used without the base to allow full rotation.

Part number	Thread	Height	A	B	C	D	Price
R-TB-1619-4	M4	26 mm	41 mm	16 mm	16 mm	15 mm	\$66
R-TB-2025-6	M6	35 mm	70 mm	20 mm	20 mm	35 mm	\$70

Included: socket head cap screws.



R-TB-2025-6



Trays

Medium component tray

For holding and organizing components.

Part number	Thread	Height	Depth	Width	Price
R-TC-500200	M6/M8	25 mm	500 mm	200 mm	\$152



R-TC-500200

Small component tray

For holding and organizing components.

Part number	Thread	Height	Depth	Width	Price
R-TC-300190-4	M4	25 mm	300 mm	190 mm	\$138
R-TC-300190-6	M6	25 mm	300 mm	190 mm	\$148



R-TC-300190-4

Component storage box

10-compartment box to hold and organize components.

Part number	Height	Depth	Width	Price
R-BC10	45 mm	203 mm	152 mm	\$15



R-BC10


Portable laser measurement and calibration



XM-60 multi-axis calibration system

Used for comprehensive accuracy and performance measurement of any machine or system.

Linear measurement range	4 meters
Linear measurement accuracy	±0.5 ppm
Laser frequency accuracy	±0.05 ppm
Resolution	1 nm
Maximum travel velocity	1 m/s



Part number: A-5103-3600

Price: \$123,806



- 1 Laser unit
- 2 Launch unit
- 3 Receiver unit
- 4 Beam shroud
- 5 90 degree bracket
- 6 Receiver batteries
- 7 Battery charger
- 8 Magnetic base
- 9 Clamp block
- 10 M8 pillars
- 11 Spirit level
- 12 Software kit
- 13 Cable clamp

Note: In addition to the parts shown above, the kit will also contain required cables and product quality documentation.

Contents of base XM-60 system case

Components and accessories

Fixture kit

- Includes: 1 Range of extrusions
2 Lathe adaptor
3 Steel mounting plate
4 Extrusion alignment aids
5 Extrusion connectors
6 Magnets
7 Allen drivers

Part number: A-5103-4620

Price: \$3,218



XM power supply kit

Part number: A-5103-4370

Price: \$193



XM battery tray

For holding the battery in the receiver unit of the XM systems.

Part number: A-5103-4480

Price: \$657



Cable clip

For holding the fiber optic cable between the laser and launch units of the XM systems.

Part number: A-5103-4340

Price: \$300



Vertical mount pin kit

These pins are used to give a rough starting alignment along the axis when attaching the laser to the mounting plate.

Part number: A-5103-4664

Price: \$90



Receiver beam shroud

Part number: A-5103-4330

Price: \$59



System case

Part number: A-5103-4360

Price: \$1,330



Mounting pillar

Part number: M-8003-0470

Price: \$94



Spirit level circular

Part number: A-9908-0323

Price: \$33



Clamp block

Part number: A-8003-0262

Price: \$263



Magnetic base

Suitable for mounting optics and XL-80 laser head when fitted with A-9908-0760 magnetic base adaptor (sold in pairs).

Part number: A-9908-0780

Price: \$78



Battery Li-Polymer 3.7 V

High-power rechargeable lithium battery (three batteries supplied with each XR20-W).

Part number: A-9920-0330

Price: \$99



Battery charger and cables

Battery charger and a set of power cables for any territory (UK, Europe and USA).

Price: \$236





USB cable

Part number: A-9908-0286

Price: \$29



QC20-W wireless ballbar



QC20-W ballbar kit with glass calibrator

The Renishaw QC20-W ballbar contains a precision linear transducer of Renishaw's own design. Signal processing is carried out within the ballbar and data transmitted to a suitable PC using a Bluetooth® Class 2 module.

- Includes:
- QC20-W wireless ballbar (and one CR2 battery)
 - Center pivot
 - Tool cup
 - Extension bars – 50 mm, 150 mm and 300 mm
 - Glass calibrator
 - System software (including manuals)
 - Setting ball
 - Machine validation cards
 - Calibration certificate
 - Bluetooth® adaptor
 - System carry case (the case includes cut-outs for the optional small circle and VTL adaptors)



Part number: A-8014-1510

Price: \$10,478

QC10 trade-in for QC20-W

A complete working QC-10 kit can be traded in to obtain this special price on a complete QC20-W kit.

Part number: A-8014-BB-TRADEIN

Price: \$7,038

QC20-W ballbar upgrade kit

The lowest cost entry to QC20-W use is with the QC20-W upgrade kit. The kit includes a new ballbar, battery and BB20 software. The packaging fits directly into the later style aluminum framed case. Users with earlier plastic or wooden cases should purchase a new QC20-W case separately (see below).

- Includes:
- QC20-W wireless ballbar upgrade kit
 - QC20-W wireless ballbar
 - Tool cup
 - System software (including manuals)
 - Setting ball
 - Machine validation cards
 - Calibration certificate
 - Foam tray (fits aluminum QC10 case only)
 - Partial arc test kit
 - Bluetooth® adaptor
 - 2nd spare battery



Part number: A-8014-BBUG

Price: \$4,793

QC20-W system carrying case

The new QC20-W case has dedicated locations to carry the small circle accessory kit and VTL, and is lockable.

Part number: M-8014-1600

Price: \$357



Small circle accessory kit (SCAK)

The small circle accessory kit is used with the QC20-W ballbar to allow tests with a radius of 50 mm. The existing QC10 small circle accessory kit (SCAK) cannot be used with the QC20-W. The SCAK includes a 50 mm glass calibrator, calibration certificate and the small circle adaptor, which is supplied with an additional center ball already fitted.

If you already use the QC10 SCAK, just purchase the new adaptor, which is a simple screw mount to the QC20-W body. You can retain your existing 50 mm glass calibrator (see QC20-W spare parts overleaf).

Part number: A-8014-1540

Price: \$999



VTL adaptor kit

The VTL adaptor is available for 2-axis CNC applications. This replaces the "tool cup" in the standard set-up and gives restricted movement of the center cup in a single axis, enabling typical 2-axis machines such as vertical turning lathes and laser cutting machines etc to benefit from QC20-W ballbar diagnosis.

Part number: A-8014-0417

Price: \$326



Lathe adaptor kit

The lathe adaptor kit allows you to perform 360°, 100 mm radius ballbar tests on a lathe. The kit consists of an arm assembly for attachment to the lathe turret and a spindle bar for attachment in the lathe spindle. Both arm and spindle include magnetic cups in which to locate the ballbar.

- Includes:
- Lathe adaptor arm assembly
 - Spindle bar assembly
 - Spherical adaptor
 - Center cup
 - Cup screw (with magnetic cup)
 - 5 mm long-arm hex key
 - 3 mm hex key
 - Set of user instructions
 - Plastic carrying case

Part number: A-8014-0551

Price: \$1,195



Ballbar TRACE Kit *

Ballbar TRACE is a new, time-based software package for the QC20-W ballbar. The software is free of charge to existing QC20-W users. The flexibility of Ballbar TRACE opens up QC20-W for many new applications, including 5-axis ballbar verification to ISO10791-6 and static monitoring.

TRACE Kit with 25 mm straight shank *

Part number: TRACE-1003 Price: \$951

TRACE Kit with 1/2 in straight shank *

Part number: TRACE-1004 Price: \$951

TRACE Kit with 1 in straight shank *

Part number: TRACE-1007 Price: \$951



Ballbar TRACE individual parts

Ballbar centering device

Used to center the pillar/tool cup on the spindle for performing Ballbar TRACE measurements.

Part number: S-8BBR-0052 Price: \$150



Tool kit

For adjusting the ballbar centering device.

Part number: A-4071-0060 Price: \$10



Mounting pillar

For extending the tool cup down from the spindle.

Part number: M-8003-0470 Price: \$94



Straight shank

Used to help mount centering device in the spindle.

25 mm Part number: A-5625-1003 Price: \$218

1/2 in Part number: A-5625-1004 Price: \$218

1 in Part number: A-5625-1007 Price: \$218



* TRACE Kits vary only by accompanying shank. If multiple shanks are desired, order a single kit and the extra shanks individually.

QC20-W ballbar system spare parts



Item	Description	Part number
1	QC20-W ballbar assembly (including balls)	Only available as RBE
2	QC20-W system carrying case (not fully shown)	M-8014-1600
3	Transducer ball	A-8014-0182
4	Center cup	A-8014-0522
5	Center ball	A-8014-0141
6	Cover ring	A-8014-1592
7	Center pivot assembly	A-8014-1281
8	50 mm extension bar	A-8014-0231
9	150 mm extension bar	A-8014-0144
10	300 mm extension bar	A-8014-0145
11	Tool cup assembly	A-8014-0521
12	Setting ball	A-8014-1570
13	Tool cup extension	A-8014-1610
14	Glass calibrator	A-8014-0280
15	Spanner set	A-8014-1141
16	Lithium battery	A-8014-CR2
17	Battery end cap assembly	A-8014-1593
Not shown	Getting started DVD	A-8014-1285
Not shown	Validation card (minimum order quantity 10)	A-8014-VCAR
Not shown	Validation card holder (minimum order quantity 10)	A-8014-VCHD
Not shown	Ballbar20 software upgrade	A-8014-0717
Not shown	Cup cleaning kit	A-8014-0423

Small circle accessory kit

Item	Description	Part number
18	50 mm glass calibrator	A-8014-0491
19	Small circle adaptor	A-8014-1560

VTL adaptor kit

Item	Description	Part number
20	VTL adaptor kit	A-8014-0417

Lathe kit (cannot be stored in system case)

Item	Description	Part number
Not shown	Cup screw assembly	A-8014-0552
Not shown	Spindle bar assembly	A-8014-0553

QC20-W spare parts continued

Glass calibrator

A glass calibrator is supplied with all QC20-W kits and is used to calibrate the length of a ballbar. This type of calibrator is manufactured from a material which has a temperature expansion coefficient of almost zero.

Part number: A-8014-0280

Price: \$2,180



Cover ring

The cover ring needs to be removed from the QC20-W body before attaching the small circle adaptor.

Part number: A-8014-1592

Price: \$26



Tool cup assembly

The condition of the phosphor bronze bearings in the tool cups affects the errors measured by the transducer. Tool cups cannot be repaired (if they are damaged they must be replaced).

Part number: A-8014-0521

Price: \$140



Tool cup extension

The tool cup extension will provide the required clearances for conducting a vertical 220° partial arc test on a machine, for collet sizes up to ER40 (63 mm diameter collet nut). It has two different outer diameters, the smaller diameter is 12 mm and the larger diameter is ½ inch, to suit different collets.

Part number: A-8014-1610

Price: \$45



Transducer ball

If a ball joint is dropped onto a hard surface, the ball sphericity may be affected, which will add to the errors measured by the ballbar system. If this happens, discard the ball joint and replace it with a new one, using the special spanner provided.

Part number: A-8014-0182

Price: \$155



Battery end cap assembly

The battery end cap assembly is supplied with a center ball already fitted.

Part number: A-8014-1593

Price: \$220



Center ball

If a ball joint is dropped onto a hard surface, the ball sphericity may be affected, which will add to the errors measured by the ballbar system. If this happens, discard the ball joint and replace it with a new one.

Part number: A-8014-0141

Price: \$155



Center pivot assembly

The magnetic center pivot assembly has a clamping mechanism that can be locked/unlocked by pulling the lever to the horizontal/vertical position. The center pivot assembly is supplied with a center cup fitted.

Part number: A-8014-1281

Price: \$523



Center cup

The condition of the phosphor bronze bearings in the center cups affects the errors measured by the transducer. Center cups cannot be repaired (if they are damaged they must be replaced).

Part number: A-8014-0522

Price: \$175



Setting ball

The setting ball is placed into the center mount cup when setting the zero coordinates for a test.

Part number: A-8014-1570

Price: \$53



Extension bars

By assembling the ballbar with different combinations of extension bars, it is possible to carry out ballbar tests with 100, 150, 250, 300, 400, 450, 550 or 600 mm radii.

Length 50 mm

Part number: A-8014-0231

Price: \$212

Length 150 mm

Part number: A-8014-0144

Price: \$255

Length 300 mm

Part number: A-8014-0145

Price: \$345



Spanner set

The C spanners can be used to ensure the screw joints on the ballbar (including any extension bars) are not loose and the screw joints on the tool cup extension (if used) are tight. The battery end cap spanner is designed to securely hold the battery end cap when unscrewing the center ball.

Part number: A-8014-1141

Price: \$18



QC20-W spare parts continued

Spherical adaptor

This adaptor is for use with the lathe kit to set in as the stationary cup.

Part number: A-8014-1565

Price: \$69

30 mm small circle adaptor

Used to run a ballbar test with a 30 mm radius. The ballbar is still physically 130 mm in length but the measurement is happening between the 30 mm section provided by the adaptor.

Part number: A-8014-1272

Price: \$219



Validation card

Double-sided card for recording ballbar test results and displaying on the tested machine (insert into card holder below).

Note: Pack of 10.

Part number: A-8014-VCAR

Price: \$6



Validation card holder

Plastic wallet with self-adhesive back to attach to the machine.

Note: Pack of 10.

Part number: A-8014-VCHD

Price: \$6

Cup cleaning kit

The tool cups are magnetic and may attract steel swarf and chips into the cup during use. Clear any swarf from the cups before storing them away with the cleaning kit.

Part number: A-8014-0423

Price: \$20



50 mm glass calibrator (small circle accessory kit)

The 50 mm glass calibrator includes a calibration certificate.

Part number: A-8014-0491

Price: \$731



Small circle adaptor (small circle accessory kit)

The small circle adaptor is supplied with an additional center ball already fitted. The adaptor is a simple screw fitting to the main ballbar body.

Part number: A-8014-1560

Price: \$316



Spindle bar assembly (lathe adaptor kit)

The spindle bar assembly is fitted with a clamp holder and clamp.

Part number: A-8014-0553

Price: \$318



Cup screw assembly (lathe adaptor kit)

The cup screw assembly is supplied with a center cup already fitted.

Part number: A-8014-0552

Price: \$171



Bluetooth® USB wireless adaptor

Provides Windows PC with Bluetooth® communications capability.
Tested and compatible with QC20-W.

Part number: A-8014-BTA1

Price: \$102

Lithium battery for QC20-W

CR2 lithium battery.

Part number: A-8014-CR2

Price: \$9

Machine checking gage

The Renishaw MCG is designed for rapid, volumetric accuracy evaluation for CMMs. The gage takes account of variations due to probe, machine and software errors.

Measuring range: Vertically: $\pm 45^\circ$
Horizontally: 360°
Total gage error: $\pm 0.5 \mu\text{m}$

Two kits are available, each supplied in a hardwood box.

MCG1 – small kit

Suitable for machines up to 40 in (1000 mm) cubed.

Part number: A-1007-0006 **Price:** \$3,444

MCG2 – large kit


Suitable for machines larger than 40 in (1000 mm) cubed.

Part number: A-1007-0056 **Price:** \$4,318



MCG spares and accessories

Description	Part number	MCG1	MCG2	Price
SA3-M3/M2 stylus adaptor	M-5000-4163	*	*	\$14
SE2-20 mm stylus extension	M-5000-3592	*	*	\$15
SE7-5 mm stylus extension	M-5000-7634	*	*	\$12
Pivot	A-1007-0017	*	*	\$321
Special stylus	A-5000-7650	*	*	\$88
101 mm arm	A-1007-0007	*	*	\$630
151 mm arm	A-1007-0008	*	*	\$659
226 mm arm	A-1007-0009	*	*	\$689
380 mm arm	A-1007-0010	*	*	\$724
532 mm arm	A-1007-0011		*	\$770
685 mm arm	A-1007-0012		*	\$830
76 mm pillar	M-1007-0023	*	*	\$75
127 mm pillar	M-1007-0024	*	*	\$155
235 mm pillar	M-1007-0025		*	\$197
Baseplate	A-1007-0061	*	*	\$517
Additional weights	A-1007-0018	*	*	\$26



XL laser calibration system

Used for comprehensive accuracy and performance measurement of any machine or system.


Linear measurement range	80 meters
Linear measurement accuracy	±0.5 ppm
Laser frequency accuracy	±0.05 ppm
Resolution	1 nm
Maximum travel velocity	4 m/s
Dynamic capture rate	10 Hz – 50 kHz



Contents of base XL system case

XL laser system components

Kit part number	Kit price	Includes	Part number	Price	Index
A-9908-0405	\$14,600	XL-80 laser	N/A		1A
		Universal power supply	A-9908-0299	\$163	1B
		USB cable	A-9908-0286	\$29	1C
		XL system support disk	A-9908-0303	No charge	Not shown
		AUX I/O connector	A-9908-0329	\$45	Not shown
		Laser Capture and Analysis software	A-9925-0201	\$1,839	Not shown
A-9908-0700	\$1,028	XL translation stage	A-9908-0700	\$1,028	2A
		Spirit level circular	A-9908-0323	\$33	2B
		Tripod adaptor	A-9908-0770	\$32	Not shown
A-9908-0510	\$9,624	XC-80 compensator	A-9908-0564	\$8,001	3A
		Material temperature sensor and cable	A-9908-0879	\$1,388	3B
		Air temperature sensor and cable	A-9908-0878	\$1,388	3C
		XC mounting plate	A-9908-0892	\$124	3D
		USB cable	A-9908-0286	\$29	3E
A-8003-0440	\$3,316	Linear reflector (qty 2)	A-8003-0219	\$680 each	4A
		Linear interferometer	A-8003-0557	\$2,631	4B
		Alignment target (qty 2)	A-8003-0478	\$25 each	4C
A-8003-0441	\$4,415	Angular interferometer	A-8003-0186	\$2,724	5A
		Angular reflector	A-8003-0181	\$2,020	5B
		Alignment target (qty 2)	A-8003-0478	\$25 each	5C
A-8003-0443	\$5,927	Short range straightness reflector	A-8003-0615	\$3,889	6A
		Woollaston short range	A-8003-0393	\$3,300	6B
A-8003-0444	\$5,927	Long range straightness reflector	A-8003-0620	\$3,889	7A
		Woollaston long range	A-8003-0430	\$3,301	7B
A-8003-4209	\$841	Straightness shutter	A-8003-4209	\$841	8A
A-8003-STAK	\$3,691	Laser beam steerer LS350	A-8003-3072	\$1,720	14
		Fixed turning mirror	A-8003-1325	\$942	8B
		Large straightness retroreflector	A-8003-0604	\$1,093	8C
		Straightness base	A-8003-0576	\$312	8D
A-8003-0665	\$5,927	Optical square	N/A		9A
		Bracket squareness optic	M-8003-1680	\$44	9B
A-8003-0442	\$3,569	Flatness mirror (qty 2)	A-8003-0630	\$1,390 each	10A
		Base (150 mm)	A-8003-0256	\$367	10B
		Base (100 mm)	A-8003-0257	\$358	10C
		Base (50 mm)	A-8003-0258	\$326	10D
A-8003-4270	\$3,263	Long range retroreflector	A-8003-2061	\$2,308	11A
		Periscope	A-8003-2039	\$2,005	11B
		Long range target	M-8003-2081	\$32	11C
		Clamp screw (qty 2)	M-8003-0221	\$15 each	11D
A-8003-0447	\$1,350	Clamp block (qty 2)	A-8003-0262	\$263 each	12A
		Base plate (qty 2)	A-8003-0522	\$277 each	12B
		Mounting pillar (qty 3)	M-8003-0470	\$94 each	12C
		M8 adaptor	A-8003-0979	\$118	12D
		XL-80Q quad laser head	A-9908-0455	\$15,841	Not shown
		Base case	M-9908-0313	\$811	
		Full system case	M-9908-0314	\$1,137	
		Tripod	A-9908-0295	\$1,329	Not shown
		Tripod case	M-9908-0527	\$256	Not shown
		Swivel mirror	A-8003-1304	\$1,451	13
		Fixed turning mirror	A-8003-1325	\$942	15
		Magnetic base (qty 2)	A-9908-0780	\$78	16
Magnetic base adaptor	A-9908-0760	\$37	17		



Contents of full XL system case (tray)



Contents of full XL system case (tray removed)

XL laser calibration systems

Base system kit

Includes: XL-80 laser head
XC-80 environmental compensator kit
LaserXL™ software
Software support disk
XL tripod stage kit

Part number: XL80-BASE

Price: \$25,252



XL-80 laser head

Linear system kit

Includes:	Components of base system kit	XL80-BASE
	Linear measurement optics	A-8003-0440
	Beam steerer LS350	A-8003-3072
	Optics mounting kit	A-8003-0447
	2 magnetic bases	A-9908-0780
	Magnetic base adaptor	A-9908-0760
	Tripod	A-9908-0295
	Tripod case	M-9908-0527
	Base system case	M-9908-0313

Part number: A-9908-LIN1

Price: \$34,149



XC-80 environmental compensation unit

Linear/angular system kit

Includes:	Components of base system kit	XL80-BASE
	Linear measurement optics	A-8003-0440
	Angular measurement optics	A-8003-0441
	Beam steerer LS350	A-8003-3072
	Optics mounting kit	A-8003-0447
	2 magnetic bases	A-9908-0780
	Magnetic base adaptor	A-9908-0760
	Tripod	A-9908-0295
	Tripod case	M-9908-0527
	Base system case	M-9908-0313

Part number: A-9908-ANG1

Price: \$38,564



XL system case and tripod case

Advanced system kit

Includes:	Components of base system kit	XL80-BASE
	Linear measurement optics	A-8003-0440
	Angular measurement optics	A-8003-0441
	Swivel mirror	A-8003-1304
	Long range straightness optics	A-8003-0444
	Short range straightness optics	A-8003-0443
	Straightness accessory kit	A-8003-STAK
	Straightness shutter	A-8003-4209
	Squareness measurement kit	A-8003-0665
	Optics mounting kit	A-8003-0447
	2 magnetic bases	A-9908-0780
	Magnetic base adaptor	A-9908-0760
	Tripod	A-9908-0295
	Tripod case	M-9908-0527
	Full system case	M-9908-0314

Part number: A-9908-ADV1

Price: \$60,934

ML-10 to XL-80 upgrade

Includes: Components of base system kit XL80-BASE

- XL-80 laser head
- XC-80 environmental compensator kit
- LaserXL™ software
- Software support disk
- XL tripod stage kit

Additional parts that are not included but recommended for transportation and mounting purposes are:

- Base system case M-9908-0313
- or
- Full system case M-9908-0314
- and
- ML-XL tripod adaptor A-9908-0765

Traded-in system must include the ML10 and EC10 with an air and material sensor. A non-working unit has a surcharge of \$1,500.

Part number: SYS-XL-UPG **Price:** \$18,939

General laser interferometer system to XL-80 upgrade

Includes: Components of base system kit XL80-BASE

- XL-80 laser head
- XC-80 environmental compensator kit
- LaserXL™ software
- Software support disk
- XL tripod stage kit

Additional parts that are not included but recommended for transportation and mounting purposes are:

- Base system case M-9908-0313
- or
- Full system case M-9908-0314

- Universal tripod A-9908-0295
- Universal tripod case M-9908-0527
- Magnetic bases A-9908-0780
- XL Magnetic base adaptor A-9908-0760

Traded-in system must include the ML10 and EC10 with an air and material sensor. A non-working unit has a surcharge of \$1,500.

Part number: SYS-XL-UG2 **Price:** Call for pricing

Optics

All Renishaw optics housings are lightweight aluminum with a hard anodized finish for durability and good thermal stability.

Linear kit (standard 40 m)

Includes: 1 linear beam splitter
2 linear reflectors
2 alignment targets

Part number: A-8003-0440

Price: \$3,316



Small linear accessory kit

Please call for details.

Part number: A-8003-3244

Price: \$1,824




Long range linear optics kit (80 m max)

For use with the ML10X for linear measurements in excess of 40 m.

Includes: Periscope
Large retroreflector

Part number: A-8003-4270

Price: \$3,263



Angular kit

Includes: 1 angular beam splitter
1 angular reflector
2 alignment targets

Part number: A-8003-0441

Price: \$4,415



Linear/angular combination kit

This combination kit is a cost-saving solution, allowing linear and angular measurement to be made with a single set-up.

Includes: 1 angular beam splitter
1 angular reflector
1 linear reflector
2 alignment targets

Part number: A-8003-2774

Price: \$5,050



Straightness measurement kits

Short range

Suitable for measurements up to 4 m (160 in)

Part number: A-8003-0443

Price: \$5,927

Long range

Suitable for measurements from 1 m to 30 m (40 in to 1200 in)

Part number: A-8003-0444

Price: \$5,927



Straightness accessory kit

Facilitates measurements on vertical axes and in other difficult configurations.

- Includes:
- 1 fixed turning mirror
 - 1 large retroreflector
 - 1 stainless steel base
 - 1 LS350 beam steerer

Note: XL-80 and ML10 users require straightness shutter, part number A-8003-4209, shown on page 4-8.

Part number: A-8003-STAK

Price: \$3,691



Squareness measurement

This precision pentaprism is used in conjunction with straightness optics to measure squareness of machine axes. It includes a mounting bracket for a fixed turning mirror and LS350 beam steerer.

Part number: A-8003-0665

Price: \$5,927



Flatness measurement kit

The turning mirrors rotate and tilt for easy alignment and are fitted with non-slip pads. The lightweight aluminum bases have precision stainless feet and guides.

- Includes:
- 2 turning mirrors
 - 1 50 mm flatness base
 - 1 100 mm flatness base
 - 1 150 mm flatness base

Part number: A-8003-0442

Price: \$3,569



Standard optics mounting kit

This universal mounting kit is designed for use with the complete range of Renishaw measuring optics.

- Includes:
- 2 mounting blocks
 - 3 stainless pillars
 - 1 stainless M8 adaptor
 - 2 stainless bases

Part number: A-8003-0447

Price: \$1,350



Magnetic base

Suitable for mounting optics and XL-80 laser head when fitted with A-9908-0760 magnetic base adaptor (sold in pairs).

Part number: A-9908-0780

Price: \$78



CMM optics mounting kit

Designed specifically to aid the mounting of laser optics and other accessories on coordinate measuring machines. Recommended for UCC error mapping requirements.

Part number: A-1333-0174

Price: \$848




Beam steerer LS350

This is the best time-saving device a laser system user could buy. It works with all the measuring optic kits, including HP optics using the HP optic adaptor plate. Included in straightness accessory kit.

Part number: A-8003-3072

Price: \$1,720



Swivel mirror

This is used for directing the laser beam through any angle from 0° to 106°, for example for diagonal measurement and slant bed lathes. It works with all the optics kits, including HP optics using the HP optic adaptor plate.

Part number: A-8003-1304

Price: \$1,451



Fixed turning mirror

This can be used with angular optics for 90° accessories. Included in straightness accessory kit.

Part number: A-8003-1325

Price: \$942



Quarter wave plate

Used with linear optics for plane mirror interferometry applications.

Part number: A-8003-1998

Price: \$1,635



Straightness shutter

Required for vertical straightness measurements.

Part number: A-8003-4209

Price: \$841



Pan and tilt adaptor

Adaptor for tripod to allow for easy mounting at an angle and easy swivel adjustment.

Part number: A-9908-1170

Price: \$1,339




Linear diagonal measurement fixture kit

Includes: Custom diagonal plate to attach laser and optics
Mounting post
Heat shield

Laser, optics, clamp blocks and magnetic bases not included.

Part number: S-8LMS-2124

Price: \$1,810



Tripod and cases

Universal tripod

Tripod only, without the stage.

Part number: A-9908-0295

Price: \$1,329



XL translation stage

Part number: A-9908-0700

Price: \$1,028



Tripod adaptor

This allows the XL translation stage to be used with the Renishaw universal tripod or any other tripod with a standard camera mounting thread.

Part number: A-9908-0770

Price: \$32



Tripod converter ML-XL

Part number: A-9908-0765

Price: \$76



Magnetic base adaptor

This allows the XL translation stage to be mounted on any base or fixture with an M8 x 1.25 mounting hole.

Part number: A-9908-0760

Price: \$37



Universal tripod case

Lightweight fabric.

Part number: M-9908-0527

Price: \$256



System cases

Base system case

Suitable for basic laser system including linear and angle optics with accessories.

Part number: M-9908-0313

Price: \$811



Full system case

Suitable for an advanced laser system including linear, angle, short range and long range straightness, squareness and flatness optics with accessories.

Part number: M-9908-0314

Price: \$1,137



TB20 universal kit

Used to activate a trigger based on the signal received from encoders.

- Includes:
- TB20 trigger box
 - XL trigger cable
 - Power supply cable
 - Plug adaptor kit
 - TB20 encoder and controller port connectors
 - Calibration user guide card



Part number: A-8003-4475

Price: \$4,715

TB20 upgrade from TB10

Part number: UPG-TB10-SERV-1

Price: \$3,300

TB20 connector kit

Part number: A-8003-4462

Price: \$144



XL trigger cable

Part number: A-9908-0377

Price: \$433



Power USB cable

Part number: A-9920-0390

Price: \$46



USB power supply

USB power supply adaptors for any territory (UK, Europe and USA).


Part number: A-9920-0450

Price: \$50



Software

XCal-View analysis software



XCal-View is used to comprehensively analyse legacy file formats. Its intuitive user interface makes it a simple but powerful tool for data analysis. The software provides automatic reporting that conforms to many international machine performance checking standards, making compliance simple. Standards include ISO, ASME, VDI, JIS and GB/T and an additional Renishaw analysis to succinctly summarize the result.

XCAL View (single user)

Part number: A-9925-0208 **Price:** \$479


XCAL View (dual user)

Part number: A-9925-0200 **Price:** \$958

XCAL View (10 users)

Part number: A-9925-0203 **Price:** \$3,832

QuickView XL software



QuickView is the simple, intuitive software package that allows you to understand the dynamic performance of many different machines and devices such as stages, machine tools and CMMs. It brings the functionality of an oscilloscope to the mechanical engineer, right on your desktop.

- Capture, review, and save dynamic data
- Measure distance, velocity and acceleration against time
- Display continuous “streaming” data or set trigger levels to capture single or multi-shot “events”
- Linear, angular or straightness modes
- Optional hardware – compact low mass optics kit

Applications

- Measure consistency of position, velocity and acceleration
- Determine movement in a locked rotary axis (torsional vibration)
- Detect dynamic yaw and lateral play (slop)
- Measure vibration
- Perform ASME B5.54 CNC tests such as Feedrate and acceleration, Minimum Block Execution Time (MBET) and Least Increment

Benefits include:

- Live data display allowing analysis of motion and positional characteristics
- Save data for analysis in other applications such as Excel® and MathCad
- Flexible measurement – avoids the need for defined measurement targets and sequences

Part number: A-9908-0302 **Price:** \$1,002

Spare parts

The following items are normally supplied as parts of system kits but can be purchased as individual components for replacement purposes.

Clamp block

Part number: A-8003-0262

Price: \$263



Locking screw assembly

For use with clamp block.

Part number: A-8003-4501

Price: \$53



Locking screw pressure pad

Brass pad and rubber retaining ring.

Part number: A-8003-4500

Price: \$8



Clamp screws

Long (for use with clamp block)

Part number: M-8003-0264

Price: \$15



Short (for use with linear and angular optics)

Part number: M-8003-0221

Price: \$15



LS350 (for use with LS350 beam steerer)

Part number: M-8003-3083

Price: \$15



For use with fixed turning mirror.

Part number: M-8003-1070

Price: \$16



For use with swivel mirror.

Part number: M-8003-1063

Price: \$16



Mounting pillar

110 mm long with M8 × 1.25 male thread at one end, female at the other.

Part number: M-8003-0470

Price: \$94



Straightness accessory base

Part number: A-8003-0576

Price: \$312



Large retroreflector

For use with vertical straightness measurements.

Part number: A-8003-0604

Price: \$1,093



M8 adaptor

Part number: A-8003-0979

Price: \$118



Alignment target

Part number: A-8003-0478

Price: \$25



Linear beam splitter

Part number: A-8003-0557

Price: \$2,631



Linear reflector

Part number: A-8003-0219

Price: \$680



Angular reflector

Part number: A-8003-0181

Price: \$2,020



Angular beam splitter

Part number: A-8003-0186

Price: \$2,724



Cables

XC-80 temperature sensor cable (5 m)

Part number: A-9908-0932

Price: \$145



USB to serial adaptor

Allows QC10 ballbar and other serial devices to be used with notebook PCs that do not have an RS232 serial port.

Part number: A-8014-0670

Price: \$145



USB cable

Part number: A-9908-0286

Price: \$29



Temperature sensor cable connector kit

Part number: A-9904-1636

Price: \$69



Translation stage screws

Part number: A-9908-0750

Price: \$25



XR20-W rotary axis calibrator and components



Portable laser measurement and calibration

5-30

XR20-W rotary axis calibrator

The XR20-W rotary axis calibrator allows the measurement of rotary axis positional accuracy to within 1 arc second. Totally wireless operation and modular mounting systems ensure suitability for a wide range of machines.

- Includes:
- XR20-W
 - Mounting ring
 - Adaptor plate
 - Centration aid
 - Chuck adaptor
 - Battery charger
 - Batteries Li-polymer × 3
 - Electrical adaptor for use in any territory
 - USB cable and mains adaptor
 - Rotary XL software including system manual
 - Peli™ system case

Part number: A-9920-0400

Price: \$23,987



Off Axis Rotary Software (OARS) package

This optional software package enables the XR20-W to be used on machines where it is difficult or impossible to mount the device on the center of rotation.

Please note: Additional mounting hardware may be required for some machines. Please contact Renishaw for further information.

Part number: A-9920-0304 **Price:** \$1,319


OARS bracket

Part number: A-9920-0700 **Price:** \$3,606

Complete OARS kit

Includes bracket, OARS software and carrying case.

Part number: OARS-KIT1 **Price:** \$4,713



XR20-W rotary axis calibrator upgrade

Part number: XR20W-UPG **Price:** \$15,592

NOTE: The standard trade-in allowance quoted is on the basis that a complete and fully functional RX10 kit is returned. Non-functional, damaged or incomplete kits may be considered for trade-in at Renishaw's discretion. If accepted, the trade-in allowance will be reduced.

Rotary software kit

Part number: A-9925-0202 **Price:** \$1,571

XR20-W kit components

Mounting ring

The mounting ring bolts or clamps directly to the test surface for ease of centring the system on the test axis.

Part number: A-9920-0440 **Price:** \$615



Mounting ring adaptor 150 mm

The adaptor plate enables fitting to rotary tables with unsuitable center recesses. It can also be used to secure the XR20-W to the chuck adaptor and custom mounts.

Part number: A-9920-0270 **Price:** \$385



Chuck (lathe) adaptor

The adaptor has a 40 mm diameter to fit most popular chuck sizes. It can also be used to secure the XR20-W to users' own custom mounts.

Part number: A-9920-0280 **Price:** \$512



Centration aid

The centration aid fits temporarily inside the mounting ring to assist visual centration before XR20-W insertion.

Part number: A-9920-0340 **Price:** \$10



Fixings kit

A complete set of screws and allen keys for XR20-W.

Part number: A-9920-0430 **Price:** \$10



Battery Li-Polymer 3.7 V

High-power rechargeable lithium battery (three batteries supplied with each XR20-W).

Part number: A-9920-0330 **Price:** \$99



Battery charger and cables

Battery charger and a set of power cables for any territory (UK, Europe and USA).

Part number: A-9920-0320 **Price:** \$236



Battery cover

Replacement battery cover for XR20-W.

Part number: A-9920-0460 **Price:** \$35



USB cover plug

Replacement protective plug for USB socket on XR20-W.

Part number: A-9920-0380 **Price:** \$8



USB power supply

USB power supply adaptors for any territory (UK, Europe and USA).

Part number: A-9920-0450 **Price:** \$50



XR20 case

Heavy duty transport and storage case for XR20-W.

Part number: A-9920-0360 **Price:** \$786



Training

Renishaw offers world class training at their modern facilities in Hoffman Estates, Illinois, only 45 minutes from Chicago's O'Hare airport. Regular classes are held once per month for both laser and ballbar product groups. In-house courses start on Tuesday morning and conclude around midday on the Friday. The training includes a mix of classroom work and hands-on experience in the Renishaw technology center where we have a selection of modern machines for students to work with. If you have a large group, or prefer not to travel, on-site training is also available.

Information on training classes and class schedules can be found on the web at www.renishaw.com/training-usa.

Our standard, in-house training courses cover the following subjects:

- The 21 degrees of freedom
- Accuracy and the environment
- Relative thermal behaviour
- Machine geometry and design
- Determining relative errors
- Interpreting analysis data
- Troubleshooting set-up and machine errors
- Machine tool part programs
- Hardware set-up procedure
- Software set-up and data capture
- Correcting errors on the machine

Two basic training courses are offered:

Learning practical laser interferometry

In addition to the standard metrology subjects, the laser class will cover the following aspects:

- Laser interferometry theory
- Laser kit parts identification
- Current laser technology
- Linear, angular and straightness measurements
- Cosine, deadpath and Abbé errors
- Error compensation
- Using the laser as a diagnostic tool
- Implementing maintenance programs
- Accessories for the laser

Part number: A-8003-LATC **Price:** \$1,728

One-day hands-on ballbar training at Vincennes University

Part number: A-8003-BBVU **Price:** \$510



Using and understanding the QC20-W ballbar and machine metrology

The comprehensive course provides students with a detailed understanding of the most powerful machine tool diagnostic device you can buy.

Specialist features of the course include:

- Why buy a ballbar?
- When to use a ballbar
- Ballbar theory
- Ballbar kit parts identification
- Ballbar accessories

Training materials, lunch and refreshments are provided each day.

Part number: A-8003-BBTC **Price:** \$1,728

Advanced training at Renishaw Inc

Charged per student, per day

Part number: A-8003-0008 **Price:** \$799

Training on-site at customer's premises (1-2 days)

Part number: T-2000-1080-S **Price:** \$6,157

Training on-site at customer's premises (4 days)

Part number: T-2000-1081-S **Price:** \$10,261

Additional day's training on-site at customer's premises

Part number: A-8003-0006 **Price:** \$2,052

Calibration rentals

All rentals require the creation of a rental agreement that must be sent in with the purchase order.

XL-80 linear rental

Rental system including everything listed in the linear system kit.

Part number: XL80-BASE-RENTAL-US

Price: \$1,708/week

XL-80 linear and angular rental

Rental system including everything listed in the linear/angular system kit.

Part number: XL-80-LNAN-RENTAL-US

Price: \$1,929/week

XR20-W rental with angular beam splitter

Part number: XR20W-RENTAL-US

Price: \$1,334/week

Non-contact position encoders



Absolute position optical encoders

RESOLUTE™ absolute linear and rotary encoder range

- RELA ZeroMet™ spar scale 6-10
- RSLA stainless steel spar scale 6-11
- *FASTRACK*™ carrier-type scale system with RTLA stainless steel ribbon scale (plus RTLA-S self-adhesive version) 6-12
- RESA angle encoder scale 6-13
- REXA angle encoder scale 6-14



Incremental position optical encoders

ATOM™ miniature linear and rotary encoder

- ATOM series readhead 6-15
- RTLF stainless steel ribbon scale 6-16
- RCLC glass scale 6-16
- RCDM angle encoder scale 6-16



RG2 20 µm pitch linear encoder range

- RGH22 series readhead 6-17
- RGH24 series readhead 6-18
- RGH25F series readhead 6-19
- RGS20 and RGS40 gold scale 6-20



RG2 20 µm pitch rotary encoder range

- RGH20 and RGH20F series readhead 6-22
- RESR angle encoder scale 6-23



Ultra-high vacuum (UHV) encoder range

- RESOLUTE UHV, TONiC™ UHV, RGH25F UHV and RGH20F UHV readheads 6-24



RG4 40 µm pitch linear and rotary encoder range

- RGH34 series readhead 6-26
- RGH40 series readhead 6-27
- RGH41 series readhead 6-28
- RGH45 series readhead 6-29
- RGS40-G glass scale 6-30
- *FASTRACK* carrier-type scale system with RTLr stainless steel ribbon scale (plus RTLr-S self-adhesive version) 6-31



•VIONiC™ encoder range

- VIONiC encoder system 6-32

TONiC™ encoder range

- TONiC encoder system 6-34
- TONiC DOP (dual output) encoder system 6-36
- RGSZ20 gold scale 6-38



SiGNUM™ encoder range

- SiGNUM series readhead 6-40
- SiGNUM with FANUC serial interface 6-42



VIONiC, TONiC and SiGNUM linear and rotary scale range

- RELM linear ZeroMet™ scale 6-44
- RSLM linear stainless steel scale 6-45
- RTALC high-accuracy incremental linear encoder scale system 6-46
- RESM angle encoder scale 6-48
- RESD distance-coded scale 6-49
- REXM / REXT ultra-high accuracy angle encoder 6-50



Accessories

- Interpolators, interfaces and DROs 6-51
- Scale applicators 6-51
- Custom solutions 6-51



Magnetic encoders

- Rotary magnetic encoders 6-53
- Linear and ring magnetic encoders 6-60



RLE laser interferometer systems

- RLD detector units 6-65
- RLE system benefits 6-65
- RCU10 compensation system 6-66
- RPI parallel interface 6-66
- HS20 laser head 6-67



Welcome

Renishaw offers a wide range of compact magnetic and optical encoders to meet the diverse requirements of industrial automation. This section details an extensive selection of robust magnetic linear, ring and rotary encoders, optical incremental linear and rotary encoders, laser interferometers and our range of optical true-absolute linear and rotary encoders.

Renishaw's optical encoder systems are based on an innovative non-contact arrangement which provides zero mechanical hysteresis and excellent metrology, yet can withstand a variety of contaminants such as dust, light oils and scratches without compromising signal integrity. This ensures customers' machines run reliably with little or no maintenance.

Highlights in Renishaw's range are the VIONiC™ ultra-high accuracy, all-in-one digital incremental encoder (see page 6-32), the ground-breaking RESOLUTE™ absolute encoder (see page 6-6) and the miniature ATOM™ incremental encoder (see page 6-15). RESOLUTE features single track technology, a completely unique mode of operation and performance that defies convention, and is a world-leading product that defines Renishaw's commitment to unrivaled innovation in encoder development. ATOM uniquely combines miniaturization with leading-edge dirt immunity, signal stability and reliability. The new encoder achieves unmatched performance as a consequence of a design which avoids the many compromises traditionally associated with miniaturized encoders.

In addition to these benefits, Renishaw encoders have an established reputation for being easy to install and set up. Scale is available in many lengths with special formula self-adhesive backing, removing the need for drilling and tapping, and saving time and money.

All optical readhead and interface combinations feature a unique set-up LED which speeds installation and removes the need for complex set-up equipment or oscilloscopes.

In addition to market-leading product performance, Renishaw provides unequalled engineering back-up with a global team of experienced engineers always on hand to offer application advice and expert installation support.

To ensure that we never hold up your production, stock is held at over 30 Renishaw operations worldwide and, thanks to flexible manufacturing techniques, even out-of-stock items can be manufactured and shipped promptly.

Renishaw's encoder systems are used in all sectors of industrial automation such as semiconductor, electronics, medical, flat panel display manufacturing, printing, scientific research, robotics, solar PV, specialist machine tools, precision metrology and advanced motion systems.

Innovation

Each year, Renishaw re-invests approximately 14% of turnover into engineering, research and development. The results are ground-breaking products such as VIONiC™ and ATOM that demonstrate our commitment to developing unique technologies that push encoder performance to new levels. You will not find 'me too' replicas of competitors in this catalog; only superior encoder designs that offer higher fidelity positional feedback.



Quality

We are so confident of our products that we warrant them with a comprehensive two-year guarantee. If you need to exchange a product, we will offer an immediate replacement anywhere in the world, to ensure that you do not suffer additional downtime. All returned products are thoroughly investigated and you will receive a report explaining exactly what caused the fault. In cases where problems are caused by customer damage, we can apply our applications engineering experience to help eliminate the cause.

Delivery

ISO9001-certified quality management system meets rapid delivery! Our efficient processes are tuned to enable us to react quicker than the competition to increases in demand. Allied to this, we hold large quantities of stock locally at subsidiaries around the world for 'next-day' deliveries. OEM customers can also benefit from consignment stock and kanban arrangements.

Price

Renishaw not only supplies encoders at a fair price, but also gives customers better price performance ratios and minimizes cost of ownership. How? As well as embedding quality and reliability into the fundamental encoder design, we develop novel production techniques that reduce manufacturing costs, allowing us to pass on the savings.



RESOLUTE absolute linear and rotary encoder range

Operating principles of optical encoders

RESOLUTE is a family of true absolute, fine pitch optical encoder products. Linear scale options include high-accuracy RSLA stainless steel spar scale, RELA ZeroMet scale and RTLA-S stainless steel tape scale, also available with the *FASTRACK*™ RTLA track-mounted linear encoder scale system. Rotary options include RESA stainless steel rings and REXA ultra-high accuracy rings.

How it works...

RESOLUTE communicates in purely serial format, using a variety of industry-standard protocols, of both proprietary and open standard.

The process begins...

The controller initiates operation by sending a request to the readhead, instructing it to capture the absolute position on the scale – linear or rotary – at that instant. The readhead responds by flashing a high-power LED source to illuminate the scale. The flash duration is as brief as 50 ns to minimize image blur on moving axes. Crucially, its timing is controlled within a few nanoseconds to preserve the relationship between requested and reported position – one of the essential features that makes RESOLUTE ideally suited to very high-specification motion systems.

Single track scale

The scale is essentially a single track of full-width contrasting lines, based on a nominal pitch of 30 µm. The absence of multiple parallel tracks gives important immunity from yaw errors and much more lateral tolerance in head position.

Image acquisition

The scale is imaged, via an aspheric lens which minimizes distortion, onto a custom detector array designed specifically for RESOLUTE. The optical arrangement, with a folded illumination path but direct imaging, is highly compact yet stable, thus assuring the fidelity essential for excellent metrology.

Data decoding and analysis

Once captured by the detector, the image is transferred by analog-to-digital converter (ADC) at about 500 Mb/s to a powerful Digital Signal Processor (DSP). Specially-developed algorithms then obtain a true absolute, but relatively 'coarse' position from the code embedded in the scale. This process is checked, and corrections are made by further algorithms in the DSP which exploit redundancy and intentional restrictions in the scale code. Meanwhile other routines calculate a very high-resolution 'fine' position, which is then combined with the coarse position to provide a truly absolute and very high-resolution location.

Final checks and data output


After final error-checking procedures this information is uploaded again in the appropriate protocol to the controller, as a pure serial word representing position to within 1 nm. Protection against electrical noise disturbance is provided by the addition of a Cyclic Redundancy Check (CRC). The entire process, from request to response, can take as little as 12 µs and be repeated up to 25 000 times per second. By a variety of techniques, including adjusting the light flash duration to the axis speed, this performance is achieved at up to 100 m/s while, crucially, preserving exceptionally low positional jitter at lower operating speeds.

And the result is...

The outcome is an encoder with generous installation tolerances: RESOLUTE allows ±0.5° in yaw, pitch and roll and an impressive ±150 µm in ride height. Meanwhile the generous optical footprint and advanced error correcting procedures confer excellent immunity to optical contamination, both particulate and greasy smears. All this while maintaining 1 nm resolution at 100 m/s: RESOLUTE is the answer to the toughest absolute challenge.



RESOLUTE™ absolute optical encoder summary



- True absolute non-contact optical encoder system: no batteries required.
- Wide set-up tolerances for quick and easy installation.
- High dirt immunity to scratches and light oils.
- Resolutions to 1 nm or 32-bit rotary.
- 100 m/s maximum speed for all resolutions (to 36,000 rev/min).
- 30 μm nominal scale pitch ensures exceptional motion control performance.
- ± 40 nm Sub-Divisional Error (SDE) for smooth velocity control.
- Less than 10 nm RMS jitter for improved positional stability.
- Built-in separate position-checking algorithm provides inherent safety.
- IP64-sealed readhead for high reliability in harsh environments.
- Integral set-up LED enables easy installation and provides diagnostics at a glance.
- Readhead and linear/rotary scales are bolt-hole compatible with SiGNUM™ encoders.
- Operates up to 80 °C.
- Integral over-temperature alarm.
- Variety of serial protocols available. Contact your local representative for the latest list.


Compatible with:

- RELA ZeroMet spar scales.
- RSLA stainless steel spars.
- *FASTRACK* with RTLA.
- RTLA-S self-adhesive tape scale.
- RESA angle encoders.
- Ultra-high accuracy REXA angle encoders.

System features



Unique single-track absolute optical scale

- Absolute position is determined immediately upon switch-on.
- No battery back-up.
- Much higher tolerance to yaw de-phasing than dual-track systems.
- Fine pitch (30 µm nominal period) optical scale for superior motion control compared to inductive, magnetic or other non-contact optical absolute encoders.
- High-accuracy graduations marked directly onto tough engineering materials for outstanding metrology and reliability.



High dirt immunity

- Advanced optics and embedded surplus code means RESOLUTE even reads dirty scale.
- Absolute position can be determined in all three cases shown here; clean scale (left), grease contamination (below left), particle contamination (below). Images were taken with a digital microscope.



Unique detection method

- Readhead acts like an ultra-fast miniature digital camera, taking images of a coded scale.
- Photos are analyzed by a high-speed DSP to determine absolute position.
- Built-in position-check algorithm constantly monitors calculations for ultimate safety and reliability.
- Advanced optics and determination algorithms are designed to provide low noise (jitter <10 nm RMS) and low Sub-Divisional Error (SDE ±40 nm).

Range of rotary (angle) and linear scales

- Tough RELA high-precision ZeroMet spars with ±1 µm accuracy available up to 1500 mm length.
- Shatter-proof RSLA high-precision stainless steel scale, offering higher accuracy than glass scales and long lengths up to 5 m, with ±4 µm accuracy over a complete 5 m length (for longer lengths contact your local representative).
- RTLA with *FASTRACK*, and RTLA-S tape scales with ±5 µm/m accuracy and easiest installation.
- RESA ring with unique taper mount has large through hole for easy installation.
- REXA ultra-high accuracy ring with ±1 arc second total installed accuracy with dual readheads.

Range of protocols and resolutions

Protocol	Resolutions	
	Linear	Rotary
<i>BiSS</i>	50 nm 5 nm 1 nm	18-bit 26-bit 32-bit
Drive-Cliq*	50 nm 1 nm	26-bit 29-bit
FANUC	50 nm 1 nm	23-bit (high type A) 27-bit (high type B)
Mitsubishi	50 nm 1 nm	23-bit 27-bit
Panasonic	100 nm 50 nm 1 nm	23-bit
Yaskawa	50 nm 1 nm	23-bit (fully closed loop) 24-bit (rotary controlled servomotors) 26-bit (rotary controlled servomotors) 30-bit (rotary controlled servomotors)

* Functional safety variant available.

RELA absolute high-accuracy scale


System features

- Single track optical absolute scale.
- $\pm 1 \mu\text{m}$ guaranteed accuracy.
- $30 \mu\text{m}$ nominal scale pitch ensures exceptional motion control performance.
- Robust ZeroMet™ offers $0.75 \pm 0.35 \mu\text{m}/\text{n}^\circ\text{C}$ (at 20°C) thermal expansion plus ease of handling and installation.
- Scale mounting options: self-adhesive or clips and clamps.
- Available in lengths up to 1500 mm.
- $\pm 40 \text{ nm}$ Sub-Divisional Error for smooth velocity control.
- Resolution to 1 nm.
- Maximum speed of 100 m/s.

RELA absolute high-accuracy ZeroMet™ scale is compatible with Renishaw's revolutionary true absolute optical encoder system, RESOLUTE.

RELA offers certified $\pm 1 \mu\text{m}$ accuracy combined with low thermal expansion ZeroMet to suit the most demanding precision applications. The high performance of the scale is augmented by Renishaw's RESOLUTE absolute optical readhead offering $\pm 40 \text{ nm}$ Sub-Divisional Error, resolution to 1 nm, low noise (jitter) and a maximum speed of 100 m/s.

RELA provides excellent dirt immunity and easy set-up, whilst offering levels of performance previously only available from delicate fine pitch systems.



RSLA absolute high-accuracy stainless steel scale

System features

- Single track optical absolute scale.
- 30 µm nominal scale pitch ensures exceptional motion control performance.
- Robust special composition stainless steel with defined coefficient of thermal expansion 10.1 ±0.2 µm/m/°C (at 20°C).
- Coilable for simple storage and handling.
- Available in defined lengths up to 5 m.
- ±40 nm Sub-Divisional Error for smooth velocity control.
- Resolution to 1 nm.
- Maximum speed of 100 m/s.


RSLA absolute high-accuracy stainless steel scale is compatible with Renishaw's revolutionary true absolute optical encoder system, RESOLUTE.

RSLA stainless steel scale is available in a range of lengths up to 5 m, with 5 m lengths having an overall accuracy better than ±4 µm – an industry first! Combined with readheads featuring low Sub-Divisional Error (±40 nm), advanced optics, resolution to 1 nm and simple installation and set-up, RSLA provides outstanding motion control performance.

RSLA offers the ease of use of a tape scale yet has the performance of a glass spar; the scale can be coiled for simple storage and handling yet behaves as a spar once uncoiled. The choice of mechanical or adhesive mounting makes RSLA perfect for long-travel applications where metrology cannot be compromised.



FASTRACK™ and RTLA-S high-accuracy absolute linear encoder scale system



RTLA absolute linear encoder tape scale from Renishaw combines $\pm 5 \mu\text{m}/\text{m}$ accuracy with the ruggedness of stainless steel. Two versions are available; self-adhesive RTLA-S, and RTLA for use with the revolutionary *FASTRACK* track system from Renishaw.

Designed for applications that demand high accuracy and an independent expansion coefficient with tape scale convenience, RTLA-S and RTLA are read by Renishaw's ground-breaking RESOLUTE absolute readhead. 1 nm resolution, 100 m/s maximum speed, ultra-low Sub-Divisional Error and jitter result in a linear encoder system that outperforms any other encoder in its class.

RTLA-S is laid onto the substrate using its self-adhesive backing tape. A patented application tool makes this a quick, simple and inexpensive process. A clamp is fitted at a single point to lock the scale to the substrate.

RTLA (without self-adhesive) is used with *FASTRACK*. In this case, the scale is held securely in place by two miniature, yet rugged, guide rails. Again, the scale is clamped in a single point to allow independent expansion with extremely low hysteresis, even over wide temperature ranges. If damaged, the scale can be pulled out of the guide rails and quickly replaced, even where access is limited, thus reducing machine downtime. This feature also makes the linear encoder system ideal for large machines that need to be sectioned for transportation.

RTLA-S and RTLA with *FASTRACK* are suitable for many applications, including FPD manufacturing and inspection machines, P-V manufacturing, linear motors with aluminum substrates, axes that are exposed to potential damage, large CMMs and other machines that require the scale to be installed/removed for transit, or simply for any application where thermal expansion of the scale must be independent of the machine structure.

- High-accuracy ($\pm 5 \mu\text{m}/\text{m}$) absolute scale. Further improvement possible with error correction.
- Compatible with RESOLUTE absolute readheads.
- RTLA scale expands at its own low thermal coefficient ($10.1 \pm 0.2 \mu\text{m}/\text{m}/^\circ\text{C}$ at 20°C).
- Use with *FASTRACK* for very low hysteresis.
- *FASTRACK* guide rails are pre-aligned in reels for cut-to-suit flexibility.
- Quick installation. *FASTRACK* adds fast scale replacement capability.
- Scale can be locked to the substrate at a single datum point anywhere along the axis.
- RTLA scale can bridge gaps in the substrate up to 25 mm.
- High solvent immunity.
- Incremental RTLC version for TONiC readheads also available.

RESA absolute angle encoder



RESA is a one-piece stainless steel ring with a single track, true absolute scale marked directly onto the periphery.

Read by Renishaw's revolutionary absolute fine pitch encoder system, RESOLUTE, it has high tolerance to dirt, scratches and greasy fingerprints that can cause other encoder systems to miscount.

The RESA offers impressive accuracy with resolution to 0.00030 arc second, suiting the most demanding precision applications.

The low profile RESA, with large internal diameter, is easy to design into most installations. Equally important, its low mass, low inertia design does not compromise system performance.

RESA is available in a wide range of sizes and line counts, providing compatibility with industry standard controllers.

System features

- Compatible with the revolutionary true absolute encoder, RESOLUTE.
- Angular resolution to 0.00030 arc second.
- System repeatability to 0.0075 arc second.
- 36,000 rev/min maximum speed for all resolutions.
- Patented taper mount simplifies integration and minimizes installation errors.
- Large internal diameter for ease of integration.
- Available in sizes from Ø52 mm to Ø550 mm.
- Custom sizes also available.
- Low mass and low inertia.
- Ultra-low inertia versions also available.
- Integral set-up LED on readhead for quick set-up and instant 'health check' at any time.
- 30 µm nominal scale pitch ensures exceptional motion control performance.
- Resolutions to 23-bit with Panasonic; to 27-bit with FANUC and Mitsubishi; 29-bit with Siemens DRIVE-CLiQ, 30-bit with Yaskawa; and to 32-bit with BiSS.
- Operates down to -40 °C with RESOLUTE ETR.

REXA ultra-high accuracy absolute angle encoder



With zero coupling losses and exceptional repeatability, the REXA ultra-high accuracy angle encoder achieves better than ± 1 arc second total installed accuracy.

Like the RESM encoder, the REXA is a stainless steel ring with the scale graduations marked axially onto the periphery, but with a number of differences to improve upon RESM's already impressive accuracy.

REXA has a thicker cross-section to ensure that the only significant installation error is eccentricity. Eccentricity is easily removed by using 2 readheads, and combining the signals inside the host controller.

The only errors remaining are graduation errors and readhead SDE, both of which are so small they are often negligible.

As a non-contact encoder, REXA offers dynamic performance advantages, eliminating coupling losses, oscillation, shaft torsion and other hysteresis errors that plague enclosed encoders.


The REXA system operates at temperatures up to $+80$ °C and speeds to 8 500 rev/min.

REXA total installed accuracy grades:

REXA diameter	Total installed accuracy (with 2 readheads)
≥ 100 mm	± 1 arc second
75 mm	± 1.5 arc second
≤ 57 mm	± 2 arc second

- Use with two RESOLUTE readheads to give ultra-high accuracy.
- Installed accuracy to ± 1 arc second with dual readheads.
- Sub-Divisional Error to ± 0.04 arc second.
- Resolutions to 0.00030 arc second.
- Repeatability to 0.01 arc second.
- Wide range of standard sizes from 52 mm to 417 mm.
- Large internal diameter for ease of integration.
- Flange mounted with easy 4-point adjustment method.

ATOM™ miniature encoder system



ATOM is the world's first miniature encoder with filtering optics, providing improvements in dirt immunity, signal stability and reliability for linear and rotary applications.

ATOM features a number of other advances that help maintain signal stability, including integral Auto Gain Control and Auto Offset Control, along with a highly reliable IRED light source, making the product suitable for use in applications demanding quality and dependability.

The miniature readhead is available in two formats: hi-flex cable output or Flexible-Printed Circuit (FPC) output. The FPC version helps reduce overall package size, with a reduced Z-height and easy cable routing.

ATOM is available with a range of high-accuracy optical linear and rotary scales, including conventional glass spars, 'unbreakable' stainless steel tape scales and glass discs. Installation has been simplified by an intuitive set-up LED on the readhead that indicates signal level. Optical reference mark phasing and incremental signal optimization can be achieved with the simple press of a button.

ATOM is suitable for use in a variety of applications that require compact size, including laser scanners, CMM arms, semiconductor manufacturing, compact linear motors/motion stages, small DDR torque motors, galvanometers and microscope stages.

ATOM – miniaturization without compromise.


- Miniature package:
8.35 mm × 12.7 mm × 20.5 mm
(7.3 mm × 12.7 mm × 20.5 mm for FPC version).
- Highest signal stability and dirt immunity in its class due to filtering optics.
- Long-term stability provided by integral Auto Gain Control and Auto Offset Control.
- Low Sub-Divisional Error (SDE) and jitter.
- Easy installation and diagnostics using the set-up LED on the readhead.
- Fast, simple calibration at the push of a button.
- Auto-phase optical reference mark.
- Available in 20 μm and 40 μm scale pitch versions.
- Analog output direct from the readhead.
- Multiple interpolation options, with resolutions to 1 nm.
- Range of high-accuracy rotary and linear scales.

System features

High performance

- **Need higher speed?**
ATOM is the fastest encoder in its class, with maximum speeds up to 20 m/s and a range of high-speed interpolation options for digital versions.
- **Need higher accuracy?**
ATOM offers linear tape scales with specified overall accuracy to $\pm 5 \mu\text{m/m}$ @20 °C, without the need for 2-point compensation that competitor encoders require.
- **Need smoother velocity control?**
Reduce velocity ripple, improve scanning performance, reduce blur on vision systems and image capturing – all thanks to ATOM's superior optical scheme and integral Auto Offset Control (AOC).

- **Need improved positional stability and repeatability?**
ATOM has low noise (jitter), allowing users to increase servo-loop gain without instability, whilst reaping other dynamic performance benefits such as faster settling times and higher acceleration.




Typical accuracy for a 1 m length of RTL F 20 μm scale

Lissajous stability

ATOM features a miniaturized version of Renishaw's unique filtering optics that are used in the TONiC encoder range.

This optical scheme is tuned to a specific spatial frequency, so it rejects other harmonics, including those caused by dirt or other contaminants.

The result is a Lissajous with high purity, that retains its fidelity even when the scale is exposed to contamination: ideal for applications where reliability is critical.



Product range

- **20 μm and 40 μm readheads with high-flex cable:** for general purpose applications. Superior quality cable tested to 20 million flex cycles.
- **20 μm and 40 μm readheads with FPC cable:** side exit FPC cable allows the smallest overall package size.
- **Stainless steel tape scale (RTL F):** high-accuracy scales with graduations directly marked onto the steel tape surface. Available on reels for cut-to-suit flexibility.
- **Glass linear spars (RCLC):** conventional glass scales, available in lengths up to 130 mm.
- **Glass discs (RCDM):** high-accuracy rotary scales with outer diameters down to 17 mm.



RGH22 series readhead



Renishaw's RG2 linear encoder system is a non-contact optical encoder designed for position feedback solutions.

The system uses a common reflective tape scale scanned by a readhead chosen from a range of options offering industry-standard digital square wave or analog sinusoidal output signal formats.

Renishaw's patented optical scheme is used in all readhead series and gives proven performance benefits together with high tolerance to scale contamination.

The RGH22 range is suitable for use in a broad range of applications, offering high resolution and high speed with stability and reliability.

A dual limit sensor option is also available offering two dedicated signal outputs, left and right end-of-axis travel indication.

RGH22 is an ideal feedback solution wherever precision controlled movement is required. The RGH22 readheads offer the full set of RG2 features and integral interpolation in a robust package, with an integral set-up LED for quick and easy installation.

Common applications include coordinate measuring and layout machines, semi-conductor/electronics manufacturing and inspection, height gages, electronics assembly and testing, linear motors, digital image setters and a variety of custom linear motion solutions.

Single limit range

RGH22D – 5 µm resolution
 RGH22X – 1 µm resolution
 RGH22Z – 0.5 µm resolution
 RGH22Y – 0.1 µm resolution
 RGH22B – 1 Vpp differential

Dual limit range

RGH22P – 5 µm resolution
 RGH22Q – 1 µm resolution
 RGH22R – 0.5 µm resolution
 RGH22S – 0.1 µm resolution
 RGH22H – 50 nm resolution
 RGH22A – 1 Vpp differential

- Non-contact open optical system.
- Integral interpolation.
- Industry-standard digital and analog output options.
- Resolutions from 5 µm to 50 nm.
- Integral reference and limit sensors.
- Dual limit sensor option.
- Integral set-up LED.
- Uses RGS20-S self-adhesive scale.

RGH24 series readhead



Renishaw's RG2 linear encoder system is a non-contact optical encoder designed for position feedback solutions.

The system uses a common reflective tape scale scanned by a readhead chosen from a range of options offering industry-standard digital square wave or analog sinusoidal output signal formats.

Renishaw's unique patented optical scheme is used in all readhead series to provide high tolerance to scale contamination.

RGH24 is an ideal feedback solution wherever precision controlled movement is required.

The RGH24 readheads offer a wide selection of output configurations and their compact size and low mass makes the system ideal for small XY stages and actuators.

An integral set-up LED enables quick and easy installation.

Common applications include semiconductor/electronics manufacturing and inspection, co-ordinate measuring and layout machines, height gages, linear motors, pre-press printing and a variety of custom linear motion solutions.

Digital range

RGH24D – 5 µm resolution
 RGH24X – 1 µm resolution
 RGH24Z – 0.5 µm resolution
 RGH24W – 0.2 µm resolution
 RGH24Y – 0.1 µm resolution
 RGH24H – 50 nm resolution
 RGH24I – 20 nm resolution
 RGH24O – 10 nm resolution

Analog range

RGH24B – 1 Vpp differential

- Non-contact open optical system.
- Compact size.
- Low mass.
- Integral interpolation.
- Digital and analog output options.
- Resolutions from 5 µm to 10 nm.
- Integral set-up LED.
- Uses RGS20-S self-adhesive scale.
- Reference mark or limit switch capability.

RGH25F series readhead



Renishaw's RGH25F offers all the benefits of the market-leading RG2 non-contact linear encoder systems; patented filtering optical scheme, high contamination tolerance and high speed.

The RGH25F has been designed for use with Renishaw's RGS20-S gold-plated scale in precision applications requiring fine resolutions, high accuracy, compact size and low mass.

The readhead is enclosed in an RFI screened housing and uses proven solid state components to give outstanding reliability.

The REF interfaces can be mounted remotely to interpolate the signals produced by the readhead.

The interfaces incorporate automatic gain control and unique self-tuning adaptive electronics which, combined with the filtering optics, ensure excellent signal integrity, and give a low cyclic error.

Common applications include optical fiber alignment, semiconductor manufacturing, inspection, precision stages and other systems requiring high resolution where space is at a premium.

Readhead

RGH25F – common readhead

Interfaces:

Digital


REF0004 – 5 μm resolution
 REF0020 – 1 μm resolution
 REF0040 – 0.5 μm resolution
 REF0100 – 0.2 μm resolution
 REF0200 – 0.1 μm resolution
 REF0400 – 50 nm resolution
 REF1000 – 20 nm resolution
 REF2000 – 10 nm resolution
 REF4000 – 5 nm resolution

Analog

REF0000 – 1 V_{pp} differential

- Customer selectable AGC. operational at all speeds.
- Digital and analog output options.
- Resolutions from 5 μm to 5 nm.
- Binary interpolation factors from $\times 4$ to $\times 4096$.
- Low cyclic error (<50 nm).
- Self-tuning adaptive electronics give reliability and high accuracy.
- Uses low profile RGS20-S self-adhesive scale.
- Low mass.
- Tri-colored set-up LED indicating signal strength.

RGS20 and RGS40 gold scale



Renishaw's patented RGS20-S scale comprises 20 μm graduations on a steel strip 6 mm wide and 0.2 mm thick and features a thin gold surface layer to enhance reflectivity.

A lacquer coating provides protection against handling and contamination. The 20 μm pitch scale is suitable for use with all Renishaw RG2 series readheads (RGH22, RGH24 and RGH25), whilst the 40 μm RGS40-S is suitable for use with the RGH34 and RGH41 readheads.

The scale is supplied with a specially formulated adhesive backing tape. Installation is quick, easy and suits both high-volume production and one-off field service installations.

To simplify customer inventory and maximize production flexibility, the scale can be supplied on a reel for 'cut-to-suit' convenience at the point of installation.

RGS20-S and RGS40-S are suitable for mounting to most common engineering materials including metals, granites, ceramics and composites, whilst RGS20-P and RGS40-P polyester-coated versions have an increased resilience to solvent and lubricant attack.

The scale ends are rigidly fixed to the axis substrate by means of epoxy fastened end clamps, eliminating the need to drill holes. Because the scale has a very small cross section, it is 'mastered' to the substrate and matches its thermal expansion. Differential movement between the scale and the substrate is close to zero, even throughout significant temperature swings.

- RGS20 20 μm tape scales for RGH22, RGH24 and RGH25 readheads.
- RGS40 40 μm tape scales for RGH34 and RGH41 readheads.
- 'Cut-to-length' flexibility.
- Lengths up to 50m (>50m by special order).
- Protective lacquer or tough polyester coating option for applications using harsh solvents.
- Efficient, accurate installation.
- Affixes to most common engineering materials.
- Self-adhesive.
- Automated application.

Technical specifications

Scale

Type	Reflective gold plated steel tape with protective lacquer coating or tough polyester coating option for applications using harsh solvents and self-adhesive backing	
Scale pitch	RGS20-S, RGS20-P = 20 µm	RGS40-S, RGS40-P = 40 µm
Linearity	RGS20-S = ±3 µm/m RGS20-P = ±5 µm/m	RGS40-S = ±3 µm/m RGS40-P = ±5 µm/m
Scale length	Up to 50 m (>50 m by special order)	
Substrate materials	Metals, ceramics and composites with expansion coefficients between 0 and 22 µm/m/°C (steel, aluminum, ZeroMet, granite, ceramic etc.)	
Expansion coefficient	Matches that of substrate material with scale ends fixed by epoxy mounted end clamps	
End fixing	Epoxy mounted end clamps (A-9523-4015) using two-part epoxy adhesive (A-9531-0342) Scale end movement <1 µm over temperature range -20 °C to +50 °C	
Operating specification	Temperature: -10 °C to +120 °C (scale only, also refer to data sheet) Minimum installation temperature +10 °C Humidity: 95% relative humidity (non-condensing) to EN 60068-2-78	

Reference mark

Type	Magnetic actuator	
Mounting options	Adhesive mounted	A-9531-0250
	Screw mounted	A-9531-0287
	Adhesive or screw mounted 90° actuator for use with RGH24, RGH25 or RGH34	A-9541-0037
Position	One or more at user selected locations	
Repeatability	Output synchronized with incremental channels Repeatability of position (uni-directional) maintained within these conditions: Temperature range: RGS20-S, RGS20-P ±10 °C from installation temperature RGS40-S, RGS40-P ±20 °C from installation temperature Speed: Refer to individual readhead specifications Magnetic field: steady ±0.02 T or changing ±7.5 T/s	

Limit switch

Type	Magnetic actuator	
Mounting options	Adhesive mounted 10 mm actuator	A-9531-0251
	Adhesive mounted 24.35 mm actuator	A-9531-2052
	Adhesive mounted 50 mm actuator	A-9531-2054
	Flush mounted actuator	A-9531-0285
	Adhesive or screw mounted 90° actuator for use with RGH24, RGH25 and RGH34	A-9541-0040
Position	One or more at user-selected locations	
Repeatability	0.1 mm	

RGH20 and RGH20F series readhead



The RGH20 is a compact readhead for use with Renishaw's range of 20 µm RESR rotary encoders and RSLR high accuracy linear scale.

Like all Renishaw encoders, the RGH20 offers reliable, high-speed, open, non-contact performance with excellent immunity to dust, scratches and light oils on the scale.

The RGH20 also benefits from Renishaw's integral readhead set-up LED which simplifies installation and monitors signal condition during operation.

The ultra-compact RGH20F connects to the REF interface to give high-accuracy digital and analog outputs. The REF interface incorporates advanced signal processing and offers high speed and resolution.

Digital and analog RGH20

RGH20D – 5 µm resolution
 RGH20X – 1 µm resolution
 RGH20Z – 0.5 µm resolution
 RGH20W – 0.2 µm resolution
 RGH20Y – 0.1 µm resolution
 RGH20H – 50 nm resolution
 RGH20I – 20 nm resolution
 RGH20O – 10 nm resolution
 RGH20B – 1 Vpp differential

RGH20F/REF system options

REF0004 – 5 µm resolution
 REF0020 – 1 µm resolution
 REF0040 – 0.5 µm resolution
 REF0100 – 0.2 µm resolution
 REF0200 – 0.1 µm resolution
 REF0400 – 50 nm resolution
 REF1000 – 20 nm resolution
 REF2000 – 10 nm resolution
 REF4000 – 5 nm resolution
 REF0000 – 1 Vpp differential

- Compatible with 20 µm RESR angle encoder and RSLR high-accuracy linear scales.
- Filtering optics provide excellent dirt immunity.
- Compact and robust housing.
- Industry-standard digital and analog outputs.
- Integral interpolation and set-up LED on RGH20 option.
- Ultra-compact RGH20F/REF system gives high accuracy and high resolution.
- Resolutions from 5 µm to 5 nm.
- Reference mark or single limit switch sensor.
- Hi-flex double-screen 8-core cable.

RESR angle encoder scale



The RESR is a one-piece stainless steel ring with graduations marked directly onto the periphery.

The RESR offers impressive accuracy with resolution to 0.008 arc second, suiting the most demanding precision applications.

Read by Renishaw's filtering optics readheads, including the RGH20, RGH34 and RGH40, the system has a high tolerance to dirt, scratches and greasy fingerprints that can cause other encoder systems to miscount.

The low profile RESR, with a large internal diameter, is easy to design into most installations. More importantly, its low mass, low inertia design will not compromise system performance. A repeatable reference mark is available to provide a home (datum) position, while Renishaw's RGH40 readhead with filtering optics offers dual limit sensors.

System features

- High-speed, non-contact, optical performance
- Graduation accuracy to ± 0.5 arc second
- Angular resolution to 0.008 arc second
- System repeatability to 0.008 arc second
- Wide range of sizes and line counts provide compatibility with industry-standard controllers ($\text{\O}52$ mm to $\text{\O}550$ mm with line counts from 4,096 to 86,400)
- Patented taper mount simplifies integration and minimizes installation errors
- Filtering optics provide excellent dirt immunity
- UHV compatible
- Low magnetic permeability as standard
- Compact size for easy integration
- Low mass and low inertia
- Compatible with RGH20, RGH34 or RGH40 readheads to offer industry-standard analog or digital incremental outputs with reference mark option
- Integral set-up LED on all Renishaw encoders for quick set-up and instant "health check" at any time
- Ultra-low inertia versions also available in 75 mm, 100 mm, 150 mm and 200 mm sizes

Ultra-high vacuum (UHV) encoders

RESOLUTE UHV, TONiC UHV and RGH25F UHV readheads


All products in Renishaw's range of ultra-high vacuum (UHV) compatible encoders are designed for use in a variety of scientific, semiconductor and other advanced industrial applications with vacuum pressures to 10^{-11} Torr. The fundamental principles of operation are the same as those for our equivalent standard-atmosphere products, but the UHV variants are designed to eliminate unvented voids and are specially constructed from clean, vacuum-compatible materials and adhesives. The suitability of the products for use in UHV environments is qualified by an independent specialist test house, including a Residual Gas Analysis (RGA) spectrum test.

The range includes versions of RESOLUTE, TONiC and RGH25F readheads, along with a variety of linear and rotary scales, offering superior performance and high reliability.

RESOLUTE UHV uses the same true-absolute encoder operating principles as the rest of the RESOLUTE range. This provides an encoder with fine-pitch performance, combined with wide set-up tolerances and built-in safety. RESOLUTE determines absolute position immediately upon switch-on, eliminating uncontrolled movements and facilitating complete command of axes without the need for reference returns or 'wake-and-shake' routines. With 1 nm resolution, ± 40 nm SDE and < 10 nm RMS noise, RESOLUTE also offers users a significant performance upgrade.

All incremental readheads in the range include dynamic signal conditioning comprising Auto Gain Control (AGC) for solid and dependable signals over extended machine lifetimes, and Auto Offset Control (AOC) for improved signal fidelity. AOC and the encoder's low positional noise also add the benefit of reducing velocity ripple on direct-drive systems, thereby helping minimize heat build-up in motors inside the vacuum.

High accuracy is assured, with linear measuring standards including options of self-adhesive tape scale, stainless steel and ZeroMet spars. Angle encoder options include the low-profile RESR/RESM and the ultra-high accuracy REXM ring with guaranteed installed accuracy better than ± 1 arc second.




UHV product features

- RESOLUTE UHV is the first true-absolute optical encoder for UHV environments
 - Constructed from vacuum-compatible materials and adhesives to give low outgassing rates
 - Proven clean RGA
 - Bake-out temperature of 120 °C
 - Non-contact open optical system for high-speed, reliable operation with zero friction and zero wear
 - Industry-standard digital and analog outputs with resolutions to 1 nm
 - Low power consumption minimizes heat dissipation
 - No unvented voids
 - Adaptive electronics offer high performance, long-term reliability
- and low Sub-Divisional Error (SDE) (± 40 nm for RESOLUTE UHV, ± 30 nm for TONiC UHV, ± 50 nm for RGH25F UHV)
 - UHV compatible cables
 - TONiC UHV encoder features optical reference mark
 - Range of high-accuracy linear and rotary scales

Products	Scale options	Features
RESOLUTE UHV	<i>FASTRACK</i> RTLA track-mounted scale system	True-absolute with no movement required to determine absolute position, position-checking algorithm, safe extraction after power-outs, pure serial communications with CRC check, excellent motion control performance and easiest installation.
	RTLA-S stainless steel tape scale	
	RSLA stainless spar	
	RELA low expansion ZeroMet spar	
	RESA ring	
	REXA ultra-high accuracy ring	
TONiC UHV	RGSZ20-S tape scale	High-accuracy scales, <i>IN-TRAC</i> ™ optical reference mark technology, advanced Auto Gain Control (AGC) and Auto Offset Control (AOC), lowest noise (jitter) and Sub-Divisional Error (SDE) for the best motion control performance, and easy installation.
	<i>FASTRACK</i> RTLC track-mounted scale system	
	RTLC-S stainless tape scale	
	RSLM stainless spar	
	RELM low expansion ZeroMet spar	
	RESM ring	
REXM ultra-high accuracy ring		
RGH25F UHV	RGS20-S tape scale	Easy installation, high repeatability, AGC and AOC.

RGH34 series readhead



Renishaw's RGH34 series is a non-contact optical encoder system that offers the performance and reliability of the established RG2 linear encoder system with the versatility of a miniaturized component system.

Renishaw's unique patented filtering optical technology eliminates friction, hysteresis and wear while giving high contamination tolerance and exceptional reliability. The system reads Renishaw's RGS40-S self-adhesive scale.

The component style construction allows integration flexibility for even the smallest motion systems, while the generous set-up tolerances, easy-to-install adhesive scale and integral set-up LED make installation quick and easy.

Designed for OEM applications where a conventional enclosed readhead cannot be fitted, the RGH34 brings reliable state-of-the-art performance to size-sensitive precision linear and rotary motion applications such as ultra-small linear actuators, microscopes and microstages.

Common readhead

RGH34U

Digital range

RG134T – 10 µm resolution
 RG134D – 5 µm resolution
 RG134G – 2 µm resolution
 RG134X – 1 µm resolution
 RG134N – 0.4 µm resolution
 RG134W – 0.2 µm resolution
 RG134Y – 0.1 µm resolution

Analog range

RG134B – Vpp differential

- Non-contact open optical system.
- Compact component style readhead.
- Large installation tolerances.
- High-speed operation.
- Industry-standard digital and analog output options.
- Resolutions from 10 µm to 0.1 µm.
- Optional reference or limit sensor.
- Integral set-up LED.
- Uses low profile RGS40-S, self-adhesive scale.

RGH40 series readhead



Renishaw's RGH40 readhead offers all the benefits of the market-proven RG4 linear encoder system – high-speed, non-contact performance with filtering optics to guarantee reliable performance over light oils, dust and scratches.

The RGH40 readhead is designed for use with Renishaw's RGS40-G (40 µm pitch chrome grating) glass scale and RESR angle encoder. Enclosed within a rugged, die-cast housing, the readhead uses proven solid state components to give outstanding reliability.

Dual limit switch sensing is also included as standard to provide dedicated signals for each end-of-axis indication, together with a repeatable reference or datum mark.

Installation is quick and easy to achieve thanks to generous set-up tolerances and Renishaw's unique set-up LED that indicates when optimum conditions have been achieved. This removes the need for expensive oscilloscopes or set-up equipment.

These added benefits give RGH40 readheads greater flexibility, broadening the range of applications of the existing RG2 and RG4 systems, from co-ordinate measuring and layout machines to electronics assembly and test, high-speed motion control, semiconductor manufacture and a host of custom linear motors.

Digital range


RGH40T – 10 µm resolution
 RGH40D – 5 µm resolution
 RGH40G – 2 µm resolution
 RGH40X – 1 µm resolution
 RGH40N – 0.4 µm resolution
 RGH40W – 0.2 µm resolution
 RGH40Y – 0.1 µm resolution
 RGH40H – 50 nm resolution

Analog range

RGH40A – 1 Vpp differential

- Non-contact open optical system.
- Large installation tolerances.
- High-speed operation – up to 10 m/s.
- Industry-standard digital and analog output options.
- Resolutions from 10 µm to 50 nm.
- Integral reference and dual limit sensors.
- Integral set-up LED.
- Uses Renishaw RGS40-G glass scale and RESR angle encoder.

RGH41 series readhead



Renishaw's 40 µm RGH41 series readheads offer all the benefits of the established 20 µm RG2 linear encoder system, such as reflective tape scale, patented filtering optics, set-up LED, good dirt immunity and high speed.

These compact readheads with integral interpolation provide an increased range of resolutions to match the demands of a wide range of applications, whilst their high speed enables an increase in the productivity of the end-user's system.

The 40 µm RGH41 increases the already generous set-up tolerances of the RG2, whilst maintaining Renishaw's famous contamination immunity.

For added flexibility, dual limit switch sensing is included as standard to enable dedicated signals for each end-of-axis indication, along with a repeatable reference or datum mark.

These benefits give the RGH41 greater flexibility complementing the breadth of applications in which the RG2 is already used, from coordinate measuring and layout machines to electronics assembly and test, linear motors and a host of custom linear motor solutions.

Digital range


RGH41T – 10 µm resolution
 RGH41D – 5 µm resolution
 RGH41G – 2 µm resolution
 RGH41X – 1 µm resolution
 RGH41N – 0.4 µm resolution
 RGH41W – 0.2 µm resolution
 RGH41Y – 0.1 µm resolution
 RGH41H – 50 nm resolution

Analog range

RGH41B – 1 Vpp differential (single limit)
 RGH41A – 1 Vpp differential (dual limit)

- Non-contact open optical system.
- Large installation tolerances.
- High-speed operation up to 15 m/s.
- Industry-standard digital and analog output options.
- Resolutions from 10 µm to 50 nm.
- Integral reference and dual limit sensors.
- Integral set-up LED.
- Uses Renishaw RGS40-S self-adhesive scale.

RGH45 encoder system



Renishaw's RGH45 readhead offers all the benefits of the market-proven RG4 linear encoder system – high-speed, non-contact performance with filtering optics to guarantee reliable performance over dirt, contamination and scratches.

The RGH45 readhead is designed for use with Renishaw's high-accuracy stainless steel RTLR40 tape scale. Enclosed within a rugged die-cast housing, the readhead uses proven solid state components to give outstanding reliability.

Dual limit switch sensing is also included as standard to provide dedicated signals for each end-of-axis indication, together with a repeatable reference mark (datum).

Installation is quick and easy to achieve thanks to generous readhead set-up tolerances and a rapid scale installation technique that uses the motion of the axis to lay the scale, which is then locked to the substrate via a single clamp fixed with Loctite®. Renishaw's unique set-up LED indicates when optimum conditions have been achieved, removing the need for complicated oscilloscopes or set-up equipment.

RGH45 is available with self-adhesive RTLR40-S tape scale or RTLR40 with Renishaw's unique *FASTRACK* track system that allows easy scale replacement – ideal for long machines that need to be sectioned for transit. Both scale types feature high-accuracy graduations marked directly onto stainless steel, without any coatings, providing immunity to damage from harsh solvents.

These added benefits give RGH45 readheads greater flexibility, making them ideal for use in a variety of applications including linear motors, FPD manufacturing, electronics assembly and test, printing machines and a variety of high-speed motion control systems.

Digital range

RGH45T – 10 µm resolution
 RGH45D – 5 µm resolution
 RGH45G – 2 µm resolution
 RGH45X – 1 µm resolution
 RGH45N – 0.4 µm resolution
 RGH45W – 0.2 µm resolution
 RGH45Y – 0.1 µm resolution

Analog range

RGH45A – 1 Vpp differential

- Uses RTLR40 and RTLR40-S high-accuracy stainless steel tape scale.
- Unique filtering optics and DC light servo.
- Large installation tolerances.
- Excellent dirt immunity.
- High-speed operation – up to 10 m/s.
- Industry standard digital and analog output options.
- Resolutions from 10 µm to 0.1 µm.
- Integral reference and dual limit sensors.
- Integral set-up LED.

RGS40-G glass scale



The RGS40-G is a 40 µm chrome on glass scale designed for use with Renishaw's RG4 series RGH40 filtering readheads.

The RGS40-G system offers many of the features that have made Renishaw's famous RGS tape scale such a success – high-speed, non-contact optical performance that is immune to dust, light oil and scratches.

The RGH40 benefits from filtering optics and an integral set-up LED which ensure easy installation and reliable operation.


The RGS40-G scale is easy to install and can be mounted directly to the substrate using either mechanical clips or specially-formulated adhesive.

In addition to these features, the RGS40-G is ideally suited for applications where the scale does not need to be mastered to the substrate. The thermal behaviour of RGS40-G can be compensated for by simply entering the coefficient of expansion of the scale into the host controller.

The RGS40-G boasts an extensive list of application areas, e.g. linear motion stages, linear motors, scientific instruments, metrology instruments, optical inspection, XY stages, medical equipment.

- Suitable for use with RGH40 series readheads.
- Available in 8 convenient lengths.
- Defined thermal behaviour.
- Reliable dirt immunity.
- Compatible with reference marks and limit switches.
- Clamp or adhesive mounting options.
- Can be mounted on any substrate.
- 3 × 18 mm cross section for compact installation.

FASTRACK and RTLR40-S incremental linear encoder scale system



RTL40 linear encoder tape scale from Renishaw combines $\pm 15 \mu\text{m/m}$ accuracy with the ruggedness of stainless steel. Two versions are available: self-adhesive RTL40-S and RTL40 for use with the revolutionary *FASTRACK* track system from Renishaw.

Designed for applications that demand accuracy and an independent expansion coefficient with tape scale convenience, RTL40-S and RTL40 are read by Renishaw's RGH45 readhead. RGH45 offers resolutions to $0.1 \mu\text{m}$, 10 m/s maximum speed, excellent dirt immunity and provides significant motion control performance improvements over magnetic, inductive or coarse-pitch optical encoders.

RTL40-S is laid onto the substrate using its self-adhesive backing tape. An application tool makes this a quick, simple and inexpensive process. A clamp is fitted at a single point to lock the scale to the substrate using fast curing Loctite® adhesive.

RTL40 (without self-adhesive) is used with *FASTRACK*. In this case, the scale is held securely in place by two miniature, yet rugged, guide rails. Again, the scale is clamped in a single point to allow independent expansion with extremely low hysteresis, even over wide temperature ranges. If damaged, the scale can be pulled out of the guide rails and quickly replaced, even where access is limited, thus reducing machine downtime. This feature also makes the linear encoder system ideal for large machines that need to be sectioned for transit.

RTL40-S and RTL40 with *FASTRACK* are suitable for many applications, including FPD manufacturing and inspection machines, printing machines, linear motors, axes that are exposed to potential damage, large CMMs and other machines that require the scale to be installed/removed for transit, or simply for any application where thermal expansion of the scale must be independent of the machine structure.

- Graduations marked directly onto stainless steel scale with no coatings.
- High-accuracy ($\pm 15 \mu\text{m/m}$) scale. Further improvement possible with error correction.
- Compatible with rugged and reliable RGH45 readheads.
- RTL40 scale expands at its low thermal coefficient ($10.6 \mu\text{m/m}^\circ\text{C}$).
- Use with *FASTRACK* for very low hysteresis.
- *FASTRACK* and scale are available on reels for cut-to-suit flexibility.
- Quick installation. *FASTRACK* adds fast scale replacement capability.
- Locks to substrate via a single clamp that is fixed with fast-curing Loctite®.
- High solvent immunity.

VIONiC™ series encoder system



The VIONiC encoder series integrates Renishaw's filtering optics design and interpolation technology. This creates a high-performance, digital all-in-one, incremental optical encoder which has the benefit of eliminating the need for additional adaptors or separate interfaces.

VIONiC is suitable for use across a wide range of demanding applications, including those which require dynamic motion control, superior accuracy and faster speeds.

Available in two variants, the VIONiC and VIONiCplus™ readheads offer a wide range of configurations to optimize the speed and performance of motion control systems. Both variants are quick and simple to install with wide set-up tolerances and automatic calibration.

The standard version of VIONiC incorporates dynamic signal processing techniques giving improved signal stability with Sub-Divisional Error (SDE) of typically $\leq \pm 30$ nm and resolutions down to 20 nm.

For even greater performance the VIONiCplus system can achieve an SDE of $\leq \pm 10$ nm and resolutions down to 2.5 nm, helping to realize world-leading motion control performance from a 20 μ m pitch incremental system.

- Compact readhead (35 mm x 13.5 mm x 10 mm).
- Compatible with linear and rotary scales with IN-TRAC auto-phase optical reference mark (datum).
- Third-generation filtering optics optimized for even lower noise (jitter).
- Dynamic signal processing provides ultra-low Sub-Divisional Error of typically $\leq \pm 30$ nm (VIONiC) or as low as $\leq \pm 10$ nm (VIONiCplus).
- Auto Gain Control, Auto Balance Control and Auto Offset Control ensure consistent signal strength for long-term reliability.
- Integral set-up LED for ease of installation.
- Maximum speed to 12 m/s (3.63 m/s at 0.1 μ m resolution).
- Digital signals direct from the readhead: VIONiC resolutions from 5 μ m to 20 nm VIONiCplus resolutions from 0.1 μ m to 2.5 nm.
- Integral dual limits (linear only).
- Operating temperature to +70 °C.
- Optional Advanced Diagnostic Tool (ADT) to optimize set-up and assist with system fault-finding.

System features

Need a higher speed?


- At its highest clock rate (50 MHz counter speed) the VIONiC readhead outputs quadrature edges with a minimum separation of 25.3 ns to allow this maximum possible speed at fine resolutions.

Need higher accuracy?

- VIONiC readheads are compatible with a range of linear and rotary scales, from $\pm 1 \mu\text{m/m}$ low expansion linear spar scales to ± 1 arc second total installed accuracy rings.

Need superior motion control?

- VIONiCplus implements our latest interpolation algorithms and signal processing techniques to achieve a Sub-Divisional Error as low as $< \pm 10 \text{ nm}$. Low SDE directly equates to low velocity ripple which is important for constant velocity applications, such as scanning measurement systems. VIONiCplus' intelligent interpolation chip can achieve 8,000 x interpolation which equates to 2.5 nm resolution directly out of the readhead. This system is used when precision and repeatability is of paramount importance.



Typical SDE graph for VIONiC and VIONiCplus readheads

VIONiC readheads




VIONiC readhead

- 20 μm high-performance, digital all-in-one incremental open optical encoder. It offers resolutions down to 20 nm and has a wide range of configurations to optimize the speed for your motion control system. VIONiC's dynamic signal processing gives improved signal stability with Sub-Divisional Error of typically $< \pm 30 \text{ nm}$ to help realize superior motion control performance. For example VIONiC combined with stainless steel RTLC scale can be used across a range of linear motion control applications with ribbon scale convenience and unrivalled ruggedness.

VIONiCplus readhead

- In addition to all the benefits of the VIONiC readhead, the VIONiCplus readhead offers finer resolutions down to 2.5 nm and best in class Sub-Divisional Error as low as $< \pm 10 \text{ nm}$, suitable for the most demanding applications. VIONiCplus can be used with very high accuracy 'zero' thermal expansion RELM spar scale to provide the highest level of metrology performance.

TONiC™ encoder system



Renishaw's TONiC series represents a generation of super-compact encoders, designed for highly-dynamic precision motion systems, bringing higher accuracy, speed and greater reliability to a wide variety of demanding industry sectors.

The readhead is complemented by the latest evolution of RGSZ20 gold tape scale, REXM ultra-high accuracy angle encoder and *FASTRACK* / *RTL*C scale system with bi-directional optical *IN-TRAC* reference marks, in addition to established RSLM stainless steel scale, RELM high-accuracy ZeroMet scale and RESM rotary rings.

For ultimate reliability and high dirt immunity, TONiC readheads incorporate third-generation filtering optics, tuned for even lower noise (jitter) and further enhanced by dynamic signal processing including Auto Gain Control and Auto Offset Control. The result is low Sub-Divisional Error (SDE) giving smoother velocity control for improved scanning performance and increased positional stability.

TONiC readheads also feature a detachable analog or digital interface in the form of a robust, convenient connector that can be located up to 10 m from the readhead. The interface offers digital interpolation to 1 nm resolution, with clocked outputs for optimized speed performance at all resolutions for industry-standard controllers.

- Compact readhead (35 mm × 13.5 mm × 10 mm).
- Compatible with RGSZ20 gold tape scale, *FASTRACK* / *RTL*C scale system RSLM, RELM, RESM, RESD and REXM with customer-selectable *IN-TRAC* auto-phase optical reference mark (datum).
- Third-generation filtering optics optimized for even lower noise (jitter).
- Dynamic signal processing inside the readhead, provides ultra-low cyclic error of typically ± 30 nm.
- Auto Gain Control ensures consistent signal strength for long-term reliability.
- Increased ride height tolerance and patented set-up LED for ease of installation.
- Maximum speed to 10 m/s (3.24 m/s at 0.1 μ m resolution).
- Detachable analog or digital connector with integral interpolation to 1 nm resolution (0.00075 arc seconds).
- Integral dual limits (linear only).
- Operating temperature to +70 °C.
- Dual resolution version available.

System features

Reference mark


Form	<i>IN-TRAC</i> reference mark, directly in incremental track Refer to RGSZ, <i>FASTRACK</i> / RTLC, RELM, RSLM, RESM, RESD or REXM data sheets for reference mark location Bi-directionally repeatable across full speed and temperature range Electronically phased, requires no physical adjustment
Selection	T1xx0 : Single reference mark selection by magnetic actuator (self-adhesive A-9653-0143 or bolted A-9653-0290), customer positioned. T1xx1 and T2xx1 : No selector required, all reference marks output
Repeatability	Unit of resolution repeatability, over full operating temperature and speed

Dual limit switches (linear systems only, not available on TD interfaces)

Form Magnetic actuators for P and Q limit switches

	Self-adhesive	Bolted
10 mm P limit	A-9653-0138	A-9653-0292
10 mm Q limit	A-9653-0139	A-9653-0291
20 mm P limit	A-9653-0237	–
20 mm Q limit	A-9653-0238	–
50 mm P limit	A-9653-0235	–
50 mm Q limit	A-9653-0236	–

Trigger point Leading edge of magnet from direction of travel



Mounting Self-adhesive or bolted.

Position Customer-placed at desired locations

Repeatability <0.1 mm

Dynamic signal processing

Real time signal conditioning for optimized performance across a range of operating conditions

- Automatic Gain Control (AGC)
- Automatic Offset Control (AOC)

Ultra-low cyclic error of ± 30 nm

Calibration

Simple calibration at the press of a button, no physical adjustment required

Optimization of incremental and reference mark signals

TD dual resolution interfaces

Allows output to be switched between two resolutions

NOTE: It is recommended that movement should be halted before switching resolutions

No limit outputs

TONiC™ DOP (dual output) encoder system



Renishaw's TONiC series encoders are now available with simultaneous dual output interfacing.

The robust DOP interface can be situated up to 10 m from the TONiC readhead and offers simultaneous analog and digital outputs with interpolation to 1 nm resolution. Digital outputs are clocked for optimized speed performance at all resolutions for industry-standard controllers.

The readhead is complemented by the latest evolution of RGSZ20 gold tape scale, REXM ultra-high accuracy angle encoder and *FASTRACK* / RTLC scale system with bi-directional optical *IN-TRAC* reference marks, in addition to established RSLM stainless steel scale, RELM high accuracy ZeroMet scale and RESM rotary rings.

For ultimate reliability and high dirt immunity, TONiC readheads incorporate third-generation filtering optics, tuned for even lower noise (jitter), further enhanced by dynamic signal processing including Auto Gain Control and Auto Offset Control. The result is low Sub-Divisional Error (SDE), giving smoother velocity control for improved scanning performance and increased positional stability.

- Compact readhead (35 mm x 13.5 mm x 10 mm).
- Detachable DOP interface with integral interpolation to 1 nm resolution (0.00075 arc seconds) and simultaneous digital and analog outputs.
- Compatible with RGSZ20 gold tape scale, *FASTRACK* / RTLC scale system, RSLM, RELM, RESM, RESD and REXM with customer-selectable *IN-TRAC* auto-phase optical reference mark (datum).
- Third-generation filtering optics optimized for even lower noise (jitter).
- Dynamic signal processing inside the readhead provides ultra-low Sub-Divisional Error of typically ± 30 nm.
- Auto Gain Control ensures consistent signal strength for long-term reliability.
- Increased ride height tolerance and integral set-up LED for ease of installation.
- Maximum speed to 10 m/s (3.24 m/s at 0.1 μ m resolution).
- Integral dual limits (linear only).
- Operating temperature to +70 °C.

System features

Reference mark


Form	<i>IN-TRAC</i> reference mark, directly in incremental track
	Refer to RGSZ, <i>FASTRACK</i> / RTLC, RELM, RSLM, RESM, RESD or REXM data sheets for reference mark location
	Bi-directionally repeatable across full speed and temperature range
	Electronically phased, requires no physical adjustment
Selection	T1xx0 : Single reference mark selection by magnetic actuator (self-adhesive A-9653-0143 or bolted A-9653-0290), customer-positioned
	T1xx1 and T2xx1 : No selector required, all reference marks output
Repeatability	Unit of resolution repeatability, over full operating temperature and speed

Dual limit switches (linear systems only)

Form	Magnetic actuators for P and Q limit switches
------	---

	Self-adhesive	Bolted
10 mm P limit	A-9653-0138	A-9653-0292
10 mm Q limit	A-9653-0139	A-9653-0291
20 mm P limit	A-9653-0237	–
20 mm Q limit	A-9653-0238	–
50 mm P limit	A-9653-0235	–
50 mm Q limit	A-9653-0236	–

Trigger point	Leading edge of magnet from direction of travel
---------------	---



Mounting	Self-adhesive or bolted.
Position	Customer-placed at desired locations.
Repeatability	<0.1 mm

Dynamic signal processing

Real-time signal conditioning for optimized performance across a range of operating conditions

- Automatic Gain Control (AGC)
- Automatic Offset Control (AOC)

Ultra-low cyclic error of typically ± 30 nm

Calibration

Simple calibration at the press of a button, no physical adjustment required

Optimization of incremental and reference mark signals

RGSZ20 gold scale



Renishaw's patented RGSZ20 20 μm gold scale features customer-selectable optical *IN-TRAC* reference marks. Uniquely, these are directly embedded into the incremental channel to enable electronic auto-phasing simply by pressing a button.

RGSZ20 scale is suitable for use with the TONiC encoder, featuring dynamic signal processing, ultra-low cyclic error (± 30 nm) and resolutions to 1 nm.

The scale is supplied with a specially formulated adhesive backing tape. Installation is quick, easy and suits both high-volume production and one-off field service installations.

To simplify customer inventory and maximize production flexibility, the scale can be supplied on a reel for 'cut-to-suit' convenience at the point of installation.

RGSZ20 is suitable for mounting to most common engineering materials including metals, granites, ceramics and composites, whilst the RGSZ20-P polyester-coated version has an increased resilience to solvent and lubricant attack.

The scale ends are rigidly fixed to the axis substrate by means of epoxy-fastened end clamps, eliminating the need to drill holes. Because the scale has a very small cross section, it is 'mastered' to the substrate and matches its thermal expansion. Differential movement between the scale and the substrate is close to zero, even throughout significant temperature swings.

- *IN-TRAC* optical reference marks embedded directly into the incremental channel.
- Compatible with the TONiC encoder system.
- 'Cut-to-length' flexibility.
- Lengths from 20 mm to over 50 m.
- Protective lacquer or tough polyester coating option for applications using harsh solvents.
- Quick and easy one-person installation.
- Affixes to most common engineering materials.
- Self-adhesive.
- Dual limits provide end-of-travel indication.
- Linearity of ± 3 $\mu\text{m}/\text{m}$; ± 0.75 $\mu\text{m}/60$ mm.
- RGSN20 version is supplied without *IN-TRAC* reference marks.

Technical specifications

Scale

Type	<p>RGSZ20-S: High-stability gold-plated steel tape with protective polymer coating. Fitted with a self-adhesive backing tape.</p> <p>RGSZ20-T: High-stability gold-plated steel tape with protective polymer coating. No self-adhesive backing tape.</p> <p>RGSZ20-P: High-stability gold-plated steel tape with tough polyester coating for use in applications requiring resistance to harsh solvents. Fitted with a self-adhesive backing tape.</p> <p>RGSZ20-Q: High-stability gold-plated steel tape with tough polyester coating for use in applications requiring resistance to harsh solvents. No self-adhesive backing tape.</p> <p>NOTE: RGSN20 variants of all above scales are manufactured without reference marks.</p>
Scale pitch	20 µm
Linearity	<p>RGSZ20-S and RGSZ20-T: ±3 µm/m; ±0.75 µm/60 mm</p> <p>RGSZ20-P and RGSZ20-Q: ±5 µm/m; ±1.5 µm/60 mm</p>
Scale length	20 mm to 50 m in 50 mm increments (>50 m by special order)
Substrate materials	Metals, ceramics and composites with expansion coefficients between 0 and 23 µm/m/°C (e.g. steel, aluminum, ZeroMet, granite, ceramic etc.)
Expansion coefficient	Matches that of substrate material with scale ends fixed by epoxy-mounted end clamps
End fixing	<p>Epoxy-mounted end clamps (A-9523-4015)</p> <p>Approved epoxy adhesive (A-9531-0342)</p> <p>Performance <1 µm movement over temperature range -20 °C to +50 °C</p>
Operating specification	<p>Temperature: -10 to +120 °C (Scale only, also refer to readhead data sheet)</p> <p>Minimum installation temperature: +10 °C</p> <p>Humidity: 80% maximum RH (non-condensing)</p>

Reference mark

Type	<p><i>IN-TRAC</i> reference mark, directly embedded into incremental track</p> <p>50 mm (nominal) spacing</p> <p>Bi-directional position repeatability</p>
Selection	Single reference mark selection by magnetic actuator (A-9653-0143), customer positioned
Repeatability	Unit of resolution repeatability (bi-directional) across full system-rated speed and temperature ranges

Limit switches

Type	Magnetic actuators; with dimple triggers Q limit, without dimple triggers P limit
Trigger point	The limit output is nominally asserted when the readhead limit switch sensor passes the limit magnet leading edge, but can trigger up to 3 mm before that edge
Mounting	Customer placed at desired locations
Repeatability	<0.1 mm

SiGNUM™ series readhead



Renishaw's SR readhead and Si interface are part of the SiGNUM range of optical encoders.

They have been designed for use with Renishaw's range of high-accuracy RESM and REXM angle encoders and RSLM and RELM linear encoders which incorporate the *IN-TRAC* bi-directional reference mark.

Like all Renishaw encoders, the SiGNUM range offers high-speed, reliable operation and open, non-contact performance with excellent immunity to dirt and electrical noise.

The interface incorporates dynamic signal control which, combined with the patented filtering optics, ensure excellent signal integrity and exceptionally low cyclic error.

The Si interface can be mounted remotely and a small connector on the readhead cable allows it to be fed easily through machines where access is restricted.

Readhead (SR)

SR005A – 0.5 m cable
SR010A – 1.0 m cable
SR015A – 1.5 m cable
SR030A – 3.0 m cable
SR050A – 5.0 m cable
SR100A – 10.0 m cable

Interface unit (Si)

Si-NN-0004 – 5 µm
Si-NN-0020 – 1 µm
Si-NN-0040 – 0.5 µm
Si-NN-0100 – 0.2 µm
Si-NN-0200 – 0.1 µm
Si-NN-0400 – 50 nm
Si-NN-1000 – 20 nm
Si-HN-2000 – 10 nm
Si-HN-4000 – 5 nm
Si-NN-0000 – Analog
Si-NN-0001 – Low noise analog

- *IN-TRAC* bi-directional reference mark and on-scale dual limit outputs.
- Compatible with RESM and REXM (rotary) and RELM and RSLM (linear) scales.
- Operating temperature up to +85 °C.
- Speeds up to 12.5 m/s (4591 rev/min @ Ø52 mm).
- Dynamic signal control to give cyclic error of typically ±30 nm.
- SiGNUM software for easy installation and system diagnostics.
- Integral LEDs for optimum set-up and system diagnostics.
- Industry-standard analog and digital outputs with resolutions from 5 µm to 5 nm (40 to 0.0038 arc seconds).
- Non-contact open optical system.
- Filtering optics provide excellent dirt immunity.
- High flex, UL-approved cable.

System features

IN-TRAC optical reference mark

- Integrated within the graduation for compact dimensions and simplified alignment.
- Electronically phased, requiring no physical adjustment.
- Sub-micron repeatability in both directions of travel over full operating temperature and speed range.
- Mid-point (RELM and RSLM), end-point (RELE and RSLE) or customer-selectable (RSLC).



Dynamic signal control

- Real-time signal conditioning for optimized performance across a range of operating conditions.
- Includes Auto Gain Control (AGC), Auto Offset Control (AOC) and Auto Balance Control (ABC).
- Ultra-low cyclic errors, typically ± 30 nm.



Calibration at the touch of a button

- Click of a mouse via SiGNUM software or CAL button on Si interface.
- Optimization for all output signals.

Integrated LED diagnostics

- Simplifies initial alignment and set-up.
- Reference mark and limit status.

Dual optical limit switch

- For linear and rotary axes, provides end-of-travel indication.
- User-selectable positioning.
- Independent output for each limit position.
- Ideal for linear and partial arc rotary applications.



In-line connector (option)

- In-line connector between readhead and interface for easy connectivity.
- IP68.
- Protective caps available.



SiGNUM software

- PC-based, providing real-time set-up, calibration and diagnostics.
- USB connection to SiGNUM Si interface.
- Simultaneous multiple-axis connectivity.
- Can be connected during full servo-loop operation.
- Latest version of software available for download from www.renishaw.com.

Recommended minimum PC requirements for the software:

- USB1.1
- .NET Framework 1.1 (redistributable version included with the software)
- Microsoft® Windows® 2000, Vista, XP, Windows® 7 or Windows® 10
- Microsoft® Internet Explorer 5.01 or later
- Pentium® II processor
- 128 MB RAM
- Screen resolution 800 x 600, 16-bit colors



SiGNUM™ with FANUC serial interface



The FANUC serial compatible Si-FN interface is part of the SiGNUM family of optical position encoders featuring the *IN-TRAC* autophase reference mark.

The interface connects to a standard SR readhead which works with the RESM high-accuracy angle encoder providing FANUC serial output to work with FANUC CNC controllers.

Like all Renishaw encoders, the SiGNUM range offers high-speed, reliable operation and open, non-contact performance with excellent immunity to dirt and electrical noise.

The interface incorporates dynamic signal control which, combined with the patented filtering optics, ensure excellent signal integrity and low cyclic error.

The Si-FN interface can be mounted remotely and a small connector on the readhead cable allows it to be fed easily through machines where access is restricted.

Readhead (SR)

SR005A – 0.5 m cable
SR010A – 1.0 m cable
SR015A – 1.5 m cable
SR030A – 3.0 m cable
SR050A – 5.0 m cable
SR100A – 10.0 m cable

Interface unit (Si)

Si-FN-0052 – Ø52 mm ring
Si-FN-0104 – Ø104 mm ring
Si-FN-0209 – Ø209 mm ring
Si-FN-0417 – Ø417 mm ring

- FANUC compatible serial communication eliminates need for FANUC 'High Resolution Serial Output Circuit'.
- Resolutions up to 2^{26} positions per revolution.
- *IN-TRAC* bi-directional reference mark and on-scale dual limit outputs.
- IP64 sealed readhead.
- Compatible with RESM (52 mm, 104 mm, 209 mm and 417 mm diameters).
- Operating temperature up to +85 °C.
- Speeds up to 12.5 m/sec (4,591 rev/min @ Ø52 mm).
- Dynamic signal control to give cyclic error of typically ± 30 nm.
- SiGNUM software for ease of installation and system diagnostics.
- Integral LEDs for optimum set-up and system diagnostics.
- Non-contact design for exceptional dynamic performance.
- High flex, UL-approved cable.

System features

IN-TRAC optical reference mark

- Integrated within the scale graduations for compact dimensions and simplified alignment
- Electronically phased, requiring no physical adjustment
- Sub arc second repeatability in both directions of travel over full operating temperature and speed range



Dynamic signal control

- Real-time signal conditioning for optimized performance across a range of operating conditions.
- Includes Auto Gain Control (AGC), Auto Offset Control (AOC) and Auto Balance Control (ABC).
- Ultra-low cyclic error, typically ± 30 nm.

Calibration at the touch of a button

- Click of a mouse via SiGNUM software or CAL button on Si interface.
- Optimization for all output signals.

Integrated LED diagnostics

- Remote access for convenient viewing.
- Simplifies initial alignment and set-up.
- Reference mark and limit status.



Dual optical limit switch

- Provides end-of-travel indication.
- User-selectable positioning.
- Independent output for each limit position.
- Ideal for partial rotation applications, e.g. machine tool A or B axes (RESM ring encoder).



SiGNUM software


- PC-based, providing real-time set-up, calibration and diagnostics.
- Full-function DRO capability.
- USB connection to SiGNUM Si interface.
- Simultaneous multiple-axis connectivity.

Recommended minimum PC requirements for the software:

- USB1.1
- .NET Framework 1.1 (redistributable version included with the software)
- Microsoft® Windows® 2000, Vista, XP, Windows® 7 or Windows® 10
- Microsoft® Internet Explorer 5.01 or later
- Pentium® II processor
- 128 MB RAM
- Screen resolution 800 x 600, 16-bit colors



RELM linear ZeroMet™ scale



RELM high-accuracy scale is compatible with Renishaw's VIONiC, TONiC and SiGNUM range of high-performance encoders, featuring the *IN-TRAC* auto-phase optical reference mark.

RELM offers the highest accuracy of any 20 μm pitch encoder system available today, combined with low thermal expansion ZeroMet to suit the most demanding precision applications.

RELM offers excellent dirt immunity and easy set-up, whilst offering levels of performance previously only available from delicate fine pitch systems.

RELM is easy to design into most applications, due to the flexible mounting methods, integral set-up LEDs and optional software.

System features

- *IN-TRAC* bi-directional auto-phase optical reference mark.
- High accuracy, certified to $\pm 1 \mu\text{m}$ up to 1 m, calibrated against International Standards.
- Robust ZeroMet offers $0.75 \pm 0.35 \mu\text{m}/\text{m}^\circ\text{C}$ thermal expansion plus ease of handling and installation.
- Dual limits provide on-scale end-of-travel indication.
- Scale mounting with self-adhesive or clips and clamps.

RSLM linear stainless steel scale

System features


- Total accuracy of $\pm 4 \mu\text{m}$ over 5 m.
- Available in defined lengths up to 5 m.
- Coilable for simple storage and handling.
- *IN-TRAC* auto-phase optical reference mark.
- Robust special composition stainless steel with defined coefficient of thermal expansion $10.1 \pm 0.2 \mu\text{m}/\text{m}/^\circ\text{C}$ @ 20°C .
- Dual limits provide on-scale end-of-travel indication.

RSLM high-accuracy stainless steel scale is compatible with Renishaw's VIONiC, TONiC and SiGNUM range of high-performance encoders, offering advanced features including dynamic signal processing and the *IN-TRAC* optical reference mark.

RSLM scale is available in lengths up to 5 m with an overall accuracy better than $\pm 4 \mu\text{m}$ on 5 m lengths – an industry first! Combined with readheads featuring ultra-low Sub-Divisional Error (SDE), unique filtering optics, resolution to 1 nm and simple installation and set-up, RSLM provides all the performance of a fine pitch system with the benefits of a $20 \mu\text{m}$ encoder.

RSLM offers the ease of use of a tape scale yet the performance of a glass spar; the scale can be coiled for simple storage and handling yet behaves as a spar once uncoiled. Available with a number of *IN-TRAC* reference mark options and a choice of mechanical or adhesive mounting, RSLM is perfect for long-travel applications where metrology cannot be compromised.

RTLC high-accuracy incremental linear encoder scale system



RTLC linear encoder tape scale from Renishaw combines $\pm 5 \mu\text{m/m}$ accuracy with the ruggedness of stainless steel. Two versions are available; self-adhesive RTLC-S and RTLC for use with the revolutionary *FASTRACK* track system from Renishaw.

Designed for applications that demand high accuracy and an independent expansion coefficient with tape scale convenience, RTLC-S and RTLC are read by Renishaw's compact and reliable VIONiC and TONiC family of readheads.

RTLC-S is laid onto the substrate using its self-adhesive backing tape. A patented application tool makes this a quick, simple and inexpensive process. A clamp is fitted at a single point to lock the scale to the substrate.

RTLC (without self-adhesive) is used with *FASTRACK*. In this case, the scale is held securely in place by two miniature, yet rugged, guide rails. Again, the scale is clamped in a single point to allow independent expansion with extremely low hysteresis, even over wide temperature ranges. If damaged, the scale can be pulled out of the guide rails and quickly replaced, even where access is limited, thus reducing machine downtime. This feature also makes the new linear encoder system ideal for large machines that need to be sectioned for transportation.

RTLC-S and RTLC with *FASTRACK* are suitable for many applications, including FPD manufacturing and inspection machines, P-V manufacturing, linear motors with aluminum substrates, axes that are exposed to potential damage, large CMMs and other machines that require the scale to be installed/removed for transit, or simply for any application where thermal expansion of the scale must be independent of the machine structure.

- High-accuracy ($\pm 5 \mu\text{m/m}$) scale. Further improvement possible with error correction.
- Compatible with VIONiC and TONiC high-performance readheads.
- RTLC scale expands at its own low thermal coefficient ($10.1 \pm 0.2 \mu\text{m/m/}^\circ\text{C}$ @ 20°C).
- Use with *FASTRACK* for very low hysteresis.
- *FASTRACK* guide rails are pre-aligned in reels for cut-to-suit flexibility.
- Quick installation. *FASTRACK* adds fast scale replacement capability.
- Scale can be locked to the substrate at a single datum point anywhere along the axis.
- RTLC scale can bridge gaps in the *FASTRACK* up to 25 mm.
- High solvent immunity.

System features



Example accuracy test result of 3400 mm length of RTLC scale

High-accuracy RTLC and RTLC-S scale

- $\pm 5 \mu\text{m/m}$ accuracy @ 20°C , including slope and linearity. Linearity of $\pm 2.5 \mu\text{m/m}$ can be achieved with two point error correction.
- Hardened stainless steel construction is rugged and reliable, with high scratch and solvent resistance.
- Independent expansion coefficient ($10.1 \pm 0.2 \mu\text{m/m/}^\circ\text{C}$ @ 20°C).
- Very low hysteresis: e.g. sub-micron on a center-clamped 2 m axis over the entire operating temperature range.
- $20 \mu\text{m}$ scale pitch.
- Features optical *IN-TRAC* reference marks every 50 mm; identify one or more using the reference mark selector magnet(s).
- Scale can be cut to length using a guillotine, for easy customisation.
- Track-mounted RTLC using the revolutionary new *FASTRACK* or self-adhesive mounted RTLC-S.

Compatible with VIONiC, VIONiCplus™ and TONiC readheads

- Filtering optics and Auto Gain Control for high reliability and solid Lissajous signals.
- Dynamic signal processing ensures ultra-low Sub-Divisional Error. Result: smoother scanning performance.
- High signal-to-noise ratio provides ultra-low jitter for optimum positional stability.
- Auto-phasing of *IN-TRAC* reference mark.
- Industry-standard 1 Vpp analogue outputs (TONiC readhead only) and RS422 digital resolutions available.
- Clocked outputs ensure optimized speed performance for all resolutions, for a wide variety of industry-standard controllers.
- DOP Dual output interfaces available to provide simultaneous analogue and digital outputs (TONiC systems only).



	VIONiC	VIONiCplus	TONiC
Outputs	Digital resolutions from $5 \mu\text{m}$ to 20nm direct from the readhead	Digital resolutions from $0.1 \mu\text{m}$ to 2.5nm direct from the readhead	Analogue 1 Vpp only RS422 digital resolutions from $5 \mu\text{m}$ to 1nm available when connected to a Ti, TD or DOP interface
SDE (typical)	$< \pm 30 \text{nm}$	$< \pm 10 \text{nm}$	$\pm 30 \text{nm}$
Jitter (RMS)	down to 1.6nm	down to 1.6nm	down to 0.5nm
Maximum speed	12 m/s	12 m/s	10 m/s

RESM angle encoder scale



The RESM is a one-piece stainless steel ring with 20 µm scale marked directly onto the periphery, featuring the *IN-TRAC* auto-phase optical reference mark.

The RESM offers impressive accuracy with resolution to 0.00075 arc second, suiting the most demanding precision applications.


Read by Renishaw's VIONiC, TONiC and SiGNUM encoder systems, it has high tolerance to dirt, scratches and greasy fingerprints that can cause other encoder systems to miscount.

The low profile RESM, with large internal diameter, is easy to design into most installations. Equally important, its low mass, low inertia design does not compromise system performance. Available in a wide range of sizes and line counts, providing compatibility with industry-standard controllers.

System features

- Compatible with the VIONiC, TONiC and SiGNUM encoder systems offering industry standard analog or digital incremental outputs.
- *IN-TRAC* bi-directional optical reference mark.
- Graduation accuracy to ± 0.5 arc second (550 mm ring).
- Patented taper mount simplifies integration and minimizes installation errors.
- Large internal diameter for ease of integration.
- Available in sizes from $\varnothing 52$ mm to $\varnothing 550$ mm with line counts from 8,192 to 86,400.
- Custom sizes also available.
- Low mass and low inertia.
- Ultra-low inertia versions also available.
- Dual limits (SiGNUM only).

RESD distance-coded scale



The RESD is a one-piece stainless steel ring with 20 µm scale marked directly onto the periphery, featuring distance-coded *IN-TRAC* auto-phase optical reference marks.

Distance-coded reference marks are spaced at defined unique intervals, allowing a controller to calculate absolute position with only a small movement of the axis. The RESD offers impressive accuracy with resolution to 0.001 arc second, suiting the most demanding precision applications.

Read by Renishaw's TONiC encoder system, it has high tolerance to dirt, scratches and greasy fingerprints that can cause other encoder systems to miscount.

The low profile RESD, with large internal diameter, is easy to design into most installations. Equally important, its low mass, low inertia design does not compromise system performance. RESD is available in a range of sizes and line counts, providing compatibility with industry-standard controllers.

System features

- Compatible with the TONiC T20x1 encoder system offering industry-standard analog or digital incremental outputs.
- Distance code *IN-TRAC* bi-directional optical reference marks allow absolute position to be calculated after a small movement.
- High-speed operation, up to 3,672 rev/min (10 m/s).
- Graduation accuracy to ±0.99 arc second (209 mm ring).
- High-resolution, 2 nm and 1 nm digital versions.
- Angular resolution to 0.002 arc second.
- System repeatability to 0.003 arc second.
- Patented taper mount simplifies integration and minimizes installation errors.
- Large internal diameter enables easy design-in.
- Available in sizes from Ø52 mm to Ø209 mm with line counts from 8,192 to 32,768.
- Low mass and low inertia.
- Integral set-up LED on readhead for quick set-up and instant 'health check' at any time.
- True absolute encoders also available from Renishaw. Please contact your local representative for details.

REXM/REXT ultra-high accuracy angle encoder



With zero coupling losses and exceptional repeatability, the REXM/REXT ultra-high accuracy angle encoder achieves better than ± 1 arc second total installed accuracy.

Like the RESM encoder, the REXM/REXT is a stainless steel ring with the scale graduations marked axially onto the periphery, but with a number of differences to improve upon RESM's already impressive accuracy.

REXM/REXT has a thicker cross section, to ensure that the only significant installation error is eccentricity.

Eccentricity is easily removed using two readheads, either with Renishaw's DSi (Dual Signal interface), or by combining the signals inside the host controller. The only errors remaining are graduation errors and readhead SDE, both of which are so small they are often negligible.

As a non-contact encoder, REXM/REXT offers dynamic performance advantages, eliminating coupling losses, oscillation, shaft torsion and other hysteresis errors that plague enclosed encoders.

Combining two readheads is easy with the DSi, which also offers an angularly repeatable reference position (*propoZ*™) which is unaffected by bearing wander or power cycling.

REXM/REXT total installed accuracy grades:

REXM/REXT diameter	Total installed accuracy
≥ 100 mm	± 1 arc second
75 mm	± 1.5 arc second
≤ 57 mm	± 2 arc second

Designed for axes that are limited to partial rotation, REXT rings have two reference marks, oriented diametrically opposed, for use with partial arc versions of DSi. DSi processes these reference marks to give a single, angularly-repeatable *propoZ* reference output.

- Use with two VIONic, TONic and SiGNUM encoders, combined with DSi to give ultra-high accuracy.
- Installed accuracy to ± 1 arc second with dual readheads.
- Wide range of standard sizes from 52 mm to 417 mm.
- Large internal diameter for ease of integration.
- Flange-mounted with easy 4-point adjustment method.
- Angularly-repeatable *propoZ* reference position is unaffected by bearing wander or power cycling.

Optical encoder accessories and custom solutions



Scale applicator kits and applicators ensure the easiest, most precise installation for all readhead types.



Magnetic reference mark actuators are required to produce a repeatable home position for all RG2/4 readheads. Limit switch actuators (end-of-travel output) are available in various lengths and types.



Various end clamps for RGS scale.



Not all application needs can be met with standard products. Often a custom solution is necessary, so talk to us about your requirements; anything from a special connector to a purpose designed angle encoder ring.



Assembled extension cables, bulk cable and connectors to suit all system combinations.



Swipe blocks enable a functional test of readheads without having to install a complete axis.

To provide complete solutions for optical linear and angle encoders a full range of accessories is available, from reference mark actuators to extension cables. Renishaw is committed to providing position feedback solutions to satisfy customer specific requirements, such as custom angle encoder diameters and cross sections. Please contact Renishaw for further information on how we can meet your specific requirements.

Magnetic encoder overview

AksIM true-absolute encoder

Encoder module and off-axis encoder.



Orbis absolute rotary encoder



OnAxis™ encoder ICs

AM4096, AM4096Q, AM256, AM256Q and AM512B, AM8192B.



OnAxis encoder modules

RMB20, RMB28, RMB29, RMB30 and RMF44



OnAxis robust encoders

RM08, RM22, RM36, RM44, RE22, RE36 and RE58



LM robust incremental encoders

LM10, LM13, LM15 and LA11 with magnetic scales and rings.



OnAxis commutation and incremental encoders

RMC22 and RMC35.



Accessories

Magnets and magnet actuators, interfaces and adapters, applicator tools, end clamps, reference marks, zeroing pen for RM44



The magnetic encoder range is designed and manufactured by RLS d.o.o (www.rls.si) in Slovenia, Renishaw's partner in encoder technology.

OnAxis magnetic encoders

Based on the proven OnAxis Hall sensor technology, a range of incremental and absolute encoder solutions are produced for use in harsh environments. There are many housing options available for use in a wide range of applications including automotive, industrial, medical and marine. Custom designs can also be offered to match specific design requirements.



OnAxis – The IC senses the angular position of a permanent magnet placed above it. The sine and cosine signals produced are then converted to absolute angle position data with a fast flash interpolator.



The sensor chip can be used directly on a circuit board or packaged into a protective housing.



The ability of the encoder to operate with a gap between the magnetic actuator and the encoder chip allows its incorporation into designs that need isolation of the moving elements.



Standard interface flanges with bearing/shafts can be provided for easy integration to existing designs.



Why rotary magnetic?



- Resolutions to 13 bit (8,192 cpr).
- High-speed operation to 60,000 rpm.
- Non-contact, frictionless design.
- Excellent dirt immunity to IP68.
- Operational temperature from $-40\text{ }^{\circ}\text{C}$ to $+125\text{ }^{\circ}\text{C}$.
- Industry-standard absolute, incremental and analog output formats.
- Accuracy to $\pm 0.2^{\circ}$.
- Simple installation – with self-locating design.

Optional 58 mm mounting flanges



RM08 super-small non-contact rotary encoder

RM08



Features

- Super small size – 8 mm diameter body
- 3.3 V or 5 V power supply versions
- Non-contact, frictionless design
- High speed operation to 30,000 rpm
- Protection grade IP68
- Incremental resolution to 4096 cpr
- Synchro serial with 5 to 12 bit resolution
- Industry standard analogue sinusoidal, incremental, SSI and linear output formats
- Accuracy to $\pm 0.3^\circ$
- RoHS compliant (lead free)
- For limited space applications

Technical specifications


Mechanical data

Encoder housing material	Aluminum
Encoder mass	< 2 g (with 200 mm long wires)
Wire thickness	AWG30
Magnet material	SmCo (Sm17Co2), NiCuNi coated
Magnet mass	0.4 g


Environmental data

Operating and storage temperature	-40 °C to +85 °C
-----------------------------------	------------------

Timing diagram for incremental outputs




Timing diagram for SSI




RM08 / RE08 dimensions

RM08



Dimensions and tolerances in mm

Orbis™ true absolute rotary encoder



Features

- True absolute encoder
- 14 bit resolution
- 8 proprietary Hall sensor ASICs
- Through-hole design enables its mounting anywhere along the shaft
- Wide installation tolerances
- Self-calibration after assembly
- Multiturn counter option
- Built-in self-diagnostics
- Status LED
- SPI, SSI, BiSS-C, PWM and asynchronous serial communication

Technical specifications

System data

Reading type	Axial reading
Resolution	14 bit
Maximum speed	10,000 rpm
Accuracy	±0.2° (optimal installation)
Accuracy thermal drift	±0.01°/°C
Repeatability	±2 LSB

Electrical data

Supply voltage	4.5 V to 5.5 V (at the connector)
Power consumption	65 mA typical (no output load)


Mechanical data

Available magnet sizes (ID)	12 mm, 16 mm
Available magnetic actuator sizes (ID)	6 mm, 8 mm, 10 mm, 12 mm, 15 mm
Readhead outer diameter	45 mm
Readhead inner diameter	16 mm

Environmental data

Operating temperature	0 °C to +85 °C
Storage temperature	-40 °C to +105 °C

Dimensions



*CCW - positive measuring direction

Dimensions and tolerances in mm

AksIM™ off-axis absolute rotary encoder



Features

- True absolute
- Single track
- Resolution to 20 bits
- No hysteresis
- Non contact
- High speed
- Low profile
- Custom ASIC based magnetic sensor
- Built-in self-monitoring
- Integrated status LED
- SSI, SPI, PWM, CAN or asynchronous serial RS422 communication interface
- Corrosion resistant
- Multiturn counter option

Applications

Robotic arm joints



Pan/tilt positioning



Precision gearboxes



Medical



UAV



Technical specifications

System data

Reading type	Axial reading
Resolution	From 16 to 20 bit and 16 bit multiturn counter option
Maximum speed	> 10,000 rpm
Encoder accuracy	±0.05° (before installation - errors caused by mounting inaccuracy of the readhead, ring and drive shaft are not included)

Electrical data

Supply voltage	4 V to 6 V – voltage on readhead. Consider voltage drop over cable.
Power consumption	Typ. 115 mA, max. 150 mA
Voltage drop over cable	~ 55 mV/m – without load

Mechanical data


Available ring sizes (outer diameter)	49 mm (ring MRA7) 80 mm (ring MRA8)
Cable	Ø4.2 ±0.2 mm, PUR highly flexible cable, drag-chain compatible, double-shielded

Environmental data

Operating temperature	-30 °C to +85 °C with static cable -10 °C to +80 °C with cable under dynamic conditions
Storage temperature	-40 °C to +85 °C


Dimensions

Ring type 7



NOTE:
CCW positive measuring direction.

Ring type 8



NOTE:
CCW positive measuring direction.

Dimensions and tolerances in mm

Linear and ring magnetic encoders

The linear and ring encoder system consists of a compact readhead and a magnetized ring or scale. The readhead detects the magnetic signature of the magnetized scale or ring and processes these signals to the required output.



The magnetic incremental rings bring reliable solutions to tough, hard-working applications including spindles, lathes and other machine tool applications.



The system is easy to install with a set-up LED on the readhead and an applicator tool for the tape scale.




A stick-on reference mark can be easily installed at the required position using the provided tool. Alternatively, the reference mark can be ordered at a set position within the scale.



The scale can be supplied on a reel or cut to a specific length. A stainless steel cover strip can be provided to protect the scale.

Why linear or ring magnetic?

- High-speed operation
- Excellent dirt immunity to IP68
- Stick-on reference mark
- Integral set-up LED
- Industry-standard digital and analog output options



LA11 absolute linear magnetic encoder system




Features

- True absolute system
- Suitable for highly dynamic control loops
- Small footprint
- High accuracy
- Resolutions up to 0.244 μm
- Axis lengths up to 16.3 m
- Speeds up to 7 m/s at 0.977 μm resolution
- Integral status LED
- Synchronous (SSI, SPI, BiSS) communication protocols available
- Parallel incremental output (analogue or digital)
- Double shielded, drag-chain compatible cable
- Simple and fast installation
- Robust measuring principle
- Excellent degree of protection to IP68

Applications

SMT pick and place



Printing technology



Machine tools



Assembly lines




Medical



Technical specifications

System data		Environmental data	
Incremental pole length	2 mm	Temperature	Operating 0 °C to +55 °C Storage -20 °C to +70 °C
Maximum scale length	16.3 m	Vibration (55 Hz to 2000 Hz)	300 m/s ² (IEC 60068-2-6)
System accuracy	±40 µm/m	Shock (11 ms)	300 m/s ² (IEC 60068-2-27)
Short range accuracy	< ±10 µm/10 mm	Humidity	100% (condensation permitted)
Coefficient of thermal expansion (CTE)	11 ±1 µm/m/K	EMC immunity	IEC 61000-6-2 (particularly: ESD: IEC 61000-4-2; EM fields: IEC 61000-4-3; Burst: IEC 61000-4-4; Surge: IEC 61000-4-5; Conducted disturbances: IEC 61000-4-6; Power frequency magnetic fields: IEC 61000-4-8; Pulse magnetic fields: IEC 61000-4-9)
Hysteresis	< 2 µm at 0.1 mm ride height	EMC emission	IEC 61000-6-4 (for industrial, scientific and medical equipment: IEC 55011)
Unidirectional repeatability	Unit of resolution	Environmental sealing	IP68 (according to IEC 60529)
Electrical data			
Power supply	5 V ± 5 % (voltage on readhead) and from 8 V to 30 V Consider voltage drop over cable		
Reverse polarity protection	Only for 5 V		
Set-up time after switch-on	< 350 ms		
Power consumption (without any load)	< 170 mA at 5 V power supply		
Voltage drop over cable	~ 80 mV/m - without load		
Mechanical data			
Mass	Readhead (with 1 m cable, no connector) 41 g, magnetic scale 60 g/m		
Cable	PUR high-flexibility cable, drag-chain compatible, double-shielded. Durability: 20 million cycles at 20 mm bend radius at whole temperature range		


LMA dimensions



* Scale surface print does not represent the actual ordering code. For orientation purpose only.

RoLin™ miniature encoder family

The RoLin miniature encoder family has been specifically designed for integration into high volume OEMs. High speed, high reliability and high resolution coupled with large installation tolerances all ensure that this sensor can be installed quickly and cost effectively every time.



Technical specifications

	RLM	RLB
Readhead size	12 mm × 8.5 mm × 5 mm	14 mm × 8 mm × 2 mm
Application	Linear, rotary (axial or radial reading)	
Outputs	TTL, RS422, SSI and BiSS output options available	Incremental quadrature TTL (ABZ; optionally with periodic reference mark)
Resolutions	From 0.244 µm for linear and corresponding CPR for rotary applications (depends on ring diameter)	
Speed	Up to 80 m/s for linear and corresponding rpm for rotary applications (depends on ring diameter)	
Sub-divisional error (SDE)	±2 µm	
Pole length	2 mm	
MS scales accuracy grade	±40 µm/m	
Connection accessories	E201/RLACC	

	RLC2HD	RLC2IC
Readhead size	14 mm × 8 mm × 2 mm	20 mm × 13.5 mm × 3.3 mm
Application	Linear, rotary (axial or radial reading)	
Outputs	Incremental quadrature TTL (ABZ; optionally with periodic reference mark)	Incremental quadrature RS422 (ABZ; optionally with unique or periodic reference marks)
Resolutions	From 0.244 µm for linear and corresponding CPR for rotary applications (depends on ring diameter)	
Speed	Up to 80 m/s for linear and corresponding RPM for rotary applications (depends on ring diameter)	
Sub-divisional error (SDE)	±2 µm	
Pole length	2 mm	
MS scales accuracy grade	±40 µm/m	
Connection accessories	E201/RLACC	

Scale and ring options



Scales with or without cover foil



Axial rings



Radial rings

Interferometric feedback solutions

The RLE system is a unique, advanced homodyne laser interferometer system, specifically designed for position feedback applications.

Simple system architecture reduces hardware requirements to:

- RLU laser unit
- one or two RLD10 detector heads
- measurement optics

Optical configurations allow for the following measurement types:

- linear
- planar (X-Y)
- differential

System components can be configured for specific applications to achieve:

- sub-nanometer resolution
- axis lengths up to 4 m
- velocities up to 2 m/s

The RLU laser unit, containing the HeNe laser tube, system electronics and the fiber optic launch mechanism, forms the heart of the RLE system.

Fiber optic launch capability allows the laser unit to be mounted remotely from the measurement axis, thereby eliminating a potential heat source.

RLU laser unit

Two models of the RLU are available – RLU10 and RLU20.

- Both are available in single or dual axis configurations
- The key difference is frequency stability (RLU10 = 50 ppb* and RLU20 = 2 ppb*)

Position output signals from the RLU are available as:

- differential digital RS422 with resolutions up to 10 nm
- 1 Vpp analog sine/cosine signal with a period of 158 nm (PMI)[†] and 316 nm (RRI)^{††}

Higher resolution interpolator options are also available:

- REE to provide resolutions up to 0.39 nm
- RPI20 to provide resolutions up to 38.6 picometers

* parts per billion

† PMI – plane mirror interferometer

†† RRI – retro reflector interferometer



RLE10 laser system



RLU10 laser user



X-Y stage application
– Anorad – Rockwell
Automation

RLE laser interferometer systems

RLD detector units

Most RLD10 detector units contain the fringe detection scheme, interferometer optic and integrated laser beam steerer(s).

- **Single pass interferometer (RRI)** – uses an external retroreflector target optic
 - axis lengths up to 4 m
 - 0° or 90° beam launch orientations
 - 316 nm signal period
 - Digital quadrature resolution of 20 nm
 - RPI20 resolution of 77.2 picometers
- **Double pass interferometer (PMI)** – uses an external plane mirror target optic.
 - Axis length up to 1 m
 - 0° or 90° beam launch orientations
 - 158 nm signal period
 - Digital quadrature resolution of 10 nm
 - RPI20 resolution of 38.6 picometers
- **No internal interferometer** – allows for the head to be configured with external optics for linear, angular and straightness measurements.
 - 0° beam launch orientation only
- **Double pass differential interferometer** – requires external plane mirror targets for both the reference and measurement arms
 - Axis length up to 1 m
 - 158 nm signal period
 - Digital quadrature resolution of 10 nm
 - RPI20 resolution of 38.6 picometers

As the measurement and reference beam paths have an element of commonality, this detector head offers a number of benefits:

- Measures stage/workpiece versus column/ tool for true differential measurement
- Removal of errors due to thermal translation of the interferometer mounting
- Minimization of the effects of laser frequency instability as this relationship effects both paths
- Common mode environmental effects enable the detector head to be mounted on the outside of the process chamber with minimal effect on accuracy

RLE system benefits

The unique fiber optic launch based architecture provides interferometer system performance with the ease of use normally associated with glass or tape scale based encoder systems.

These architectural advantages are achieved through a combination of the following features:

- **Fiber optic laser launch** – Enables the laser light to be taken directly to where the axis position needs to be measured, eliminating the requirement for remote beam benders, splitters and associated mounts.
- **Integrated laser beam steerers** – Incorporated in all RLD10 detector heads to further reduce alignment complexity.
- **Integrated interferometer optics** – Most RLD detector heads include prealigned interferometer optics and fringe detection system, making installation simple.
- **Removal of potential heat error source** – Fiber optic launch enables the RLU laser head to be mounted in a location that is insensitive to dissipated heat without affecting alignment or stability.



RLD10 single pass interferometer



RLD10 double pass interferometer



RLD10 differential interferometer



RLE system accessories

RCU10 compensation system

When using any laser interferometer system in a non-vacuum environment, some form of refractive index compensation is required to maintain accuracy under varying environmental conditions. This is because the fundamental fringe spacing (unit of count) is a function of the wavelength of the laser light which varies fractionally depending on the refractive index of the air through which it travels.

To counter these refractive index changes, Renishaw offers the RCU10 real-time quadrature compensation system, providing the following features and benefits:

- ± 1 ppm positioning over a broad range of environmental conditions
- Simultaneous implementation of multiple error correction algorithms
- Individual air temperature sensors for each axis
- RCU10-CS configuration software enables the RCU10 system to be configured to match the specific requirements of the application
- One to six axis capability: multi-axis systems can be formed using a number of individual RCU10 compensators connected via a high-speed serial link

RPI20 parallel interface

Renishaw's RLE laser interferometer systems directly produce 1 Vpp sine/cosine signals with periods of 316 nm and 158 nm from single and double pass interferometers respectively. These sinusoidal signals can be interpolated to provide ultra-high resolution positional feedback.

Although sine/cosine interpolation is available within a number of proprietary control systems, the analog bandwidth of these systems is often designed for tape and glass scale based encoders. These scale systems produce relatively coarse signal periods and the sinusoidal frequencies for any given velocity are considerably lower than those produced by an interferometer. This bandwidth limitation means that laser interferometer feedback systems can only be used in low velocity motion applications.


The Renishaw RPI20 parallel interface has been specifically designed to overcome this limitation by providing ultra-high resolution parallel format output at high speed. The RPI20 interpolates by 4096, produces resolutions of up to 38.6 picometers and has an analog input bandwidth of <math>< 6.5 \text{ MHz}</math>, enabling the interferometer system to be used in applications that have velocity requirements of up to 1 m/s.



RCU10 compensator and sensors



RPI20 parallel interface



The RCU10 can be used to compensate digital position feedback signals from a variety of sources and can produce compensated output signals in analog or digital format.

HS20 laser head

The Renishaw HS20 laser head, in combination with an external linear optics kit, forms a non-contact interferometric based encoder system for long axis, high-accuracy, linear position feedback applications.

The HS20 laser system is suitable for use in harsh machine shop environments with part per million (ppm or 1 µm/metre) accuracy being achievable for axis lengths of up to 60 m.†

Features of the HS20 laser head include:

- Stabilized Class II (<1 mW) HeNe laser source
- User-selectable output resolution and update rate
- Industry-standard AQuadB positional output
- 24 V system status lines
- Visual error reporting via two integral tri-colour LEDs

A single set of configuration (DIP) switches enables the HS20 to be configured to match the application. These allow selection of nominal output resolutions of 79 nm, 158 nm, 316 nm or 633 nm when used with a single pass retroreflector based interferometer configuration, and output update rates of 16 MHz, 8 MHz, 4 MHz, 2 MHz and 1 MHz, ensuring count integrity.

A digital, serial comms output is available for direct signal strength monitoring.

To maintain accuracy over a range of environmental conditions, the HS20 should be used in combination with the RCU10 compensation system, which compensates for air refractive index changes due to variations in the ambient environment. The RCU10 can also be used to convert a laser wavelength related resolution to a more standard resolution. For example, in some long axis applications the RCU10 is used to convert a resolution of 633 nm to 1 µm.

† When used together with RCU10 environmental compensator

In addition to the laser head, compensation system and optics, Renishaw offer the following components to ease installation and ensure system reliability:

HS20 alignment plate – this robust steel assembly provides mounting locations for both the HS20 and interferometer optics. This provides translation and rotation adjustment to ease laser alignment.




Standard linear optics – suitable for axis lengths up to 30 m, includes two retroreflectors and one interferometer.



Long range linear optics – suitable for axis lengths up to 60 m, includes one standard retroreflector, one long range retroreflector, a periscope and one interferometer.



Long range laser steerer – provides 0.6 mrad of pitch and yaw adjustment to ease laser alignment.



Beam-protecting ducting – supplied in 3 m sections, this beam-protecting ducting includes an air distribution system which 'stirs' the air along the axis, breaking down the thermal gradients.





Additive manufacturing solutions




Additive manufacturing solutions

Renishaw are a leading manufacturer of advanced metal additive manufacturing systems and expert provider of customer tailored solutions

Renishaw offer a total solution for metal additive manufacturing, from systems, metal powders, ancillaries and software through to an expert advice and support service.

Additive manufacturing, also called 3D printing, is a process used to create three-dimensional parts from a digital file. It involves building up, and solidifying, thin layers (25µm–50µm) of metal material to create complete parts. Standard materials include: Steel (316L), Inconel (In625, In718), Cobalt Chromium (CoCr), Titanium (Ti64Al4V) and Aluminum (AlSi10Mg) and with our open system our customers can develop their own materials and parameters.

The technology, also known as Laser Powder Bed Fusion (LPBF), is able to produce complex shapes which cannot be produced by 'traditional' techniques such as casting, forging and machining. Additive manufacturing introduces new design possibilities, including opportunities to combine multiple components in production, minimize material use and reduce tooling costs.



Machine specifications and key features



	AM400	RenAM 500M*
Maximum part building area	245 mm x 245 mm x 300 mm (X, Y, Z)	250 mm x 250 mm x 350 mm (X, Y, Z)
Build rate **	5 cm ³ – 20 cm ³ per hour	
Scan speed	up to 2000 mm/s	
Positioning speed (maximum)	7000 mm/s	
Layer thickness	20 µm – 100 µm	
Laser	400 W ytterbium modulated fibre laser	500 W ytterbium modulated fibre laser with dynamic focussing
Laser beam diameter	70 µm diameter at powder surface	
External dimensions ***	1700 mm x 800 mm x 2025 mm (L x W x H)	
Power supply	230 V 1 PH, 16 A	
Key features	Class leading patented inert atmosphere generation and low Argon consumption	Renishaw optical system with dynamic focusing Automated powder sieving and recirculation
	Flexible and rapid material changeover	Dedicate to one material for production use Ergonomically located load hopper
	Patented SafeChange™ filter	High capacity swappable dual SafeChange™ filter
		Open access material development
Materials in development	New materials are continuously under development. Please contact Renishaw for an up to date list	

** M suffix denotes a system specifically designed for Manufacturing mass production use

** Dependent upon material, density and geometry. Not all materials process at the highest build rate.


*** Without accessories

**For further information or pricing please call Renishaw direct at: 847-286-9953
or go to www.renishaw.com/additive**

The benefits of metal additive manufacturing

Metal Additive Manufacturing opens up significant production and financial benefits across the manufacturing process first from shortening the design and development cycle through rapid prototyping and lower tooling costs; to easier direct part replacement (especially legacy parts) in Maintenance, Overhaul and Repair operations.

Moreover, truly significant value-add and financial benefits arise through the ability to design and grow complex parts that simply cannot be manufactured through traditional means.



Applications

Healthcare - dental and medical

Thin wall dental copings are manufactured in production volumes. The highly complex, tailored parts are ideally suited to additive manufacturing – where intricate parts with a low overall volume are competitive when compared with traditional methods.


Early adopters of metal additive manufacturing for medical orthopedics benefit from manufacturing complex geometries and structures in high grade materials such as titanium.



Mold tooling and conformal cooling channels

Metal additive manufacturing can be used to help improve production cycle times and productivity in injection molding.

Metal mold tools used for injection moldings contain channels to cool the mold. With conventional tool making methods these cooling channels are drilled into the tool in straight lines. Metal additive manufacturing allows cooling channels to be designed and built to contour the mold. This helps to improve cooling performance, extend the life of the mold and reduce waste.



Automotive

The motor sport industry has adopted metal additive manufacturing to produce customized parts, for example cooling ducts.

Development contributes to a high proportion of the work in this industry and speed of turnaround of prototyped parts is key to competitive advantage. Functional metal parts can be rapidly produced and performance tested.



Aerospace

Metal additive manufactured parts are used in the aerospace industry for functional parts including engine turbine blades, fuel systems and guide vanes.

The topological optimization of parts can improve functionality and reduce weight. Lighter parts can contribute to lighter aircraft and reduce fuel consumption.




Additive manufacturing software

QuantAM™


QuantAM is Renishaw's own build preparation software designed specifically for Renishaw AM platforms, allowing tighter integration into the machine control software and the ability to accurately and rapidly review all build files for Renishaw AM systems, including those from third party packages. With a highly intuitive user workflow and functionality that gives the easy ability to develop your material parameters QuantAM is the most powerful of software packages for Renishaw AM.

Key features


- Competitive monthly subscription licensing guaranteeing access to all the latest updates
- STL geometry import and direct CAD model import
- Part orientation
- Add support structures
- Material development module with .CSV data import for materials development arrays
- Copy and edit material files
- Duplicate, orientate and position multiple parts
- Rapidly review your geometry and laser tool path slice-by-slice
- Review discrete laser exposures within each slice




1. Part orientation




2. Part support



3. Build set-up



Material parameter development



4. Scan path generation and review

Renishaw Build Processor for Magics


The Renishaw Build Processor for Magics from Materialise Software provides a flexible platform software package.

- Renishaw's extensive process knowledge combined with industry standard Magics' powerful software.
- Highly flexible platform with the ability to control up to 170 parameters.
- User interface: using predetermined parameters the build can be prepared in a few simple steps.
- Enhances the capabilities of Renishaw AM systems.

InfiniAM™ - Coming 2017

Renishaw's newest software offering InfiniAM is set to offer Machine Build Status Monitoring and Build Review in the cloud and to your mobile device.

- Multi-machine
- Build Process Monitoring
- Graphical reporting
- Machine Status Monitoring
- Mobile applications
- Remote access to machine (where enabled)



Additive Manufacturing Solutions Center




Located within Renishaw's new 133,000 sq. ft. facility in West Dundee, IL, USA is our 5000 sq. ft. Additive Manufacturing Solution Center.

Renishaw Solutions Centers provide a secure development environment in which you can build your knowledge and confidence using AM technology. Equipped with the latest AM systems and staffed with knowledgeable engineers, our Solutions Center offers you a fast and accessible way to rapidly deploy this exciting technology in your business.

Renishaw will support you throughout your investigation and business case development process, helping you to optimize your design, build your confidence in the AM process, and gain the evidence you need to make investment decisions, all at predictable and manageable costs.

Whilst AM can create complex geometries in a single process step, some level of finishing is generally required to produce functional products. Our world-leading knowledge and expertise in metrology, machining and finishing processes will assist you to develop an integrated manufacturing solution for your AM parts.



Additive Manufacturing Solutions Center service

Service details	Incubator cell access (fully supported)	Incubator cell access (partially supported)
Dedicated incubator cell	✓	✓
Secure office & workstation	✓	✓
Reserved access to de-build room ¹	✓	✓
Renishaw AM operator support	✓	✓
Applications support to optimize initial build	✓	✓
HSE induction & system training	✓	✓
Free powder pre-load	✓	✓
Substrates & other consumables	✓	✓
Power & Argon supply	✓	✓
Powder consumption (price per kg) ²	✓	✓
Build integrity checks – density, hardness, finish	✓	✓
Build traceability – design, run times, process parameters, materials usage, inspection results	✓	✓
Applications engineering support ³	✓	✗
Design for A.M. (D4AM) training	✓	✗
Reserved access to ⁴ : Heat treatment, Part removal (EDM, saw), Support removal, Surface treatment	✓	✗

In addition to Incubator Cell hire Renishaw can offer a range of further Production Process Development Services for those customers wishing to develop an integrated AM manufacturing process. Services include:

- CAM-driven 5-axis CNC machining, including process development and operator support
- Metrology (CMM and/or gauging) including process development & operator support
- Fixtures for machining and inspection
- Materials lab access (in Stone, UK) supporting SEM analysis, porosity checks, tensile & fatigue testing


¹ Central manned facility. Customers can reserve for sole use when required

² Machines supplied with full hopper of powder. Customer pays for consumption. N/A if customer supplies powder

³ Supported by local Customer Projects team with access to UK HQ personnel as required

⁴ Machining and metrology are central, manned facilities that customers can reserve for their sole use when required. Customer Project Engineers are available to develop machining and measurement processes. Chargeable time includes machine set-up and operation. Hourly rate is inclusive of consumption of standard cutting tools and use of standard styli. Customised tooling and styli will be charged at cost.

Bespoke services are POA. Please contact us for pricing.



Styli and accessories





Page 8-3

Technical specifications and quick reference guides

Quick selection from our extensive range.



Page 8-8

Accuracy at the point of contact

An explanation of why it is important to choose the right stylus for your application, and an overview of the entire range of stylus types.



Page 8-13

M2 threaded stylus range

Styli for use with the industry-standard CMM probes TP2, TP20 and TP200.



Page 8-21

M3 threaded stylus range

Styli for use with manual CMM probes TP1 and TP6 and the most flexible scanning probe, SP25M.



Page 8-27

M4 threaded stylus range

Optimized for stiffness and weight, styli purposely designed for the high accuracy TP7M and our comprehensive range of probing for machine tools.



Page 8-38

M5 threaded stylus range

A premium range specifically designed for highest accuracy scanning probes from Renishaw and other manufacturers.



Page 8-53

Styli for Faro arms and Zeiss probing systems

These styli have been designed especially for use on Faro portable arm CMMs and with Zeiss probing systems.



Page 8-87

Accessories

All of the 'bits and pieces' that you need to assemble anything from the most complex stylus clusters to a simple star.

Technical specifications


Ball material properties

Stylus type	Material	Grade	Deviation from spherical form	Structure	Composition	Purity	Density	Hardness	Compression strength	Bending strength	Fracture toughness K1c
			(μm)	–	(wt%)	(%)	(g/cm^3)	HV	(MPa)	(MPa)	($\text{MN}/\text{m}^{3/2}$)
AL ₂ O ₃ ruby balls	Synthetic ruby monocrystalline	Grade 5*	0.13	mono	99% AL ₂ O ₃	99.90	3.90	2300	2100	400-700	1
Silicon nitride balls	Hard pressed Si ₃ N ₄	Grade 5*	0.13	poly	Si ₃ N ₄	90	3.0-3.2	1600	3000	850	6
Zirconia oxide balls	Sintered ZrO ₂	Grade 5*	0.13	poly	ZrO ₂	90-95	6.05	1200	2000	1000	10
Alumina hollow balls	White ceramic sintered alumina AL ₂ O ₃	–	1	poly	AL ₂ O ₃	99.80	3.8-3.9	1900	2500	350	3.5
Silver steel disks	Silver steel	–	1	–	–	–	8	450	–	–	–
Silver steel simple cylinder	Silver steel	–	Roundness 4 μm	–	–	–	8	200	–	–	–
Ruby ball ended cylinder	Synthetic ruby	Ball: Grade 5*	Ball deviation from spherical form: 0.13 Concentricity: Ball/cylinder 4 μm	mono	99% AL ₂ O ₃	99.90	3.99	2300	2300	400-700	1
Tungsten carbide ball ended cylinder	Tungsten carbide	–	+ 20 μm end radius	–	92-93.5% WC 6.5-8% CO	14.8	14.95	1550	6000	–	–
Silver steel simple pointer	Silver steel	–	Cone angle 30°	–	–	–	8	300	–	–	–
Tungsten carbide radius end pointer	Tungsten carbide	–	Cone angle 30°	–	92-93.5% WC 6.5-8% CO	99.90	15	1550	6000	–	–
Aluminum hollow balls	Al. alloy 6082-T6	–	30 μm	–	95.2-98.3% AL	–	2.7	95	–	–	–

* Refers to DIN-5401 ball grade standard
* Grade 3 sphericity balls are available on request.

Extension material properties

Material	Coefficient of expansion @ 25 °C
Stainless steel	16x10 ⁻⁶ /°C
Tungsten carbide	5x10 ⁻⁶ /°C
White ceramic sintered alumina	8.1x10 ⁻⁶ /°C
Carbon fiber	-0.4x10 ⁻⁶ /°C
Titanium	9.2x10 ⁻⁶ /°C
Ruby	4.5x10 ⁻⁶ /°C
Silicon nitride	3.2x10 ⁻⁶ /°C
Zirconia	10.5x10 ⁻⁶ /°C



- A** Ball diameter
- B** Overall length
- C** Stem diameter
- D** Effective working length
- Ø M2 = 3 mm
- Ø M3 = 4 mm
- Ø M4 = 7 mm
- Ø M5 = 10 mm

M2 styli and extensions quick reference guide

These are a selection of the most popular styli.

Ruby ball / stainless steel stem

Ball diameter	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)
Length 10 mm	A-5000-7806	A-5000-7802	A-5000-7807	A-5000-7803	A-5000-3604	A-5000-4154	A-5000-4155	A-5000-4156	A-5000-4158
20 mm	–	–	A-5000-3603	A-5000-7804	A-5000-4160	A-5000-4161	–	–	–

Ruby ball / tungsten carbide stem

Ball diameter	0.3 (0.012)	0.5 (0.02)	0.7 (0.03)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
Length 10 mm	A-5000-7800	A-5000-7805	A-5000-7801	A-5003-1325	–	–	–	–	–	–
20 mm	–	A-5003-1345	A-5003-0577	SEE DRAWING	A-5003-0034	A-5003-3822	A-5003-1896	A-5003-0938	A-5003-1029	A-5003-0046
30 mm	–	–	–	A-5000-8663	A-5003-0035	A-5003-0036	A-5003-0038	A-5003-0040	A-5003-0043	A-5003-0047
40 mm	–	–	–	–	–	A-5003-0037	A-5003-0039	A-5003-0041	A-5003-0044	A-5003-0048
50 mm	–	–	–	–	–	–	–	A-5003-0042	A-5003-0045	A-5003-0049

Ruby ball / ceramic stem

Ball diameter	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
Length 30 mm	A-5003-4177	A-5003-1370	A-5003-4779	A-5003-4780
50 mm	A-5003-0064	A-5003-0065	A-5003-0066	A-5003-0470

Ruby ball / carbon fiber stem

Ball diameter	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
Length 30 mm	A-5003-4241	A-5003-4781	A-5003-4782
50 mm	A-5003-2285	A-5003-2286	A-5003-2287
75 mm	A-5003-4784	A-5003-4785	A-5003-4786
100 mm	A-5003-2289	A-5003-2290	A-5003-2291

Stylus extensions

Length	5.0 (0.20)	10.0 (0.40)	20.0 (0.80)	30.0 (1.19)	40.0 (1.58)	50.0 (1.97)	70.0 (2.76)	90.0 (3.55)
Stainless steel	A-5004-7610	A-5004-7585	A-5004-7586	A-5004-7591	A-5004-7611	–	–	–
Ceramic	–	–	–	A-5003-0070	A-5003-0071	A-5003-0072	–	–
Carbon fiber	–	–	–	–	A-5003-2280	A-5003-2281	A-5003-2282	A-5003-2283

M3 styli and extensions quick reference guide

These are a selection of the most popular styli.

Ruby ball / stainless steel stem

Ball diameter	1.0 (0.04)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
Length 21 mm	A-5000-3551	A-5000-3552	A-5000-3553	A-5000-7606	A-5000-7630
31 mm	–	–	–	A-5000-3554	A-5000-7648

Ruby ball / tungsten carbide stem

Ball diameter	0.5 (0.02)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
Length 21 mm	A-5000-7632	A-5003-0050	–	A-5003-0054	–	–	–
30 mm	–	A-5003-0051	A-5003-0052	A-5003-0055	A-5003-0057	–	–
40 mm	–	–	A-5003-0053	A-5003-0056	A-5003-0058	A-5003-0060	A-5003-0062
50 mm	–	–	–	–	A-5003-0059	A-5003-0061	A-5003-0063

Ruby ball / ceramic stem

Ball diameter	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
Length 50 mm	A-5003-0067	A-5003-0068	A-5003-0069

Ruby ball / carbon fiber stem

Ball diameter	6.0 (0.24)	8.0 (0.32)
Length 75 mm	A-5003-4860	A-5003-4861
100 mm	A-5003-4862	A-5003-4863

Stylus extensions

Length	10.0 (0.40)	20.0 (0.80)	35.0 (1.38)	50.0 (1.97)	70.0 (2.76)
Stainless steel	A-5004-7609	A-5004-7583	A-5004-7584	–	–
Ceramic	–	–	–	A-5003-0075	–
Carbon fiber	–	–	–	A-5003-4864	A-5003-4865

M4 styli and extensions quick reference guide

These are a selection of the most popular styli.

Ruby ball / stainless steel stem

Ball diameter	1.0 (0.04)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)
Length 10 mm	–	–	–	–	A-5000-6350	–	–
20 mm	A-5000-7545	A-5000-7547	A-5000-7549	A-5000-7551	SEE DRAWING	A-5000-7555	A-5000-7557
30 mm	–	–	–	–	A-5000-6352	–	–
50 mm	–	–	–	–	A-5000-7521	–	–
100 mm	–	–	–	–	A-5000-7522	–	–

Ruby ball / tungsten carbide stem

Ball diameter	1.0 (0.04)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
Length 20 mm	A-5003-4792	A-5003-2932	A-5003-4793	A-5003-4794	A-5003-4795	A-5003-4796
50 mm	–	A-5003-4797	A-5003-3680	A-5003-4799	A-5003-4800	A-5003-4801

Ruby ball / ceramic stem

Ball diameter	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)
Length 50 mm	A-5003-0235	A-5000-3709	A-5000-7795
75 mm	A-5003-0236	A-5003-2764	A-5003-4802
100 mm	A-5000-9761	A-5000-3712	A-5000-7796

Ruby ball / carbon fiber stem

Ball diameter	6.0 (0.24)	8.0 (0.32)
Length 50 mm	A-5003-1436	–
100 mm	A-5003-1358	–
150 mm	A-5003-1255	–
200 mm	A-5003-1075	–
300 mm	–	A-5003-3461

Stylus extensions

Length	10.0 (0.41)	15.0 (0.60)	20.0 (0.79)	30.0 (1.19)	50.0 (1.97)	100.0 (3.94)
Stainless steel	A-5004-7559	A-5004-7600	A-5004-7601	A-5004-7602	–	–
Ceramic	–	–	–	A-5000-7754	A-5000-7755	A-5000-7727

M5 styli and extensions quick reference guide

These are a selection of the most popular styli.

Ruby ball / tungsten carbide stem

Ball diameter	0.3 (0.012)	0.5 (0.02)	0.7 (0.03)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
Length 20 mm	A-5003-5201	A-5003-5202	A-5003-5203	A-5003-5204	A-5003-5205	A-5003-5206	A-5003-5207	A-5003-5208	A-5003-5209	A-5003-5210
30 mm	A-5003-5211	A-5003-5212	A-5003-5213	A-5003-5214	A-5003-5215	A-5003-5216	A-5003-5217	A-5003-5218	A-5003-5219	A-5003-5220
40 mm	–	–	–	–	A-5003-5221	A-5003-5222	A-5003-5223	A-5003-5224	–	–
50 mm	A-5003-5225	A-5003-5226	A-5003-5227	A-5003-5228	A-5003-5229	SEE DRAWING	A-5003-5232	A-5003-5234	A-5003-5235	A-5003-5236
75 mm	A-5003-5240	A-5003-5241	A-5003-5242	A-5003-5243	A-5003-5244	–	–	A-5003-5253	SEE DRAWING	SEE DRAWING
100 mm	–	–	–	–	–	–	A-5003-5254	–	–	–

Ruby ball / carbon fiber stem

Ball diameter	2.5 (0.10)	6.0 (0.24)	8.0 (0.32)	10.0 (0.40)
Length 20 mm	–	–	–	–
30 mm	–	–	–	–
40 mm	–	–	–	–
50 mm	–	A-5003-5237	A-5003-5238	A-5003-5239
75 mm	–	A-5003-5250	A-5003-5251	A-5003-5252
100 mm	–	SEE DRAWING	SEE DRAWING	SEE DRAWING
150 mm	–	A-5003-5265	A-5003-5266	A-5003-5267
200 mm	–	A-5003-5268	A-5003-5269	A-5003-5270
300 mm	–	A-5003-5271	A-5003-5272	A-5003-5273

Stylus extensions

Length	10.0 (0.41)	20.0 (0.79)	30.0 (1.19)	40.0 (1.58)	50.0 (1.97)	60.0 (2.37)	70.0 (2.76)	80.0 (3.15)	90.0 (3.55)	100.0 (3.94)
CF/titanium (Ø11 mm)	–	–	–	A-5555-0647	A-5555-0648	A-5555-0649	A-5555-0623	A-5555-0650	A-5555-0651	A-5555-0652
CF/titanium (Ø20 mm)	–	–	–	A-5555-0620	A-5555-0657	A-5555-0658	–	A-5555-0621	–	A-5555-0659
Stainless steel	A-5555-0142	A-5555-0140	A-5555-0669	–	A-5555-0670	–	–	–	–	A-5555-0136
Aluminum tube	–	–	–	–	A-5555-0671	–	–	–	–	A-5555-0127

Length	120.0 (4.76)	150.0 (5.91)	180.0 (7.09)	200.0 (7.88)	250.0 (9.85)	300.0 (11.82)	400.0 (15.76)	500.0 (19.70)	600.0 (23.64)
CF/titanium (Ø11 mm)	A-5555-0425	A-5555-0424	A-5555-0653	A-5555-0654	A-5555-0655	A-5555-0642	A-5555-0656	–	–
CF/titanium (Ø20 mm)	A-5555-0660	A-5555-0661	A-5555-0662	A-5555-0663	A-5555-0427	A-5555-0664	A-5555-0665	A-5555-0667	A-5555-0668
Stainless steel	–	–	–	–	–	–	–	–	–
Aluminum tube	–	–	–	A-5555-0125	–	–	–	–	–

Accuracy at the point of contact

As industry has developed its requirement for increasingly diverse and complex manufactured parts, inspection systems have had to work hard to keep up. The use of co-ordinate measuring machines (CMMs) with probing systems and in-process inspection on machine tools are two of the solutions offered by Renishaw to help you maximize your productivity and maintain the highest quality.

Successful gaging depends very much on the ability of the probe's stylus to access a feature and then maintain accuracy at the point of contact. At Renishaw, we have used our expertise in probe and stylus design to develop a comprehensive range of CMM and machine tool styli to offer you the greatest possible precision.

These notes explain the critical features of every stylus type, helping you to choose the right design for each inspection need.

What is a stylus?

A stylus is that part of the measuring system which makes contact with the component, causing the probe's mechanism to displace. The generated signal enables a measurement to be taken. The feature to be inspected dictates the type and size of stylus used. In all cases, however, maximum rigidity of the stylus and perfect sphericity of the tip are vital.

To achieve this, Renishaw's stylus stems are produced on CNC machine tools to exacting standards. Great care is taken to ensure that location faces give maximum stiffness whilst stylus mass is optimized to suit Renishaw's range of probes.

Genuine Renishaw stylus balls are produced to the highest standards and are bonded to the stems in such a way as to ensure maximum joint integrity.

The performance of your gaging can easily be degraded if you use a stylus with poor ball roundness, poor ball location, bad thread fit or a compromised design that allows excessive bending during measurement. To ensure the integrity of the data you gather, make certain that you specify and use a stylus from the comprehensive range of genuine Renishaw styli.

What naming protocol do Renishaw use to describe their styli range?

Renishaw uses the following naming protocol to allow easy identification of styli by name and part number. The examples below show how this protocol is assigned and describe the abbreviations used:

Straight styli

M2 STY D2R L20 EWL14 d1.4SS

The above protocol describes an M2 threaded straight stylus fitted with a 2 mm diameter ruby ball. It has an overall length of 20 mm, has an effective working length (EWL) of 14 mm and has a 1.4 mm diameter stainless steel stem.

Star styli

M2 STR D2R L20 5BALL L19.5 S32

The above protocol describes an M2 threaded star stylus fitted with a 2 mm diameter ruby ball. It has five balls on the star and an overall length of 19.5 mm (from the center of the ball to the rear of the star mounting face when assembled to a probe). The span of the star cluster is 32 mm.

Disk styli

M2 DSC SD18 SLVS T2.2 L2.6 BR-Y

The above protocol describes an M2 threaded disk stylus with a spherical diameter disk of 18 mm. It is made from silver steel with a disk thickness of 2.2 mm and a length of 2.6 mm. BR stands for balls/rollers followed by yes (Y) or no (N).

Cylinder styli

M2 CYL D3 SLVS L13 EWL4


The above protocol describes an M2 threaded cylinder stylus with a critical measuring element diameter of 3 mm made from silver steel. It has an overall length of 13 mm and an EWL of 4 mm.

Extensions

M4 EXT L15 d7 SS

The above protocol describes an M4 threaded extension with a length of 15 mm and a diameter of 7 mm. The extension is made from stainless steel.

Terminology



- A Ball diameter
- B Overall length
- C Stem diameter
- D Effective working length

Overall length

Renishaw uses a standard description of overall length, measuring from the rear mounting face of the stylus to the center of the ball.

Effective working length (EWL)

This is measured from the center of the ball to the point at which the stem will foul against the feature when measuring 'normal' to the part.

Choosing a stylus

To maintain accuracy at the point of contact, we recommend that you:

Keep styli short

The more a stylus bends or deflects, the lower the accuracy. Probing with the minimum stylus length for your application is the best option.

Minimize joints

Every time you join styli and extensions, you introduce potential bending and deflection points. Try, wherever possible, to keep to the minimum number of pieces for your application.

Keep the ball as large as possible

There are two reasons for this:

- firstly, it maximizes your ball/stem clearance, thereby reducing the chances for false triggers caused by 'shanking out' on the stylus stem
- secondly, the larger ball reduces the effect of the surface finish of the component being inspected.

The range of genuine Renishaw styli

Ball material

Ruby

The industry standard and the optimum stylus ball material for a vast majority of measurement applications, ruby is one of the hardest known materials. Synthetic ruby is 99% pure aluminum oxide which is grown into crystals (or "boules") at 2000 °C using the Verneuil process.

The boules are then cut and gradually machined into a highly spherical form. Ruby balls are exceptionally smooth on the surface, have great compressive strength and a high resistance to mechanical corrosion.

Very few applications exist where ruby is not the preferred ball material, however there are two applications where balls manufactured from other materials are recommended.

The first is for heavy-duty scanning applications on aluminum. Because the materials attract, a phenomenon known as 'adhesive wear' can occur, which involves build up of aluminum from the surface onto the ball. A better ball material for such applications is silicon nitride.

The second is in heavy-duty scanning applications on cast iron. Interaction between the two materials can result in 'abrasive wear' of the ruby ball surface. For such applications, zirconia balls are recommended.

Silicon nitride

Silicon nitride possesses many similar properties to ruby. It is a very hard and wear-resistant ceramic which can be machined into very high precision spheres. It can also be polished to an extremely smooth surface finish. Silicon nitride does not have the attraction to aluminum and so does not exhibit the adhesive wear seen with ruby in similar applications. However, silicon nitride does show significant abrasive wear characteristics when scanning on steel surfaces and so its applications are best confined to aluminum.

Zirconia

Zirconia is a particularly tough ceramic material with hardness and wear characteristics approaching those of ruby. Its surface properties make it an ideal material for aggressive scanning applications on cast iron components.

Stem material

Steel

Stylus stems manufactured from stainless steel are used widely for styli with ball/tip diameters of 2 mm or greater and with lengths up to 30 mm. Within this range, one-piece steel stems offer the optimum stiffness-to-weight ratio, giving adequate ball/stem clearance without compromising stiffness with a joint between the stem and threaded body.

Please contact us if you require any styli with special ball materials. We can recommend the most suitable material for scanning different materials.

Tungsten carbide

Tungsten carbide stems are best used for maximizing stiffness with either small stem diameters required for ball diameters of 1 mm and below, or lengths up to 50 mm. Beyond this, weight can become a problem and stiffness is lost due to deflection at the stem to body joint.

Ceramic

For ball diameters greater than 3 mm, and lengths over 30 mm, ceramic stems offer stiffness comparable to steel but are significantly lighter than tungsten carbide. Ceramic stemmed styli can also offer additional crash protection to your probe as the stem will shatter in a collision.

Carbon fiber (Renishaw GF)

There are many grades of carbon fiber materials, however Renishaw GF combines optimum stiffness characteristics, both longitudinally and in torsion (important in star constructions), with extremely low weight. Carbon fiber is inert and this, combined with a special resin matrix, provides excellent protection in the most hostile of machine tool environments.

Renishaw GF is ideal for maximizing stiffness while giving very low mass for styli above 50 mm in length. It is the optimum stem material for high-accuracy strain gage technology probes with excellent vibration-damping characteristics and negligible co-efficient of thermal expansion.

The genuine Renishaw stylus range comprises several types:

Straight styli



These are the simplest form of stylus, incorporating highly spherical industrial ruby balls and a choice of stem material.

Ruby is an extremely hard material and hence stylus wear is minimized. It is also of low density, keeping tip mass to a minimum, which avoids unwanted probe triggers caused by machine motion or vibration.

Mounted on stems made from a range of materials – stainless steel, tungsten carbide, ceramic and a specialized carbon fiber material, “Renishaw GF” – these simple ruby ball styli are suitable for most inspection applications.

Each stylus has an effective working length (EWL) which is the penetration that can be achieved by the ball before the stem fouls against the feature.

The size of the ball and the EWL of the stylus chosen are dictated by the size of the feature to be inspected. However, keeping the stylus ball as large as possible and the stem as short as possible will ensure maximum ball/stem clearance, whilst providing a greater yet still rigid EWL. Using larger ruby balls also reduces the effect of the surface finish of the component being inspected.

Probing with very long stylus/extension combinations is not recommended with standard kinematic touch trigger probes as the rigidity is reduced and accuracy lost due to stylus bending. This is not the case with other types of probe such as those with strain gage technology, as their very low trigger forces permit the use of long stylus/extension combinations without a significant loss of accuracy.

Star styli



These stylus clusters provide you with multiple-tip probing of complex features and bores. Four or five ruby ball systems are mounted rigidly on a stainless steel center. Three standard sizes are offered – alternatively, you can create custom-made star styli using a 5-way stylus center and any of the genuine Renishaw stylus range.

Star styli can be used to inspect a variety of different features. Their use can reduce inspection cycle times by allowing multi-tip probing, minimizing the need to move the probe to extreme points of internal features such as the sides or grooves in a bore. Using star styli also allows effective probing in the –Z (upwards) direction when using a 5-way probe, provided that the stylus tips extend beyond the diameter of the probe body. Each tip on a star stylus requires datuming (sometimes referred to as ‘qualifying’ or ‘calibrating’) in the same manner as a single-ball stylus. The ‘span’ of star styli is taken from ball center to ball center.

Disk styli



These styli are used to probe undercuts and grooves within bores which may be inaccessible to star styli. They are ‘sections’ of highly spherical balls and are available in various diameters and thicknesses. Full rotational adjustment and the ability to add a center stylus are features of the Renishaw range of disk styli that make them particularly flexible and easy to use.

Probing with the 'spherical edge' of a simple disk is effectively the same as probing on or about the equator of a large stylus ball. However, only a small area of this ball surface is available for contact and hence thinner disks require careful angular alignment in order to ensure correct contact with the feature being probed.

A simple disk requires datuming for only one diameter (usually in a ring gage), but limits effective probing to only X and Y directions.

Adding a 'radius end roller' allows you to datum and hence probe in the Z direction, provided that the center of the 'radius end roller' extends beyond the diameter of the probe. The 'radius end roller' can be datumed on a sphere or a slip gage. Rotating and locking the disk about its center axis allows the 'radius end roller' to be positioned to suit the application.

Disks may also have a threaded center to allow the fixing of a center stylus, giving the additional flexibility of probing the bottom of deep bores (where access for the disk may be limited).

Styli for specialist applications


A range of specialist styli is available to enable probing of features such as thread form, thin sectioned material, tool setting and other specialist applications.

Cylinder styli



These are used for probing holes in thin sheet material. In addition, various threaded features can be probed and the centers of tapped holes located. Ball-ended cylinder styli allow full datuming and probing in X, Y and Z directions, thus allowing surface inspection to be performed.

Pointer and ceramic hollow ball styli



Pointer styli are designed for the inspection of thread forms, specific points and scribed lines (to lower accuracy). The use of a radius end pointer stylus allows more accurate datuming and probing of features as detailed above and can also be used to inspect the location of very small holes.

Ceramic hollow ball styli are ideal for probing deep features and bores in X, Y and Z directions, with the need to datum only one ball. There are two versions in the range, 18 mm and 30 mm diameter, specially designed for the TP2 / TP20 / TP200 and TP6 probes respectively. Probing with such a large diameter ball can average out the effects of very rough surfaces.

Tool setting styli



Typically, these are fitted with a square tip and can have threaded or plain shaft attachments. The tip faces are ground to ensure high squareness and parallelism. The TS27R tool setting probe for machining centers can also be fitted with a tungsten carbide disk stylus.

Crash protection devices



Renishaw's stylus crash protection devices are designed to break in the event of impact and protect the probe from damage.

Accessories and tools

A wide range of accessories including extensions, 4 and 5-way centers and stylus knuckles complement the genuine Renishaw stylus range to achieve fully flexible inspection.

Stylus centers



These provide maximum probing flexibility with a single probe. Taking up to five styli of the same mounting thread, this accessory allows you to build stylus configurations to your own specification.

Stylus knuckles



These give full adjustment about two axes, allowing the stylus to be orientated to probe angled features. This adjustment is especially useful when the probe cannot be correctly orientated by the probe head, or when access for the head is limited.

Stylus extensions



These provide additional probing penetration by extending the stylus away from the probe. However, using stylus extensions can reduce probe accuracy due to loss of rigidity. This is not the case with electronic probes, whose extremely low trigger forces render them less sensitive to this type of inaccuracy.

Stylus thread adaptors



These allow M2, M3, M4 and M5 threaded styli to be interchanged on the majority of touch trigger probes. They are particularly useful for adapting the extensive range of specialized application M2 styli for use on larger probes.

Stylus tools

Specifically designed for mounting styli correctly onto probes and for the construction of specialized stylus combinations, Renishaw's stylus tools protect your investment.

S7 stylus tool



The S7 stylus tool is used for tightening styli and accessories when connecting to one another or directly into the probe. It is specifically designed to yield if excessive tightening force is applied, avoiding damage to the threads of stylus and probe.

Stylus crank



A stylus crank can allow access to features that are otherwise difficult to reach, and are often used in lathe inspection applications.

Renishaw stylus kits

Renishaw styli and accessories are available in a wide selection of kits, ranging from a small precision set of the most frequently used styli, to a comprehensive set to meet virtually every inspection need.

Some sets are housed in a quality wooden case for maximum protection and superb presentation. The styli are held in a wood insert, individually located in a nylon sleeve providing protection for the mounting threads. This type of box features a removable module which houses up to twelve ruby ball styli and contains a tray for disks, tools and accessories. This allows the stylus selection for a particular inspection task to be brought to the CMM's table. The sloping lid design of this kit provides easy access to styli, minimizing handling of ruby balls and contact surfaces, thus aiding cleanliness.

Probing kits are also available to include a probe, probe head, extension bars and styli.

Custom design service

If you cannot achieve your objectives using our extensive range of standard products, Renishaw's Styli and Custom Products Division offers a unique service by providing customers with a total solution for their probing needs for CMM, machine tool or scanning applications.

The Division includes expertise in applications, design, engineering and manufacturing with extensive experience in providing tailor-made product solutions to specific customer's requirements.

In many application problems, the solution lies in the choice of the stylus which influences access of the workpiece features, inspection times and probe performance. All of these aspects are considered within the design of a custom stylus, ensuring that the solution incorporates the ideal choice of materials and optimizes probe performance for your particular application.

Renishaw's Styli and Custom Products Division has supplied over 5,000 different custom styli into probing applications worldwide, so the solution to your application problem may already exist.

For advice and further details, please contact your nearest Renishaw distributor.

Always use genuine Renishaw styli or your probe performance will be compromised!

M2 threaded stylus range

Ruby ball styli (stainless steel stems)

Ball material	Part number								
Ruby	A-5000-7806	A-5000-7802	A-5000-7807	A-5000-7803	A-5000-3604	A-5000-4154	A-5000-4155	A-5000-4156	A-5000-4158
Price	\$32	\$22	\$22	\$22	\$22	\$22	\$36	\$39	\$72
Silicon nitride	A-5004-0210	A-5004-1918	A-5003-6120	A-5004-1920	A-5003-2138	A-5003-9524	A-5004-1921	A-5004-0237	A-5004-1922
Price	\$53	\$69	\$69	\$69	\$69	\$69	\$78	\$78	\$112
Zirconia	A-5003-7757	A-5004-0165	A-5003-7723	A-5004-2913	A-5004-2914	A-5003-7261	A-5003-2186	A-5004-2203	A-5004-2915
Price	\$69	\$69	\$69	\$69	\$69	\$69	\$78	\$78	\$112
A Ball dia. mm (in.)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)
B Length mm (in.)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	11.0 (0.44)
C Stem dia. mm (in.)	0.7 (0.03)	0.7 (0.03)	1.0 (0.04)	1.0 (0.04)	1.5 (0.06)	1.5 (0.06)	2.5 (0.10)	2.5 (0.10)	2.5 (0.10)
D EWL* mm (in.)	4.5 (0.18)	4.5 (0.18)	6.0 (0.24)	6.5 (0.26)	7.0 (0.28)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	11.0 (0.44)
Mass grams	0.3	0.3	0.3	0.3	0.4	0.4	0.7	0.9	1.5

10 mm range


Ball material	Part number			
Ruby	A-5000-3603	A-5000-7804	A-5000-4160	A-5000-4161
Price	\$25	\$25	\$25	\$25
Silicon nitride	A-5003-1730	A-5004-1923	A-5003-6691	A-5004-0236
Price	\$76	\$69	\$73	\$69
Zirconia	A-5004-2916	A-5004-2917	A-5004-1057	A-5004-2918
Price	\$69	\$69	\$69	\$69
A Ball dia. mm (in.)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)
B Length mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
C Stem dia. mm (in.)	1.4 (0.06)	1.4 (0.06)	1.5 (0.06)	1.5 (0.06)
D EWL* mm (in.)	14.0 (0.56)	16.4 (0.65)	17.0 (0.67)	20.0 (0.79)
Mass grams	0.4	0.4	0.5	0.6

20 mm range

Ruby ball styli (tungsten carbide stems)

Ball material	Part number			
Ruby	A-5000-7800	A-5000-7805	A-5000-7801	A-5003-1325
Price	\$111	\$90	\$84	\$77
Silicon nitride	A-5004-2016**	A-5003-2020**	–	A-5004-2018
Price	\$189	\$169	–	\$69
Zirconia	–	A-5003-7672	A-5004-2632**	A-5004-2919**
Price	–	\$165	\$210	\$191
A Ball dia. mm (in.)	0.3 (0.012)	0.5 (0.02)	0.7 (0.03)	1.0 (0.04)
B Length mm (in.)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)
C Stem dia. mm (in.)	0.2 (0.01)	0.4 (0.02)	0.5 (0.02)	0.7 (0.03)
D EWL* mm (in.)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)	4.0 (0.16)
Mass grams	0.3	0.3	0.3	0.3

10 mm range




** Special * Effective working length

Ruby ball styli (tungsten carbide stems) – continued


Ball material	Part number					
Ruby	A-5003-1345	A-5003-0577	A-5000-7808	A-5003-0033	A-5003-0034	
Price	\$105	\$107	\$49	\$55	\$55	
Silicon nitride	A-5004-2019**	–	A-5004-1508	A-5004-2021	A-5004-1925	
Price	\$169	–	\$86	\$86	\$86	
Zirconia	A-5004-2920	A-5004-1714**	A-5004-0435	A-5004-2921	A-5004-2922	
Price	\$217	\$104	\$86	\$86	\$86	
A	Ball dia. mm (in.)	0.5 (0.02)	0.7 (0.03)	1.0 (0.04)	1.0 (0.04)	1.5 (0.06)
B	Length mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
C	Stem dia. mm (in.)	0.3 (0.012)	0.5 (0.02)	0.7 (0.03)	0.8 (0.04)	1.0 (0.04)
D	EWL* mm (in.)	7.0 (0.28)	12.0 (0.48)	7.0 (0.28)	12.5 (0.50)	12.5 (0.50)
	Mass grams	0.48	0.32	0.50	0.41	0.50

20 mm range




Ball material	Part number					
Ruby	A-5003-3822	A-5003-1896	A-5003-0938	A-5003-1029	A-5003-0046	
Price	\$27	\$72	\$78	\$78	\$44	
Silicon nitride	A-5004-1017	A-5004-1928	A-5004-1021	A-5004-1929	A-5004-1930	
Price	\$86	\$86	\$86	\$86	\$95	
Zirconia	A-5004-2923	A-5004-2924	A-5004-0437	A-5004-2925	A-5004-2926	
Price	\$86	\$86	\$86	\$86	\$95	
A	Ball dia. mm (in.)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
B	Length mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	22.0 (0.87)	20.0 (0.79)
C	Stem dia. mm (in.)	1.0 (0.04)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)
D	EWL* mm (in.)	14.0 (0.55)	15.5 (0.62)	17.0 (0.67)	22.0 (0.87)	20.0 (0.79)
	Mass grams	0.48	0.50	0.77	1.24	1.98

20 mm range



Ball material	Part number						
Ruby	A-5000-8663	A-5003-0035	A-5003-0036	A-5003-0038	A-5003-0040	A-5003-0043	A-5003-0047
Price	\$84	\$38	\$44	\$44	\$44	\$44	\$49
Silicon nitride	A-5004-2022	A-5004-1931	A-5003-7573	A-5004-1932	A-5004-1933	A-5004-1944	A-5004-1945
Price	\$86	\$86	\$86	\$86	\$86	\$86	\$95
Zirconia	A-5004-2927	A-5004-1711	A-5004-1058	A-5004-2928	A-5004-0264	A-5004-2929	A-5004-2930
Price	\$104	\$86	\$86	\$86	\$86	\$86	\$95
A	Ball dia. mm (in.)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)
B	Length mm (in.)	27.5 (1.08)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
C	Stem dia. mm (in.)	0.7 (0.03)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)
D	EWL* mm (in.)	20.5 (0.81)	22.5 (0.89)	22.5 (0.89)	22.5 (0.89)	27.0 (1.06)	30.0 (1.19)
	Mass grams	0.40	0.58	0.99	1.48	1.49	1.57

30 mm range




* Effective working length

** Special

Ruby ball styli (ceramic stems)

Ball material	Part number			
Ruby	A-5003-4177	A-5003-1370	A-5003-4779	A-5003-4780
Price	\$84	\$50	\$86	\$92
Silicon nitride	A-5004-1946	A-5004-1952	A-5004-1953	A-5004-1954
Price	\$103	\$103	\$112	\$121
Zirconia	A-5004-2931	A-5004-2932	A-5004-2933	A-5004-2934
Price	\$103	\$103	\$112	\$121
A Ball dia. mm (in)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
B Length mm (in)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
C Stem dia mm (in)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)	2.5 (0.10)
D EWL* mm (in)	27.0 (1.06)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
Mass grams	0.44	0.68	0.93	1.11


30 mm range



Ruby ball styli (carbon fiber stems)

Ball material	Part number		
Ruby	A-5003-4241	A-5003-4781	A-5003-4782
Price	\$100	\$104	\$109
Silicon nitride	A-5004-1955	A-5004-1956	A-5004-1957
Price	\$103	\$112	\$121
Zirconia	A-5004-2935	A-5004-2936	A-5004-0618
Price	\$164	\$112	\$121
A Ball dia. mm (in)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
B Length mm (in)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
C Stem dia mm (in)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)
D EWL* mm (in)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
Mass grams	0.57	0.79	0.96



30 mm range



Ruby ball styli (tungsten carbide stems)

Ball material	Part number							
Ruby	A-5003-0037	A-5003-0039	A-5003-0041	A-5003-0044	A-5003-0048	A-5003-0042	A-5003-0045	A-5003-0049
Price	\$49	\$49	\$49	\$49	\$53	\$44	\$49	\$53
Silicon nitride	A-5003-7269	A-5004-1959	A-5004-1960	A-5004-1961	A-5004-1962	A-5004-1963	A-5004-1964	A-5004-1965
Price	\$143	\$86	\$86	\$86	\$95	\$86	\$86	\$95
Zirconia	A-5004-2937	A-5004-2938	A-5004-1059	A-5004-2939	A-5004-2940	A-5004-2942	A-5004-2943	A-5004-2944
Price	\$86	\$86	\$86	\$86	\$95	\$86	\$86	\$95
A Ball dia. mm (in.)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
B Length mm (in.)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)
D EWL* mm (in.)	32.5 (1.28)	32.5 (1.28)	37.0 (1.46)	40.0 (1.58)	40.0 (1.58)	47.0 (1.85)	50.0 (1.97)	50.0 (1.97)
Mass grams	1.29	1.95	1.97	2.04	3.17	2.44	2.52	3.75

40 mm – 50 mm range




* Effective working length

Ruby ball styli (ceramic stems)

Ball material	Part number			
Ruby	A-5003-0064	A-5003-0065	A-5003-0066	A-5003-0470
Price	\$70	\$70	\$90	\$86
Silicon nitride	A-5004-1967	A-5004-1519	A-5004-1968	A-5004-1969
Price	\$103	\$115	\$112	\$201
Zirconia	A-5004-2945	A-5004-2946	A-5004-2947	A-5004-2948
Price	\$103	\$103	\$112	\$121
A Ball dia. mm (in)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
B Length mm (in)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)	2.5 (0.10)
D EWL* mm (in)	47.0 (1.85)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
Mass grams	0.83	0.91	1.31	1.49



50 mm range



Ruby ball styli (carbon fiber stems)

Ball material	Part number		
Ruby	A-5003-2285	A-5003-2286	A-5003-2287
Price	\$105	\$110	\$115
Silicon nitride	A-5004-1970	A-5004-1971	A-5004-1972
Price	\$103	\$112	\$121
Zirconia	A-5004-1331	A-5004-1330	A-5004-1329
Price	\$103	\$112	\$121
A Ball dia. mm (in)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
B Length mm (in)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)
D EWL* mm (in)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
Mass grams	1.00	1.10	1.20

50 mm range




* Effective working length

Ruby ball styli (carbon fiber stems)


Ball material	Part number					
Ruby	A-5003-4784	A-5003-4785	A-5003-4786	A-5003-2289	A-5003-2290	A-5003-2291
Price	\$135	\$144	\$152	\$154	\$163	\$172
Silicon nitride	A-5004-1973	A-5004-1974	A-5004-1975	A-5004-1976	A-5004-1977	A-5004-1978
Price	\$121	\$121	\$121	\$121	\$121	\$138
Zirconia	A-5004-2949	A-5004-2950	A-5004-2951	A-5004-2952	A-5004-2953	A-5004-2954
Price	\$121	\$121	\$121	\$121	\$121	\$138
A Ball dia. mm (in.)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
B Length mm (in.)	75.0 (2.96)	75.0 (2.96)	75.0 (2.96)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)
C Stem dia. mm (in.)	2.0 (0.08)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)
D EWL* mm (in.)	75.0 (2.96)	75.0 (2.96)	75.0 (2.96)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)
Mass grams	0.75	1.35	1.45	1.50	1.59	1.78

75 mm – 100 mm range



Star styli (fixed)


Part number	A-5003-4011	A-5000-7811	A-5003-4787	A-5003-4788	A-5000-7629	A-5000-3626
Span mm (in.)	10.0 (0.40)	10.0 (0.40)	20.0 (0.79)	20.0 (0.79)	18.0 (0.71)	30.0 (1.19)
Ball mm (in.)	0.5 (0.02)	1.0 (0.04)	0.5 (0.02)	1.0 (0.04)	2.0 (0.08)	2.0 (0.08)
Stem dia. mm (in.)	0.3 (0.012)	0.7 (0.03)	0.3 (0.012)	0.7 (0.03)	1.4 (0.06)	1.4 (0.06)
EWL* mm (in.)	N/A	N/A	N/A	N/A	12.0 (0.48)	12.0 (0.48)
Mass grams	0.7	0.5	0.7	0.9	1.3	1.8
Price	\$249	\$138	\$264	\$221	\$139	\$133



* Effective working length

Star stylus centers

Part number	A-5003-4789	A-5003-4790	A-5003-4791	A-5000-3609
Ball mm (in.)	1.0 (0.04)	0.5 (0.02)	1.0 (0.04)	2.0 (0.08)
Stem dia. mm (in.)	0.7 (0.03)	0.4 (0.02)	0.7 (0.03)	1.4 (0.06)
EWL* mm (in.)	3.5 (0.14)	7.0 (0.28)	11.0 (0.44)	12.0 (0.48)
Mass grams	0.31	0.43	0.45	0.44
Price	\$125	\$163	\$125	\$71




Disk styli

Part number	A-5000-3611 Ruby	A-5004-1387 Silver steel	A-5004-1395 Silver steel	A-5004-1396 Silver steel	A-5000-7809 Silver steel
Disk dia. mm (in.)	6.0 (0.24)	10.0 (0.39)	12.0 (0.47)	14.0 (0.55)	18.0 (0.71)
Disk depth mm (in.)	1.2 (0.05)	1.2 (0.05)	1.6 (0.06)	1.6 (0.06)	1.6 (0.06)
Roller depth mm (in.)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)	2.5 (0.10)	2.5 (0.10)
Stem dia. mm (in.)	2.0 (0.08)	2.0 (0.08)	4.2 (0.17)	4.2 (0.17)	4.2 (0.17)
Mass grams	0.6	1.0	2.0	2.5	3.0
Price	\$70	\$103	\$121	\$121	\$89




Part number	A-5000-3613 Silver steel	A-5000-7810 Silver steel	A-5000-4187 Silver steel
Disk dia. mm (in.)	18.0 (0.71)	25.0 (0.99)	25.0 (0.99)
Disk depth mm (in.)	2.3 (0.10)	1.6 (0.06)	3.1 (0.13)
Roller depth mm (in.)	3.0 (0.12)	2.5 (0.10)	N/A
Stem dia. mm (in.)	N/A	4.2 (0.17)	N/A
Mass grams	2.7	4.0	3.8
Price	\$105	\$89	\$99



Cylinder styli


Part number	A-5004-7589 Silver steel	A-5004-7590 Silver steel	A-5000-8876 Ruby	A-5000-8877 Ruby	A-5000-7812 Ruby	A-5003-0073 Ruby
Cylinder dia. mm (in.)	1.5 (0.06)	3.0 (0.12)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	4.0 (0.16)
Overall length mm (in.)	10.75 (0.42)	12.75 (0.50)	15.0 (0.60)	15.0 (0.60)	21.2 (0.83)	22.0 (0.87)
Stem dia. mm (in.)	1.0 (0.04)	1.5 (0.06)	N/A	N/A	1.6 (0.07)	2.0 (0.08)
EWL* mm (in.)	1.25 (0.05)	3.8 (0.15)	8.0 (0.32)	8.0 (0.32)	7.2 (0.29)	10.0 (0.40)
Mass grams	0.3	0.6	0.3	0.3	0.5	0.9
Price	\$26	\$26	\$185	\$270	\$147	\$130



* Effective working length


Parallel hemispherical-ended styli (tungsten carbide)

Part number	A-5003-1208	A-5003-1210	A-5003-1218	A-5003-1219	A-5003-1228	A-5003-0074	A-5003-1258
Cylinder dia. mm (in.)	0.3 (0.012)	0.5 (0.02)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	3.0 (0.12)
Overall length mm (in.)	10.2 (0.41)	15.3 (0.61)	35.5 (1.40)	15.8 (0.63)	16.0 (0.63)	40.0 (1.58)	22.5 (0.89)
EWL* mm (in.)	2.7 (0.11)	7.8 (0.31)	28.0 (1.10)	8.3 (0.33)	8.5 (0.34)	32.0 (1.26)	22.5 (0.89)
Mass grams	0.3	0.3	0.7	0.6	0.8	2.0	2.0
Price	\$220	\$190	\$160	\$85	\$85	\$87	\$155




Stylus extensions (stainless steel)

Part number	A-5004-7610	A-5004-7585	A-5004-7586	A-5004-7591	A-5004-7611
Length mm (in.)	5.0 (0.20)	10.0 (0.40)	20.0 (0.79)	30.0 (1.19)	40.0 (1.58)
Stem dia. mm (in.)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)
Mass grams	0.2	0.4	0.9	1.4	1.8
Price	\$12	\$13	\$15	\$17	\$19



Stylus extensions (ceramic)


Part number	A-5003-0070	A-5003-0071	A-5003-0072
Length mm (in.)	30.0 (1.19)	40.0 (1.58)	50.0 (1.97)
Stem dia. mm (in.)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)
Mass grams	0.97	1.22	1.51
Price	\$58	\$58	\$60



** Special * Effective working length


Stylus extensions (carbon fiber)

Part number	A-5003-2280	A-5003-2281	A-5003-2282	A-5003-2283
Length mm (in.)	40.0 (1.58)	50.0 (1.97)	70.0 (2.76)	90.0 (3.55)
Stem dia. mm (in.)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)	3.0 (0.12)
Outer dia. mm (in.)	3.5 (0.14)	3.5 (0.14)	3.5 (0.14)	3.5 (0.14)
Mass grams	0.9	1.0	1.3	1.5
Price	\$97	\$101	\$105	\$110



Special purpose styli

Part number	A-5004-7588 Silver steel	A-5000-7813 Tungsten carbide	A-5000-3614 Ceramic
Length mm (in.)	15.0 (0.60)	10.0 (0.40)	11.0 (0.44)
Ball dia. mm (in.)	N/A	N/A	18.0 (0.71)
End feature mm (in.)	Flat rad. 0.05 (0.002)	Spherical rad. 0.1 (0.004)	N/A
Angles	30° inclusive	30° inclusive	N/A
Mass grams	0.7	0.7	3.3
Price	\$25	\$67	\$279




M3 threaded stylus range

Ruby ball styli (stainless steel stems)

Ball material	Part number						
Ruby	A-5000-3551	A-5000-3552	A-5000-3553	A-5000-7606	A-5000-7630	A-5000-3554	A-5000-7648
Price	\$32	\$32	\$32	\$32	\$32	\$32	\$32
Silicon nitride	A-5004-1979	A-5003-5723	A-5003-6257	A-5003-5061	A-5003-6695	A-5004-1980	A-5004-1981
Price	\$69	\$69	\$69	\$69	\$78	\$69	\$78
Zirconia	A-5004-2955	A-5003-5736	A-5004-2956	A-5003-5737	A-5003-9500	A-5004-2957	A-5004-2958
Price	\$84	\$84	\$84	\$84	\$94	\$84	\$94
A Ball dia. mm (in.)	1.0 (0.04)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	4.0 (0.16)	5.0 (0.20)
B Length mm (in.)	21.0 (0.83)	21.0 (0.83)	21.0 (0.83)	21.0 (0.83)	21.0 (0.83)	31.0 (1.23)	31.0 (1.23)
C Stem dia. mm (in.)	0.7 (0.03)	1.4 (0.06)	1.5 (0.06)	2.5 (0.10)	2.5 (0.10)	2.5 (0.10)	3.5 (0.14)
D EWL* mm (in.)	4.0 (0.16)	9.6 (0.38)	14.7 (0.58)	17.2 (0.68)	21.0 (0.83)	27.0 (1.07)	31.0 (1.23)
Mass grams	1.0	1.0	1.0	1.3	1.5	2.5	3.0



21 mm – 31 mm range



Ruby ball styli (tungsten carbide stems)

Ball material	Part number						
Ruby	A-5000-7632	A-5003-0050	A-5003-0054	A-5003-0051	A-5003-0052	A-5003-0055	A-5003-0057
Price	\$98	\$44	\$44	\$49	\$44	\$44	\$44
Silicon nitride	A-5004-2023**	A-5004-1198	A-5004-1982	A-5003-8091	A-5003-5724	A-5004-1983	A-5004-1984
Price	\$323	\$86	\$86	\$86	\$86	\$86	\$86
Zirconia	A-5004-2959	A-5004-2960	A-5004-2961	A-5004-2962	A-5003-5738	A-5004-2963	A-5003-6766
Price	\$230	\$104	\$104	\$104	\$104	\$104	\$104
A Ball dia. mm (in.)	0.5 (0.02)	1.5 (0.06)	2.5 (0.10)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)
B Length mm (in.)	21.0 (0.83)	20.0 (0.79)	20.2 (0.80)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
C Stem dia. mm (in.)	0.4 (0.02)	1.0 (0.04)	2.0 (0.08)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)
D EWL* mm (in.)	2.0 (0.08)	12.5 (0.50)	12.5 (0.50)	22.5 (0.89)	22.8 (0.90)	22.5 (0.89)	24.0 (0.94)
Mass grams	1.0	0.8	1.3	0.93	1.32	1.81	1.83

20 mm – 30 mm range




** Special * Effective working length

Ruby ball styli (tungsten carbide stems) – continued

Ball material	Part number				
Ruby	A-5003-0053	A-5003-0056	A-5003-0058	A-5003-0060	A-5003-0062
Price	\$49	\$49	\$49	\$44	\$74
Silicon nitride	A-5004-1985	A-5004-1986	A-5004-1987	A-5004-1195	A-5004-1718
Price	\$86	\$86	\$86	\$86	\$103
Zirconia	A-5003-2043	A-5004-2964	A-5004-2965	A-5003-6767	A-5004-2966
Price	\$104	\$104	\$104	\$104	\$115
A Ball dia. mm (in.)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
B Length mm (in.)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)
C Stem dia. mm (in.)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)
D EWL* mm (in.)	32.5 (1.28)	32.5 (1.28)	33.7 (1.33)	36.0 (1.42)	40.0 (1.58)
Mass grams	1.58	2.28	2.30	2.38	3.50


40 mm range



Ruby ball styli (tungsten carbide stems)

Ball material	Part number		
Ruby	A-5003-0059	A-5003-0061	A-5003-0063
Price	\$53	\$53	\$53
Silicon nitride	A-5004-1199	A-5004-1988	A-5004-1201
Price	\$86	\$86	\$95
Zirconia	A-5004-2968	A-5003-6768	A-5003-7665
Price	\$104	\$104	\$115
A Ball dia. mm (in.)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
B Length mm (in.)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)
D EWL* mm (in.)	43.7 (1.72)	46.0 (1.82)	50.0 (1.97)
Mass grams	2.78	2.85	4.10



50 mm range



Ruby ball styli (ceramic stems)

Ball material	Part number		
Ruby	A-5003-0067	A-5003-0068	A-5003-0069
Price	\$70	\$70	\$70
Silicon nitride	A-5004-1989	A-5003-5725	A-5004-1990
Price	\$103	\$103	\$112
Zirconia	A-5004-2969	A-5003-5739	A-5004-2970
Price	\$125	\$125	\$136
A Ball dia. mm (in.)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
B Length mm (in.)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)
D EWL* mm (in.)	43.7 (1.72)	46.0 (1.82)	50.0 (1.97)
Mass grams	1.17	1.24	1.33

50 mm range




* Effective working length

Ruby ball styli (carbon fiber stems)



Ball material	Part number			
Ruby	A-5003-4860	A-5003-4862	A-5003-4861	A-5003-4863
Price	\$158	\$180	\$168	\$190
Silicon nitride	A-5003-5726	A-5004-1991	A-5003-5727	A-5004-5466
Price	\$129	\$147	\$147	\$155
Zirconia	A-5003-5740	A-5003-6771	A-5003-5741	A-5003-6778
Price	\$157	\$178	\$178	\$188
A Ball dia. mm (in.)	6.0 (0.24)	8.0 (0.32)	6.0 (0.24)	8.0 (0.32)
B Length mm (in.)	75.0 (2.96)	75.0 (2.96)	100.0 (3.94)	100.0 (3.94)
C Stem dia. mm (in.)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)
D EWL* mm (in.)	75.0 (2.96)	75.0 (2.96)	100.0 (3.94)	100.0 (3.94)
Mass grams	2.40	2.98	2.89	3.47

75 mm – 100 mm
range



Ruby ball styli (carbon fiber stems) – continued


Ball material	Part number						
Ruby	A-5003-7057	A-5003-7056	A-5003-7055	A-5003-7054	A-5003-7445	A-5003-7446	A-5003-7447
Price	\$275	\$275	\$301	\$301	\$275	\$301	\$301
Silicon nitride	A-5004-1992	A-5004-1993	A-5004-1994	A-5004-1995	A-5004-1996	A-5004-1997	A-5004-1998
Price	\$293	\$293	\$293	\$293	\$310	\$310	\$310
Zirconia	A-5004-2972	A-5003-9495	A-5004-2973	A-5004-2974	A-5004-2975	A-5004-2976	A-5004-2977
Price	\$355	\$355	\$355	\$355	\$376	\$376	\$376
A Ball dia. mm (in.)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	10.0 (0.40)	12.0 (0.48)	12.0 (0.48)	12.0 (0.48)
B Length mm (in.)	75.0 (2.96)	100.0 (3.94)	150.0 (5.91)	200.0 (7.88)	100.0 (3.94)	150.0 (5.91)	200.0 (7.88)
C Stem dia. mm (in.)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)
D EWL* mm (in.)	75.0 (2.96)	100.0 (3.94)	150.0 (5.91)	200.0 (7.88)	100.0 (3.94)	150.0 (5.91)	200.0 (7.88)
Mass grams	4.05	4.53	5.49	6.47	5.9	6.9	7.9



* Effective working length

Stylus extensions (stainless steel)

Part number	A-5004-7609	A-5004-7583	A-5004-7584
Length mm (in.)	10.0 (0.40)	20.0 (0.79)	35.0 (1.38)
Stem dia. mm (in.)	4.0 (0.16)	4.0 (0.16)	4.0 (0.16)
Mass grams	0.9	1.6	2.9
Price	\$13	\$15	\$12



Stylus extensions (carbon fiber)

Part number	A-5003-4864	A-5003-4865
Length mm (in.)	75.0 (2.96)	100.0 (3.94)
Stem dia. mm (in.)	4.0 (0.16)	4.0 (0.16)
Mass grams	2.53	3.02
Price	\$102	\$110



Stylus extensions (ceramic)

Part number	A-5003-0075
Length mm (in.)	50.0 (1.97)
Stem dia. mm (in.)	4.0 (0.16)
Mass grams	2.95
Price	\$58




Disk and hollow ball styli

Part number	A-5000-3615 Silver steel	A-5000-7612 Silver steel	A-5000-7669 Carbon steel
Disk dia. mm (in.)	12.7 (0.50)	35.0 (1.38)	63.5 (2.51)
Disk depth mm (in.)	2.2 (0.09)	5.0 (0.20)	6.0 (0.24)
Stem dia. mm (in.)	3.5 (0.14)	N/A	N/A
Mass grams	4.0	10.0	45.0
Price	\$74	\$126	\$134

Part number	A-5000-7814 Ceramic	A-5003-7098 Ceramic
Disk dia. mm (in.)	30.0 (1.19)	30.0 (1.19)
Disk depth mm (in.)	17.0 (0.67)	1.5 (0.06)
Stem dia. mm (in.)	N/A	4.0 (0.16)
Mass grams	13.0	3.6
Price	\$343	\$300

Star styli (fixed)

Part number	A-5003-0076	A-5003-0077
Span mm (in.)	30.0 (1.19)	50.0 (1.97)
Ball mm (in.)	2.0 (0.08)	2.0 (0.08)
Stem dia. mm (in.)	1.4 (0.06)	1.4 (0.06)
EWL* mm (in.)	11.0 (0.44)	11.0 (0.44)
Mass grams	2.38	5.25
Price	\$140	\$140




* Effective working length


M4 threaded stylus range

Ruby ball styli (stainless steel stems)

Ball material	Part number				
Ruby	A-5000-6350	A-5000-7545	A-5000-7547	A-5000-7549	A-5000-7551
Price	\$70	\$87	\$76	\$45	\$45
Silicon nitride	–	–	A-5003-5728	–	A-5003-5729
Price	–	–	\$71	–	\$63
Zirconia	–	–	A-5003-5742	–	A-5003-5743
Price	–	–	\$71	–	\$63
A Ball dia. mm (in.)	5.0 (0.20)	1.0 (0.04)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)
B Length mm (in.)	10.0 (0.39)	19.5 (0.77)	19.0 (0.75)	18.5 (0.73)	18.0 (0.71)
C Stem dia. mm (in.)	3.0 (0.12)	0.7 (0.03)	1.4 (0.05)	2.0 (0.08)	3.0 (0.12)
D EWL* mm (in.)	5.0 (0.20)	4.5 (0.18)	9.2 (0.36)	13.0 (0.52)	13.7 (0.54)
Mass grams	1.9	2.5	2.3	2.0	2.1




Part number	A-5000-7553	A-5000-6731	A-5000-6352	A-5000-7555	A-5000-7557
A Ball dia. mm (in.)	5.0 (0.20)	5.0 (0.20)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)
B Length mm (in.)	17.5 (0.69)	20.0 (0.79)	30.0 (1.19)	17.0 (0.67)	16.0 (0.63)
C Stem dia. mm (in.)	3.5 (0.14)	3.0 (0.12)	3.0 (0.12)	4.5 (0.18)	6.0 (0.24)
D EWL* mm (in.)	13.6 (0.54)	15.89 (0.63)	26.0 (1.03)	13.3 (0.52)	16.0 (0.63)
Mass grams	2.3	2.4	3.0	3.0	3.9
Price	\$45	\$70	\$70	\$50	\$67



10 mm – 30 mm range

Ruby ball styli (tungsten carbide stems)

Part number	A-5003-4792	A-5003-2932	A-5003-4793	A-5003-4794	A-5003-4795	A-5003-4796
A Ball dia. mm (in.)	1.0 (0.04)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
B Length mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
C Stem dia. mm (in.)	0.7 (0.03)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)	2.5 (0.10)
D EWL* mm (in.)	10.0 (0.40)	10.0 (0.40)	8.5 (0.33)	8.5 (0.33)	7.9 (0.31)	10.7 (0.42)
Mass grams	2.39	3.01	3.53	3.53	4.52	4.66
Price	\$77	\$86	\$86	\$86	\$92	\$92




20 mm range

* Effective working length

Ruby ball styli


Part number	A-5003-0233 Ceramic	A-5000-7521 Stainless steel	A-5003-0235 Ceramic	A-5000-3709 Ceramic	A-5000-7795 Ceramic
A Ball dia. mm (in.)	4.0 (0.16)	5.0 (0.20)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)
B Length mm (in.)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	3.0 (0.12)	4.5 (0.18)	3.8 (0.15)	4.5 (0.18)	4.5 (0.18)
D EWL* mm (in.)	33.5 (1.32)	33.5 (1.32)	33.5 (1.32)	38.5 (1.52)	50.0 (1.97)
Mass grams	3.9	5.8	5.0	4.8	5.4
Price	\$70	\$70	\$82	\$97	\$108

50 mm range





Part number	A-5003-4797 Tungsten carbide	A-5003-3680 Tungsten carbide	A-5003-4799 Tungsten Carbide	A-5003-4800 Tungsten carbide	A-5003-4801 Tungsten carbide
A Ball dia. mm (in.)	2.0 (0.08)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)
B Length mm (in.)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)	2.5 (0.10)
D EWL* mm (in.)	40.0 (1.58)	38.5 (1.52)	38.5 (1.52)	37.9 (1.49)	40.7 (1.60)
Mass grams	3.80	4.94	4.99	6.72	6.86
Price	\$92	\$96	\$96	\$100	\$100

50 mm range



A-5003-0236 Ceramic	A-5003-2764 Ceramic	A-5003-4802 Ceramic
5.0 (0.20)	6.0 (0.24)	8.0 (0.32)
75.0 (2.96)	75.0 (2.96)	75.0 (2.96)
3.8 (0.15)	4.5 (0.18)	4.5 (0.18)
58.5 (2.30)	63.5 (2.51)	75.0 (2.96)
5.63	5.64	6.20
\$86	\$103	\$115


75 mm range



* Effective working length

Ruby ball styli

Part number	A-5000-7522 Stainless steel	A-5000-9761 Ceramic	A-5000-7523 Stainless steel	A-5000-3712 Ceramic	A-5000-8156 Ceramic	A-5000-7796 Ceramic	A-5003-3461 Carbon fiber
A Ball dia. mm (in)	5.0 (0.20)	5.0 (0.20)	5.0 (0.20)	6.0 (0.24)	6.0 (0.24)	8.0 (0.32)	8.0 (0.32)
B Length mm (in)	100.0 (3.94)	100.0 (3.94)	150.0 (5.91)	100.0 (3.94)	150.0 (5.91)	100.0 (3.94)	300.0 (11.82)
C Stem dia mm (in)	4.5 (0.18)	3.8 (0.15)	4.4 (0.17)	4.5 (0.18)	4.5 (0.18)	4.5 (0.18)	4.5 (0.18)
D EWL* mm (in)	83.2 (3.38)	83.5 (3.29)	133.00 (5.24)	88.5 (3.48)	135.0 (5.31)	100.0 (3.94)	300.0 (11.82)
Mass grams	11.3	6.3	17.4	6.3	7.9	7.5	10.4
Price	\$79	\$150	\$88	\$109	\$170	\$140	\$430



100 mm – 300 mm range



* Effective working length

Ruby ball styli (carbon fiber stems)

Recommended for use with OMP400 and RMP600

Ball material	Part number			
Ruby	A-5003-7306	A-5003-6510	A-5003-6511	A-5003-6512
Price	\$128	\$145	\$274	\$289
Silicon nitride	A-5003-5730	A-5003-5731	–	–
Price	\$221	\$240	–	–
Zirconia	A-5003-5744	A-5003-5745	–	–
Price	\$221	\$240	–	–
A Ball dia. mm (in)	6.0 (0.24)	6.0 (0.24)	6.0 (0.24)	6.0 (0.24)
B Length mm (in)	50.0 (1.97)	100.0 (3.94)	150.0 (5.91)	200.0 (7.88)
C Stem dia mm (in)	4.5 (0.18)	4.5 (0.18)	4.5 (0.18)	4.5 (0.18)
D EWL* mm (in)	38.5 (1.52)	88.5 (3.48)	138.5 (5.45)	188.5 (7.42)
Mass grams	4.1	6.2	7.5	8.7


A-5003-1436	A-5003-1358	A-5003-1255	A-5003-1075
\$128	\$145	\$274	\$289
–	–	–	–
–	–	–	–
–	–	–	–
–	–	–	–
6.0 (0.24)	6.0 (0.24)	6.0 (0.24)	6.0 (0.24)
50.0 (1.97)	100.0 (3.94)	150.0 (5.91)	200.0 (7.88)
4.5 (0.18)	4.5 (0.18)	4.5 (0.18)	4.5 (0.18)
38.5 (1.52)	88.5 (3.58)	138.5 (5.46)	188.5 (7.42)
4.1	6.2	7.5	8.7



* Effective working length

Star styli

Part number	A-5000-6462 Ceramic	A-5000-7098 Ceramic
Ball mm (in.)	6.0 (0.24)	6.0 (0.24)
Length mm (in.)	100.0 (3.94)	50.0 (1.97)
Stem dia. mm (in.)	4.5 (0.18)	4.5 (0.18)
EWL* mm (in.)	88.5 (3.48)	38.5 (1.52)
Mass grams	7.5	6.0
Price	\$94	\$89




M-5000-6460
Star center
Mass 10 g


Price: \$100

Disk styli

Part number	A-5000-7596	A-5000-7597	A-5000-7598
Diameter A mm (in.)	30.0 (1.19)	35.0 (1.38)	50.0 (1.97)
Diameter B mm (in.)	21.0 (0.83)	21.0 (0.83)	23.0 (0.91)
C mm (in.)	2.2 (0.09)	2.2 (0.09)	3.0 (0.12)
D mm (in.)	3.0 (0.12)	3.0 (0.12)	4.0 (0.16)
Mass grams	8.01	9.57	13.55
Price	\$114	\$109	\$119




Part number	A-5000-6351 Silver steel
Disk dia. mm (in.)	30.0 (1.18)
Disk depth mm (in.)	3.0 (0.12)
Length mm (in.)	10.0 (0.39)
Rollers	NO
Mass grams	7.9
Price	\$165




Swivel adaptor

Part number	A-5004-7607	A-5004-7608
Length A mm (in.)	10.0 (0.40)	13.5 (0.54)
Length B mm (in.)	12.5 (0.50)	16.0 (0.63)
Mass grams	2.76	3.70
Price	\$50	\$50



Stylus crank

Part number	A-5004-7605	A-5004-7606
Length A mm (in)	21.9 (0.86)	27.6 (1.09)
Mass grams	6.07	6.94
Price	\$57	\$57



* Effective working length

Crash protection devices

Part number	A-5004-7598	A-5004-7603	A-5004-7604	A-5004-7621	* A-5003-0661	A-5004-7624	A-5004-6723
	Stainless steel	Stainless steel	Stainless steel	Silver steel	Silver steel	Silver steel	Silver steel
Price	\$8	\$5	\$5	\$25	\$25	\$25	\$25
For pack of ten	-	-	-	-	A-5004-1865	A-5004-1867	A-5004-1869
Price	-	-	-	-	\$165	\$165	\$165
Length mm (in.)	8.0 (0.32)	8.0 (0.32)	10.0 (0.40)	12.0 (0.48)	15.2 (0.60)	9.0 (0.36)	16.0 (0.63)
Mass grams	1.8	1.4	1.5	2.7	4.6	1.5	2.1
For use on	LP2	LP2	LP2	MP10	TS27R	HPMA	HPMA
	-	-	-	MP12	-	HPRA	HPRA
	-	-	-	RMP60	-	HPPA	HPPA
	-	-	-	OMP60	-	-	-
	-	-	-	MP3	-	-	-
	-	-	-	MP11	-	-	-











Use P-TL09-0003 to tighten

* Please note: If you require the full TS27R break stem kit, please order A-5003-5171.




Part number	A-5004-7616	A-5004-7618	A-5004-7619	A-5004-7620	A-5004-7622
	M3	M3	M3	M4	M4
	Silver steel				
Length mm (in.)	13.3 (0.52)	22.3 (0.88)	30.3 (1.19)	13.5 (0.53)	19.0 (0.75)
Mass grams	2.43	3.6	4.5	1.37	2.2
Price	\$25	\$25	\$25	\$25	\$25
For use on	TS20	TS20	TS20	RP1/RP2	TSA





Cranked styli

Part number	A-5000-5302	A-5000-5307	A-5000-6620	A-5000-7580
	M4	M4	M4	M4
	Tungsten steel	Tungsten steel	Tungsten steel	Tungsten steel
Length mm (in.)	32.0 (1.26)	21.6 (0.85)	27.4 (1.08)	38.8 (1.53)
Mass grams	3.8	3.85	4.7	2.5
For use on	LP2	LP2	LP2	LP2
Price	\$122	\$122	\$122	\$52


TS27R styli – parallel shafted (not M4) – not compatible with TS27 probes


Part number	A-2008-0382 Tungsten carbide	A-2008-0384 Ceramic
Overall length mm (in.)	23.0 (0.91)	22.0 (0.87)
Mass grams	12.1	7.1
Price	\$111	\$260



Stylus conversion kit for TS27R to allow horizontal machining applications (**A-2008-0448**)


Price: \$120

Stylus holder assembly
A-2008-0389
Price: \$25



Vertical machining applications

Stylus holder
A-5004-7617*
Price: \$95




Horizontal machining applications

* Order also requires 2 x P-SC13-0404


Tool datuming styli

Part number	A-5000-3212 Stainless steel	A-5000-6701 Stainless steel	A-5000-6713 Aluminum	A-5000-6403 Stainless steel
Overall length mm (in.)	53.0 (2.09)	43.0 (1.70)	96.5 (3.80)	32.5 (1.28)
Stem dia. mm (in.)	4.5 (0.18)	4.5 (0.18)	7.5 (0.30)	5.4 (0.22)
Mass grams	4.5	4.3	21.9	11.0
Price	\$107	\$107	\$128	\$107




Tool datuming styli – continued


Part number	A-2197-0157 Tungsten steel	A-2197-0158 Tungsten steel	A-2197-0159 Tungsten steel	A-2197-0160 Tungsten steel	A-2197-0161 Tungsten steel	A-2197-0162 Tungsten steel
Length mm (in.)	14.2 (0.56)	19.5 (0.77)	29.5 (1.16)	34.5 (1.36)	39.5 (1.55)	49.5 (1.95)
Mass grams	14.86	16.0	20.0	20.7	21.8	23.5
Price	\$116	\$116	\$116	\$116	\$116	\$116
For use on	HPPA	HPPA	HPPA	HPPA	HPPA	HPPA
	HPMA	HPMA	HPMA	HPMA	HPMA	HPMA
	HPRA	HPRA	HPRA	HPRA	HPRA	HPRA
	RP3	RP3	RP3	RP3	RP3	RP3



Part number	A-2008-0601 M3 Tungsten steel	A-2008-0602 M3 Tungsten steel	A-2008-0603 M3 Tungsten steel	A-2048-2050 M4 Tungsten steel	A-2048-2051 M4 Tungsten steel	A-2116-0140 M4 Tungsten steel	A-2116-0141 M4 Tungsten steel
Length mm (in.)	15.4 (0.61)	24.0 (0.96)	32.4 (1.27)	23.2 (0.91)	32.0 (1.26)	32.0 (1.26)	42.0 (1.65)
Mass grams	9.1	8.0	8.95	18.14	20.64	13.56	16.05
Price	\$116	\$116	\$116	\$137	\$137	\$109	\$127
For use on	TS20	TS20	TS20	HPA (M6 MTG)	HPA (M6 MTG)	TSA	TSA





Part number	A-2116-0142
Length mm (in.)	30.3 (0.40)
Mass grams	22.6
Price	\$158
For use on	TSA



Stylus extensions



Part number	A-5004-7599 Stainless steel	A-5004-7600 Stainless steel	A-5004-7601 Stainless steel	A-5004-7602 Stainless steel	A-5000-7754 Ceramic	A-5000-7755 Ceramic	A-5000-7727 Ceramic	A-5003-0587 Ceramic
Length mm (in.)	10.0 (0.40)	15.0 (0.60)	20.0 (0.79)	30.0 (1.19)	30.0 (1.19)	50.0 (1.97)	100.0 (3.94)	200.0 (7.87)
Stem dia. mm (in.)	7.0 (0.28)	7.0 (0.28)	7.0 (0.28)	7.0 (0.28)	7.4 (0.29)	7.4 (0.29)	7.4 (0.29)	7.4 (0.29)
Mass grams	2.4	3.7	4.8	7.4	5.1	6.7	10.6	18.4
Price	\$36	\$36	\$36	\$36	\$51	\$60	\$154	\$165



M4 styli

Tungsten carbide styli (stainless steel stems)

Part number	A-5000-7670	A-5000-7671	A-5000-7672	A-5000-9685	A-5000-9697
A Ball dia. mm (in.)	5.0 (0.20)	5.0 (0.20)	5.0 (0.20)	5.0 (0.20)	3.0 (0.12)
B Length mm (in.)	50.0 (1.97)	100.0 (3.94)	150.0 (5.91)	54.0 (2.12)	55.0 (2.17)
C Stem dia. mm (in.)	4.5 (0.18)	4.5 (0.18)	4.5 (0.18)	3.9 (0.15)	1.9 (0.07)
D EWL* mm (in.)	35.0 (1.38)	85.0 (3.35)	135.0 (5.31)	50.0 (1.97)	25.0 (0.99)
Mass grams	6.2	11.9	18.2	6.9	3.8
Price	\$70	\$79	\$88	\$159	\$147




* Effective working length

Walter styli


M1.4 thread styli

Part number	A-5003-3814	A-5003-3045	A-5003-3042	A-5000-9860	A-5003-1699
	M1.4	M1.4	M1.4	M1.4	M1.4
Stem material	Tungsten carbide	Stainless steel	Tungsten carbide	Tungsten carbide	Stainless steel
Ball material	Tungsten carbide	Tungsten carbide	Ruby	Tungsten carbide	Tungsten carbide
A Ball dia. mm (in.)	0.5 (0.02)	1.0 (0.04)	0.5 (0.02)	1.0 (0.04)	0.6 (0.02)
B Length mm (in.)	12.5 (0.49)	25.0 (0.98)	12.5 (0.49)	13.0 (0.51)	12.75 (0.50)
D EWL* mm (in.)	1.5 (0.059)	1.5 (0.059)	3.0 (0.12)	1.0 (0.04)	1.0 (0.04)
Mass grams	0.2	1.1	0.19	0.22	0.41
Price	\$259	\$172	\$259	\$129	\$259



Adaptors

Part number	A-5003-1448	A-5000-9724
D3 MTG	2 x M1.4 adaptor 20°	M1.4 adaptor 20°
Mass grams	9.73	8.31
Price	\$172	\$172




Crash protection device

Part number	A-5004-7615
Length mm (in.)	16.0 (0.63)
Mass grams	2
Price	\$60



* Effective working length




M5 threaded stylus range

Ruby micro ball styli (tungsten carbide stems)


Part number	A-5003-5201	A-5003-5202	A-5003-5203
A Ball dia. mm (in.)	0.3 (0.012)	0.5 (0.02)	0.7 (0.03)
B Length mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
C Stem dia. mm (in.)	0.2 (0.01)	0.4 (0.02)	0.5 (0.02)
D EWL* mm (in.)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
Mass grams	6.5	6.5	6.5
Price	\$92	\$79	\$79

20 mm range




A-5003-5211	A-5003-5212	A-5003-5213
0.3 (0.012)	0.5 (0.02)	0.7 (0.03)
30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
0.2 (0.01)	0.4 (0.02)	0.5 (0.02)
3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
8.95	8.95	8.98
\$96	\$86	\$86

30 mm range




Part number	A-5003-5225	A-5003-5226	A-5003-5227
A Ball dia. mm (in.)	0.3 (0.012)	0.5 (0.02)	0.7 (0.03)
B Length mm (in.)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	0.2 (0.01)	0.4 (0.02)	0.5 (0.02)
D EWL* mm (in.)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
Mass grams	15.79	15.79	15.79
Price	\$125	\$115	\$115

50 mm range



A-5003-5240	A-5003-5241	A-5003-5242
0.3 (0.012)	0.5 (0.02)	0.7 (0.03)
75.0 (2.96)	75.0 (2.96)	75.0 (2.96)
0.2 (0.01)	0.4 (0.02)	0.5 (0.02)
3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
23.84	23.84	23.84
\$134	\$125	\$115


75 mm range



Ruby ball styli (tungsten carbide stems)


Ball material	Part number						
Ruby	A-5003-5204	A-5003-5205	A-5003-5206	A-5003-5207	A-5003-5208	A-5003-5209	A-5003-5210
Price	\$71	\$61	\$61	\$61	\$61	\$67	\$67
Silicon nitride	–	–	A-5003-5732	–	–	A-5003-5733	–
Price	–	–	\$86	–	–	\$94	–
Zirconia	–	–	A-5003-5746	–	–	A-5003-5747	–
Price	–	–	\$86	–	–	\$94	–
A Ball dia. mm (in.)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
B Length mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
C Stem dia. mm (in.)	0.7 (0.03)	1.0 (0.04)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	3.0 (0.12)
D EWL* mm (in.)	5.0 (0.20)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.9 (0.47)	11.5 (0.45)
Mass grams	6.52	4.68	4.70	4.84	5.12	5.19	6.06

20 mm range




Part number	A-5003-5214	A-5003-5215	A-5003-5216	A-5003-5217	A-5003-5218	A-5003-5219	A-5003-5220
A Ball dia. mm (in.)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)	5.0 (0.20)
B Length mm (in.)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)	30.0 (1.19)
C Stem dia. mm (in.)	0.7 (0.03)	1.0 (0.04)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	3.0 (0.12)
D EWL* mm (in.)	5.0 (0.20)	12.0 (0.48)	21.0 (0.83)	21.0 (0.83)	21.0 (0.83)	21.9 (0.86)	21.5 (0.85)
Mass grams	9.01	7.28	4.81	5.14	5.58	5.64	7.10
Price	\$77	\$46	\$67	\$67	\$67	\$72	\$77

30 mm range



Part number	A-5003-5221	A-5003-5222	A-5003-5223	A-5003-5224
A Ball dia. mm (in.)	1.5 (0.06)	2.0 (0.08)	2.5 (0.10)	3.0 (0.12)
B Length mm (in.)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)	40.0 (1.58)
C Stem dia. mm (in.)	1.0 (0.04)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)
D EWL* mm (in.)	22.0 (0.87)	31.0 (1.23)	31.0 (1.23)	31.0 (1.23)
Mass grams	7.39	4.93	5.40	6.04
Price	\$96	\$86	\$86	\$86

40 mm range




* Effective working length

Ruby ball styli (<5 mm ball diameter) (tungsten carbide stems)

Part number	A-5003-5228	A-5003-5229	A-5003-5230	A-5003-5231	A-5003-5233	A-5003-5232	A-5003-5234	A-5003-5235
A Ball dia. mm (in.)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	2.5 (0.10)	2.5 (0.10)	3.0 (0.12)	4.0 (0.16)
B Length mm (in.)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	0.7 (0.03)	1.0 (0.04)	1.0 (0.04)	1.0 (0.04)	1.5 (0.06)	2.0 (0.08)	2.0 (0.08)	2.0 (0.08)
D EWL* mm (in.)	5.0 (0.20)	5.0 (0.20)	41.0 (1.62)	5.0 (0.20)	5.0 (0.20)	41.0 (1.62)	41.0 (1.62)	41.9 (1.65)
Mass grams	15.81	14.82	5.05	14.85	14.94	6.48	6.50	6.55
Price	\$109	\$105	\$96	\$77	\$77	\$86	\$86	\$86



50 mm range



Ruby ball styli (≥5 mm ball diameter)

Ball material	Part number			
Ruby	A-5003-5236	A-5003-5237	A-5003-5238	A-5003-5239
Price	\$86	\$96	\$105	\$115
Silicon nitride	–	A-5003-5734	–	–
Price	–	\$134	–	–
Zirconia	–	A-5003-5748	–	–
Price	–	\$134	–	–
	Tungsten carbide	Carbon fiber	Carbon fiber	Carbon fiber
A Ball dia. mm (in.)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)	10.0 (0.40)
B Length mm (in.)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
C Stem dia. mm (in.)	3.0 (0.12)	4.0 (0.16)	6.0 (0.24)	6.0 (0.24)
D EWL* mm (in.)	41.5 (1.63)	39.5 (1.56)	39.5 (1.56)	44.5 (1.75)
Mass grams	9.19	6.10	7.96	8.91

50 mm range





* Effective working length

Ruby ball styli (1 mm – 10 mm ball diameter)

Part number	A-5003-5243 Tungsten carbide	A-5003-5244 Tungsten carbide	A-5003-5248 Tungsten carbide	A-5003-5249 Tungsten carbide	A-5003-5250 Carbon fiber	A-5003-5251 Carbon fiber	A-5003-5252 Carbon fiber
A Ball dia. mm (in.)	1.0 (0.04)	1.5 (0.06)	4.0 (0.16)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)	10.0 (0.40)
B Length mm (in.)	75.0 (2.96)	75.0 (2.96)	75.0 (2.96)	75.0 (2.96)	75.0 (2.96)	75.0 (2.96)	75.0 (2.96)
C Stem dia. mm (in.)	0.7 (0.03)	1.0 (0.04)	3.0 (0.12)	3.0 (0.12)	4.0 (0.16)	6.0 (0.24)	6.0 (0.24)
D EWL* mm (in.)	5.0 (0.20)	5.0 (0.20)	66.0 (2.60)	66.0 (2.60)	65.1 (2.56)	64.5 (2.54)	69.5 (2.74)
Mass grams	23.86	23.90	11.61	11.80	6.59	9.06	10.01
Price	\$115	\$105	\$96	\$105	\$125	\$115	\$125

75 mm range




* Effective working length

M5 styli

Ruby ball styli (≤50 mm EWL)

Part number	A-5003-5253 Tungsten carbide	A-5003-5255 Tungsten carbide	A-5003-5256 Tungsten carbide	A-5003-5257 Tungsten carbide	A-5003-5261 Carbon fiber
A Ball dia. mm (in.)	3.0 (0.12)	4.0 (0.16)	4.0 (0.16)	5.0 (0.20)	8.0 (0.32)
B Length mm (in.)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)
C Stem dia. mm (in.)	2.0 (0.08)	2.0 (0.08)	3.0 (0.12)	3.0 (0.12)	6.0 (0.24)
D EWL* mm (in.)	20.0 (0.79)	30.5 (1.20)	50.0 (1.97)	50.0 (1.97)	50.0 (1.97)
Mass grams	25.71	25.75	23.07	23.31	22.97
Price	\$125	\$125	\$144	\$125	\$144

100 mm range





* Effective working length

Ruby ball styli (>50 mm EWL)

Ball material		Part number						
Ruby		A-5003-5254	A-5003-5259	A-5003-5258	A-5003-5260	A-5003-5262	A-5003-5264	A-5003-5263
	Price	\$144	\$134	\$144	\$153	\$163	\$173	\$153
Silicon nitride		–	A-5003-5735	–	–	–	–	–
	Price	–	\$188	–	–	–	–	–
Zirconia		–	A-5003-5749	–	–	–	–	–
	Price	–	\$188	–	–	–	–	–
		Tungsten carbide	Carbon fiber	Tungsten carbide	Carbon fiber	Carbon fiber	Carbon fiber	Carbon fiber
A	Ball dia. mm (in.)	3.0 (0.12)	6.0 (0.24)	5.0 (0.20)	6.0 (0.24)	8.0 (0.32)	10.0 (0.40)	10.0 (0.40)
B	Length mm (in.)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)	100.0 (3.94)
C	Stem dia. mm (in.)	1.5 (0.06)	4.0 (0.16)	3.0 (0.12)	4.0 (0.16)	6.0 (0.24)	6.0 (0.24)	6.0 (0.24)
D	EWL* mm (in.)	55.0 (2.17)	58.9 (2.32)	91.0 (3.59)	90.1 (3.55)	89.5 (3.52)	94.5 (3.72)	95.5 (3.76)
	Mass grams	16.30	19.66	14.40	7.08	10.17	11.11	23.91

100 mm range




* Effective working length

M5 styli

Ruby ball styli (carbon fiber stems)


Part number	A-5003-5265	A-5003-5266	A-5003-5267
A Ball dia. mm (in.)	6.0 (0.24)	8.0 (0.32)	10.0 (0.40)
B Length mm (in.)	150.0 (5.91)	150.0 (5.91)	150.0 (5.91)
C Stem dia. mm (in.)	4.0 (0.16)	6.0 (0.24)	6.0 (0.24)
D EWL* mm (in.)	137.0 (5.39)	135.0 (5.31)	144.5 (5.69)
Mass grams	9.09	13.71	14.66
Price	\$230	\$249	\$269

150 mm range



A-5003-5268	A-5003-5269	A-5003-5270
6.0 (0.24)	8.0 (0.32)	10.0 (0.40)
200.0 (7.88)	200.0 (7.88)	200.0 (7.88)
4.0 (0.16)	6.0 (0.24)	6.0 (0.24)
187.0 (7.36)	180.0 (7.09)	194.5 (7.66)
10.07	15.92	16.87
\$326	\$345	\$364

200 mm range





* Effective working length

Ruby ball styli (carbon fiber stems)

Part number	A-5003-5271	A-5003-5272	A-5003-5273	
A	Ball dia. mm (in.)	6.0 (0.24)	8.0 (0.32)	10.0 (0.40)
B	Length mm (in.)	300.0 (11.82)	300.0 (11.82)	300.0 (11.82)
C	Stem dia. mm (in.)	4.0 (0.16)	6.0 (0.24)	6.0 (0.24)
D	EWL* mm (in.)	287.0 (11.30)	280.0 (11.03)	294.5 (11.59)
	Mass grams	12.02	20.33	21.28
	Price	\$422	\$441	\$460


300 mm range



* Effective working length

Stylus extensions – thermo stable carbon fiber stems, titanium ends

Part number	A-5555-0647	A-5555-0648	A-5555-0649	A-5555-0623	A-5555-0650	A-5555-0651	A-5555-0652
Length mm (in.)	40.0 (1.58)	50.0 (1.97)	60.0 (2.37)	70.0 (2.76)	80.0 (3.15)	90.0 (3.55)	100.0 (3.94)
Stem dia. mm (in.)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)
Mass grams	7.6	8.3	9.0	9.7	10.4	11.1	11.8
Price	\$157**	\$159**	\$162**	\$166**	\$170**	\$182**	\$187**




M5 extension tools

A-5003-6134

For M5 threaded extensions with
11 mm (0.44 mm stem diameter)


Price: \$21



A-5003-6135

For M5 threaded extensions with
20 mm (0.79 in) stem diameter

Price: \$21




Note: These tools are designed to fit stylus extensions for Renishaw probes without causing any internal damage.

** Special

Stylus extensions – thermo stable carbon fiber stems, titanium ends


Part number	A-5555-0425	A-5555-0424	A-5555-0653	A-5555-0654	A-5555-0655	A-5555-0642	A-5555-0656
Length mm (in.)	120.0 (4.73)	150.0 (5.91)	180.0 (7.09)	200.0 (7.88)	250.0 (9.85)	300.0 (11.82)	400.0 (15.76)
Stem dia. mm (in.)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)
Mass grams	13.2	15.4	17.5	18.9	22.4	25.9	33.0
Price	\$191**	\$201**	\$208**	\$221**	\$238**	\$280**	\$333**



** Special


Stylus extensions – thermo stable carbon fiber stems, titanium ends

Part number	A-5555-0620	A-5555-0657	A-5555-0658	A-5555-0621	A-5555-0659	A-5555-0660	A-5555-0661
Length mm (in.)	40.0 (1.58)	50.0 (1.97)	60.0 (2.37)	80.0 (3.15)	100.0 (3.94)	120.0 (4.73)	150.0 (5.91)
Stem dia. mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
Mass grams	23.8	25.1	26.5	29.3	32.1	34.9	39.0
Price	\$154**	\$159**	\$162**	\$170**	\$192**	\$203**	\$214**



Stylus extensions – thermo stable carbon fiber stems, titanium ends




Part number	A-5555-0662	A-5555-0663	A-5555-0427	A-5555-0664	A-5555-0665	A-5555-0667	A-5555-0668
Length mm (in.)	180.0 (7.09)	200.0 (7.88)	250.0 (9.85)	300.0 (11.82)	400.0 (15.76)	500.0 (19.70)	600.0 (23.64)
Stem dia. mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
Mass grams	43.2	46.0	52.9	59.9	73.8	87.7	101.5
Price	\$229**	\$238**	\$266**	\$298**	\$349**	\$420**	\$280**



** Special


Stylus extensions – stainless steel

Part number	A-5555-0142	A-5555-0140	A-5555-0669	A-5555-0670	A-5555-0136
Length mm (in.)	10.0 (0.40)	20.0 (0.79)	30.0 (1.19)	50.0 (1.97)	100.0 (3.94)
Stem dia. mm (in.)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)	11.0 (0.44)
Mass grams	6.0	13.0	20.0	34.8	73.0
Price	\$25**	\$25**	\$25**	\$27**	\$29**



Stylus extensions – aluminum

Part number	A-5555-0671	A-5555-0127	A-5555-0125
Length mm (in.)	50.0 (1.97)	100.0 (3.94)	200.0 (7.88)
Stem dia. mm (in.)	20.0 (0.79)	20.0 (0.79)	20.0 (0.79)
Mass grams	47.2	50.0	85.0
Price	\$71**	\$73**	\$92**






** Special

M5 styli




Disk styli

Part number	A-5003-5288 Silver steel	A-5003-5289 Silver steel	A-5003-5290 Silver steel	A-5003-5291 Silver steel
Disk diameter mm (in.)	12.0 (0.48)	21.0 (0.83)	35.0 (1.38)	63.5 (2.51)
Disk depth mm (in.)	3.0 (0.12)	3.0 (0.12)	5.0 (0.20)	5.0 (0.20)
Roller depth mm (in.)	5.0 (0.20)	5.0 (0.20)	8.0 (0.32)	8.0 (0.32)
Mass grams	2.52	5.23	14.00	51.00
Price	\$125	\$134	\$144	\$163



Hemispherical styli

Part number	A-5003-5275 Ceramic	A-5003-5276 Ceramic	A-5003-5277 Ceramic
Ball diameter mm (in.)	16.0 (0.63)	22.0 (0.87)	30.0 (1.19)
Length mm (in.)	19.5 (0.77)	20.5 (0.81)	24.5 (0.96)
Mass grams	7.0	14.0	19.7
Price	\$225	\$225	\$300




Styli for FARO® arms

These styli have been designed especially for use on FARO® portable arm CMMs. Their robust design and construction utilizes Grade 5 Zirconia balls that have a high fracture toughness. The balls are bonded to the high strength tungsten carbide stem with impact resistant adhesive, and specialist construction techniques have been incorporated to ensure that the joint between the body and stem is extremely rigid and virtually indestructible.


1¼–20 UN thread styli

Part number	A-5003-7673	A-5003-7674	A-5003-7675
Ball dia (mm)	3	6	N/A
Length (mm)	57	57	57
Price	\$325	\$325	\$325



M6 styli


Part number	A-5003-7676	A-5003-7677	A-5003-7678	A-5003-7679
Ball dia	1/8 in	1/4 in	3 mm	6 mm
Length (mm)	43	43	43	43
Price	\$225	\$225	\$225	\$225



FARO® kit

A-5003-9190 FARO® probe kit 0073 12 piece

Price: \$1,034



Position	Part number	Description
1	A-5003-9127	M6M - M6F EXT L101.6 (4.0) D18 AL
2 and 3	A-5003-9126	M6M - M6F EXT L76.2 (3.0) D18 AL
4	A-5003-9186	M6F FARO EXT 60 DEG ADAPTOR
5	A-5003-9187	M6F FARO EXT 90 DEG ADAPTOR
6 and 7	P-SC08-0635	SCREW HEX SKT CAPHD M6X35 STST
8	A-5003-7679	STYLUS M6 DIA 6 MM 21 PROBE 0067
9	A-5003-7678	STYLUS M6 DIA 3 MM 21 PROBE 0065
10	M-5003-9133	FARO ADAPTOR 1.25-20 UN-M6
11	P-TL01-0500	SKT WRENCH 5MM A/F
12	P-TL09-0012	12 MM A/F OPEN/RING SPANNER


M5 styli, adaptors and accessories for Zeiss analog probe systems

Schematics not shown to scale

Styli with conical stem base, titanium base, tungsten carbide stem, ruby ball


Part number	A-5555-0001	A-5555-0002	A-5555-0003	A-5555-0004	A-5555-0005	A-5555-0006	A-5555-0007	A-5555-0008
Zeiss order number	600331-9096	602030-9003	602030-9004	600331-9098	602030-9005	602030-9006	602030-9007	600331-9097
DK (mm)	3	3	3	3	5	5	5	8
L (mm)	50	75	75	115	75	75	100	80
DG (mm)	19	19	19	19	19	19	19	19
ML (mm)	21.5	35	50	18	35	50	60	57
DS (mm)	2	2	2	2	3.5	3.5	3.5	6
Weight (g)	23	30	22	56	34	28	38	45
Price	\$94	\$96	\$90	\$143	\$106	\$101	\$106	\$140

Part number	A-5555-0009	A-5555-0010	A-5555-0011
Zeiss order number	600331-9099	602030-9008	602030-9009
DK (mm)	8	8	8
L (mm)	100	115	140
DG (mm)	19	19	19
ML (mm)	60	56.5	100
DS (mm)	6	6	6
Weight (g)	57	68	74
Price	\$150	\$150	\$159




Adaptor with thread/conical stem base, stainless steel

Part number	A-5555-0013	A-5555-0014
Zeiss order number	600331-0001	602030-0018
D (mm)	18	18
L (mm)	10	12
Weight (g)	12	10
Price	\$34	\$25



Conical holder, stainless steel

Part number	A-5555-0015	A-5555-0016	A-5555-0017
Zeiss order number	602030-8350	602030-8351	602030-8352
DS (mm)	2	3.5	6
L (mm)	24	24	24
DG (mm)	19	19	19
Weight (g)	29	29	29
Price	\$64	\$60	\$57




Tungsten carbide styli, titanium base, tungsten carbide stem, ruby ball

Schematics not shown to scale

Part number	A-5555-0018	A-5555-0019	A-5555-0020	A-5555-0021	A-5555-0022	A-5555-0023	A-5555-0024	A-5555-0025
Zeiss order number	602030-9010	600342-8020	602030-9011	600342-8021	600342-8025	602030-9012	602030-9013	600342-8022
DK (mm)	3	3	3	3	4	4	5	5
L (mm)	25	33.5	50	58	33.5	64	50	53
DG (mm)	11	11	11	11	11	11	11	11
ML (mm)	15	23.5	40	48	23.5	54	40	43
DS (mm)	2	2	2	2	2	2	3.5	3.5
Weight (g)	4	4.5	5.2	5.5	4.5	5.9	9	9.8
Price	\$45	\$45	\$45	\$45	\$57	\$60	\$53	\$50

Part number	A-5555-0026	A-5555-0027	A-5555-0028	A-5555-0029	A-5555-0030	A-5555-0031	A-5555-0032	A-5555-0033
Zeiss order number	602030-9015	600342-8026	600342-8027	600342-8023	600342-8123	602030-9014	602030-9016	602030-9017
DK (mm)	5	6	7	8	8	8	8	8
L (mm)	75	54	55	63.5	63.5	74	75	100
DG (mm)	11	11	11	11	19	11	11	11
ML (mm)	65	44	45	50.5	41.5	61	62	87
DS (mm)	3.5	3.5	3.5	6	6	6	6	6
Weight (g)	12.5	10	10	24.8	36.7	29.5	30	40
Price	\$57	\$57	\$60	\$64	\$69	\$66	\$66	\$66

Part number	A-5555-0034	A-5555-0035	A-5555-0036	A-5555-0037	A-5555-0038	A-5555-0039	A-5555-0040
Zeiss order number	600342-8024	600342-8124	600342-8028	600342-8128	600342-8029	600342-8129	602030-9018
DK (mm)	8	8	9	9	10	10	10
L (mm)	114.5	114.5	64.5	64.5	65.5	65.5	118
DG (mm)	11	19	11	19	11	19	11
ML (mm)	101.5	92.5	51.5	42.5	52.5	43.5	105
DS (mm)	6	6	6	6	6	6	6
Weight (g)	45.8	57.5	26.3	36.8	25.8	37.5	47.3
Price	\$66	\$83	\$67	\$81	\$73	\$94	\$73



Tungsten carbide styli, titanium base, tungsten carbide stem, silicon nitride ball

Schematics not shown to scale


Part number	A-5555-3777	A-5555-3778	A-5555-3779	A-5555-3780	A-5555-3781	A-5555-3782	A-5555-3783	A-5555-3784
Zeiss order number	-	-	-	-	-	-	-	-
DK (mm)	1	1	1	1.5	2	2	2	2
L (mm)	20	25	30	30	20	25	30	40
DG (mm)	11	11	11	11	11	11	11	11
ML1 (mm)	5	5	5	8	-	-	-	-
ML (mm)	10	15	20	20	10	15	20	30
DS1 (mm)	0.8	0.8	0.8	1	-	-	-	-
DS (mm)	1	1	1	1.5	1	1	1.5	1.5
Weight (g)	3.5	3.5	3.8	3.5	3.5	3.5	3.8	4
Price	\$52	\$52	\$52	\$52	\$52	\$52	\$52	\$52

Part number	A-5555-3785	A-5555-3786	A-5555-3787	A-5555-3734	A-5555-3788	A-5555-3789
Zeiss order number	626115-0303-025	626115-0300-033	626115-0302-050	626115-0300-058	626115-0400-034	6262115-0401-064
DK (mm)	3	3	3	3	4	4
L (mm)	25	33.5	50	58	33.5	64
DG (mm)	11	11	11	11	11	11
ML (mm)	15	23.5	40	48	23.5	54
DS (mm)	2	2	2	2	2	2
Weight (g)	4	4.5	5.3	5.5	4.5	5.9
Price	\$53	\$53	\$53	\$53	\$54	\$64

Part number	A-5555-3790	A-5555-3791	A-5555-3792	A-5555-3793	A-5555-3794	A-5555-3795
Zeiss order number	-	626115-0501-050	626115-0501-053	626115-0500-075	-	-
DK (mm)	5	5	5	5	5	6
L (mm)	30	50	53	75	100	54
DG (mm)	11	11	11	11	11	11
ML (mm)	20	40	43	65	90	44
DS (mm)	3.5	3.5	3.5	3.5	3.5	3.5
Weight (g)	8	9	9.8	12.5	18	10
Price	\$62	\$64	\$64	\$67	\$76	\$66

Part number	A-5555-3796	A-5555-3797	A-5555-3798	A-5555-3799	A-5555-3800	A-5555-3801
Zeiss order number	-	626115-0800-064	626115-0800-075	626115-0801-100	626115-0800-115	-
DK (mm)	7	8	8	8	8	9
L (mm)	55	63.5	75	100	114.5	64.5
DG (mm)	11	11	11	11	11	11
ML (mm)	45	50.5	62	87	101.5	51.5
DS (mm)	3.5	6	6	6	6	6
Weight (g)	10	36.6	29.4	39.9	45.7	26.3
Price	\$74	\$74	\$85	\$89	\$94	\$87


Part number	A-5555-3802	A-5555-3803	A-5555-3804
Zeiss order number	-	-	-
DK (mm)	10	10	10
L (mm)	65.5	118	150
DG (mm)	11	11	11
ML (mm)	52.5	105	135
DS (mm)	6	6	6
Weight (g)	25.8	47.3	60
Price	\$97	\$108	\$111



Reference styli (red dot), high-strength stainless steel base and stem, ruby ball

Schematics not shown to scale

Part number	A-5555-3805
Zeiss order number	600342-8023-010
DK (mm)	8
L (mm)	63.5
DG (mm)	11
ML (mm)	50.5
DS (mm)	6
Weight (g)	24.8
Price	\$106



Thermo stable carbon fiber styli, titanium base, thermo stable carbon fiber stem, ruby ball

Part number	A-5555-1916	A-5555-1847	A-5555-0730	A-5555-3806	A-5555-1917	A-5555-0731
Zeiss order number	626105-0300-025	626105-0300-033	626105-0300-050	626105-0300-058	626105-0400-033	626105-0400-064
DK (mm)	3	3	3	3	4	4
L (mm)	25	33.5	50	58	33.5	64
DG (mm)	11	11	11	11	11	11
ML (mm)	15	23.5	40	48	23.5	54
DS (mm)	2	2	2	2	2	2
Weight (g)	4	4.2	4.5	4.9	4.2	4.6
Price	\$69	\$71	\$73	\$83	\$76	\$92

Part number	A-5555-0732	A-5555-2013	A-5555-0735	A-5555-0410	A-5555-0733	A-5555-0734
Zeiss order number	626105-0510-050	—	626105-0510-075	626105-0510-100	626105-0610-054	626105-0710-055
DK (mm)	5	5	5	5	6	7
L (mm)	50	53	75	100	54	55
DG (mm)	11	11	11	11	11	11
ML (mm)	40	43	65	90	44	45
DS (mm)	3.5	3.5	3.5	3.5	3.5	3.5
Weight (g)	4.8	4.9	5	5.4	4.9	4.9
Price	\$85	\$85	\$87	\$104	\$90	\$104

Part number	A-5555-3807	A-5555-2011	A-5555-1918	A-5555-3808	A-5555-9361	A-5555-1112
Zeiss order number	626105-0820-063	626105-0820-075	626105-0820-100	626105-0820-114	626105-0820-150	626105-0820-200
DK (mm)	8	8	8	8	8	8
L (mm)	63.5	75	100	114.5	150	200
DG (mm)	11	11	11	11	11	11
ML (mm)	50.5	62	87	101.5	137	187
DS (mm)	6	6	6	6	6	6
Weight (g)	7	7.3	7.5	9.5	11	13
Price	\$111	\$115	\$120	\$124	\$157	\$173

Part number	A-5555-3809	A-5555-3810	A-5555-3811	A-5555-0643	A-5555-0644
Zeiss order number	—	626105-1020-065	626105-1020-118	626105-1020-150	626105-1020-200
DK (mm)	9	10	10	10	10
L (mm)	64.5	65.5	118	150	200
DG (mm)	11	11	11	11	11
ML (mm)	51.5	52.5	105	137	187
DS (mm)	6	6	6	6	6
Weight (g)	7.2	8	14.5	16	19
Price	\$117	\$133	\$150	\$185	\$205

Thermo stable carbon fiber styli, titanium base, thermo stable carbon fiber stem, silicon nitride ball


Schematics not shown to scale

Part number	A-5555-3812	A-5555-1828	A-5555-3813	A-5555-3814	A-5555-3815	A-5555-3816
Zeiss order number	-	626105-0301-033	-	626103-0301-058	-	-
DK (mm)	3	3	3	3	4	4
L (mm)	25	33.5	50	58	33.5	64
DG (mm)	11	11	11	11	11	11
ML (mm)	15	23.5	40	48	23.5	54
DS (mm)	2	2	2	2	2	2
Weight (g)	4	4.2	4.5	4.9	4.2	4.6
Price	\$96	\$97	\$99	\$110	\$115	\$118

Part number	A-5555-3817	A-5555-0759	A-5555-2012	A-5555-9045	A-5555-3818	A-5555-3819
Zeiss order number	626105-0511-050	-	626105-0511-075	626105-0511-100	-	-
DK (mm)	5	5	5	5	6	7
L (mm)	50	53	75	100	54	55
DG (mm)	11	11	11	11	11	11
ML (mm)	40	43	65	90	44	45
DS (mm)	3.5	3.5	3.5	3.5	3.5	3.5
Weight (g)	4.8	4.9	5	5.4	4.9	4.9
Price	\$111	\$111	\$113	\$131	\$117	\$131

Part number	A-5555-0720	A-5555-2010	A-5555-3820	A-5555-3821	A-5555-1169	A-5555-1179
Zeiss order number	626105-0821-063	-	626105-0821-100	626105-0821-114	626105-0821-150	626105-0821-200
DK (mm)	8	8	8	8	8	8
L (mm)	63.5	75	100	114.5	150	200
DG (mm)	11	11	11	11	11	11
ML (mm)	50.5	62	87	101.5	137	187
DS (mm)	6	6	6	6	6	6
Weight (g)	7	7.3	7.5	9.5	11	13
Price	\$140	\$141	\$147	\$150	\$184	\$199

Part number	A-5555-3822	A-5555-3823	A-5555-3824	A-5555-3825	A-5555-1171
Zeiss order number	-	-	626105-1021-118	626105-1021-150	626105-1021-200
DK (mm)	9	10	10	10	10
L (mm)	64.5	65.5	118	150	200
DG (mm)	11	11	11	11	11
ML (mm)	51.5	52.5	105	137	187
DS (mm)	6	6	6	6	6
Weight (g)	7.2	8	14.5	16	19
Price	\$143	\$159	\$177	\$212	\$231




Ceramic styli, titanium base, ruby ball

Schematics not shown to scale

Part number	A-5555-0041	A-5555-0042	A-5555-0043	A-5555-0044	A-5555-0045	A-5555-0046	A-5555-0047	A-5555-0048
Zeiss order number	600342-8013	600342-8016	600342-8017	600342-8014	600342-8018	600342-8118	600342-8019	600342-8119
DK (mm)	5	6	7	8	9	9	10	10
L (mm)	53	54	55	63.5	64.5	64.5	65.5	65.5
DG (mm)	11	11	11	11	11	19	11	19
ML (mm)	43	44	45	50.5	51.5	42.5	52.5	43.5
DS (mm)	3.5	3.5	3.5	6	6	6	6	6
Weight (g)	4.6	4.7	5	8.3	8.4	21	9	38
Price	\$52	\$57	\$64	\$69	\$71	\$80	\$80	\$87


Part number	A-5555-0049	A-5555-0050	A-5555-0051
Zeiss order number	600342-8114	600342-8015	600342-8115
DK (mm)	8	8	8
L (mm)	63.5	114.5	114.5
DG (mm)	19	11	19
ML (mm)	41.5	101.5	92.5
DS (mm)	6	6	6
Weight (g)	33	11.8	38
Price	\$71	\$80	\$81



Small ball styli, stepped stem, stainless steel base, tungsten carbide stem, ruby ball


Part number	A-5555-0052	A-5555-0053	A-5555-0054	A-5555-0055	A-5555-0056	A-5555-0057	A-5555-0058	A-5555-0059
Zeiss order number	602030-8060	602030-8061	602030-8062	602030-8063	602030-8064	602030-8065	602030-8066	602030-8067
DK (mm)	0.8	1	1.35	1.35	1.5	1.5	2	2
L (mm)	32	32	32	44	32	44	32	44
DG (mm)	11	11	11	11	11	11	11	11
ML (mm)	12	12	12	19	12	19	12	19
ML1 (mm)	4.8	5.0	-	-	-	-	-	-
DS (mm)	1	1	1	1	1	1	1.5	1.5
DS1 (mm)	0.6	0.8	-	-	-	-	-	-
Weight (g)	6.8	6.8	6.9	7.5	6.5	7.5	7.3	8
Price	\$78	\$67	\$66	\$69	\$66	\$69	\$66	\$69

Part number	A-5555-0060	A-5555-0061	A-5555-0062	A-5555-0063
Zeiss order number	602030-8068	602030-8069	602030-8070	602030-8071
DK (mm)	2	2.5	2.5	2.5
L (mm)	58	32	44	58
DG (mm)	11	11	11	11
ML (mm)	33	12	19	33
DS (mm)	1.5	1.5	1.5	1.5
Weight (g)	8	7.3	8	8
Price	\$67	\$66	\$69	\$73



Small ball styli, titanium base, tungsten carbide stem, ruby ball


Part number	A-5555-0064	A-5555-0065	A-5555-0066	A-5555-0067	A-5555-0068
Zeiss order number	602030-9019	602030-9020	602030-9021	602030-9022	602030-9023
DK (mm)	1	1.5	2	2.5	3.5
L (mm)	55	55	55	55	55
DG (mm)	11	11	11	11	11
ML (mm)	5	5	5	5	10
DS (mm)	0.8	1	1.5	2	2.5
Weight (g)	11.9	11.9	11.9	11.9	11.9
Price	\$140	\$131	\$127	\$131	\$131



Cube star, titanium base, tungsten carbide stem, ruby ball


Schematics not shown to scale

Part number	A-5555-0069	A-5555-0070	A-5555-0071	A-5555-0072	A-5555-0073
Zeiss order number	602030-9024	602030-9025	602030-9026	602030-9027	602030-9028
DK (mm)	1	1.5	2	2.5	3.5
L (mm)	45	45	45	45	45
ML (mm)	7	7.5	7.5	8	15
DS (mm)	2	2	2	2	2
DS1 (mm)	0.8	1	1.5	1.5	-
B (mm)	15	15	15	15	15
Weight (g)	17.3	17.3	17.3	17.3	17.3
Price	\$191	\$191	\$191	\$207	\$222



Styli for thread measurement, stainless steel base, tungsten carbide stem, ruby ball


Part number	A-5555-0074	A-5555-0075	A-5555-0076	A-5555-0077
Zeiss order number	602030-9070	602030-9071	602030-9072	602030-9073
DK (mm)	1.35	2.3	1.8	0.8
L (mm)	40	40	40	40
DG (mm)	11	11	11	11
ML (mm)	9	12	10	5
DS (mm)	1	1	1	0.6
B (mm)	2	2.5	2	1.9
Weight (g)	11	13	12	7
Price	\$103	\$124	\$134	\$199



Long threaded styli, thread length 12.5 mm, stainless steel base, tungsten carbide stem, ruby ball

Part number	A-5555-0078	A-5555-0079	A-5555-0080	A-5555-0081	A-5555-0082	A-5555-0083	A-5555-0084
Zeiss order number	600342-8200	600342-8201	600342-8202	600342-8203	600342-8221	600342-8222	600342-8250
DK (mm)	1.35	1.5	2	2.5	3	5	0.3
L (mm)	32.85	33	33.5	34	34.5	43.5	21.8
DG (mm)	11	11	11	11	19	19	11
ML (mm)	23.85	24	24.5	25	16.5	25.5	12.8
ML1 (mm)	-	-	-	-	-	-	2.3
DS (mm)	1	1	1.5	1.5	2	3.5	1
DS1 (mm)	-	-	-	-	-	-	0.2
Weight (g)	6	7	7	7	20	23	6
Price	\$46	\$46	\$41	\$43	\$55	\$64	\$80

Part number	A-5555-0085	A-5555-0086	A-5555-0087	A-5555-0088
Zeiss order number	600342-8251	600342-8252	600342-8253	600342-8254
DK (mm)	0.5	0.6	0.8	1
L (mm)	22	22.1	22.3	22.5
DG (mm)	11	11	11	11
ML (mm)	13	13.1	13.3	13.5
ML1 (mm)	2.5	4.6	4.8	5.0
DS (mm)	1	1	1	1
DS1 (mm)	0.3	0.4	0.6	0.8
Weight (g)	6	6	6	6
Price	\$64	\$64	\$62	\$55



M5 styli for Zeiss probing systems


Long threaded styli, thread length 5 mm, stainless steel base, tungsten carbide stem, ruby ball

Schematics not shown to scale

Part number	A-5555-0799	A-5555-9324	A-5555-3826	A-5555-3827	A-5555-0686	A-5555-3828
Zeiss order number	626115-0140-033	626115-0150-033	626115-0200-034	–	626115-0250-034	–
DK (mm)	1.35	1.5	2	2.5	2.5	3
L (mm)	32.85	33	33.5	34	34	25.5
DG (mm)	11	11	11	11	11	11
ML (mm)	23.85	24	24.5	25	25	16.5
DS (mm)	1	1	1.5	1	1.5	2
Weight (g)	6	7	7	7	7	9
Price	\$46	\$46	\$41	\$41	\$43	\$52


Part number	A-5555-3829	A-5555-0331	A-5555-1157	A-5555-1842	A-5555-1844	A-5555-1843
Zeiss order number	–	626115-0030-022	626115-0050-022	626115-0060-022	626115-0080-022	626115-0100-022
DK (mm)	5	0.3	0.5	0.6	0.8	1
L (mm)	34.5	21.8	22	22.1	22.3	22.5
DG (mm)	11	11	11	11	11	11
ML (mm)	25.5	12.8	13	13.1	13.3	13.5
ML1 (mm)	–	2.3	2.5	4.6	4.8	1.5
DS (mm)	3.5	1	1	1	1	1
DS1 (mm)	–	0.2	0.3	0.4	0.6	0.8
Weight (g)	9	6	6	6	6	6
Price	\$60	\$80	\$64	\$64	\$62	\$55

Part number	A-5555-1873
Zeiss order number	–
DK (mm)	1.5
L (mm)	33
DG (mm)	11
ML (mm)	24
ML1 (mm)	7
DS (mm)	1.5
DS1 (mm)	1
Weight (g)	7
Price	\$62




Flat washer for star styli, stainless steel

Part number	A-5555-0089	A-5555-0090
Zeiss order number	600341-0140	600341-0141
D (mm)	11	19
B (mm)	1.5	2
Weight (g)	1	4
Price	\$15	\$16



Grooved washer for star styli, stainless steel


Part number	A-5555-0091	A-5555-0092
Zeiss order number	600341-0150	600341-0151
D (mm)	11	19
B (mm)	2	4
Weight (g)	1	7
Price	\$46	\$48



Tungsten carbide pin for star styli


Schematics not shown to scale

Part number	A-5555-0093	A-5555-0094	A-5555-0095	A-5555-0096
Zeiss order number	600341-0520	600341-0521	600341-0522	600341-0523
L (mm)	10	10	18	18
D (mm)	1	1.5	2	3.5
Weight (g)	1	1	1	3
Price	\$6	\$6	\$8	\$8




Rotary adaptor, titanium

Part number	A-5555-0099	A-5555-0713
Zeiss order number	602030-9095	612030-9737
L (mm)	30	29
D (mm)	18	11
Weight (g)	43	13
Price	\$170	\$170




Holder, 90 degree offset, titanium

Part number	A-5555-1097
Zeiss order number	626105-6901-001
ML (mm)	17
DG (mm)	11
L (mm)	22.5
Weight (g)	6
Price	\$53




Rotary knuckle, slewing range 360 degrees, swing range 180 degrees, titanium

Part number	A-5003-5278	A-5555-3841
Zeiss order number	-	-
L (mm)	51	58
D (mm)	11	18
Weight (g)	19	58
Price	\$247	\$291



Holder, 90 degrees, stainless steel

Part number	A-5555-0104
Zeiss order number	600341-8160
DS1 (mm)	1-1.5
L (mm)	45
DG (mm)	11
DS (mm)	6
Weight (g)	16
Price	\$64




Fits with styli A-5555-0107 to A-5555-0115

M5 styli for Zeiss probing systems

5-way holder, stainless steel


Schematics not shown to scale

Part number	A-5555-0105	A-5555-0106	A-5555-1245
Zeiss order number	600341-8367	600341-8368	626115-5000-199
DS (mm)	1	1.5	2
L (mm)	10	10	10
DG (mm)	11	11	11
Weight (g)	3.2	3.2	3.2
Price	\$64	\$64	\$64



Styli for holder, tungsten carbide stem, ruby ball


Part number	A-5555-0107	A-5555-0108	A-5555-0109	A-5555-0110	A-5555-0111
Zeiss order number	600341-8454	600341-8450	600341-8451	600341-8452	600341-8453
DK (mm)	1	0.3	0.5	0.6	0.8
L (mm)	16	15.3	15.5	15.6	15.8
DS (mm)	1	1	1	1	1
DS1 (mm)	0.8	0.2	0.3	0.4	0.6
ML (mm)	5	2.3	2.5	4.6	4.8
Weight (g)	1	1	1	1	1
Price	\$48	\$64	\$165	\$48	\$46



Part number	A-5555-0112	A-5555-0113	A-5555-0114	A-5555-0115	A-5555-0116	A-5555-0117
Zeiss order number	600341-8500	600341-8501	600341-8502	600341-8503	600341-8510	600341-8511
DK (mm)	1.35	1.5	2	2.5	3	5
L (mm)	26.35	26.5	27	27.5	38	45
DS (mm)	1	1	1.5	1.5	2	3.5
Weight (g)	1	1	1	1	2	6
Price	\$48	\$39	\$45	\$46	\$45	\$50


Holder for swivel styli, stainless steel

Part number	A-5555-0118
Zeiss order number	600341-8180
L (mm)	40
DG (mm)	11
DS (mm)	6
DS1 (mm)	1-1.5
Weight (g)	15
Price	\$80



Styli for swiveling components, S4 steel ball, tungsten carbide stem, ruby ball


Part number	A-5555-0119	A-5555-0120
Zeiss order number	600341-8183	600341-8185
DK (mm)	1	2
L (mm)	17.5	28.5
DS (mm)	1	1.5
DS1 (mm)	0.8	-
ML (mm)	5	24.5
Weight (g)	1	1
Price	\$69	\$66



Star styli, stainless steel base, tungsten carbide stem, ruby ball


Part number	A-5555-1153	A-5555-1135	A-5555-3839
Zeiss order number	-	-	-
DK (mm)	0.6	0.8	1
L (mm)	40	40	40
DG (mm)	11	11	11
DS (mm)	4	4	4
DS1 (mm)	0.4	0.6	0.8
ML (mm)	30	30	30
A (mm)	8	8	8
Weight (g)	9	9	9
Price	\$701	\$631	\$573

Schematics not shown to scale




Reference sphere with stem, M8 thread, stainless steel, ceramic ball including certificate

Part number	A-5555-3842	A-5555-3843	A-5555-3844	A-1034-0124
Zeiss order number	-	-	-	-
DK (mm)	15	20	25	30
L (mm)	130	135	140	145
DG (mm)	24	24	24	24
SW (mm)	22	22	22	22
Price	\$397	\$502	\$525	\$550



Spherical disk styli, aluminum base, high-strength steel disk

Part number	A-5555-0121	A-5555-0122	A-5555-0123	A-5555-0124
Zeiss order number	600341-8090	600341-8095	602030-8091	000000-1165-629
DK (mm)	10	15	20	15
L (mm)	21.5	21.5	60	40
DG (mm)	7	10	7	7
B (mm)	1.5	1.5	1	1
Weight (g)	3	6	8	5
Price	\$166	\$168	\$247	\$212



Extensions

Aluminum, stainless steel ends

Part number	A-5555-0125	A-5555-0126	A-5555-0127	A-5555-0128	A-5555-0129	A-5555-0130	A-5555-0131	A-5555-0132
Zeiss order number	600341-8420	600341-8421	600341-8422	600341-8423	600341-8424	600341-8425	600341-8265	600341-8264
L (mm)	200	150	100	80	60	40	120	100
D (mm)	20	20	20	20	20	20	11	11
Weight (g)	84.7	67.4	50.7	44.8	37.7	29	30.9	25.6
Price	\$92	\$81	\$73	\$71	\$71	\$67	\$48	\$46

Part number	A-5555-0133	A-5555-0134	A-5555-0135
Zeiss order number	600341-8263	600341-8262	600341-8261
L (mm)	80	60	40
D (mm)	11	11	11
Weight (g)	20.6	15.4	10.3
Price	\$45	\$41	\$39

Stainless steel

Part number	A-5555-0136	A-5555-0137	A-5555-0138	A-5555-0139	A-5555-0140	A-5555-0141	A-5555-0142
Zeiss order number	600341-0260	600341-0258	600341-0256	600341-0254	600341-0252	600341-0251	600341-0250
L (mm)	100	80	60	40	20	15	10
D (mm)	11	11	11	11	11	11	11
Weight (g)	73	58	42	28	13	9	6
Price	\$29	\$29	\$27	\$25	\$25	\$25	\$25


Titanium

Part number	A-5555-0143	A-5555-0144	A-5555-0145	A-5555-0146	A-5555-0147	A-5555-0148	A-5555-0149	A-5555-0150
Zeiss order number	602030-9044	602030-9045	602030-9046	602030-9047	602030-9048	602030-9049	602030-9050	602030-9051
L (mm)	10	15	20	25	25	40	40	50
D (mm)	11	11	11	11	18	11	18	11
Weight (g)	3.9	5.7	7.5	9.5	24.6	12.6	31.5	13.2
Price	\$30	\$34	\$36	\$37	\$39	\$39	\$48	\$62

Part number	A-5555-0151	A-5555-0152	A-5555-0153	A-5555-0154	A-5555-0155	A-5555-0156	A-5555-0157	A-5555-0158
Zeiss order number	602030-9052	602030-9053	602030-9054	602030-9055	602030-9056	602030-9057	602030-9058	602030-9059
L (mm)	50	60	60	75	75	80	80	90
D (mm)	18	11	18	11	18	11	18	11
Weight (g)	33.3	14.2	35.1	15.3	37.9	15.6	38.8	16.5
Price	\$71	\$64	\$74	\$67	\$78	\$73	\$80	\$73

Part number	A-5555-0159	A-5555-0160	A-5555-0161	A-5555-0162	A-5555-0163	A-5555-0164	A-5555-0165	A-5555-0166
Zeiss order number	602030-9060	602030-9061	602030-9062	602030-9063	602030-9064	602030-9065	602030-9066	602030-9067
L (mm)	90	100	100	120	120	150	150	200
D (mm)	18	11	18	11	18	11	18	18
Weight (g)	40.6	17.2	42.5	19.8	46.1	22.5	51.6	61
Price	\$85	\$73	\$89	\$78	\$97	\$85	\$106	\$115

Part number	A-5555-0167	A-5555-0168
Zeiss order number	602030-9068	602030-9069
L (mm)	250	300
D (mm)	18	18
Weight (g)	70	79
Price	\$127	\$143



Black thermo stable carbon fiber, titanium ends

Schematics not shown to scale


Part number	A-5555-0647	A-5555-0648	A-5555-0649	A-5555-0623	A-5555-0650	A-5555-0651
Zeiss order number	626107-1040-100	626107-1050-100	626107-1060-100	626107-1070-100	626107-1080-100	626107-1090-100
L (mm)	40	50	60	70	80	90
D (mm)	11	11	11	11	11	11
Weight (g)	9	10	11	10	12	13
Price	\$157	\$159	\$162	\$166	\$170	\$182

Part number	A-5555-0652	A-5555-0425	A-5555-0424	A-5555-0653	A-5555-0654	A-5555-0655
Zeiss order number	626107-1100-100	626107-1120-100	626107-1150-100	626107-1180-100	626107-1200-100	626107-1250-100
L (mm)	100	120	150	180	200	250
D (mm)	11	11	11	11	11	11
Weight (g)	14	15	17	19	21	24
Price	\$187	\$191	\$201	\$208	\$221	\$238

Part number	A-5555-0642	A-5555-0656	A-5555-0620	A-5555-0657	A-5555-0658	A-5555-0621
Zeiss order number	626107-1300-100	626107-1400-100	626107-2040-100	626107-2050-100	626107-2060-100	626107-2080-100
L (mm)	300	400	40	50	60	80
D (mm)	11	11	21	20	21	21
Weight (g)	27	34	26	28	29	32
Price	\$280	\$333	\$154	\$159	\$162	\$170

Part number	A-5555-0659	A-5555-0661	A-5555-0663	A-5555-0427	A-5555-0664	A-5555-0665
Zeiss order number	626107-2100-100	626107-2150-100	626107-2200-100	626107-2250-100	626107-2300-100	626107-2400-100
L (mm)	100	150	200	250	300	400
D (mm)	21	21	21	21	21	20
Weight (g)	34	41	48	55	62	75
Price	\$192	\$214	\$238	\$266	\$298	\$349

Part number	A-5555-0667	A-5555-0668
Zeiss order number	626107-2500-100	626107-2600-100
L (mm)	500	600
D (mm)	20	20
Weight (g)	89	103
Price	\$420	\$280



Adaptor plate extension for MT/VAST. Black thermo stable carbon fiber, titanium cube and plate adaptor

Schematics not shown to scale



Part number	A-5555-3845	A-5555-3846	A-5555-3847	A-5555-3848	A-5555-3849	A-5555-3850
Zeiss order number	-	-	-	-	-	-
L (mm)	25	40	50	60	80	100
DG (mm)	11	11	11	11	11	11
ML (mm)	66.5	81.5	91.5	101.5	121.5	141.5
B (mm)	15	15	15	15	15	15
Weight (g)	60	62	64	66	68	70
Price	\$259	\$266	\$273	\$282	\$298	\$309

Part number	A-5555-3851	A-5555-3740	A-5555-3852	A-5555-0699	A-5555-1985	A-5555-1986
Zeiss order number	-	-	-	625107-2025-130	625107-2040-130	625107-2050-130
L (mm)	120	150	200	25	40	50
DG (mm)	11	11	11	20	20	20
ML (mm)	161.5	191.5	241.5	66.5	81.5	91.5
B (mm)	15	15	15	15	15	15
Weight (g)	72	77	84	60	62	64
Price	\$321	\$361	\$374	\$277	\$284	\$291

Part number	A-5555-1987	A-5555-0700	A-5555-1988	A-5555-1989	A-5555-0701	A-5555-1990
Zeiss order number	626107-2060-130	626107-2080-130	626107-2100-130	625107-2120-130	625107-2150-130	625107-2200-130
L (mm)	60	80	100	120	150	200
DG (mm)	20	20	20	20	20	20
ML (mm)	101.5	121.5	141.5	161.5	191.5	241.5
B (mm)	15	15	15	15	15	15
Weight (g)	66	68	70	72	77	84
Price	\$300	\$317	\$335	\$349	\$376	\$418

Part number	A-5555-1979	A-5555-1980	A-5555-1855	A-5555-1981	A-5555-1982	A-5555-1983
Zeiss order number	626107-2025-110	626107-2040-110	626107-2050-110	625107-2060-110	625107-2080-110	625107-2100-110
L (mm)	25	40	50	60	80	100
DG (mm)	20	20	20	20	20	20
ML (mm)	71.5	86.5	96.6	106.5	126.5	146.5
B (mm)	20	20	20	20	20	20
Weight (g)	74	76	78	80	82	84
Price	\$265	\$284	\$293	\$302	\$319	\$337


Part number	A-5555-1938	A-5555-1937	A-5555-1984
Zeiss order number	626107-2120-110	626107-2150-110	626107-2200-110
L (mm)	120	150	200
DG (mm)	20	20	20
ML (mm)	166.5	196.5	246.5
B (mm)	20	20	20
Weight (g)	86	91	98
Price	\$349	\$376	\$418



Schematics not shown to scale

Cube, titanium

Part number	A-5555-0189	A-5555-0190
Zeiss order number	600341-8361	600341-8002
B (mm)	15	20
Weight (g)	12.6	31.5
Price	\$50	\$60




Cube, aluminum

Part number	A-5555-0191	A-5555-0192
Zeiss order number	602030-8363	602030-8362
B (mm)	15	20
Weight (g)	7.5	20
Price	\$69	\$87

Double cube (titanium)


Part number	A-5555-0194
Zeiss order number	600342-8103
B (mm)	20
L (mm)	40
Weight (g)	64
Price	\$108



Spherical disk, high-strength steel

Part number	A-5555-0196	A-5555-0197	A-5555-0198	A-5555-0199	A-5555-0200	A-5555-0201	A-5555-0203
Zeiss order number	602030-0004	602030-0005	602030-0006	602030-0007	602030-0008	602030-0009	602030-0011
B (mm)	4	4	4	5	5	5	4
DK (mm)	15	20	30	40	50	60	20
M5/8 (mm)	M5	M5	M5	M5	M5	M5	8
Weight (g)	5	9	21	42	64	89	8
Price	\$134	\$134	\$136	\$145	\$145	\$148	\$147

Part number	A-5555-0204	A-5555-0205	A-5555-0206	A-5555-0207	A-5555-0208
Zeiss order number	600341-0200	600341-0203	600341-0204	600341-0205	600341-0206
B (mm)	2	4	4	5	6
DK (mm)	20	30	40	50	60
M5/8 (mm)	8	8	8	8	8
Weight (g)	4	10	21	36	59
Price	\$138	\$138	\$140	\$154	\$159




M5 styli for Zeiss probing systems

Hole location gage, stainless steel


Schematics not shown to scale

Part number	A-5555-0209	A-5555-0210	A-5555-0211	A-5555-0212	A-5555-0213	A-5555-0214
Zeiss order number	602030-0012	602030-0013	600203-0014	602030-0015	602030-0016	600203-0017
G1	M4	M5	M6	M8	M10	M12
L (mm)	16	16	18	20	25	25
DG (mm)	10	10	12	15	18	20
ML (mm)	10	10	12	12	15	15
MB (mm)	1.8	1.8	1.8	3	3	3
Weight (g)	4	4	7	13	25	33
Price	\$73	\$73	\$71	\$74	\$74	\$76




Star stylus, stainless steel base, tungsten carbide stem, ruby ball

Part number	A-5555-0215
Zeiss order number	600331-8093
DK (mm)	5
L (mm)	80
DG (mm)	19
DS (mm)	3.5
Weight (g)	70
Price	\$437




Pointed stylus, titanium base, tungsten carbide stem

Part number	A-5555-0216
Zeiss order number	600342-8051
L (mm)	61
DG (mm)	11
ML (mm)	39
DS (mm)	3.5
Weight (g)	12
Price	\$69




Cube extension, titanium

Part number	A-5555-0217
Zeiss order number	602030-0019
L (mm)	120
B (mm)	20
Weight (g)	87
Price	\$265



Knuckle, swing range 180 degrees, titanium


Part number	A-5555-0218	A-5555-0219
Zeiss order number	600342-9002	600342-9003
L (mm)	30	36
D (mm)	11	18
Weight (g)	11.2	37.2
Price	\$122	\$140



Bolts for spherical disk and cube, stainless steel

Schematics not shown to scale

Part number	A-5555-0221	A-5555-0222	A-5555-0223
Zeiss order number	600341-0210	600341-0211	600341-0212
L (mm)	35	30	17.5
ML (mm)	26	21	9
Weight (g)	9	9	7
Price	\$19	\$17	\$15




Bolts for cubes, stainless steel

Part number	A-5555-0224	A-5555-0225
Zeiss order number	600341-0220	600341-0221
ML (mm)	26	21
Weight (g)	4	3
Price	\$9	\$9


Adaptor, stainless steel

Part number	A-5555-0226	A-5555-0227	A-5555-0228
Zeiss order number	602030-0215	602030-0315	602030-0318
Threads	M5/M2	M5/M3	M5/M4
L (mm)	10	10	10
DG (mm)	11	11	11
Weight (g)	5.2	5.2	5.2
Price	\$20	\$20	\$20



Holder for digitalization styli, stainless steel

Part number	A-5555-0231	A-5555-0232
Zeiss order number	602030-9113	602030-9115
L (mm)	119	127
D (mm)	15.81	9.52
B	M2	M2
Weight (g)	126	87
Price	\$268	\$302




Adaptor plates for Zeiss probe heads

Adaptor plate for dynamic systems (ST), aluminum


Part number	A-5555-0322	A-5555-0251
Zeiss order number	600660-8240	600660-8251
Quantity in kit	1	2
Weight (g)	72	144
Price	\$300	\$599

Schematics not shown to scale



Adaptor plate for Prismo dynamic systems (ST), aluminum


Part number	A-5555-0253	A-5555-3900
Zeiss order number	620660-8251-000	—
Quantity in kit	2	1
Weight (g)	144	72
Price	\$599	\$300



Adaptor plate for measuring systems MT/Vast, aluminum, with active ID chip


Part number	A-5555-0255	A-5555-0256	A-5555-0258*
Zeiss order number	600667-9601	600667-9611	600667-8571
Quantity in kit	1	2	1
Weight (g)	153	306	130
Price	\$441	\$881	\$441

* adaptor plate without cube




Adaptor plate for XXT TL1, reference plate for XXT TL1

Part number	A-5555-1235	A-5555-1236
Zeiss order number	620161-8055-000	620161-8058-000
Weight (g)	4.6	4.6
Price	\$390	\$312




Adaptor plate for VAST XXT TL2, reference plate for XXT TL2

Part number	A-5555-1237	A-5555-1238
Zeiss order number	620161-8065-000	620161-8068-000
Weight (g)	5.4	5.4
Price	\$369	\$369



Adaptor plate for VAST XXT TL3, reference plate for XXT TL3

Part number	A-5555-1239	A-5555-1240
Zeiss order number	620161-8075-000	620161-8078-000
Weight (g)	4.6	4.6
Price	\$369	\$369



VAST XXT TL1 with star adaptor

Part number	A-5555-1241
Zeiss order number	626103-8031-055
Weight (g)	6.3
Price	\$340

VAST XXT TL3 with star adaptor

Part number	A-5555-1242
Zeiss order number	626103-8033-055
Weight (g)	6.3
Price	\$340

M3 styli, adaptors and accessories for Zeiss analog probe systems

Schematics not shown to scale

Carbide styli XXT, titanium base, tungsten carbide stem, ruby ball


Part number	A-5004-3176	A-5004-2185	A-5004-1702	A-5004-2186	A-5555-3853	A-5004-3179
Zeiss order number	626113-0030-013	626113-0030-020	626113-0050-013	626113-0050-020	626113-0060-014	626113-0060-020
DK (mm)	0.3	0.3	0.5	0.5	0.6	0.6
L (mm)	13	20	13	20	14	20
DG (mm)	5	5	5	5	5	5
ML (mm)	4	11	4	11	5	1
ML1 (mm)	2.3	2.3	2.3	2.3	4.6	4.6
DS (mm)	1	1	1	1	1	1
DS1 (mm)	0.2	0.2	0.3	0.3	0.4	0.4
Weight (g)	0.62	0.69	0.61	0.69	0.61	0.68
Price	\$167	\$73	\$73	\$73	\$57	\$60

Part number	A-5004-3273	A-5004-3274	A-5004-1883	A-5004-3187	A-5555-3854	A-5004-1863
Zeiss order number	626113-0080-014	626113-0080-020	626113-0080-034	626113-0100-014	626113-0101-020	626113-0100-020
DK (mm)	0.8	0.8	0.8	1	1	1
L (mm)	14	20	34	14	20	20
DG (mm)	5	5	5	5	5	5
ML (mm)	5	11	25	5	11	11
ML1 (mm)	-	4.8	4.1	-	5.1	5
DS (mm)	0.6	1	1	0.8	1	1
DS1 (mm)	-	0.6	0.6	-	0.6	0.8
Weight (g)	0.62	0.69	0.8	0.63	0.7	0.69
Price	\$57	\$57	\$69	\$59	\$64	\$60

Part number	A-5004-3519	A-5004-3427	A-5555-9341	A-5004-3272	A-5004-1862	A-5555-9339
Zeiss order number	626113-0130-020	626113-0100-030	626113-0100-040	626113-0150-014	626113-0150-020	626113-0151-030
DK (mm)	1	1	1	1.5	1.5	1.5
L (mm)	20	30	40	14	20	30
DG (mm)	5	5	5	5	5	5
ML (mm)	11	21	31	5	11	21
ML1 (mm)	-	5	5	-	-	-
DS (mm)	0.8	1	1	1	1	1
DS1 (mm)	-	0.8	0.8	-	-	-
Weight (g)	0.7	0.8	1.5	0.65	0.72	0.84
Price	\$54	\$64	\$66	\$57	\$60	\$62

Part number	A-5555-9340	A-5004-1779	A-5004-3188	A-5004-1861	A-5004-0656	A-5555-3855
Zeiss order number	626113-0150-030	626113-0151-040	626113-0200-014	626113-0200-020	626113-0200-030	626113-0021-040
DK (mm)	1.5	1.5	2	2	2	2
L (mm)	30	40	14	20	30	40
DG (mm)	5	5	5	5	5	5
ML (mm)	22.5	31	5	11	21	31
DS (mm)	1	1	1	1	1	1.5
Weight (g)	0.9	1.6	0.66	0.72	0.83	1.7
Price	\$67	\$69	\$59	\$62	\$60	\$64

Part number	A-5555-3856	A-5555-3857	A-5004-3428
Zeiss order number	626113-0250-020	626113-0250-030	626113-0250-040
DK (mm)	2.5	2.5	2.5
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	1.5	1.5	1.5
Weight (g)	1	1.5	2
Price	\$60	\$62	\$64




M3 styli for Zeiss probing systems

Reference styli XXT (red dot), titanium base, thermo stable carbon fiber stem, ruby ball

Schematics not shown to scale

Part number	A-5555-2033	A-5555-3858
Zeiss order number	626103-0501-030	626103-0501-050
DK (mm)	5	5
L (mm)	30	50
DG (mm)	5	5
ML (mm)	21	41
DS (mm)	3.5	3.5
Weight (g)	1.1	1.4
Price	\$110	\$106



Thermo stable carbon fiber styli XXT, titanium base, thermo stable carbon fiber stem, ruby ball


Schematics not shown to scale

Part number	A-5555-3859	A-5004-0802	A-5555-1251	A-5004-1884	A-5004-0803	A-5555-3860
Zeiss order number	626103-0300-025	626103-0300-033	626103-0300-040	626103-0300-042	626103-0300-050	626103-0300-058
DK (mm)	3	3	3	3	3	3
L (mm)	25	33	40	42	50	58
DG (mm)	5	5	5	5	5	5
ML (mm)	16	24	31	33	41	49
DS (mm)	2	2	2	2	2	2
Weight (g)	0.65	0.7	0.8	0.8	0.8	1
Price	\$89	\$97	\$96	\$99	\$99	\$106

Part number	A-5555-3861	A-5555-3862	A-5004-2786	A-5004-2108	A-5003-0062	A-5004-0806
Zeiss order number	626103-0300-059	626103-0300-075	626103-0401-050	626103-0500-030	626103-0500-040	626103-0500-050
DK (mm)	3	3	4	5	5	5
L (mm)	59	75	50	30	40	50
DG (mm)	5	5	5	5	5	5
ML (mm)	50	66	41	21	31	41
DS (mm)	2	2	2	3.5	3.5	3.5
Weight (g)	1	1	1	1.1	1.2	1.4
Price	\$106	\$108	\$99	\$106	\$74	\$106

Part number	A-5555-3864	A-5555-1114	A-5004-3429	A-5555-3865	A-5555-1115	A-5555-3866
Zeiss order number	626103-0500-060	626103-0501-075	626103-0600-050	626103-0610-070	626103-0600-100	626103-0800-030
DK (mm)	5	5	6	6	6	8
L (mm)	60	75	50	70	100	30
DG (mm)	5	5	5	5	5	5
ML (mm)	51	66	40	61	91	30
DS (mm)	3.5	3.5	3.5	3.5	3.5	5
Weight (g)	1.5	1.8	1.5	1.8	2.4	1.86
Price	\$108	\$113	\$126	\$127	\$129	\$138


Part number	A-5555-3867	A-5555-3868	A-5555-3869	A-5004-0808
Zeiss order number	626103-0830-050	626103-0830-070	626103-0830-100	626103-0800-125
DK (mm)	8	8	8	8
L (mm)	50	70	100	125
DG (mm)	5	5	5	5
ML (mm)	50	70	100	125
DS (mm)	5	5	5	5
Weight (g)	2.1	2.6	2.7	2.9
Price	\$148	\$154	\$159	\$162



Thermo stable carbon fiber styli XXT, titanium base, thermo stable carbon fiber stem, silicon nitride ball


Schematics not shown to scale

Part number	A-5555-3870	A-5555-3871	A-5555-3872	A-5004-1858	A-5555-3873	A-5555-3874
Zeiss order number	626103-0301-033	626103-0301-050	626103-0502-050	626103-0500-075	626103-0801-070	626103-0801-125
DK (mm)	3	3	5	5	8	8
L (mm)	33	50	50	75	70	125
DG (mm)	5	5	5	5	5	5
ML (mm)	24	41	41	66	70	125
DS (mm)	2	2	3.5	3.5	5	5
Weight (g)	0.7	0.8	1.4	1.8	2.6	2.9
Price	\$122	\$126	\$134	\$138	\$205	\$212




Thermo stable carbon fiber clamping styli XXT, titanium base, thermo stable carbon fiber stem, ruby ball

Part number	A-5555-3875	A-5555-3876	A-5004-3282
Zeiss order number	626103-0301-020	626103-0301-030	626103-0301-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	0.7	0.75	0.8
Price	\$99	\$104	\$110



Thermo stable carbon fiber clamping styli XXT, titanium base, thermo stable carbon fiber stem, silicon nitride ball


Part number	A-5555-3877	A-5555-3878	A-5555-3879
Zeiss order number	626103-0311-020	626103-0311-030	626103-0311-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	0.7	0.75	0.8
Price	\$104	\$110	\$113



¼ star styli, thermo stable carbon fiber XXT, titanium base, thermo stable carbon fiber stem, ruby ball


Schematics not shown to scale

Part number	A-5555-1273	A-5555-1274	A-5555-1275
Zeiss order number	626103-0302-020	626103-0302-030	626103-0302-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	0.8	0.9	1
Price	\$157	\$162	\$168




¼ star styli, thermo stable carbon fiber XXT, titanium base, thermo stable carbon fiber stem, silicon nitride ball

Part number	A-5555-3880	A-5555-3881	A-5555-3901
Zeiss order number	626103-0312-020	626103-0312-030	626103-0312-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	0.8	0.9	1
Price	\$157	\$162	\$168




½ star styli, thermo stable carbon fiber XXT, 90 degrees, titanium base, thermo stable carbon fiber stem, ruby ball

Part number	A-5555-3882	A-5555-3883	A-5004-3284
Zeiss order number	626103-0303-020	626103-0303-030	626103-0303-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	1.4	1.5	1.6
Price	\$309	\$314	\$319



½ star styli, thermo stable carbon fiber XXT, 90 degrees, titanium base, thermo stable carbon fiber stem, silicon nitride ball

Part number	A-5555-3884	A-5555-3885	A-5555-3886
Zeiss order number	626103-0313-020	626103-0313-030	626103-0313-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	1.4	1.5	1.6
Price	\$309	\$314	\$319




M3 styli for Zeiss probing systems

1/2 star styli, thermo stable carbon fiber XXT, 180 degrees, titanium base, thermo stable carbon fiber stem, ruby ball


Schematics not shown to scale

Part number	A-5555-3887	A-5555-3888	A-5004-0654
Zeiss order number	626103-0304-020	626103-0304-030	626103-0304-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	1.4	1.5	1.6
Price	\$309	\$314	\$235



1/2 star styli, thermo stable carbon fiber XXT, 180 degrees, titanium base, thermo stable carbon fiber stem, silicon nitride ball


Part number	A-5555-3889	A-5555-3890	A-5555-3891
Zeiss order number	626103-0314-020	626103-0314-030	626103-0314-040
DK (mm)	3	3	3
L (mm)	20	30	40
DG (mm)	5	5	5
ML (mm)	11	21	31
DS (mm)	2	2	2
Weight (g)	1.4	1.5	1.6
Price	\$309	\$314	\$319



Extension XXT, thermo stable black carbon fiber, titanium ends

Part number	A-5555-3892	A-5555-1947	A-5004-3430	A-5555-3893	A-5004-0002	A-5555-3894
Zeiss order number	626103-5020-000	626103-5025-000	626103-5030-000	626103-5040-000	626103-5050-000	626103-5060-000
D (mm)	5	5	5	5	5	5
L (mm)	20	25	30	40	50	60
Weight (g)	1.2	1.25	1.3	1.4	1.5	1.7
Price	\$73	\$78	\$81	\$71	\$99	\$106


Part number	A-5555-1948	A-5004-2001	A-5004-1859	A-5555-3895	A-5555-1276
Zeiss order number	626103-5075-000	626103-5080-000	626103-5100-000	626103-5130-000	626103-5150-000
D (mm)	5	5	5	5	5
L (mm)	75	80	100	130	150
Weight (g)	1.7	1.8	2	2.5	2.7
Price	\$120	\$124	\$140	\$166	\$182



Clamping screw XXT, titanium


Schematics not shown to scale

Part number	A-5004-1856
Zeiss order number	626103-6110-004
DG (mm)	5
L (mm)	8
Weight (g)	0.5
Price	\$18




Clamping screw XXT with internal M3 thread, titanium

Part number	A-5004-1857
Zeiss order number	626103-6110-005
DG (mm)	5
L (mm)	8
Weight (g)	0.7
Price	\$18




Cube XXT 90 degrees, 1 way, titanium

Part number	A-5004-3437
Zeiss order number	626103-6110-001
B (mm)	5
L (mm)	6.5
Weight (g)	0.64
Price	\$71




Cube XXT 180 degrees, 2 way, titanium

Part number	A-5555-3896
Zeiss order number	626103-6110-002
B (mm)	5
L (mm)	13
Weight (g)	1.05
Price	\$81



Cube star XXT, titanium

Part number	A-5555-3897
Zeiss order number	626103-6110-003
B (mm)	5
L (mm)	13
Weight (g)	1.8
Price	\$90




M3 styli for Zeiss probing systems

Cube XXT, 6 star, titanium


Schematics not shown to scale

Part number	A-5555-3898
Zeiss order number	626103-6110-006
B (mm)	5
DG (mm)	12
Weight (g)	1.8
Price	\$113



Cube XXT, 8 star, titanium

Part number	A-5555-3899
Zeiss order number	626103-6110-007
B (mm)	5
DG (mm)	14
Weight (g)	2.3
Price	\$131



Knuckle XXT, titanium


Part number	A-5004-3285
Zeiss order number	626103-6180-001
B (mm)	5
L (mm)	10
Weight (g)	1.65
Price	\$168

Tungsten carbide styli, stainless steel base, tungsten carbide stem, ruby ball

Schematics not shown to scale


Part number	A-5555-0261	A-5555-0263	A-5555-0265	A-5555-0267	A-5555-0268	A-5555-0269	A-5555-0270	A-5555-0271
Zeiss order number	602030-8104	602030-8113	602030-8112	602030-8115	602030-8116	602030-8117	602030-8118	602030-8119
DK (mm)	2	3	4	0.5	0.6	0.8	1	1.5
L (mm)	22	40	33	22	22	22	22	22
DG (mm)	4	5.5	4	4	4	4	4	4
ML (mm)	9	21.5	23	9	9	9	9	9
ML1 (mm)	-	-	-	2.5	4.6	4.8	5	-
DS (mm)	1	2	2.5	1	1	1	1	1
DS1 (mm)	-	-	-	0.3	0.4	0.6	0.8	-
Weight (g)	1	4	2.5	1	1	1	1	1
Price	\$32	\$43	\$43	\$55	\$55	\$52	\$48	\$41

Part number	A-5555-0272	A-5555-0273	A-5555-0274	A-5555-0276	A-5555-0277
Zeiss order number	602030-8120	602030-8121	602030-8023	602030-8021	602030-8106
DK (mm)	1	0.3	2	3	3
L (mm)	10.5	22	21	21.5	21
DG (mm)	4	4	4	4	4
ML (mm)	5.5	9	15	15.5	13
ML1 (mm)	5	2.3	-	-	-
DS (mm)	10	1	1	1.5	2
DS1 (mm)	0.8	.02	-	-	-
Weight (g)	1	1	1	1	1
Price	\$53	\$74	\$36	\$41	\$39




Ceramic styli, stainless steel base, ceramic stem, ruby ball

Part number	A-5555-0264	A-5555-0266	A-5555-0275
Zeiss order number	602030-8102	602030-8101	602030-8020
DK (mm)	4	5	6
L (mm)	32	32	13
DG (mm)	4	4	4
ML (mm)	26	19	9
DS (mm)	2	2	2
Weight (g)	1	1	1
Price	\$43	\$45	\$48



Stainless steel extensions

Part number	A-5004-7609	A-5004-7583	A-5555-0286	A-5555-0287	A-5555-0288
Zeiss order number	602030-8301	602030-8302	602030-8303	602030-8304	602030-8305
L (mm)	10	20	30	40	50
D (mm)	4	4	4	4	4
Weight (g)	0.7	1.6	2.6	3.7	4.7
Price	\$13	\$15	\$18	\$23	\$23




M2 styli, adaptors and accessories for Zeiss analog probe systems

Schematics not shown to scale

Ceramic styli, stainless steel base, ceramic stem, ruby ball


Part number	A-5555-0278	A-5555-0279
Zeiss order number	602030-8002	602030-8004
DK (mm)	6	5
L (mm)	13	22.5
DG (mm)	3	3
ML (mm)	9	16.5
DS (mm)	2	2
Weight (g)	1	1
Price	\$48	\$55



Tungsten carbide styli, stainless steel base, tungsten carbide stem, ruby ball


Part number	A-5555-0308	A-5555-0309	A-5555-0282	A-5555-0310	A-5555-0311	A-5003-3822	A-5003-0938	A-5555-0312
Zeiss order number	602030-8006	602030-8007	602030-8001	602030-8008	602030-8009	602030-8005	602030-8003	602030-8015
DK (mm)	1	1	2	2	2	2	3	4
L (mm)	10.5	15.5	11	11	16	21	21.5	12
DG (mm)	3	3	3	3	3	3	3	3
ML (mm)	6.5	11.5	5	7	12	15	15.5	8
DS (mm)	0.8	0.8	1	1	1	1	1.5	2.5
Weight (g)	0.3	0.3	1	1	1	1	1	1
Price	\$36	\$36	\$25	\$27	\$27	\$27	\$78	\$34

Part number	A-5555-0313	A-5555-0283
Zeiss order number	602030-8016	602030-8034
DK (mm)	4	5
L (mm)	22	22.5
DG (mm)	3	3
ML (mm)	18	16.5
DS (mm)	2.5	2
Weight (g)	1	1
Price	\$36	\$50



Steel styli, stainless steel base and stem, ruby ball


Part number	A-5555-0314	A-5555-0315	A-5555-0316
Zeiss order number	602030-8017	602030-8018	602030-8019
DK (mm)	6	6	8
L (mm)	13	28	13
DS (mm)	3	3	3
DG (mm)	3	3	3
Weight (g)	0.9	1.8	2
Price	\$45	\$46	\$66



Star styli, stainless steel cube base and stem, ruby ball


Schematics not shown to scale.

Part number	A-5555-0294	A-5555-0295
Zeiss order number	602030-8011	602030-8010
DK (mm)	2	2
L (mm)	32	22
ML (mm)	9.5	4.5
DS (mm)	1.4	1.4
B (mm)	5.5	5.5
Weight (g)	1	1
Price	\$126	\$133




Styli for star configuration, stainless steel base and stem, ruby ball

Part number	A-5555-0296
Zeiss order number	602030-8012
DK (mm)	2
L (mm)	19.5
DG (mm)	3
ML (mm)	13.5
DS (mm)	1.5
Weight (g)	1
Price	\$43




Spherical disk styli, stainless steel base, tungsten carbide stem, ceramic disk

Part number	A-5555-0297	A-5555-0298
Zeiss order number	602030-8201	602030-8202
DK (mm)	8	4
L (mm)	32	32
DG (mm)	3	3
ML (mm)	19	19
DS (mm)	1.5	1
B (mm)	1.5	1
Weight (g)	1	1
Price	\$117	\$87




Spherical disk styli, stainless steel base and stem, ceramic disk

Part number	A-5555-0299	A-5555-0300
Zeiss order number	602030-8203	602030-8204
DK (mm)	14	20
L (mm)	5.5	5.5
B (mm)	2	2.5
Weight (g)	1	3
Price	\$157	\$187



Pointer styli, stainless steel base, cone point, tungsten carbide

Part number	A-5555-0317	A-5555-0318
Zeiss order number	602030-8342	602030-8343
L (mm)	10	10
DG (mm)	3	3
DS (mm)	1.5	1.5
DK	30°	60°
Weight (g)	1	1
Price	\$28	\$28




M2 styli for Zeiss probing systems

Stainless steel extension


Schematics not shown to scale

Part number	A-5004-7610	A-5004-7585	A-5004-7586	A-5004-7591	A-5004-7611
Zeiss order number	602030-8321	602030-8322	602030-8323	602030-8324	602030-8325
L (mm)	5	10	20	30	40
D (mm)	3	3	3	3	3
Weight (g)	0.2	0.5	1	1.4	2.2
Price	\$12	\$13	\$15	\$17	\$19




5-way holder, rotary, stainless steel

Part number	A-5000-3627
Zeiss order number	602030-8381
L (mm)	7.5
B (mm)	7
Weight (g)	1.2
Price	\$48



5-way holder, stainless steel

Part number	A-5555-0319	A-5555-0320
Zeiss order number	602030-9104	602030-9103
L (mm)	9.1	5.4
D (mm)	10.5	7
Weight (g)	3.4	1
Price	\$81	\$39



Renishaw tools and accessories for the assembly of M2, M3 and M5 styli to Zeiss measuring probe heads

Schematics not shown to scale

Stylus tool (M2 and M3 styli)

Part number	A-5555-0233
Zeiss order number	602030-0001
DK (mm)	1.2
L (mm)	23
Weight (g)	1
Price	\$10



Allen keys DIN 911

Part number	A-5555-0234	A-5555-0235	A-5555-0236
Zeiss order number	602030-0002	602030-0042	602030-0021
B (mm)	SW1.5	SW0.9	SW2.5
Weight (g)	1	1	2
Price	\$1	\$1	\$1



Tool kit

consisting of:

Part number	A-5555-0237
Zeiss order number	600341-8595
Price	\$30

	1 x offset screwdriver DIN 911-2	1 x offset screwdriver DIN 911-3	1 x offset screwdriver DIN 911-4	2 x pin-type spanner 2.9 mm	1 x single-headed spanner DIN 894
DK (mm)	-	-	-	2.9	-
L (mm)	-	-	-	70	-
D (mm)	-	-	-	5	-
B	SW2	SW3	SW4	-	SW13
Weight (g)	1	5	10	15 each	39

Stylus tool kit (2 x pin-type spanners 2.9 mm for M5)

Part number	A-5555-0238
Zeiss order number	600341-8596
DK (mm)	2.9
L (mm)	70
D (mm)	5
Weight (g)	15
Price	\$23

Stylus tool 1.7 mm for M5

Part number	A-5555-0239
Zeiss order number	602030-0027
DK (mm)	1.7
L (mm)	49
D (mm)	2.5
Weight (g)	1
Price	\$10

Pin-type spanner 2.9 mm for M5

Part number	A-5555-0240
Zeiss order number	602030-0222
DK (mm)	2.9
L (mm)	70
D (mm)	5
Weight (g)	7.5
Price	\$12

Assortment of screws

Part number	A-5555-0241
Zeiss order number	600341-8590
Weight (g)	27
Price	\$28

Includes:

- 10 spring-lock washers FS 5x7
- 2 cheese-head screws M5x12
- 2 cheese-head screws M5x20
- 4 grub screws 10 mm long
- 2 grub screws 25 mm long

Spring-lock washers

Part number	A-5555-0242
Zeiss order number	600341-0042
Price	\$5

Includes:

- 10 x FS 5.7 spring-lock washers


C spanners DIN 1810

Part number	A-5555-0243	A-5555-0244
Zeiss order number	602030-0045	602030-0044
DK (mm)	11	21
Price	\$14	\$17

Accessories


Stylus knuckles

Part number	A-5000-7534	A-5003-4697	A-5000-9902 Rotary	A-5000-7616	A-5003-4686 Rotary	A-5003-4689 Rotary	* A-5003-5278 Rotary	A-5003-5279 Rotary
Thread size	M2	M2	M2	M3	M3	M4	M5	M5
Effective length mm (in.)	8.0 (0.32)	13.5 (0.54)	16.5 (0.65)	12.0 (0.48)	17.0 (0.67)	33.0 (1.30)	36.5 (1.44)	46.5 (1.84)
Center offset mm (in.)	4.5 (0.18)	N/A	N/A	6.0 (0.24)	N/A	N/A	N/A	N/A
Mass grams	1.6	1.1	1.3	3.7	1.5	9.8	16.5	64.9
Price	\$71	\$108	\$81	\$71	\$130	\$140	\$247	\$86




* Not for use with SP80


Stylus centers







Part number	A-5000-8395 4-way	A-5000-3627 5-way	A-5000-7610 5-way	A-5000-7792 5-way
Thread size	M2	M2	M3	M4
Effective length mm (in.)	7.5 (0.30)	7.5 (0.30)	13.0 (0.52)	18.0 (0.71)
Center size mm (in.)	7.5 (0.30)	7.0 (0.28)	10.0 (0.40)	15.0 (0.60)
Mass grams	1.1	0.8	3.6	12.1
Price	\$64	\$48	\$50	\$60








Adaptors

Part number	A-5004-7593 Stainless steel	A-5004-7592 Stainless steel	A-5004-7595 Stainless steel	A-5004-7597 Stainless steel	A-5004-7596 Stainless steel	A-5004-7613 Stainless steel	A-5003-0856 Stainless steel	A-5555-0227 Stainless steel
Male/female thread	M2/M3	M3/M2	M4/M2	M4/M3	M4/M3	M5/M4	M5/M4	M5/M3
Length mm (in.)	7.0 (0.28)	5.0 (0.20)	5.0 (0.20)	9.0 (0.36)	20.0 (0.79)	6.5 (0.26)	9.0 (0.36)	10.0 (0.40)
Mass grams	0.4	0.6	1.5	1.4	3.2	6.0	4.6	5.0
Price	\$12	\$14	\$32	\$32	\$20	\$32	\$29	\$20
								




Part number	A-5555-0226 Stainless steel	A-5000-7751 Ceramic	A-5004-7612 Stainless steel	A-5000-7752 Ceramic	A-5000-7753 Ceramic	A-2054-4657 Stainless steel	A-5000-9302 Stainless steel	A-5000-9303 Stainless steel
Male/female thread	M5/M2	M4/M3	TF6/M3	M4/M3	M4/M3	M4/Ø4.5	M5/Ø8.0	M5/Ø10.0
Length mm (in.)	10.0 (0.40)	50.0 (1.97)	18.0 (0.71)	75.0 (2.96)	100.0 (3.94)	10.0 (0.40)	22.0 (0.87)	22.0 (0.87)
Mass grams	5.0	4.4	1.9	5.2	6.3	5.0	18.0	20.0
Price	\$20	\$60	\$35	\$91	\$104	\$34	\$62	\$62
								

Cubes and bolts

Part number	A-5555-0189 Titanium	A-5555-0190 Titanium	A-5555-0194 Titanium	A-5003-5683 Titanium	A-5003-5684 Titanium
Thread size	M5	M5	M5	M5 – M2	M5 – M2
Length mm (in.)	15.0 (0.60)	20.0 (0.79)	20.0 (0.79)	15.0 (0.60)	20.0 (0.79)
Width mm (in.)	15.0 (0.60)	20.0 (0.79)	40.0 (1.58)	15.0 (0.60)	20.0 (0.79)
Mass grams	12.85	32.55	63.50	13.75	35.18
Price	\$50	\$60	\$108	\$86	\$101




Part number	A-5003-5679 Stainless steel	A-5003-5678 Stainless steel	A-5003-5677 Stainless steel	A-5003-5676 Stainless steel
Thread size	M5 – M2	M5 – M2	M5	M5
Length mm (in.)	28.0 (1.11)	33.0 (1.30)	28.0 (1.11)	33.0 (1.30)
Mass grams	6.7	7.1	6.0	6.4
Price	\$18	\$18	\$18	\$18




Stylus tools


A-5004-7582
For M2 and M3
threaded styli
Price: \$9




A-5004-7587
For M4
threaded styli
Price: \$12



A-5004-7614
For M5
threaded styli
Price: \$15



A-5003-2300
For the M2 carbon fiber
range of styli
Price: \$48




These tools are designed to fit styli to Renishaw probes without causing any internal damage.

Stylus kits

M2 comprehensive stylus kit

A-5000-0001

Price: \$2,808




Position	Part number	Description
1	A-5000-3626	M2 STR D2 5BALL L19.2 S30
2	A-5000-7810	M2 DSC D25SLVS T1.5 L8.6 BR-Y2.5
3	A-5000-7629	M2 STR D2 5BALL L19.2 S18
4	A-5000-3627	M2 ACC CENTER 5WAY
5	A-5000-7534	M2 ACC KNUCKLE OFFSET
6	A-5000-7809	M2 DSC D18SLVS T1.5 L8.6 BR-Y2.5
7	A-5000-7811	M2 STR D1 4BALL L7.5T S10
8	A-5000-3614	M2 HEM D18CE
9	A-5004-7593	M2-M3 EXT L7SS
10-11	A-5004-7582	M2-M3 STYLUS TOOL
12-15	A-5004-7610	M2 EXT L5 D3SS
16-17	A-5004-7591	M2 EXT L30 D3SS
18-19	A-5004-7611	M2 EXT L40 D3SS
20	P-TL01-0150	S3 HEX WRENCH 1.5 MM A/F
21	A-5000-3611	M2 DSC D6R T1.2 L10 BR-Y2
22	A-5000-7813	M2 PNT D1.4TC 30DEG L10
23-24	A-5000-7806	M2 STY D1R L10 EWL4.5 D0.7SS
25	A-5000-7802	M2 STY D1.5R L10 EWL4.5 D0.7SS
26-28	A-5000-7807	M2 STY D2R L10 EWL6 D1SS
29	A-5000-7803	M2 STY D2.5R L10 EWL6 D1SS
30	A-5000-3604	M2 STY D3R L10 EWL7.5 D1.5SS
31-32	A-5000-7805	M2 STY D0.5R L10 EWL3 D0.4TC
33	A-5000-7801	M2 STY D0.7R L10 EWL4 D0.5TC
34	A-5000-7800	M2 STY D0.3R L10 EWL2 D0.2TC
35	A-5000-4158	M2 STY D8R L11 EWL11 D2.5SS
36-37	A-5000-4156	M2 STY D6R L10 EWL10 D2.5SS
38-39	A-5000-4155	M2 STY D5R L10 EWL10 D2.5SS
40-42	A-5000-4154	M2 STY D4R L10 EWL10 D1.5SS
43-46	A-5000-3604	M2 STY D3R L10 EWL7.5 D1.5SS
47-48	A-5004-7586	M2 EXT L20 D3SS
49	A-5000-7808	M2 STY D1R L20 EWL7 D0.7TC
50-54	A-5000-3603	M2 STY D2R L20 EWL14 D1.4SS
55-56	A-5000-7804	M2 STY D2.5R L20 EWL16.5 D1.4SS
57-58	A-5000-4160	M2 STY D3R L20 EWL17.5 D1.5SS
59-60	A-5004-7585	M2 EXT L10 D3SS
61	A-5004-7589	M2 CYL D1.5SLVS L11 EWL1.5
62	A-5004-7585	M2 EXT L10 D3SS
63	A-5004-7590	M2 CYL D3SLVS L13 EWL3.8
64	A-5000-4160	M2 STY D3R L20 EWL17.5 D1.5SS
65-67	A-5000-4161	M2 STY D4R L20 EWL20 D1.5SS
68	A-5004-7588	M2 PNT D3SLVS 30DEG L15
69	A-5000-7812	M2 SPH D2R L20 EWL7.2 SS

M2 stylus enhancement kit

A-5000-0002

Price: \$1,032




Position	Part number	Description
1	A-5000-7810	M2 DSC D25SLVS T1.5 L8.6 BR-Y2.5
2	P-TL01-0150	S3 HEX WRENCH 1.5 MM A/F
3-4	A-5004-7582	M2-M3 STYLUS TOOL
5	A-5000-7811	M2 STR D1 4BALL L7.5T S10
6	A-5000-7809	M2 DSC D18SLVS T1.5 L8.6 BR-Y2.5
7	A-5004-7611	M2 EXT L40 d3SS
8	A-5000-7813	M2 PNT D1.4TC 30deg L10
9	A-5000-7801	M2 STY D0.7R L10 EWL4 d0.5TC
10	A-5000-7805	M2 STY D0.5R L10 EWL3 d0.4TC
11	A-5000-7800	M2 STY D0.3R L10 EWL2 d0.2TC
12	A-5000-7803	M2 STY D2.5R L10 EWL6 d1SS
13	A-5000-7807	M2 STY D2R L10 EWL6 d1SS
14	A-5000-7802	M2 STY D1.5R L10 EWL4.5 d0.7SS
15	A-5000-7806	M2 STY D1R L10 EWL4.5 d0.7SS
16-17	A-5000-7804	M2 STY D2.5R L20 EWL16.5 d1.4SS
18	A-5000-7812	M2 SPH D2R L20 EWL7.2 SS
19	A-5000-7808	M2 STY D1R L20 EWL7 d0.7TC

M2 high performance kit

A-5003-2310


Price: \$710



Position	Part number	Description
1	A-5003-2283	M2 EXT L90 d3CF
2	A-5003-2282	M2 EXT L70 d3CF
3	A-5003-2281	M2 EXT L50 d3CF
4	A-5003-2280	M2 EXT L40 d3CF
5	A-5003-2287	M2 STY D6R L50 EWL50 d3CF
6	A-5003-2286	M2 STY D5R L50 EWL50 d3CF
7	A-5003-2285	M2 STY D4R L50 EWL50 d3CF
8-9	A-5004-7582	M2-M3 STYLUS TOOL
10-11	A-5003-2300	M2 STYLUS TOOL CF RANGE

Stylus kit 201 for M2 probes


Price: \$630



Position	Part number	Quantity	Description
1	A-5000-7806	1	M2 STY D1R L10 EWL4.5 d0.7SS
2	A-5000-7807	1	M2 STY D2R L10 EWL6 d1SS
3	A-5000-3604	1	M2 STY D3R L10 EWL7.5 d1.5SS
4	A-5000-3603	1	M2 STY D2R L20 EWL14 d1.4SS
5	A-5000-4160	1	M2 STY D3R L20 EWL17.5 d1.5SS
6	A-5000-3611	1	M2 DSC D6R T1.2 L10 BR-Y2
7	A-5000-3626	1	M2 STR D2 5BALL L19.2 S30
8	A-5000-7809	1	M2 DSC D18SLVS T1.5 L8.6 BR-Y2.5
9	A-5004-7585	2	M2 EXT L10 d3SS
10	A-5000-7534	1	M2 ACC KNUCKLE OFFSET
11	A-5004-7582	2	M2-M3 STYLUS TOOL
12	P-TL01-0150	1	S3 HEX WRENCH 1.5 MM A/F
13	M-5000-3541	1	S8 TP2 SPANNER (not pictured)
14	A-1015-7658	1	TP2 & STYLI BOX (not pictured)

Stylus kit 204 for M2 probes


Price: \$1,290



Position	Part number	Quantity	Description
1	A-5000-7806	1	M2 STY D1R L10 EWL4.5 d0.7SS
2	A-5000-7807	1	M2 STY D2R L10 EWL6 d1SS
3	A-5000-3604	1	M2 STY D3R L10 EWL7.5 d1.5SS
4	A-5000-4154	1	M2 STY D4R L10 EWL10 d1.5SS
5	A-5000-4155	1	M2 STY D5R L10 EWL10 d2.5SS
6	A-5000-4156	1	M2 STY D6R L10 EWL10 d2.5SS
7	A-5000-4158	1	M2 STY D8R L11 EWL11 d2.5SS
8	A-5000-3603	1	M2 STY D2R L20 EWL14 d1.4SS
9	A-5000-4160	1	M2 STY D3R L20 EWL17.5 d1.5SS
10	A-5000-4161	1	M2 STY D4R L20 EWL20 d1.5SS
11	A-5000-3611	1	M2 DSC D6R T1.2 L10 BR-Y2
12	A-5004-7589	1	M2 CYL D1.5SLVS L11 EWL1.5
13	A-5004-7590	1	M2 CYL D3SLVS L13 EWL3.8
14	A-5004-7588	1	M2 PNT D3SLVS 30deg L15
15	A-5000-7809	1	M2 DSC D18SLVS T1.5 L8.6 BR-Y2.5
16	A-5000-7810	1	M2 DSC D25SLVS T1.5 L8.6 BR-Y2.5
17	A-5000-3614	1	M2 HEM D18CE
18	A-5000-7534	1	M2 ACC KNUCKLE OFFSET
19	A-5004-7592	1	M3-M2 EXT L5SS
20	A-5000-3627	1	M2 ACC Center 5WAY
21	A-5004-7585	2	M2 EXT L10 d3SS
22	A-5004-7586	2	M2 EXT L20 d3SS
23	A-5004-7591	2	M2 EXT L30 d3SS
24	A-5004-7582	2	M2-M3 STYLUS TOOL
25	P-TL01-0150	1	S3 HEX WRENCH 1.5 MM A/F
26	M-5000-3541	1	S8 TP2 SPANNER (not pictured)
27	A-1015-7749	1	COMP BOX ASSEMBLY (not pictured)

Stylus kit 206 for M2 probes


Price: \$1,972



Position	Part number	Quantity	Description
1	A-5000-7806	5	M2 STY D1R L10 EWL4.5 d0.7SS
2	A-5000-7807	3	M2 STY D2R L10 EWL6 d1SS
3	A-5000-3604	5	M2 STY D3R L10 EWL7.5 d1.5SS
4	A-5000-4154	3	M2 STY D4R L10 EWL10 d1.5SS
5	A-5000-4155	2	M2 STY D5R L10 EWL10 d2.5SS
6	A-5000-4156	2	M2 STY D6R L10 EWL10 d2.5SS
7	A-5000-4158	1	M2 STY D8R L11 EWL11 d2.5SS
8	A-5000-3603	5	M2 STY D2R L20 EWL14 d1.4SS
9	A-5000-4160	3	M2 STY D3R L20 EWL17.5 d1.5SS
10	A-5000-4161	3	M2 STY D4R L20 EWL20 d1.5SS
11	A-5000-3611	1	M2 DSC D6R T1.2 L10 BR-Y2
12	A-5004-7589	1	M2 CYL D1.5SLVS L11 EWL1.5
13	A-5004-7590	1	M2 CYL D3SLVS L13 EWL3.8
14	A-5004-7588	1	M2 PNT D3SLVS 30deg L15
15	A-5000-7809	1	M2 DSC D18SLVS T1.5 L8.6 BR-Y2.5
16	A-5000-7810	1	M2 DSC D25SLVS T1.5 L8.6 BR-Y2.5
17	A-5000-3614	1	M2 HEM D18CE
18	A-5000-7534	1	M2 ACC KNUCKLE OFFSET
19	A-5004-7592	1	M3-M2 EXT L5SS
20	A-5000-3627	3	M2 ACC Center 5WAY
21	A-5004-7585	3	M2 EXT L10 d3SS
22	A-5004-7586	2	M2 EXT L20 d3SS
23	A-5004-7591	2	M2 EXT L30 d3SS
24	A-5004-7582	2	M2-M3 STYLUS TOOL
25	P-TL01-0150	1	S3 HEX WRENCH 1.5 MM A/F
26	M-5000-3541	1	S8 TP2 SPANNER (not pictured)
27	A-1015-7749	1	COMP BOX ASSEMBLY (not pictured)

A-5003-6151 M3 stylus kit for SP25M/SM25-1/SH25-1

Price: \$435




Position	Part number	Description
1	A-5003-5970	M3 STY D3R L21 EWL13.5 d2CF
2	A-5003-5971	M3 STY D4R L21 EWL13.5 d3CF
3	A-5003-5977	M3 STY D4SIN L21 EWL13.5 d3CF
4	A-5003-5972	M3 STY D4R L31 EWL23.5 d3CF
5	A-5003-5973	M3 STY D4R L40 EWL32.5 d3CF
6	A-5003-5974	M3 STY D5R L50 EWL42.5 d3CF
7	A-5004-7582	M2-M3 STYLUS TOOL

www.renishaw.com

A-5003-6152 M3 stylus kit for SP25M/SM25-2/SH25-2

Price: \$455




Position	Part number	Description
1	A-5003-5975	M3 STY D5R L21 EWL13.5 d3CF
2	A-5003-5978	M3 STY D5SIN L21 EWL13.5 d3CF
3	A-5003-5974	M3 STY D5F L50 EWL42.5 d3CF
4	A-5003-5976	M3 STY D6R L50 EWL50 d4CF
5	A-5003-4860	M3 STY D6R L75 EWL75 d4CF
6	A-5004-7582	M2-M3 STYLUS TOOL

www.renishaw.com

A-5003-6153 M3 stylus kit for SP25M/SM25-3/SH25-3

Price: \$515




Position	Part number	Description
1	A-5003-5975	M3 STY D5R L21 EWL13.5 d3C/F
2	A-5003-5978	M3 STY D5SIN L21 EWL13.5 d3C/F
3	A-5003-5974	M3 STY D5R L50 EWL42.5 d3C/F
4	A-5003-4860	M3 STY D6R L75 EWL75 d4C/F
5	A-5003-4863	M3 STY D8R L100 EWL100 d4C/F
6	A-5004-7582	M2-M3 STYLUS TOOL

www.renishaw.com

A-5003-8124 M3 stylus kit for SP25M/SM25-4/SH25-4

Price: \$1,200




Position	Part number	Description
1	A-5003-7057	M3 STY D10R L25 EWL75 d4C/F
2	A-5004-7582	M2-M3 STYLUS TOOL
3	A-5003-7056	M3 STY D10R L100 EWL100 d4C/F
4	A-5003-7055	M3 STY D10R L150 EWL150 d4C/F
5	A-5004-7582	M2-M3 STYLUS TOOL
6	A-5003-7054	M3 STY D10R L200 EWL200 d4C/F
7	A-5003-0069	M3 STY D5R L50 EWL50 d2.5CER
8	A-5000-7630	M3 STY D5R L21 EWL21 d2.5SS

www.renishaw.com

Stylus kit 101 for M3 probes


Price: \$805



Position	Part number	Quantity	Description
1	A-5000-3551	1	M3 STY D1R L21 EWL4 d0.6SS
2	A-5000-3552	1	M3 STY D2R L21 EWL8 d1.4SS
3	A-5000-3553	1	M3 STY D3R L21 EWL12 d1.5SS
4	A-5000-3554	5	M3 STY D4R L31 EWL27 d2.5SS
5	A-5000-7648	1	M3 STY D5R L31 EWL31 d3.5SS
6	A-5000-3615	1	M3 DSC D12.7SLVS T2 L30.8 BR-N
7	A-5000-7669	1	M3 DSC D63.5CS T6 L4 BR-N
8	A-5004-7584	1	M3 EXT L35 d4SS
9	A-5004-7583	1	M3 EXT L20 d4SS
10	A-5000-7616	1	M3 ACC KNUCKLE OFFSET
11	A-5000-7610	1	M3 ACC Center 5WAY
12	A-5004-7582	2	M2-M3 STYLUS TOOL
13	P-TL01-0150	1	S3 HEX WRENCH 1.5 MM A/F
14	A-1041-7569	1	SA7 ADAPTOR (not pictured)
15	M-5000-3571	2	STYLUS SHANK ADAPTOR (not pictured)
16	A-1015-7650	1	TP1 STYLI BOX (not pictured)

Stylus kit 102 for M3 probes


Price: \$1,209



Position	Part number	Quantity	Description
1	A-5000-3551	3	M3 STY D1R L21 EWL4 d0.6SS
2	A-5000-3552	5	M3 STY D2R L21 EWL8 d1.4SS
3	A-5000-3553	3	M3 STY D3R L21 EWL12 d1.5SS
4	A-5000-3554	7	M3 STY D4R L31 EWL27 d2.5SS
5	A-5000-7648	1	M3 STY D5R L31 EWL31 d3.5SS
6	A-5000-3615	1	M3 DSC D12.7SLVS T2 L30.8 BR-N
7	A-5000-7669	1	M3 DSC D63.5CS T6 L4 BR-N
8	A-5004-7584	2	M3 EXT L35 d4SS
9	A-5004-7583	2	M3 EXT L20 d4SS
10	A-5004-7593	1	M2-M3 EXT L7SS
11	A-5000-7616	1	M3 ACC KNUCKLE OFFSET
12	A-5000-7610	2	M3 ACC Center 5WAY
13	A-5004-7582	2	M2-M3 STYLUS TOOL
14	P-TL01-0150	1	S3 HEX WRENCH 1.5 MM A/F
15	A-1041-7569	1	SA7 ADAPTOR (not pictured)
16	M-5000-3571	2	STYLUS SHANK ADAPTOR (not pictured)
17	A-1015-7650	1	TP1 STYLUS BOX (not pictured)

A-5000-7829 M4 stylus kit (TP7M use)


Price: \$1,614



Position	Part number	Description
1	A-5000-7796	M4 STY D8R L100 EWL100 d4.5CE
2	A-5000-7753	M4-M3 EXT L100CE
3	A-5000-7752	M4-M3 EXT L75CE
4	A-5000-7795	M4 STY D8R L50 EWL50 d4.5CE
5	A-5000-7751	M4-M3 EXT L50C
6	A-5000-7755	M4 EXT L50 d7.4CE
7	A-5000-7754	M4 EXT L30 d7.4CE
8	A-5000-7792	M4 ACC Center 5WAY
9	A-5000-7814	M3 HEM D30CE
10-11	A-5004-7597	M4-M3 EXT L9SS
12	A-5000-7610	M3 ACC Center 5WAY
13	A-5000-3627	M2 ACC Center 5WAY
14-18	A-5004-7592	M3-M2 EXT L5SS
19-20	A-5004-7587	M4 STYLUS TOOL
21-22	A-5004-7582	M2-M3 STYLUS TOOL
23	A-5004-7596	M4-M3 EXT L20SS
24	A-5000-7545	M4 STY D1R L19.5 EWL4 d0.7SS
25-28	A-5000-7547	M4 STY D2R L19 EWL8 d1.4SS
29	A-5000-7551	M4 STY D4R L18 EWL13 d3SS

A-5003-6168 M5 stylus kit SP80


Price: \$900



Position	Part number	Description
1-2	A-5004-7614	M5 STYLUS TOOL
3	A-5003-6134	M5 ACC D11 EXTENSION TOOL
4	P-TL01-0250	S3 HEX WRENCH 2.5 MM A/F
5-6	A-5555-0189	M5 ACC 15X15 CUBE
7-8	A-5555-0136	M5 EXT L100 d11SS
9-10	A-5555-0670	M5 EXT L50 d11SS
11-12	A-5003-5218	M5 STY D3R L30 EWL21 d2TC
13-14	A-5003-5236	M5 STY D5R L50 EWL41 d3TC
15	A-5003-5251	M5 STY D8R L75 EWL62 d6CF
16	A-5003-5262	M5 STY D8R L100 EWL87 d6CF

A-5003-5911 M5 stylus kit - standard


Price: \$1,236



Position	Part number	Description
1	A-5555-0189	M5 ACC 15X15 CUBE
2	A-5003-5677	M5 ACC CUBE BOLT L28
3-4	A-5004-7614	M5 STYLUS TOOL
5	P-TL01-0250	S3 HEX WRENCH 2.5 MM A/F
6	A-5003-6134	M5 ACC D11 EXTENSION TOOL
7-8	A-5555-0670	M5 EXT L50 d11SS
9-10	A-5555-0136	M5 EXT L100 d11SS
11	A-5003-5262	M5 STY D8R L100 EWL87 d6CF
12-14	A-5003-5251	M5 STY D8R L75 EWL62 d6CF
15-17	A-5003-5236	M5 STY D5R L50 EWL41 d3TC
18-20	A-5003-5218	M5 STY D3R L30 EWL21 d2TC
21	A-5003-5733	M5 STY D4SN L20 EWL11 d2TC

A-5003-5909 M5 stylus kit - comprehensive


Price: \$3,760



Position	Part number	Description
1-4	A-5555-0189	M5 ACC 15X15 CUBE
5-8	A-5003-5677	M5 ACC CUBE BOLT L28
9-10	A-5003-5278	M5 ACC KNUCKLE d11 ROTARY
11-14	A-5555-0669	M5 EXT L30 d11SS
15-16	A-5555-0623	M5 EXT L70 d11CF
17-18	A-5555-0652	M5 EXT L100 d11CF
19-22	A-5555-0648	M5 EXT L50 d11CF
23-24	A-5555-0654	M5 EXT L200 d11CF
25-27	A-5004-7614	M5 STYLUS TOOL
28-29	A-5003-6134	M5 ACC D11 EXTENSION TOOL
30	P-TL01-0250	S3 HEX WRENCH 2.5 MM A/F
31	P-TL01-0150	S3 HEX WRENCH 1.5 MM A/F
32	A-5003-5261	M5 STY D8R L100 EWL50 d6CF
33	A-5003-5262	M5 STY D8R L100 EWL87 d6CF
34-35	A-5003-5251	M5 STY D8R L75 EWL62 d6CF
36-37	A-5003-5236	M5 STY D5R L50 EWL41 d3TC
38-39	A-5003-5234	M5 STY D3R L50 EWL41 d2TC
40-43	A-5003-5218	M5 STY D3R L30 EWL21 d2TC
44	A-5003-5733	M5 STY D4SN L20 EWL11 d2TC
45	A-5003-5288	M5 DSC D12SLVS T3 L3 BR-Y5
46	A-5003-5289	M5 DSC D21SLVS T3 L3 BR-Y5
47	A-5003-5276	M5 HEM D22CE d7SS

A-5003-5910 M5 stylus kit - general purpose


Price: \$2,575



Position	Part number	Description
1	A-5003-5279	M5 ACC KNUCKLE d20 ROTARY
2-3	A-5555-0140	M5 EXT L20 d11SS
4	A-5555-0669	M5 EXT L30 d11SS
5-6	A-5555-0648	M5 EXT L50 d11CF
7-8	A-5555-0671	M5 EXT L50 d20AL
9-10	A-5555-0652	M5 EXT L100 d11CF
11-12	A-5555-0127	M5 EXT L100 d20AL
13	A-5555-0125	M5 EXT L200 d20AL
14	A-5003-5676	M5 ACC CUBE BOLT L33
15-16	A-5555-0190	M5 ACC 20X20 CUBE
17	A-5003-6135	M5 ACC D20 EXTENSION TOOL
18-19	A-5003-6134	M5 ACC D11 EXTENSION TOOL
20	P-TL01-0300	S3 HEX WRENCH 3.0 MM A/F
21	P-TL01-0250	S3 HEX WRENCH 2.5 MM A/F
22	P-TL01-0150	S3 HEX WRENCH 1.5 MM A/F
23-25	A-5004-7614	M5 STYLUS TOOL
26	A-5003-5262	M5 STY D8R L100 EWL87 d6CF
27	A-5003-5251	M5 STY D8R L75 EWL62 d6CF
28	A-5003-5238	M5 STY D8R L50 EWL37 d6CF
29-31	A-5003-5236	M5 STY D5R L50 EWL41 d3TC
32-33	A-5003-5218	M5 STY D3R L30 EWL21 d2TC
34	A-5003-5733	M5 STY D4SN L20 EWL11 d2TC
35	A-5003-5288	M5 DSC D12SLVS T3 L3 BR-Y5
36	A-5003-5290	M5 DSC D35SLVS T5 L4 BR-Y8
37	A-5003-5276	M5 HEM D22CE d7SS

A-5003-5912 M5 stylus extension kit - 11 mm


Price: \$1,475



Position	Part number	Description
1-2	A-5555-0654	M5 EXT L200 d11CF
3-4	A-5555-0424	M5 EXT L150 d11CF
5-7	A-5555-0652	M5 EXT L100 d11CF
8-9	A-5555-0648	M5 EXT L50 d11CF
10-11	A-5003-6134	M5 ACC D11 EXTENSION TOOL

A-5003-5913 M5 stylus extension kit - 20 mm


Price: \$2,065



Position	Part number	Description
1-2	A-5555-0664	M5 EXT L300 d20CF
3-5	A-5555-0663	M5 EXT L200 d20CF
6-8	A-5555-0661	M5 EXT L150 d20CF
9-11	A-5555-0659	M5 EXT L100 d20CF
12-13	A-5003-6135	M5 ACC D20 EXTENSION TOOL

Datum balls

Datum spheres are made from hard-wearing tungsten carbide and come supplied with individual certificates stating ball diameter and roundness. All sphere measurements are performed on equipment traceable to UK (NPL) standards. Grade 3 sphericity balls are used.



Datum sphere kit	Part number	Price
Ø12 mm datum ball	A-1034-0028	\$545
Ø19 mm datum ball	A-1034-0027	\$545
Ø25 mm datum ball	A-1034-0026	\$545
Ø¾ in datum ball	A-1034-0031	\$545
Ø1 in datum ball	A-1034-0035	\$545

Fixing stud – a fixing stud is required with each kit to attach the pillar to the table surface

Thread size	Part number	Price
M6 x 1	A-1034-0352	\$27
M8 x 1.25	A-1034-0351	\$27
M10 x 1.5	A-1034-0350	\$27
5/16 - 18 x UNC	A-1034-0354	\$27
3/8 - 16 x UNC	A-1034-0353	\$27

Optional extras

Datum ball	Part number	Price
Ø12 mm	A-1034-0005	\$335
Ø19 mm	A-1034-0023	\$335
Ø25 mm	A-1034-0002	\$335
Ø¾ in	A-1034-0032	\$335
Ø1 in	A-1034-0036	\$335

Adaptors/extension	Part number	Price
2 way adaptor	A-1034-0356	\$82
3 way adaptor	A-1034-0357	\$186
Pillar extension 75 mm (2.96 in) long	A-1034-0355	\$82

Gram gage

The gram gage allows the optimum trigger force to be set to maximize probe performance on all standard Renishaw touch trigger probes.

Part number: P-GA01-0001

Price: \$374


Overall length	95 mm
Needle length	41 mm
Depth	27 mm
Width	43 mm
Range	4 gram to 35 gram range with 1 gram graduations




Custom stylus fax back form

Fax to: (847) 286 9974


Please fill in your stylus requirements in the space provided and fax back to us. Our design team will carry out a feasibility study and present you with a solution to your application problem.



Thread size	Length	EWL	Ball diameter	Ball material	Stem material	Quantity required



Thread size	Length	EWL	Cylinder diameter	Cylinder material	Quantity required



Thread size	Length	Disk diameter	Disk thickness	Disk material	Disk roller Y or N?	Quantity required

Notes

Probe head: _____ Probing orientation: _____

Application (what are you measuring?) _____


Company name: _____ Date: _____

Address: _____

Telephone: _____

Contact name: _____ Fax: _____

Department: _____ Email: _____



Repair services



Renishaw repair services

Services offered

Repair

Your product is repaired to factory performance specifications, and carries a 3-month warranty.

Repair By Exchange (RBE)

Your product is replaced by a refurbished or as new product, shipped to you once we have received your failed product. RBEs carry a 6-month warranty.

Advance RBE

Your product is replaced by a refurbished or as new product, shipped to you on the same day that you report a fault. Advance RBEs carry a 6-month warranty.

Replace new

Your product is replaced by a new product, carrying a new factory warranty.

Please note:

The services offered on each product vary – please consult the detailed list that follows.

On Advance RBE, in order to get you a replacement product as soon as possible, it is necessary to charge a small additional premium on top of the price of the product to cover additional administration.

Available repair services for Specials are quoted per job.

All the following prices are for guidance only. When units are received with excessive wear and tear, or obsolete product is returned for repair, Renishaw reserves the right to quote a different service/replacement charge.

Advance replacements

Advance replacement is a Renishaw premium service aimed at minimizing your downtime. This service is only available on products where a Repair By Exchange (RBE) service is offered. Through this service we ship an RBE in advance of receipt of your inoperative product.

Please note:

- 1) A \$95 charge applies to each advance replacement.
- 2) Your inoperative product must be returned to Renishaw within 14 working days of receipt of the advance replacement.
- 3) Failure to do so will result in an issuance of a non-return invoice in the amount of the difference between the RBE price and the new list price.
- 4) Return of your inoperative product after the issuance of the non-return invoice will not result in a credit of the non-return invoice, and your inoperative product will be returned to you.
- 5) Advance replacements sent out under a warranty claim will not be credited if the returned product is damaged, or no fault is found with the returned product.
- 6) Returns of advance replacements will be accepted if:
 - a) they are returned unused, and in the original packaging within ten working days of invoice date, and
 - b) the return has been pre-approved by Renishaw through the issuance of a Return Goods Authorization (RGA) number, and
 - c) the return passes Renishaw inspection, and
 - d) a re-stocking fee of \$95 or 20% is applied, whichever is the greater.

Coordinate Measuring Machine products

Manual probe heads

Description	Check and test	Repair	Repair by exchange	RBE part number
MH20	\$100	N/A	\$1,095	A-4043-0024-RBE
MH20i	\$100	N/A	\$1,395	A-4099-0022-RBE
MH8	\$100	N/A	\$760	A-1332-0002-RBE
MIH	\$225	\$980	\$1,975	A-1070-0003-RBE
PH1	\$100	N/A	\$550	A-1049-1795-RBE
PH5	\$100	N/A	N/A	Replace at new list price
PH6	\$100	N/A	N/A	Replace at new list price

Motorized and servo positioning heads

Description	Check and test	Calibration	Minor repair	Major repair	Repair by exchange	RBE part number
REVO®	\$480				\$9,320	A-3060-0040-RBE
REVO2	\$480				\$10,350	A-5759-1000-RBE
PH20	\$480				\$4,125	A-5669-0001-RBE
PH9/PH9A	Obsolete				Call for upgrade options to PH10 system	
PH10M	\$480	\$595	\$1,095	\$2,340	\$5,120	A-1025-6050-RBE
PH10MQ	\$480	\$595	\$1,095	\$2,340	\$5,120	A-1036-6001-RBE
PH10MQH	\$480	\$595	\$1,095	\$2,340	\$5,120	A-1036-0100-RBE
PH10T	\$480	\$595	\$1,095	\$2,340	\$5,120	A-1025-7526-RBE
PH10M Plus	\$480	\$595	\$1,095	\$2,340	\$5,120	A-5863-1000-RBE
PH10T Plus	\$480	\$595	\$1,095	\$2,340	\$5,120	A-5863-2000-RBE
PH10MQ Plus	\$480	\$595	\$1,095	\$2,340	\$5,120	A-5863-3000-RBE

Description	Check and test	Upgrade	Upgrade part number	Repair by exchange	RBE part number
PHS	\$615			\$4,255	A-2150-0815-RBE
PHS upgrade (>10 years old)		\$18,720	A-2150-0815-UPG		

Controllers

Description	Calibration	Repair	Repair by exchange	RBE part number
ACC2 (upgrade to ACC2-2)	N/A	N/A	\$1,110 (RS232 only)	A-1520-0101-RBE
ACC2-2	N/A	N/A	\$1,110 (RS232 only)	A-1520-0101-RBE
PHC9/RS232	Obsolete		Call for upgrade options to PH10 system	
PHC9/IEEE	Obsolete		Call for upgrade options to PH10 system	
PHC10/RS232 (upgrade to PHC10-3 Plus)	N/A	N/A	\$1,110	A-5863-0100-RBE
PHC10-2/RS232 (upgrade to PHC10-3 Plus)	N/A	N/A	\$1,110	A-5863-0100-RBE
PHC10-3 Plus	\$280	N/A	\$1,110	A-5863-0100-RBE
PHS PC card	N/A	N/A	\$1,460	A-2150-0824-RBE
PHS PC card (B&S)	N/A	N/A	\$1,460	A-2150-1360-RBE

Probes


Description	Price	Repair	Repair by exchange	RBE part number
Probe recertification (check and test)	\$100			
Description	Repair	Repair by exchange	RBE part number	
SP25M probe body	N/A	\$1,745	A-2237-1000-RBE	
SM25-1 module	N/A	\$1,245	A-2237-1111-RBE	
SM25-2 module	N/A	\$1,245	A-2237-1112-RBE	
SM25-3 module	N/A	\$1,245	A-2237-1113-RBE	
SM25-4 module	N/A	\$1,420	A-2237-1114-RBE	
SM25-5 module	N/A	\$1,860	A-2237-1115-RBE	
TM25-20 module	N/A	\$690	A-2237-1200-RBE	
SP600M	N/A	\$4,120	A-2098-0104-RBE	
TP1S	N/A	\$925	A-1041-7540-RBE	
TP1SM	N/A	\$925	A-1041-7541-RBE	

Probes continued

Description	Repair	Repair by exchange	RBE part number
TP2-5W	N/A	\$930	A-1042-1890-RBE
TP6	N/A	\$925	A-1039-0001-RBE
TP6A	N/A	\$925	A-1039-0028-RBE
TP7M	N/A	\$1,290	A-1073-0121-RBE
TPES	N/A	\$730	A-1311-0033-RBE
TP20 low force probe module only	N/A	\$900	A-1371-0392-RBE
TP20 standard force probe module only	N/A	\$900	A-1371-0270-RBE
TP20 medium force probe module only	N/A	\$900	A-1371-0271-RBE
TP20 extended force probe module only	N/A	\$900	A-1371-0272-RBE
TP20 6-way probe module only	N/A	\$1,000	A-1371-0419-RBE
EM1 TP20 extension module	N/A	\$1,000	A-1371-0430-RBE
EM2 TP20 extension module	N/A	\$1,000	A-1371-0431-RBE
TP20 body only	N/A	\$690	A-1371-0275-RBE
TP20 body (non-inhibit)	N/A	\$690	A-1371-0636-RBE



TP200 stylus module	N/A	N/A	Replace at new list price
TP200 probe sensor	N/A	\$1,100	A-1207-0020-RBE
TP200B probe sensor	N/A	\$1,100	A-1207-0046-RBE



Description	Check and test	Minor repair	Major repair	Repair by exchange	RBE part number
SP80	\$145	\$1,875	\$3,040	\$5,060	A-2238-0101-RBE
SP80H	\$145	\$1,875	\$3,040	\$5,060	A-2238-0414-RBE

Interfaces

Description	Repair	Repair by exchange	RBE part number
PI7-3	N/A	N/A	Replace at new list price
PI200-3	N/A	N/A	Replace at new list price

Machine checking gage

Description	Calibration
Small checking gage set (includes arms, pivot and stylus; excludes needed replacement items)	\$438
Large checking gage set (includes arms, pivot and stylus; excludes needed replacement items) (The machine checking gage is sent to the UK for calibration.)	\$479

Changing systems

Description	Calibration	Minor repair	Major repair	Repair by exchange	RBE part number
ACR1	\$450	\$910	\$1,940	\$5,050	A-1051-1300-RBE
ACR2	N/A	N/A	N/A	\$1,990	A-1383-0003-RBE
ACR3	N/A	\$405 (port replacement only)	N/A	\$2,925	A-5036-0005-RBE
FCR25	N/A	\$360 (port replacement only)	N/A	\$695	A-2237-1401-RBE
(for use with MRS)					
FCR25-L3	N/A	\$360 (port replacement only)	N/A	\$1,040	A-2237-1403-RBE
MCR20	N/A	\$440 (port replacement only)	N/A	\$1,095	A-1371-0163-RBE
SCR600	N/A	N/A	N/A	\$2,065	A-2098-0724-RBE
SCR200	N/A	\$1,160	N/A	\$2,065	A-1085-0370-RBE

Machine Tool products


Inspection probes for machining centers

Description	Price
Recertification (check and test)	\$100

Description	Repair	Repair by exchange	RBE part number
CP1 probe	Obsolete	Call for upgrade options	
MP1/R probe	Obsolete	Call for upgrade options	
MP1/S probe	Obsolete	Call for upgrade options	
MP3 probe	N/A	\$785	A-2053-5358-RBE
MP3 wide angle OMP short arm	Obsolete	Call for upgrade options to RMP60	
MP3 wide angle OMP long arm	Obsolete	Call for upgrade options to RMP60	
MP3 360° OMP	Obsolete	Call for upgrade options to RMP60	
MP11 probe	N/A	\$785	A-2045-0003-RBE
MP12 probe	Obsolete	Call for upgrade options	
MP16 (RMP2)	N/A	Call for upgrade options to RMP60	
MP15	N/A	\$880	A-2116-0621-RBE
MP15F	N/A	\$880	A-2116-0685-RBE

MP700 probe module Obsolete Call for upgrade options

MP700 OMP 35° Obsolete Call for upgrade options
 MP700 OMP 70° Obsolete Call for upgrade options



OMP40	N/A	\$1,210	Legacy:A-4071-0001-RBE Modulated:A-4071-2001-RBE
OMP400	N/A	\$1,720	Legacy:A-5069-0001-RBE Modulated:A-5069-2001-RBE
OMP60	N/A	\$1,210	Legacy:A-4038-0001-RBE Modulated:A-4038-2001-RBE
OMP600	N/A	\$1,650	A-5180-2001-RBE
RMP40	N/A	\$1,545	A-5480-0001-RBE
RMP60	N/A	\$1,610	A-4113-0001-RBE
RMP60Q	N/A	\$1,610	A-5742-0001-RBE
RMP60MQ	N/A	\$965	A-5742-1003-RBE
RMP600	N/A	\$1,930	A-5312-0001-RBE
OMP60M/RMP60M probe module	N/A	\$910	A-4038-1002-RBE
OMP60M transmission module	N/A	\$750	A-4038-1003-RBE

Description	Check test	Minor repair	Medium repair	Major repair	Repair by exchange	RBE part number
MSP80 rear exit	\$430	\$1,120	\$4,475	\$6,950	\$12,500	A-2238-1255-RBE
MSP80 side exit	\$430	\$1,120	\$4,475	\$6,950	\$12,500	A-2238-1270-RBE

Tool setting probes for machining centers

Description	Repair	Upgrade	Upgrade part number
MP4 side exit (obsolete, upgrade to TS34 side exit)	N/A	\$2,187	RI-2197-3000
MP4 rear exit (obsolete, upgrade to TS34 rear exit)	N/A	\$2,187	RI-2197-2100
MP6 probe only (obsolete, replace with MP3)	N/A	\$785	A-2053-5358-RBE
MP6 base only	N/A	N/A	Replace at new list price

Description	Rewire	Repair by exchange	RBE part number
TS27R	\$210	\$890	A-2008-0368-RBE
TS34 rear exit	N/A	\$1,015	A-2197-2100-RBE
TS34 side exit	N/A	\$1,015	A-2197-3000-RBE

Description	Repair	Repair by exchange	RBE part number
NC3	N/A	\$1,605	A-4179-1500-RBE
NC4 generic TX (separate)	N/A	\$1,055	A-4114-5200-RBE
NC4 generic RX (separate)	N/A	\$1,055	A-4114-5300-RBE
NC4 TX separate with connector	N/A	\$1,055	A-4114-2345-RBE
NC4 RX separate with connector	N/A	\$1,055	A-4114-2346-RBE
NC4F95 compact	N/A	\$2,100	A-5299-5210-RBE
NC4F115 compact	N/A	\$2,100	A-5299-5010-RBE
NC4F145 compact	N/A	\$2,100	A-5299-5310-RBE
NC4F230 compact	N/A	\$2,100	A-5299-5110-RBE
NC4F300 compact	N/A	\$2,100	A-5299-5710-RBE
NC4F300 modular	N/A	\$2,100	A-4114-5100-RBE
NCPCB	N/A	N/A	Replace at new list price
OTS	N/A	\$1,000	A-5401-2001-RBE
OTS (AA)	N/A	\$1,080	A-5514-2001-RBE
TRS2	N/A	\$675	A-5450-0400-RBE(TRS2)
RTS	N/A	\$1,640	A-5646-0001-RBE

Inspection probes for turning centers

Description	Repair	Repair by exchange	RBE part number
LP2 probe	N/A	\$795	A-2063-6098-RBE
LP2DD probe	N/A	\$795	A-2063-8020-RBE
LP2H probe	N/A	\$795	A-2064-0002-RBE
LTO2	Obsolete	Call for upgrade options	
LTO2S	Obsolete	Call for upgrade options	
LTO2T (25 mm shank)	Obsolete	Call for upgrade options	
LTO2T (1 in shank)	Obsolete	Call for upgrade options	
LTO3T (25 mm shank)	Obsolete	Call for upgrade options	
LTO3T (1 in shank)	Obsolete	Call for upgrade options	
MP250	N/A	\$1,080	A-5500-1600-RBE
OLP40	N/A	\$1,205	A-5625-2001-RBE
OMP40M	N/A	\$770	A-5626-2001-RBE
RLP40	N/A	\$1,650	A-5627-0001-RBE
RMP40M	N/A	\$965	A-5628-0001-RBE

Tool setting arms

Description	Repair	Repair by exchange	RBE part number
HPRA 6 in with RP3	N/A	\$1,540	A-2176-0691-RBE
HPRA 8 in with RP3	N/A	\$1,540	A-2176-0692-RBE
HPRA 10 in with RP3	N/A	\$1,540	A-2176-0693-RBE
HPRA 12 in with RP3	N/A	\$1,540	A-2176-0694-RBE
HPRA 15 in with RP3	N/A	\$1,540	A-2176-0695-RBE
HPRA 18 in with RP3	N/A	\$1,540	A-2176-0697-RBE
HPRA 24 in with RP3	N/A	\$1,540	A-2176-0698-RBE
HPPA 6 in rear exit with RP3	N/A	\$1,820	A-2275-0181-RBE
HPPA 8 in rear exit with RP3	N/A	\$1,820	A-2275-0182-RBE
HPPA 10 in rear exit with RP3	N/A	\$1,820	A-2275-0183-RBE
HPPA 12 in rear exit with RP3	N/A	\$1,820	A-2275-0184-RBE
HPPA 15 in rear exit with RP3	N/A	\$1,820	A-2275-0185-RBE
HPPA 18 in rear exit with RP3	N/A	\$1,820	A-2275-0186-RBE
HPMA 6 in rear exit with RP3	N/A	\$2,050	A-2181-0645-RBE
HPMA 8 in rear exit with RP3	N/A	\$2,050	A-2181-0646-RBE
HPMA 10 in rear exit with RP3	N/A	\$2,050	A-2181-0647-RBE
HPMA 12 in rear exit with RP3	N/A	\$2,050	A-2181-0648-RBE
HPMA 15 in rear exit with RP3	N/A	\$2,050	A-2181-0649-RBE
HPMA 18 in rear exit with RP3	N/A	\$2,050	A-2181-0650-RBE
HPMA 24 in rear exit with RP3	N/A	\$2,050	A-2181-0651-RBE
HPGA (side exit)	N/A	\$1,985	A-5616-0352-RBE

Tool setting probes for turning centers

Description	Repair	Repair by exchange	RBE part number
RP1 probe	N/A	\$765	A-2154-0007-RBE
RP2 probe	N/A	\$765	A-2116-0149-RBE
RP3 probe	N/A	\$765	A-2197-0049-RBE
TS20 probe	N/A	N/A	Replace at new list price

Interfaces, receivers and inductive systems

Description	Repair	Repair by exchange	RBE part number
HSI	N/A	N/A	Replace at new list price
IMM (inductive module machine)	N/A	N/A	Call for availability
IMP (inductive module probe) assembly	N/A	N/A	Call for availability
MI5	N/A	Obsolete	Call for details
MI8	N/A	N/A	Replace with HSI interface at list price
MI12	N/A	\$770	A-2075-0142-RBE
NCi interface	N/A	N/A	Replace at new list price
OMI	Obsolete		Call for upgrade options
OMI-2	N/A	\$845	A-5191-0050-RBE
OMI-2T	N/A	\$845	A-5439-0050-RBE
OMM	Obsolete		Call for upgrade options
OMM-2	N/A	\$675	A-5492-0051-RBE
RMI	Obsolete	\$1,000	A-4113-0050-RBE
			Replace with A-5687-0050-RBE
RMI-Q	N/A	\$1,000	A-5687-0050-RBE
SSR converter board	Obsolete	N/A	Replace with HSI interface at new list price
			price
TSi interface	N/A	N/A	Replace at new list price

Gaging systems

Description	Repair by exchange	RBE part number
EQUATOR™ 300 machine	\$7,800	A-5504-0070-RBE
EQUATOR™ 300 extended height machine	\$8,000	A-5504-0085-RBE
EQUATOR™ controller	\$1,875	A-5696-0101-RBE
SP25M body	\$1,745	A-2237-1000-RBE
SM25-2 module	\$1,245	A-2237-1112-RBE
MODUS™ EQUATOR™ replacement dongle	Call for price	A-5639-3000-RBE

Calibration systems

Renishaw recommends the following calibration frequencies:

XM-60	Every 1-2 years
ML10/ML10X/XL-80	Every 2-3 years
EC10/XC-80	Every 12 months
Ballbar	Every 12 months
RX10	Every 2-3 years
XR20-W	Every 1-3 years

Check and test \$300

Repair prices

Description	Repair	Repair by exchange	RBE part number
XC-80	\$2,070	N/A	N/A
XL-80	\$2,070	N/A	N/A
QC10 ballbar (mechanical assembly only)	N/A	N/A	Call for upgrade options
RX10 (less than seven years old)	\$2,600	N/A	N/A
RX10 (more than seven years old)	\$3,750	N/A	N/A
RX10 (more than ten years old)	\$6,240	N/A	N/A
QC20-W (mechanical assembly only)	N/A	\$3,210	A-8014-1520-RBE
XL-80 tripod	\$360	N/A	N/A
XR20-W**	\$3,735	N/A	N/A
XM-60	Call for pricing	N/A	N/A

Calibration prices

	Standard calibration	Express calibration
ML10/ML10X	\$990	\$1,125
EC10 *	\$990	\$1,125
QC10 (includes calibrator)	\$780	\$885
XC-80 *	\$990	\$1,125
XL-80	\$990	\$1,125
Calibrator 50 mm (glass only)	\$265	\$370
Calibrator 300 mm (glass only)	\$300	\$405
Calibrator 50 mm (for QC10) with replacement of center ball, tool cup (2) and center cups	\$625	\$730
Calibrator 50 mm (for QC20) with replacement of center ball	\$385	\$490
RX10	\$1,545	N/A
XR20-W**	\$1,370	N/A
QC20 (includes calibrator)	\$780	\$885
Copy of calibration certificate	\$130	
XM-60	Call for pricing	N/A

* Price includes one air sensor and up to three material sensors. Each additional sensor \$260. Please send in your sensors with your EC10 and XC-80.

** XR20-W must be shipped in proper packaging. Failure to do so could damage unit and delay return after service. Alternative packaging solutions other than the XR20-W case are available for purchase which provide protection for your unit and save transport costs. XR20W-CAL-BOX is an economic and safe alternative to shipping XR20-W in its case. The packaging is reusable and can be purchased for \$66.

A "standard" calibration will take a maximum of five working days and an "express" calibration will take a maximum of two working days. Express calibrations must be scheduled by calling the Renishaw Service Center at: 847/286-9953 extension 62123.

Ballbar calibration includes ballbar and calibrator calibration, and replacement of ball and mount assembly, center cup assembly, center ball assembly, and tool cup assembly. A new cleaning kit will also be supplied.

Traceable calibration certificates will be issued at the time of calibration and enclosed with the returned units.

Replacement parts

Description	Part number	Price
ACR1 short port replacement kit	A-5036-0049	\$285
ACR1 long port replacement kit	A-1051-7077	\$275
ACR1 mixed port replacement kit	A-1051-7076	\$275
MP8 shank switch assembly	Obsolete	Call for upgrade options
OMP60 shank switch assembly	A-4038-0177	\$190
MP3/MP6 probe outer diaphragm kit	A-2053-8156	\$105
LP2 service kit	A-2063-7542	\$75
LP2DD service kit	A-2063-8023	\$175
Ballbar center cup assembly	A-8014-0522	\$175
Ballbar center ball assembly	A-8014-0141	\$155
Ballbar magnetic tool cup	A-8014-0521	\$140
Ballbar ball and mount assembly	A-8014-0182	\$155
Ballbar cleaning kit	A-8014-0423	\$20
Ballbar service kit	A-8014-0786	\$505
MP7/MP8/MP9/MP10 battery cap seal	M-2107-0115	\$30
MP7/MP8/MP9/MP10 battery cap screw	P-SC08-0335	\$5
OMP40 pull-up cone assembly	A-4071-0094	\$45
OMP40 round battery cap seal	A-4071-1157	\$25
OMP40 round battery cap	A-4071-0096	\$105
OMP40 rectangular battery cassette	A-4071-1166	\$135
OMP40/OMP60/RMP60 battery cassette seal	A-4038-0301	\$85
OMP60/RMP60 battery cassette	A-4038-0300	\$195
OMP60/RMP60 outer diaphragm kit	A-4038-0302	\$75
OMP60/RMP60 shank switch bobbin	A-4038-0303	\$185
MP700 battery symbol battery cap	A-2107-0075	\$85
OMP60/RMP60 new type shank switch	A-4038-0177	\$190
OLP40/RLP40 eyelid service kit	A-5625-0005	\$30
OLP40/RLP40 metal battery cassette	A-5625-1166	\$160
OTS/RTS battery cap	A-5401-0301	\$180
TS27R front cover	A-2008-1015	\$95
OTS/RTS front cover kit	A-5401-8512	\$135
TS34 chip shield	A-2008-6007	\$135

About Renishaw

Renishaw is an established world leader in engineering technologies, with a strong history of innovation in product development and manufacturing. Since its formation in 1973, the company has supplied leading-edge products that increase process productivity, improve product quality and deliver cost-effective automation solutions.

A worldwide network of subsidiary companies and distributors provides exceptional service and support for its customers.

Products include:

- Additive manufacturing and vacuum casting technologies for design, prototyping, and production applications
- Dental CAD/CAM scanning systems and supply of dental structures
- Encoder systems for high-accuracy linear, angle and rotary position feedback
- Fixturing for CMMs (co-ordinate measuring machines) and gauging systems
- Gauging systems for comparative measurement of machined parts
- High-speed laser measurement and surveying systems for use in extreme environments
- Laser and ballbar systems for performance measurement and calibration of machines
- Medical devices for neurosurgical applications
- Probe systems and software for job set-up, tool setting and inspection on CNC machine tools
- Raman spectroscopy systems for non-destructive material analysis
- Sensor systems and software for measurement on CMMs
- Styli for CMM and machine tool probe applications

For worldwide contact details, visit www.renishaw.com/contact



RENISHAW HAS MADE CONSIDERABLE EFFORTS TO ENSURE THE CONTENT OF THIS DOCUMENT IS CORRECT AT THE DATE OF PUBLICATION BUT MAKES NO WARRANTIES OR REPRESENTATIONS REGARDING THE CONTENT. RENISHAW EXCLUDES LIABILITY, HOWSOEVER ARISING, FOR ANY INACCURACIES IN THIS DOCUMENT.

© 2017 Renishaw plc. All rights reserved.

Renishaw reserves the right to change specifications without notice.

RENISHAW and the probe symbol used in the RENISHAW logo are registered trade marks of Renishaw plc in the United Kingdom and other countries.

apply innovation and names and designations of other Renishaw products and technologies are trade marks of Renishaw plc or its subsidiaries.

All other brand names and product names used in this document are trade names, trade marks or registered trade marks of their respective owners.

Part no.: H-ALLPRICE

Issued: 12.2017