MeasurLink® ENABLED



V-Anvil Micrometers SERIES 314 — 3 Flutes and 5 Flutes

- Measures the outside diameter of taps and reamers with an odd number of flutes.
- Measures pitch diameter: refer to "Quick Guide to Precision Measuring Instruments" on page B-80.
- Measuring faces: Carbide.
- Equipped with Ratchet Stop for constant measuring force.



SPECIFICATIONS

Metric		For 3-flute cutting tools				
Order No.	Range (mm)	Resolution (mm)	Maximum permissible error J _{MPE} (µm)	Anvil	Remarks	
Digimatic (LCD)						
314-251-30	1 - 15	0.001	±4	60°	w/groove	
314-252-30	10 - 25				w/groove	
314-253-30	25 - 40		±5		_	
314-261-30	1 - 15		±4		_	
314-262-30	10 - 25				_	
FI						

Inch / Metric For 3-flute cutting tools					
Order No.	Range (in)	Resolution	Maximum permissible error JMPE (in)	Anvil	Remarks
Digimatic (LCD)					
314-351-30	0.05 - 0.6		±0.0002	60°	w/groove
314-352-30	0.4 - 1	0.00005 in/ 0.001 mm			w/ groove
314-353-30	1 - 1.6		±0.00025		_
314-361-30	0.05 - 0.6		±0.0002		_
314-362-30	0.4 - 1				_

- Flatness: 0.3 μm/0.000012 in (Spindle), 1.0 μm/0.00004 in (Anvil)
 Battery: SR44 (1 pc.), 938882, for initial operational checks (standard accessory)
 Battery life: Approx. 2.4 years under normal use

- Length standard: Electromagnetic rotary sensor
 Standard accessories: Spanner (301336), 1 pc. (for maximum measuring range up to 40 mm (1.6 in)), Setting Standards for V-Anvil Micrometer


 Note: For functional details, refer to page B-7.

The models above use the same connection cables and connection units as our IP rated micrometers but these digital V-Anvil Micrometers are not IP rated.

Measurement example



Pitch Diameter Measurement of Tap by Single-wire Method



Optional Accessories

optional /			
Order No.	Туре	Description	
05CZA662	В	Connecting cable (1 m)	
05CZA663	В	Connecting cable (2 m)	
06AFM380B	В	USB Input Tool Direct (2 m)	
02AZD790B	В	Connecting cables for U-WAVE-T (160 mm)	
02AZE140B	В	Connecting cables for U-WAVE-T For foot switch	
264-622	IP67	U-WAVE-TM	
264-623	Buzzer	U-WAVE-TM	
264-626	IP67	U-WAVE-TMB	
264-627	Buzzer	U-WAVE-TMB	
02AZF310	IP67/ buzzer	Connecting unit for U-WAVE-TM/TMB	





Ph 866-945-5742 email:sales@willrich.com

